



INSTITUTE OF ENGINEERING & TECHNOLOGY

MOHANLAL SUKHADIA UNIVERSITY, UDAIPUR

Name : Lavina Tamboli | Class: Btech-CSE IV sem) | Subject: DBMS Lab

Experiment-6

AIM: Write the queries to implement the JOINS.

Step-1: Write a Query to show table Customers.

```
mysql> select* from customers;
+-----+-----+-----+-----+-----+
| customer_id | first_name | last_name | age | country |
+-----+-----+-----+-----+-----+
| 1 | John | Doe | 31 | USA |
| 2 | Robert | Luna | 22 | USA |
| 3 | David | Robinson | 22 | UK |
| 4 | John | Reinhardt | 25 | UK |
| 5 | Betty | Doe | 25 | UAE |
+-----+-----+-----+-----+-----+
5 rows in set (0.01 sec)
```

Step-2: Write a Query to show table Orders.

```
mysql> select * from orders;
+-----+-----+-----+-----+
| order_id | item | amount | customer_id |
+-----+-----+-----+-----+
| 1 | keyword | 400 | 4 |
| 2 | mouse | 300 | 4 |
| 3 | monitor | 12000 | 3 |
| 4 | keyboard | 400 | 1 |
| 4 | mousepad | 250 | 2 |
+-----+-----+-----+-----+
5 rows in set (0.00 sec)
```

Step-3: Write a Query to show table Shippings.

```
mysql> select * from shippings;
+-----+-----+-----+
| shippings_id | status | customer_id |
+-----+-----+-----+
| 1 | Pending | 2 |
| 2 | Pending | 4 |
| 3 | Delivered | 3 |
| 4 | Pending | 5 |
| 5 | Delivered | 1 |
+-----+-----+-----+
5 rows in set (0.00 sec)
```



INSTITUTE OF ENGINEERING & TECHNOLOGY

MOHANLAL SUKHADIA UNIVERSITY, UDAIPUR

Name : Lavina Tamboli | Class: Btech-CSE IV sem) | Subject: DBMS Lab

Step-4: Write a Query to find customer_id, first_name and the orders item using JOINS.

```
mysql> SELECT customers.customer_id, customers.first_name, orders.item
-> FROM customers
-> JOIN orders
-> ON customers.customer_id = orders.customer_id;
```

customer_id	first_name	item
4	John	keyword
4	John	mouse
3	David	monitor
1	John	keyboard
2	Robert	mousepad

5 rows in set (0.01 sec)

Step-5: Find out the customer_id, first_name, age and the amount of ordered item by the customer using JOIN.

```
mysql> SELECT customers.customer_id, customers.first_name, customers.age, orders.amount
-> FROM customers
-> JOIN orders
-> ON customers.customer_id = orders.customer_id;
```

customer_id	first_name	age	amount
4	John	25	400
4	John	25	300
3	David	22	12000
1	John	31	400
2	Robert	22	250

5 rows in set (0.00 sec)

Step-6: find out the customer_id, first_name, age and the amount of ordered item by the customer using INNER JOIN.

```
mysql> select customers.first_name, customers.customer_id, orders.order_id, orders.item, orders.amount
-> FROM customers
-> INNER JOIN orders
-> ON customers.customer_id = orders.customer_id;
```

first_name	customer_id	order_id	item	amount
John	4	1	keyword	400
John	4	2	mouse	300
David	3	3	monitor	12000
John	1	4	keyboard	400
Robert	2	4	mousepad	250

5 rows in set (0.00 sec)



INSTITUTE OF ENGINEERING & TECHNOLOGY

MOHANLAL SUKHADIA UNIVERSITY, UDAIPUR

Name : Lavina Tamboli | Class: Btech-CSE IV sem) | Subject: DBMS Lab

Step-7: find out the customer_id, first_name, age and the amount of ordered item by the customer using RIGHT JOIN.

```
mysql> SELECT customers.first_name, customers.customer_id, orders.order_id, orders.item, orders.amount
-> FROM customers
-> RIGHT JOIN orders
-> ON customers.customer_id = orders.customer_id;
```

first_name	customer_id	order_id	item	amount
John	4	1	keyword	400
John	4	2	mouse	300
David	3	3	monitor	12000
John	1	4	keyboard	400
Robert	2	4	mousepad	250

5 rows in set (0.00 sec)

Step-8: find out the customer_id, first_name, age and the amount of ordered item by the customer using LEFT JOIN.

```
mysql> select customers.first_name, customers.customer_id, orders.order_id, orders.item, orders.amount
-> FROM customers
-> LEFT JOIN orders
-> ON customers.customer_id = orders.customer_id;
```

first_name	customer_id	order_id	item	amount
John	1	4	keyboard	400
Robert	2	4	mousepad	250
David	3	3	monitor	12000
John	4	2	mouse	300
John	4	1	keyword	400
Betty	5	NULL	NULL	NULL

6 rows in set (0.00 sec)

Step-9: Write a Query to JOIN three tables: customers, orders, shippings.

```
mysql> SELECT customers.first_name, orders.item, shippings.status
-> FROM customers
-> JOIN orders ON customers.customer_id = orders.customer_id
-> JOIN shippings ON customers.customer_id = shippings.customer_id;
```

first_name	item	status
Robert	mousepad	Pending
John	mouse	Pending
John	keyword	Pending
David	monitor	Delivered
John	keyboard	Delivered

5 rows in set (0.00 sec)