

Private Constructors in Java

Object-Oriented Programming

December 3, 2025

Agenda

- 1 Introduction to Private Constructors
- 2 Example 1: Singleton Pattern
- 3 Example 2: Utility Classes
- 4 Example 3: Factory Method Pattern
- 5 Example 4: Builder Pattern
- 6 Example 5: Constant/Enum-like Classes
- 7 Best Practices and Considerations
- 8 Summary

What is a Private Constructor?

Definition

A private constructor is a constructor that can only be accessed within the class itself, preventing instantiation from outside the class.

- **Access Modifier:** private
- **Visibility:** Only within the class
- **Purpose:** Control object creation
- **Common Uses:** Singleton pattern, utility classes, factory methods

Key Point

When all constructors are private, the class cannot be instantiated using the `new` keyword from outside.

Basic Syntax

Example (Private Constructor Declaration)

```
|1  public class MyClass {  
|2      // Private constructor  
|3      private MyClass() {  
|4      }  
|5  }
```

Example (Attempting External Instantiation - ERROR!)

```
|1  public class Test {  
|2      public static void main(String[] args) {  
|3          MyClass obj = new MyClass(); // Error!  
|4      }  
|5  }
```

Singleton Pattern - Eager Initialization

Purpose

Ensure a class has only one instance and provide global access to it.

```
1  public class DatabaseConnection {  
2      private static final DatabaseConnection instance =  
3          new DatabaseConnection();  
4      private DatabaseConnection() {  
5          System.out.println("Database connection created");  
6      }  
7      public static DatabaseConnection getInstance() {  
8          return instance;  
9      }  
10     public void connect() {  
11         System.out.println("Connected to database");  
12     }  
13 }
```

Singleton Usage

Example (Using the Singleton)

```
1 public class Main {  
2     public static void main(String[] args) {  
3         // Get the singleton instance  
4         DatabaseConnection db1 = DatabaseConnection.getInstance();  
5         DatabaseConnection db2 = DatabaseConnection.getInstance();  
6         db1.connect();  
7         // Check if both references point to same object  
8         System.out.println("Same instance? " + (db1 == db2));  
9         // Output: Same instance? true  
10    }  
11 }
```

Important

The constructor is private, so you cannot use `new DatabaseConnection()`. You must use `getInstance()`.

Utility Classes I

Purpose

Create classes that contain only static methods and constants. No instance needed.

```
1 public final class MathUtils {  
2     private MathUtils() {  
3         throw new AssertionError(  
4             "Utility class cannot " +  
5             "be instantiated");  
6     }  
7     public static double  
8         calculateCircleArea(double radius) {  
9             return Math.PI * radius * radius;  
10        }
```

```
1     public static int factorial(int n) {  
2         if (n <= 1) return 1;  
3         return n * factorial(n - 1);  
4     }  
5     public static boolean isPrime(int number  
6         ) {  
7         if (number <= 1) return false;  
8         for (int i = 2;i <= Math.sqrt(number  
9                 ));  
10            i++) {  
11                if (number % i == 0)  
12                    return false;  
13            }  
14        }
```

Using Utility Classes

Example (Correct Usage)

```
1 public class Calculator {  
2     public static void main(String[] args) {  
3         double area = MathUtils.calculateCircleArea(5.0);  
4         int fact = MathUtils.factorial(5);  
5         boolean prime = MathUtils.isPrime(17);  
6         System.out.println("Area: " + area);  
7         System.out.println("Factorial: " + fact);  
8         System.out.println("Is Prime: " + prime);  
9     }  
10 }
```

Example (Incorrect Usage - ERROR!)

```
1 // This will cause compilation error  
2 MathUtils utils = new MathUtils(); // Error!
```

Factory Method Pattern

Purpose

Control object creation through factory methods instead of constructors.

```
1  public class Employee {  
2      private String name; private String type; private double salary;  
3      private Employee(String name, String type, double salary) {  
4          this.name = name; this.type = type;  
5          this.salary = salary;  
6      }  
7      public static Employee createManager(String name) {  
8          return new Employee(name, "Manager", 75000.0);  
9      }  
10     public static Employee createDeveloper(String name) {  
11         return new Employee(name, "Developer", 60000.0);  
12     }  
13     public static Employee createIntern(String name) {  
14         return new Employee(name, "Intern", 30000.0);  
15     }  
16     public String getDetails() {  
17         return name + " - " + type + " - $" + salary;  
18     }  
}
```

Using Factory Methods

Example (Creating Employees)

```
1  public class Company {  
2      public static void main(String[] args) {  
3          // Using factory methods  
4          Employee manager = Employee.createManager("Alice");  
5          Employee developer = Employee.createDeveloper("Bob");  
6          Employee intern = Employee.createIntern("Charlie");  
7          System.out.println(manager.getDetails());  
8          System.out.println(developer.getDetails());  
9          System.out.println(intern.getDetails());  
10         // This would cause compilation error:  
11         // Employee emp = new Employee("Name", "Type", 50000); // Error!  
12     }  
13 }
```

Output

Alice - Manager - \$75000.0

Bob - Developer - \$60000.0

Builder Pattern with Private Constructor

Purpose

Create complex objects step by step with a fluent interface.

```
1  public class Computer {  
2      private final String cpu;  
3      private final int ram;  
4      private final int storage;  
5      private final boolean hasGraphicsCard;  
6      // Private constructor  
7      private Computer(Builder builder) {  
8          this.cpu = builder.cpu;  
9          this.ram = builder.ram;  
10         this.storage = builder.storage;  
11         this.hasGraphicsCard = builder.hasGraphicsCard;  
12     }  
13     // Static Builder class  
14     public static class Builder {  
15         // Required parameters  
16         private final String cpu;  
17         private final int ram;  
18         // Optional parameters  
19     }
```

Builder Pattern (Continued)

```
1  public Builder(String cpu, int ram) {
2      this.cpu = cpu;
3      this.ram = ram;
4  }
5  public Builder storage(int storage) {
6      this.storage = storage;
7      return this;
8  }
9  public Builder graphicsCard(boolean hasGraphicsCard) {
10     this.hasGraphicsCard = hasGraphicsCard;
11     return this;
12 }
13 public Computer build() {
14     return new Computer(this);
15 }
16 }
17 @Override
18 public String toString() {
19     return "Computer[CPU=" + cpu + ", RAM=" + ram +
20             " GB, Storage=" + storage +
21             " GB, Graphics=" + hasGraphicsCard + "]";
22 }
23 }
```

Using the Builder Pattern

Example (Building Computers)

```
1  public class ComputerShop {  
2      public static void main(String[] args) {  
3          // Using builder pattern  
4          Computer gamingPC = new Computer.Builder("Intel i9", 32)  
5              .storage(1000)  
6              .graphicsCard(true)  
7              .build();  
8  
9          Computer officePC = new Computer.Builder("Intel i5", 16)  
10             .storage(512)  
11             .build();  
12  
13         System.out.println("Gaming PC: " + gamingPC);  
14         System.out.println("Office PC: " + officePC);  
15  
16         // This would cause compilation error:  
17         // Computer pc = new Computer(); // Error!  
18     }  
19 }
```

Constant Classes with Private Constructor

Purpose

Create classes that only contain constants, similar to enums but more flexible.

```
1  public final class ApplicationConstants {  
2      // Private constructor to prevent instantiation  
3      private ApplicationConstants() {  
4          // Throw exception if someone tries to instantiate via reflection  
5          throw new IllegalStateException("Constants class");  
6      }  
7      // Database constants  
8      public static final String DB_URL = "jdbc:mysql://localhost:3306/mydb";  
9      public static final String DB_USERNAME = "admin";  
10     public static final String DB_PASSWORD = "password";  
11     // Application settings  
12     public static final int MAX_USERS = 1000;  
13     public static final int SESSION_TIMEOUT = 1800; // seconds  
14     public static final String APP_VERSION = "2.1.0";  
15     // Error messages  
16     public static final String ERROR_INVALID_INPUT = "Invalid input provided";  
17     public static final String ERROR_DB_CONNECTION = "Database connection failed";  
18 }
```

Using Constant Classes

Example (Accessing Constants)

```
1  public class DatabaseManager {  
2      public void connectToDatabase() {  
3          try {  
4              String url = ApplicationConstants.DB_URL;  
5              String user = ApplicationConstants.DB_USERNAME;  
6              String password = ApplicationConstants.DB_PASSWORD;  
7  
8              System.out.println("Connecting to: " + url);  
9              System.out.println("Max users allowed: " +  
10                  ApplicationConstants.MAX_USERS);  
11             // Database connection logic here  
12         } catch (Exception e) {  
13             System.out.println(ApplicationConstants.ERROR_DB_CONNECTION);  
14         }  
15     }  
16     public void validateInput(String input) {  
17         if (input == null || input.trim().isEmpty()) {  
18             throw new IllegalArgumentException(  
19                 ApplicationConstants.ERROR_INVALID_INPUT);  
20         }  
21     }  
22 }
```

Best Practices for Private Constructors

- ① **Singleton Pattern:** Use for classes that need exactly one instance
- ② **Utility Classes:** Mark class as `final` and throw exception in constructor
- ③ **Factory Methods:** Use when object creation logic is complex
- ④ **Builder Pattern:** Use for creating complex objects with many parameters
- ⑤ **Constant Classes:** Prevent instantiation of classes containing only constants

Important Considerations

- **Testing:** Private constructors can make testing more challenging
- **Reflection:** Can bypass private constructors (use `SecurityManager`)
- **Serialization:** Special care needed for singleton serialization
- **Inheritance:** Classes with only private constructors cannot be subclassed

When to Use Private Constructors

Appropriate Uses

- Singleton classes
- Utility classes
- Factory classes
- Builder classes
- Constant containers
- Enum-like classes

Avoid When

- Normal instantiation needed
- Class needs inheritance
- Simple value objects
- Framework components
- Test-heavy codebases

Use private constructors judiciously to enforce design constraints

Summary

- **Private constructors** restrict object creation to within the class
- **Five common patterns:**
 - ① Singleton Pattern - Single instance
 - ② Utility Classes - No instance needed
 - ③ Factory Methods - Controlled creation
 - ④ Builder Pattern - Complex object construction
 - ⑤ Constant Classes - Prevent instantiation
- **Benefits:** Better control, encapsulation, design enforcement
- **Considerations:** Testing difficulty, reflection issues

Key Takeaway

Private constructors are a powerful tool for enforcing specific object creation patterns and maintaining control over how instances of your classes are created and used.