

Write a beginner C++ program for a Roast Generator. Ask for the user's name and store 10 roasts in a list. Use a placeholder like '{name}' in the roasts and replace it with the user's input. Pick a roast at random. Make the code very simple for a first-year student.

Here's a very simple beginner-friendly C++ program for a roast generator. It uses basic concepts: arrays, input/output, random selection, and string replacement.

```
</> C++  
  
#include <iostream>  
#include <string>  
#include <cstdlib> // for rand() and srand()  
#include <ctime>   // for time()  
  
using namespace std;  
  
int main() {  
    string name;  
  
    // Ask user for name  
    cout << "Enter your name: ";  
    getline(cin, name);  
  
    // List of 10 roasts with placeholder {name}  
    string roasts[10] = {  
        "{name}, you run like Windows 98.",  
        "{name}, even Google can't find your talent.",  
        "{name}, you bring everyone so much joy when you leave.",  
        "{name}, you are proof that evolution can go in reverse.",  
        "{name}, your brain is on airplane mode.",
```

+ Ask anything



```
// Pick random roast
int index = rand() % 10;
string selectedRoast = roasts[index];

// Replace {name} with actual name
size_t pos = selectedRoast.find("{name}");
if (pos != string::npos) {
    selectedRoast.replace(pos, 6, name);
}

// Print result
cout << "\nYour roast:\n";
cout << selectedRoast << endl;

return 0;
}
```

How it works (quick idea)

- Takes your name as input
- Stores 10 roast strings in an array
- Picks one randomly using `rand()`
- Replaces `{name}` with your actual name
- Prints the final roast

If you want, I can show you a slightly upgraded version (with multiple replacements or better randomness) once you're comfortable with this.

📄 🌟 💬 ↗️ ↺️ ...

+ Ask anything



File Edit Selection View Go Run Terminal Help

FOCP 11 - ASSIGNMENTS

EXPLORER

OPEN EDITORS

BANK_BALANCE.cpp

Untitled-1

roastgenerator.cpp

FOCP 11 - ASSIGNMENTS

.gitignore

a.exe

assignment1Ques1.cpp

assignment1Ques2.cpp

BANK_BALANCE.cpp

BANK_BALANCE.exe

CountPairs.cpp

CountPairs.exe

CountPairs.png

HelpAliceToFindTheParity.cpp

HelpAliceToFindTheParity.exe

MOVIE_TICKETS.cpp

MOVIE_TICKETS.exe

Q8.cpp

Q10.cpp

roastgenerator.cpp

roastgenerator.exe

TooChocolately.cpp

TooChocolately.exe

TurnOFFLights.cpp

TurnOFFLights.exe

TurnOFFLights.png

OUTLINE

TIMELINE

roastgenerator.cpp

main()

```
24     "{name}, your secrets are always safe with me. I never even listen.",
25     "{name}, you are like a cloud. When you disappear, it's a beautiful day.",
26     "{name}, you have the charisma of a damp rag."
27 };
28
29
30
31 // Pick random roast
32 int index = rand() % 10;
33 string selectedRoast = roasts[index];
34
35 // Replace {name} with actual name
36 size_t pos = selectedRoast.find("{name}");
37 if (pos != string::npos) {
38     selectedRoast.replace(pos, 6, name);
39 }
40
41 // Print result
42 cout << "\nYour roast:\n";
43 cout << selectedRoast << endl;
44
```

PROBLEMS

OUTPUT

DEBUG CONSOLE

TERMINAL

PORTS

```
p\FOCP 11 - ASSIGNMENTS\" && g++ roastgenerator.cpp -o roastgenerator && "c:\Users\ISHIKA\OneDrive\Engineering_Journey\Desktop\FOCP
P 11 - ASSIGNMENTS\roastgenerator
Enter your name: ishika

Your roast:
ishika, even Google can't find your talent.

c:\Users\ISHIKA\OneDrive\Engineering_Journey\Desktop\FOCP 11 - ASSIGNMENTS>cd "c:\Users\ISHIKA\OneDrive\Engineering_Journey\Desktop\FOCP
p\FOCP 11 - ASSIGNMENTS\" && g++ roastgenerator.cpp -o roastgenerator && "c:\Users\ISHIKA\OneDrive\Engineering_Journey\Desktop\FOC
P 11 - ASSIGNMENTS\roastgenerator
Enter your name: ishika

Your roast:
ishika, even Google can't find your talent.
```

cmd

Code

Ln 46, Col 2

Spaces: 4

UTF-8

CRLF

{ }

C++

Win32



ChatGPT ▾

Share



I am running my C++ Roast Generator, but it gives me the exact same roast every time I restart the program. I removed the 'srand' line. Why is this happening and how do I make it give a different roast every time I click run?

That behavior is actually expected once you removed `srand`.

What's going wrong

`rand()` doesn't generate truly random numbers by itself—it follows a **fixed sequence**.

- If you **don't** use `srand()`, the program always starts from the **same starting point (seed)**
- So every time you run the program → same sequence → same first number → same roast

Think of it like a playlist that always starts from song #1 unless you shuffle it.

Why `srand(time(0))` fixes it

When you write:

❏ C++



```
srand(time(0));
```

you're telling the program:

"Start the random sequence from a different point each time (based on current time)."

Since time changes every second, the starting point changes → different random number → different roast.



Fix (put this back)

+ Ask anything



Upgrade

ChatGPT can make mistakes. Check important info. See [Cookie Preferences](#).

Fix (put this back)

```
</> C++  
  
srand(time(0));
```

Full correct placement:

```
</> C++  
  
int main() {  
    srand(time(0)); // <-- must be before rand()  
  
    // rest of your code  
}
```

Small but important detail

If you accidentally put `srand(time(0))` inside a loop, it can still repeat values (because time may not change fast enough). So:

- Call `srand()` only once at the start of `main()`

If you want a slightly better (modern) method

For later (not required now), C++ has better randomness:

```
</> C++  
  
#include <random>
```

But for first-year level, `rand()` + `srand(time(0))` is perfectly fine.

+ Ask anything

File Edit Selection View Go Run Terminal Help

FOCP 11 - ASSIGNMENTS

EXPLORER

OPEN EDITORS

BANK_BALANCE.cpp

Untitled-1

roastgenerator.cpp

FOCP 11 - ASSIGNMENTS

.gitignore

a.exe

assignment1Ques1.cpp

assignment1Ques2.cpp

BANK_BALANCE.cpp

BANK_BALANCE.exe

CountPairs.cpp

CountPairs.exe

CountPairs.png

HelpAliceToFindTheParity.cpp

HelpAliceToFindTheParity.exe

MOVIE_TICKETS.cpp

MOVIE_TICKETS.exe

Q8.cpp

Q10.cpp

roastgenerator.cpp

roastgenerator.exe

TooChocolatey.cpp

TooChocolatey.exe

TurnOFFLights.cpp

TurnOFFLights.exe

TurnOFFLights.png

OUTLINE

TIMELINE

roastgenerator.cpp

main()

```
32 // Pick random roast
33 int index = rand() % 10;
34 string selectedRoast = roasts[index];
35
36 // Replace {name} with actual name
37 size_t pos = selectedRoast.find("{name}");
38 if (pos != string::npos) {
39     selectedRoast.replace(pos, 6, name);
40 }
41
42 // Print result
43 cout << "\nYour roast:\n";
44 cout << selectedRoast << endl;
45
46 return 0;
47 }
```

PROBLEMS

OUTPUT

DEBUG CONSOLE

TERMINAL

PORTS

```
P 11 - ASSIGNMENTS\roastgenerator
Enter your name: ishika

Your roast:
ishika, even Google can't find your talent.

c:\Users\ISHIKA\OneDrive\Engineering_Journey\Desktop\FOCP 11 - ASSIGNMENTS>cd "c:\Users\ISHIKA\OneDrive\Engineering_Journey\Desktop\FOCP 11 - ASSIGNMENTS\" && g++ roastgenerator.cpp -o roastgenerator && "c:\Users\ISHIKA\OneDrive\Engineering_Journey\Desktop\FOCP 11 - ASSIGNMENTS\roastgenerator
Enter your name: ishika

Your roast:
ishika, your brain is on airplane mode.

c:\Users\ISHIKA\OneDrive\Engineering_Journey\Desktop\FOCP 11 - ASSIGNMENTS>
```

cmd

Code

Ln 47, Col 2 Spaces: 4 UTF-8 CRLF {} C++ Win32