2021/4/19 6.S081 / Fall 2020

```
Toggle navigation 6.S081: Operating System Engineering

    Schedule

    Class

    Overview

         • Administrivia
         · Handin website
         o 6.S081 2019

    Labs

    Tools

    Guidance

    Lab Utilities

    Lab System calls

    <u>Lab Page tables</u>

    <u>Lab Traps</u>

    Lab Lazy allocation

         • Lab Copy on-write

    Lab Multithreading

         • Lab Lock
         • Lab File system

    Lab mmap

    Lab network driver

    xv6

    xv6

    xv6 book

    References

    Piazza
```

Tools Used in 6.S081

For this class you'll need the RISC-V versions of a couple different tools: QEMU 5.1, GDB 8.3, GCC, and Binutils.

We highly recommend using a Debathena machine, such as athena.dialup.mit.edu, to work on the labs. If you use the MIT Athena machines that run Linux, then all of these tools are located in the 6.828 locker: just type 'add -f 6.828' to get access to them. If you don't have access to a Debathena machine, you can install the tools directly or use virtual machine with Linux via the instructions below.

If you are having trouble getting things set up, please come by to office hours or post on Piazza. We're happy to help!

Using Athena

2020

ssh into one of the Athena dialup machines and add the tools:

```
$ ssh {your kerberos}@athena.dialup.mit.edu
$ add -f 6.828
```

Installing on macOS

First, install developer tools:

```
$ xcode-select --install
```

Next, install <u>Homebrew</u>, a package manager for macOS:

Next, install the RISC-V compiler toolchain:

```
$ brew tap riscv/riscv
$ brew install riscv-tools
```

The brew formula may not link into /usr/local. You will need to update your shell's rc file (e.g. /usr/local) to add the appropriate directory to /usr/local) to add the appropriate directory to /usr/local.

PATH=\$PATH:/usr/local/opt/riscv-gnu-toolchain/bin

Finally, install QEMU:

brew install qemu

Installing via APT (Debian/Ubuntu)

Make sure you are running either "bullseye" or "sid" for your debian version (on ubuntu this can be checked by running cat/etc/debian_version), then run:

```
sudo apt-get install git build-essential gdb-multiarch qemu-system-misc gcc-riscv64-linux-gnu binutils-riscv64-linux-gnu
```

2021/4/19 6.S081 / Fall 2020

(The version of QEMU on "buster" is too old, so you'd have to get that separately.)

gemu-system-misc fix

At this moment in time, it seems that the package <code>qemu-system-misc</code> has received an update that breaks its compatibility with our kernel. If you run <code>make qemu</code> and the script appears to hang after

qemu-system-riscv64 -machine virt -bios none -kernel kernel/kernel -m 128M -smp 3 -nographic -drive file=fs.img,if=none,format=raw,id=x0 -device virtio-blk-device,drive=x0,bus=virtio-mmio-bus.0

you'll need to uninstall that package and install an older version:

```
$ sudo apt-get remove qemu-system-misc
$ sudo apt-get install qemu-system-misc=1:4.2-3ubuntu6
```

Installing on Arch

sudo pacman -S riscv64-linux-gnu-binutils riscv64-linux-gnu-gcc riscv64-linux-gnu-gdb qemu-arch-extra

Other Linux distributions (i.e. compiling your own toolchain)

We assume that you are installing the toolchain into /usr/local on a modern Ubuntu installation. You will need a fair amount of disk space to compile the tools (around 9GiB). If you don't have that much space, consider using an MIT Athena machine.

First, clone the repository for the RISC-V GNU Compiler Toolchain:

```
$ git clone --recursive https://github.com/riscv/riscv-gnu-toolchain
```

Next, make sure you have the packages needed to compile the toolchain:

\$ sudo apt-get install autoconf automake autotools-dev curl libmpc-dev libmpfr-dev libmppr-dev gawk build-essential bison flex texinfo gperf li

Configure and build the toolchain:

```
$ cd riscv-gnu-toolchain
$ ./configure --prefix=/usr/local
$ sudo make
$ cd ..
```

Next, retrieve and extract the source for QEMU 5.1.0:

```
$ wget https://download.qemu.org/qemu-5.1.0.tar.xz
$ tar xf qemu-5.1.0.tar.xz
```

Build QEMU for riscv64-softmmu:

```
$ cd qemu-5.1.0
$ ./configure --disable-kvm --disable-werror --prefix=/usr/local --target-list="riscv64-softmmu"
$ make
$ sudo make install
$ cd ..
```

Windows (i.e. running a Linux VM)

We haven't tested it, but it might be possible to get everything you need via the Windows Subsystem for Linux or otherwise compiling the tools yourself.

However, an easier option would probably be to run a virtual machine with one of the other operating systems listed above. With platform virtualization, Linux can cohabitate with your normal computing environment. Installing a Linux virtual machine is a two step process. First, you download the virtualization platform.

- <u>VirtualBox</u> (free for Mac, Linux, Windows) <u>Download page</u>
- VMware Player (free for Linux and Windows, registration required)
- VMware Fusion (Downloadable from IS&T for free).

VirtualBox is a little slower and less flexible, but free!

Once the virtualization platform is installed, download a boot disk image for the Linux distribution of your choice.

• <u>Ubuntu Desktop</u> is one option.

This will download a file named something like ubuntu-18.04.3-desktop-amd64.iso. Start up your virtualization platform and create a new (64-bit) virtual machine. Use the downloaded Ubuntu image as a boot disk; the procedure differs among VMs but is pretty simple.

Testing your Installation

To test your installation, you should be able to check the following:

```
$ riscv64-unknown-elf-gcc --version
riscv64-unknown-elf-gcc (GCC) 10.1.0
...
$ qemu-system-riscv64 --version
QEMU emulator version 5.1.0
```

You should also be able to compile and run xv6:

2021/4/19 6.S081 / Fall 2020

```
# in the xv6 directory
$ make qemu
# ... lots of output ...
init: starting sh
$
```

To quit qemu type: Ctrl-a x.

Questions or comments regarding S6.081? Send e-mail to the course staff at $\underline{65081@lists.csail.mit.edu}$.

Creative Commons License Top // S6.081 home // Last updated Thursday, 03-Sep-2020 11:23:54 EDT