

Laxmi Charitable Trust's
Sheth L.U.J College of Arts & Sir M.V. College of Science and Commerce
Department of Information Technology (B.Sc.I.T Semester V)
Applied business Analytics Practical
Practical – VIII

Roll No.:T031	Name:Ishita Patel
Class:TYIT	Batch:1
Date of Assignment:11/09/26	Date/Time of Submission:11/09/26

Dataset: supermarket_sales.csv

Part A: Confidence Interval Estimation

1. Load the supermarket_sales.csv dataset into a Pandas DataFrame.

Code:-

```
# PRACTICAL: CONFIDENCE INTERVAL ESTIMATION AND BOOTSTRAPPING
# Dataset: supermarket_sales.csv
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
from scipy import stats
# PART A: CONFIDENCE INTERVAL ESTIMATION
# 1. Load the dataset
df = pd.read_csv("supermarket_sales.csv")
print("Dataset Loaded Successfully!")
print("=" * 60)
```

Output:-

```
Dataset Loaded Successfully!
```

2. Display the first five records and check the size of the dataset.

Code:-

```
# 2. Display first five records and dataset size
print("\nFirst Five Records:")
print(df.head())

print("\nDataset Size:")
print("Rows:", df.shape[0])
print("Columns:", df.shape[1])
```

Output:-

```

First Five Records:
  invoice_id branch      city customer_type gender_customer \
0  750-67-8428    A    Yangon      Member      Female
1  226-31-3081    C  Naypyitaw      Normal      Female
2  631-41-3108    A    Yangon      Normal      Male
3  123-19-1176    A    Yangon      Member      Male
4  373-73-7910    A    Yangon      Normal      Male

  product_line  unit_cost  quantity  5pct_markup  revenue \
0  Health and beauty    74.69         7    26.1415  548.9715
1  Electronic accessories    15.28         5     3.8200   80.2200
2  Home and lifestyle     46.33         7    16.2155  340.5255
3  Health and beauty     58.22         8    23.2880  489.0480
4  Sports and travel     86.31         7    30.2085  634.3785

  date    time  payment_method  cogs  gm_pct  gross_income  rating
0  01/05/19  13:08      Ewallet  522.83  4.761905    26.1415    9.1
1  03/08/19  10:29        Cash   76.40  4.761905     3.8200    9.6
2  03/03/19  13:23  Credit card  324.31  4.761905    16.2155    7.4
3  1/27/2019  20:33      Ewallet  465.76  4.761905    23.2880    8.4
4  02/08/19  10:37      Ewallet  604.17  4.761905    30.2085    5.3

Dataset Size:
Rows: 1000
Columns: 17

```

3. Select the revenue column for analysis.

Code:-

```

# Prepare revenue column
# If revenue column does not exist, use Total as revenue
if "revenue" not in df.columns:
    if "Revenue" in df.columns:
        df["revenue"] = df["Revenue"]
    elif "Total" in df.columns:
        df["revenue"] = df["Total"]
    elif "total" in df.columns:
        df["revenue"] = df["total"]
    else:
        raise ValueError(
            "Revenue column not found. Please check your CSV column names."
        )
# 3. Select revenue column
revenue = df["revenue"]
print("\nRevenue Column:")
print(revenue.head())

```

Output:-

```

Revenue Column:
0    548.9715
1     80.2200
2    340.5255
3    489.0480
4    634.3785
Name: revenue, dtype: float64

Missing Values in Revenue:
0
Missing values after handling: 0

```

4. Check and handle missing values in the selected column.

Code:-

```
# 4. Check and handle missing values
print("\nMissing Values in Revenue:")
print(revenue.isnull().sum())
# Remove missing values
revenue = revenue.dropna()
print("Missing values after handling:", revenue.isnull().sum())
```

Output:-

```
Missing Values in Revenue:
0
Missing values after handling: 0
```

5. Calculate the sample size, sample mean, and sample standard deviation.

Code:-

```
# 5. Calculate sample size, mean and standard deviation
n = len(revenue)
sample_mean = revenue.mean()
sample_std = revenue.std()
print("\nSample Statistics:")
print("Sample Size:", n)
print("Sample Mean:", round(sample_mean, 2))
print("Sample Standard Deviation:", round(sample_std, 2))
# Function to calculate confidence interval
def confidence_interval(data, confidence):
    n = len(data)
    mean = np.mean(data)
    std = np.std(data, ddof=1)
    # Standard Error
    se = std / np.sqrt(n)
    # t critical value
    t_value = stats.t.ppf(
        (1 + confidence) / 2,
        df=n - 1
    )
    margin_error = t_value * se
    lower = mean - margin_error
    upper = mean + margin_error
    return lower, upper
```

Output:-

```
Sample Statistics:
Sample Size: 1000
Sample Mean: 322.97
Sample Standard Deviation: 245.89
```

6. Calculate the 90% confidence interval for the population mean revenue.

Code:-

```
# 6. Calculate 90% confidence interval
ci_90 = confidence_interval(revenue, 0.90)
print("\n90% Confidence Interval:")
print("Lower:", round(ci_90[0], 2))
print("Upper:", round(ci_90[1], 2))
```

Output:-

```
90% Confidence Interval:
Lower: 310.17
Upper: 335.77
```

7. Calculate the 95% confidence interval for the population mean revenue.

Code:-

```
# 7. Calculate 95% confidence interval
ci_95 = confidence_interval(revenue, 0.95)
print("\n95% Confidence Interval:")
print("Lower:", round(ci_95[0], 2))
print("Upper:", round(ci_95[1], 2))
```

Output:-

```
95% Confidence Interval:
Lower: 307.71
Upper: 338.23
```

8. Calculate the 99% confidence interval for the population mean revenue.

Code:-

```
# 8. Calculate 99% confidence interval
ci_99 = confidence_interval(revenue, 0.99)
print("\n99% Confidence Interval:")
print("Lower:", round(ci_99[0], 2))
print("Upper:", round(ci_99[1], 2))
```

Output:-

```
99% Confidence Interval:
Lower: 302.9
Upper: 343.03
```

9. Display the confidence intervals in a suitable table.

Code:-

```
# 9. Display confidence intervals in a table
ci_table = pd.DataFrame({
    "Confidence Level": ["90%", "95%", "99%"],
    "Lower Limit": [
        ci_90[0],
        ci_95[0],
        ci_99[0]
    ],
    "Upper Limit": [
```

```

        ci_90[1],
        ci_95[1],
        ci_99[1]
    ]
})
print("\nConfidence Interval Table:")
print(ci_table.round(2))

```

Output:-

```

Confidence Interval Table:
  Confidence Level  Lower Limit  Upper Limit
0              90%         310.17         335.77
1              95%         307.71         338.23
2              99%         302.90         343.03

```

10. Compare the 90%, 95%, and 99% confidence intervals.

Code:-

```

# 10. Compare confidence intervals
print("\nComparison of Confidence Intervals:")
print("90% CI :", round(ci_90[0], 2), "to", round(ci_90[1], 2))
print("95% CI :", round(ci_95[0], 2), "to", round(ci_95[1], 2))
print("99% CI :", round(ci_99[0], 2), "to", round(ci_99[1], 2))
print("\nObservation:")
print("As the confidence level increases, the interval becomes wider.")

```

Output:-

```

Comparison of Confidence Intervals:
90% CI : 310.17 to 335.77
95% CI : 307.71 to 338.23
99% CI : 302.9 to 343.03

Observation:
As the confidence level increases, the interval becomes wider.

```

11. Create a suitable visualization to display the sample mean and confidence interval.

Code:-

```

# 11. Visualization of sample mean and confidence intervals
levels = ["90%", "95%", "99%"]
lower_values = [ci_90[0], ci_95[0], ci_99[0]]
upper_values = [ci_90[1], ci_95[1], ci_99[1]]
errors_lower = [
    sample_mean - ci_90[0],
    sample_mean - ci_95[0],
    sample_mean - ci_99[0]
]
errors_upper = [
    ci_90[1] - sample_mean,
    ci_95[1] - sample_mean,
    ci_99[1] - sample_mean
]


```

```

]
plt.figure(figsize=(8, 5))
plt.errorbar(
    levels,
    [sample_mean] * 3,
    yerr=[errors_lower, errors_upper],
    fmt='o',
    capsize=8
)
plt.axhline(
    sample_mean,
    linestyle='--',
    label='Sample Mean'
)
plt.title("Confidence Intervals for Mean Revenue")
plt.xlabel("Confidence Level")
plt.ylabel("Revenue")
plt.legend()
plt.grid(True)
plt.show()

```

Output:-



12. Interpret the 95% confidence interval in the context of supermarket revenue.

Code:-

```

# 12. Interpretation of 95% confidence interval
print("\n95% Confidence Interval Interpretation:")
print(
    f"We are 95% confident that the true population mean revenue "
    f"lies between {ci_95[0]:.2f} and {ci_95[1]:.2f}."
)

```

Output:-

95% Confidence Interval Interpretation:

We are 95% confident that the true population mean revenue lies between 307.71 and 338.23.

13. Select the customer_type column and calculate the proportion of customers belonging to each category.

Code:-

```
# CUSTOMER TYPE PROPORTION
# 13. Select customer_type column
# Handle different possible column names
if "customer_type" in df.columns:
    customer_type = df["customer_type"]
elif "Customer type" in df.columns:
    customer_type = df["Customer type"]

elif "Customer Type" in df.columns:
    customer_type = df["Customer Type"]
else:
    raise ValueError(
        "Customer type column not found. Check your CSV column name."
    )
# Calculate proportion of each category
customer_proportion = customer_type.value_counts(normalize=True)
print("\nCustomer Type Proportions:")
print(customer_proportion)
```

Output:-

```
Customer Type Proportions:
customer_type
Member      0.501
Normal      0.499
Name: proportion, dtype: float64
```

14. Calculate the 95% confidence interval for the proportion of Member customers.

Code:-

```
# 14. 95% CI for proportion of Member customers
member_count = (customer_type == "Member").sum()
total_customers = customer_type.notna().sum()
p_hat = member_count / total_customers
# Standard error for proportion
se_proportion = np.sqrt(
    (p_hat * (1 - p_hat)) / total_customers
)
# 95% z critical value
z_value = stats.norm.ppf(0.975)
margin_proportion = z_value * se_proportion
proportion_lower = p_hat - margin_proportion
proportion_upper = p_hat + margin_proportion
# Keep values between 0 and 1
```

```

proportion_lower = max(0, proportion_lower)
proportion_upper = min(1, proportion_upper)
print("\nMember Customer Proportion:")
print("Number of Members:", member_count)
print("Total Customers:", total_customers)
print("Sample Proportion:", round(p_hat, 4))
print("\n95% Confidence Interval for Member Proportion:")
print(
    round(proportion_lower, 4),
    "to",
    round(proportion_upper, 4)
)
print(
    f"\nPercentage: {proportion_lower * 100:.2f}% "
    f"to {proportion_upper * 100:.2f}%"
)

```

Output:-

```

Member Customer Proportion:
Number of Members: 501
Total Customers: 1000
Sample Proportion: 0.501

95% Confidence Interval for Member Proportion:
0.47 to 0.532

Percentage: 47.00% to 53.20%

```

15. Interpret the confidence interval for the population proportion in a business context.

Code:-

```

# 15. Business interpretation
print("\nBusiness Interpretation:")
print(
    f"We are 95% confident that the true proportion of Member "
    f"customers in the supermarket population is between "
    f"{proportion_lower * 100:.2f}% and "
    f"{proportion_upper * 100:.2f}%."
)

```

Output:-

```

Business Interpretation:
We are 95% confident that the true proportion of Member customers in the supermarket population is between 47.00% and 53.20%.

```

Part B: Bootstrapping

16. Select the revenue column and calculate its original sample median.

Code:-

```

# 16. Original sample median
original_median = revenue.median()
print("\n" + "=" * 60)

```



```
print("PART B: BOOTSTRAPPING")
print("=" * 60)
print("\nOriginal Sample Median:")
print(round(original_median, 2))
```

Output:-

```
Original Sample Median:
253.85
```

17. Create a bootstrap sample by randomly selecting observations from the original sample with replacement.

18. Calculate the median of the bootstrap sample.

19. Repeat the bootstrapping process 1,000 times and store the median from each bootstrap sample.

Code:-

```
# 17-19. Bootstrap sampling
np.random.seed(42)
bootstrap_medians = []
num_bootstrap = 1000
for i in range(num_bootstrap):
    # Select observations with replacement
    bootstrap_sample = np.random.choice(
        revenue,
        size=len(revenue),
        replace=True
    )
    # Calculate median
    bootstrap_median = np.median(bootstrap_sample)
    # Store result
    bootstrap_medians.append(bootstrap_median)
# Convert to NumPy array
bootstrap_medians = np.array(bootstrap_medians)
```


20. Create a histogram of the bootstrap median values.

Code:-

```
# 20. Histogram of bootstrap median values
plt.figure(figsize=(8, 5))
plt.hist(
    bootstrap_medians,
    bins=30,
    edgecolor="black"
)
plt.axvline(
    original_median,
    linestyle="--",
    linewidth=2,
    label="Original Median"
)
```

```
plt.title("Bootstrap Distribution of Median Revenue")
plt.xlabel("Bootstrap Median Revenue")
plt.ylabel("Frequency")
plt.legend()
plt.grid(True)
plt.show()
```

Output:-



21. Calculate the 2.5th percentile and 97.5th percentile of the bootstrap median values.

Code:-

```
# 21. Calculate 2.5th and 97.5th percentiles
lower_percentile = np.percentile(
    bootstrap_medians,
    2.5
)

upper_percentile = np.percentile(
    bootstrap_medians,
    97.5
)

print("\nBootstrap Percentiles:")
print("2.5th Percentile:", round(lower_percentile, 2))
print("97.5th Percentile:", round(upper_percentile, 2))
```

Output:-

```
Bootstrap Percentiles:
2.5th Percentile: 232.87
97.5th Percentile: 273.61
```

22. Use these percentile values to calculate the 95% bootstrap confidence interval for the population median.

Code:-

```
# 22. 95% Bootstrap Confidence Interval
bootstrap_ci = (
    lower_percentile,
    upper_percentile
)
print("\n95% Bootstrap Confidence Interval:")
print(
    round(bootstrap_ci[0], 2),
    "to",
    round(bootstrap_ci[1], 2)
)
```

Output:-

```
95% Bootstrap Confidence Interval:
232.87 to 273.61
```

23. Display the original sample median and the bootstrap confidence interval.

Code:-

```
# 23. Display original median and bootstrap CI
bootstrap_result = pd.DataFrame({
    "Original Median": [original_median],
    "Lower 95% CI": [bootstrap_ci[0]],
    "Upper 95% CI": [bootstrap_ci[1]]
})
print("\nBootstrap Result:")
print(bootstrap_result.round(2))
```

Output:-

```
Bootstrap Result:
   Original Median  Lower 95% CI  Upper 95% CI
0           253.85         232.87         273.61
```

24. Compare the original median with the bootstrap confidence interval.

Code:-

```
# 24. Compare original median with CI
print("\nComparison:")
print("Original Median:", round(original_median, 2))
print(
    "Bootstrap CI:",
    round(bootstrap_ci[0], 2),
    "to",

```

```

round(bootstrap_ci[1], 2)
)
if bootstrap_ci[0] <= original_median <= bootstrap_ci[1]:
    print("The original median lies inside the bootstrap confidence interval.")
else:
    print("The original median lies outside the bootstrap confidence interval.")

```

Output:-

```

Comparison:
Original Median: 253.85
Bootstrap CI: 232.87 to 273.61
The original median lies inside the bootstrap confidence interval.

```

25. Interpret the bootstrap confidence interval in the context of supermarket revenue.

Code:-

```

# 25. Business interpretation
print("\nBusiness Interpretation:")
print(
    f"The bootstrap analysis estimates that the population median "
    f"revenue is likely to fall between {bootstrap_ci[0]:.2f} "
    f"and {bootstrap_ci[1]:.2f} with 95% confidence."
)

```

Output:-

```

Business Interpretation:
The bootstrap analysis estimates that the population median revenue is likely to fall between 232.87 and 273.61 with 95% confidence.

```

26. Write a conclusion explaining how confidence intervals and bootstrapping can help businesses make decisions using sample data.

Code:-

CONCLUSION

Confidence intervals provide a range of plausible values for population parameters such as mean revenue and customer proportion. They help businesses understand the uncertainty associated with sample data.

Bootstrapping repeatedly resamples the available data and calculates a statistic such as the median. This provides a bootstrap distribution that can be used to estimate a confidence interval without requiring strong assumptions about the population distribution.

Therefore, confidence intervals and bootstrapping help supermarket businesses make more reliable decisions about revenue, customers, sales performance, and business planning.