

Index number : 190026T

Name : AHAMED M.I.I

In []:

```

#1)

import numpy as np
import cv2 as cv
import matplotlib.pyplot as plt

f = open(r'E:\Aca\aca sem 4\Image Processing & Machine vision\exercises\exercise_08\
assert f is not None

n = int(f.readline())

#first image
l = f.readline().split()
im1_fn = l[0]
K1 = np.array([float(i) for i in l[1:10]]).reshape((3,3))
R1 = np.array([float(i) for i in l[10:19]]).reshape((3,3))
t1 = np.array([float(i) for i in l[19:22]]).reshape((3,1))

#second image
l = f.readline().split()
im2_fn = l[0]
K2 = np.array([float(i) for i in l[1:10]]).reshape((3,3))
R2 = np.array([float(i) for i in l[10:19]]).reshape((3,3))
t2 = np.array([float(i) for i in l[19:22]]).reshape((3,1))

im1 = cv.imread(r'E:\Aca\aca sem 4\Image Processing & Machine vision\exercises\exer
assert im1 is not None

im2 = cv.imread(r'E:\Aca\aca sem 4\Image Processing & Machine vision\exercises\exer
assert im2 is not None

fig , ax = plt.subplots(1,2,figsize=(15,15))
ax[0].imshow(cv.cvtColor(im1, cv.COLOR_BGR2RGB))
ax[0].set_title('Image 1')
ax[0].set_xticks([]), ax[0].set_yticks([])

ax[1].imshow(cv.cvtColor(im2, cv.COLOR_BGR2RGB))
ax[1].set_title('Image 2')
ax[1].set_xticks([]), ax[1].set_yticks([])

```

```

[[-2.87071497e-04 -3.96261289e-02  2.94221686e+02]
 [-3.55039713e-02  1.65329260e-04  1.78860854e+01]
 [-2.76702814e+02  2.12942175e+01 -9.06669374e+03]]

```

Image 1




Image 2



```
In [ ]: #2)

P1 = K1 @ np.hstack((R1,t1))
P2 = K2 @ np.hstack((R2,t2))

from scipy.linalg import null_space

def skew(x):
    x = x.ravel()
    return np.array ([[0, -x[2], x[1]], [x[2], 0, -x[0]], [-x[1], x[0], 0]])

C = null_space(P1)
C = C * np.sign(C[0,0])

e2 = P2 @ C

e2x = skew(e2)

F = e2x @ P2 @ np.linalg.pinv(P1)
print(F)
```

```
[[-2.87071497e-04 -3.96261289e-02  2.94221686e+02]
 [-3.55039713e-02  1.65329260e-04  1.78860854e+01]
 [-2.76702814e+02  2.12942175e+01 -9.06669374e+03]]
```

```
In [ ]: #3)

x = np.array([130, 115,1])

cv.circle(im1 , (x[0], x[1]), 5 , (0,0,255), -1)

fig , ax = plt.subplots()
ax.imshow(cv.cvtColor(im1, cv.COLOR_BGR2RGB))
ax.set_title('Image 1')
ax.set_xticks([]), ax.set_yticks([]);

l2 = F @ x.T
p1 = np.array([0, (l2[0]*0 + l2[2])/l2[1]]).astype(int)
p2 = np.array([500, (l2[0]*500 + l2[2])/l2[1]]).astype(int)

cv.line(im2, (p1[0],p1[1]),(p2[0], p2[1]),(255,0,0),5)

img1=cv.cvtColor(im1, cv.COLOR_BGR2RGB)
img2=cv.cvtColor(im2, cv.COLOR_BGR2RGB)

fig1 , ax = plt.subplots(1,2,figsize=(15,15))
ax[0].imshow(cv.cvtColor(im1, cv.COLOR_BGR2RGB))
ax[0].set_title('Image 1')
ax[0].set_xticks([], ax[0].set_yticks([])

ax[1].imshow(cv.cvtColor(im2, cv.COLOR_BGR2RGB))
ax[1].set_title('Image 2')
ax[1].set_xticks([], ax[1].set_yticks([]);
```

Image 1




Image 1





Image 2



In []:

```
#4)

sift = cv.SIFT_create()
# find the keypoints and descriptors with SIFT
kp1, des1 = sift.detectAndCompute(img1, None)
kp2, des2 = sift.detectAndCompute(img2, None)

FLANN_INDEX_KDTREE = 1
index_params = dict(algorithm = FLANN_INDEX_KDTREE, trees = 5)
search_params = dict(checks=50)
flann = cv.FlannBasedMatcher(index_params, search_params)
matches = flann.knnMatch(des1, des2, k=2)
pts1 = []
pts2 = []

for i, (m, n) in enumerate(matches):
    if m.distance < 0.8 * n.distance:
        pts2.append(kp2[m.trainIdx].pt)
        pts1.append(kp1[m.queryIdx].pt)

pts1 = np.int32(pts1)
pts2 = np.int32(pts2)
F, mask = cv.findFundamentalMat(pts1, pts2, cv.FM_LMEDS)

pts1 = pts1[mask.ravel() == 1]
pts2 = pts2[mask.ravel() == 1]

def drawlines(img1, img2, lines, pts1, pts2):
    r, c = img1.shape[0], img1.shape[1]
    img1 = cv.cvtColor(img1, cv.COLOR_RGB2BGR)
    img2 = cv.cvtColor(img2, cv.COLOR_RGB2BGR)
```

```

for r,pt1,pt2 in zip(lines,pts1,pts2):
    color = tuple(np.random.randint(0,255,3).tolist())
    x0,y0 = map(int, [0, -r[2]/r[1] ])
    x1,y1 = map(int, [c, -(r[2]+r[0]*c)/r[1] ])
    img1 = cv.line(img1, (x0,y0), (x1,y1), color,1)
    img1 = cv.circle(img1,tuple(pt1),5,color,-1)
    img2 = cv.circle(img2,tuple(pt2),5,color,-1)
return img1,img2

lines1 = cv.computeCorrespondEpilines(pts2.reshape(-1,1,2), 2,F)
lines1 = lines1.reshape(-1,3)
img5,img6 = drawlines(img1,img2,lines1,pts1,pts2)

lines2 = cv.computeCorrespondEpilines(pts1.reshape(-1,1,2), 1,F)
lines2 = lines2.reshape(-1,3)
img3,img4 = drawlines(img2,img1,lines2,pts2,pts1)
fig , ax = plt.subplots(1,2,figsize=(15,15))
ax[0].imshow(cv.cvtColor(img5, cv.COLOR_BGR2RGB))
ax[0].set_title('Image 1')
ax[0].set_xticks([]), ax[0].set_yticks([])

ax[1].imshow(cv.cvtColor(img3, cv.COLOR_BGR2RGB))
ax[1].set_title('Image 2')
ax[1].set_xticks([]), ax[1].set_yticks([])
plt.show()

```

Image 1




Image 2

