Keyless Anti-Theft Bicycle Lock System

"Research Paper Title: Electronic Development for a Keyless Anti-Theft Bicycle Lock System Prototype this is my reference research paper" *Generated by LeapSpace*

Key Findings: Electronic Development for a Keyless Anti-Theft Bicycle Lock System Prototype

Key Findings Table

Theme	Main finding	Population / system context	Citations
Authentication	Keyless bicycle-lock research is dominated by simple methods such as RFID, NFC, PIN, app-based access, and some biometric proposals, but security validation is usually limited.	Bicycle locks, bike sharing, adjacent smart-lock and two-wheeler systems	[1] [2] [3] [4] [5] [6] [7] [8] [9] [10]
RFID/NFC evidence	RFID is widely used as low-cost ID-matching access control, while NFC is favored for short-range phone-mediated access; however, bicycle-specific pairing, false accept/reject, and mutual-authentication data are largely absent.	RFID and NFC lock prototypes, mostly adjacent domains rather than bicycles	[1] [2] [3] [4] [11] [12] [13] [14]
Actuation	Servo, solenoid, DC motor, worm gear, relay, and ESP32-class control approaches form the main implementation toolkit for electronic lock release.	Bicycle rental locks, smart locks, adjacent latch systems	[15] [16] [17] [18] [19] [20] [21] [22] [23]
Reliability gap	Electromechanical feasibility is demonstrated, but unlocking force, release time, jam tolerance, and lifecycle reliability are rarely reported for bicycle locks.	Bicycle and adjacent lock prototypes	[18] [22] [24] [25] [26]

Theme	Main finding	Population / system context	Citations
Anti-theft features	The most mature layer in the literature is sensing and alerting: vibration, accelerometer, gyroscope, piezo sensing, alarms, SMS/GSM, app alerts, GPS, and tracking are common.	Bicycle and two-wheeler anti-theft systems	[15] [27] [28] [29] [30] [31]
Security evidence	Many systems claim improved security, but bicycle-specific adversarial tests against spoofing, relay, cutting, picking, or tamper opening are generally missing.	Bicycle locks and adjacent smart-lock contexts	[32] [33] [34] [35] [36] [37]
Power and durability	Low-power operation and outdoor exposure are recognized as critical, but repeated lock/unlock battery endurance and environmental failure sequences are seldom quantified for portable bicycle locks.	Portable bicycle locks, rental-bike nodes, e-bike systems	[38] [39] [40] [41] [42] [43] [44] [45] [46]
Usability and validation	The field is prototype-heavy but evaluation-light; convenience is a major motivator, yet lock-specific field trials, user error rates, and comparable metrics are sparse.	Cyclists, commuters, bike-share users, prototype studies	[27] [47] [48] [49] [50] [51] [52]

Direct Answer

For a reference paper titled **“Electronic Development for a Keyless Anti-Theft Bicycle Lock System Prototype,”** the strongest evidence-backed framing is that a solid prototype should be organized around **four subsystems**: **authentication**, **electronic actuation**, **tamper detection and alerting**, and **power/environmental robustness** [1] [15] [27] [39].

The literature supports presenting the system as follows:

1. **Authentication:** use a practical keyless method such as RFID, NFC, smartphone app, PIN, or fingerprint, but note that most published systems rely on simple ID matching or static credentials rather than thoroughly validated secure mutual authentication [1] [2] [3] [4] [9] [13].

2. **Actuation:** use a servo, solenoid, or motorized latch controlled by a microcontroller such as ESP32, because these mechanisms recur across bicycle-rental and adjacent smart-lock prototypes [15] [18] [19] [20].
3. **Anti-theft protection:** strengthen the lock with vibration or motion sensing, local alarm, and remote alert/tracking, since this is the most consistently developed part of the literature [27] [28] [29] [31].
4. **Evaluation:** your paper will be stronger if it measures unlock latency, false alarms, battery drain, and resistance to both cyber and physical tampering, because these are the main evidence gaps in existing work [34] [45] [50] [53].

Taken together, the evidence suggests that **electronic keyless bicycle locks are promising as integrated smart-security systems, but the literature does not yet prove that they are mechanically or cryptographically robust under real-world bicycle theft conditions** [15] [27] [34] [47].

Confidence level: High - This conclusion is directly supported by repeated cross-source patterns in authentication, actuation, sensing, and evaluation gaps [1] [15] [27] [39].

Study Scope

This report synthesizes prototype-oriented literature on **electronic keyless anti-theft bicycle lock systems** and nearby domains such as two-wheeler security, rental-bike locking, smart locks, and embedded latch systems [15] [27] [54]. The covered themes include **authentication architectures, electromechanical actuation, anti-theft sensing and alerting, power management, durability, and prototype validation** [1] [15] [28] [38] [50]. Methods represented in the evidence are mostly **design descriptions, proof-of-concept implementations, prototype demonstrations, and limited field observations**, with comparatively little standardized adversarial or longitudinal testing [27] [47] [48] [50].

Assumptions & Limitations

The evidence base is uneven: many cited systems are **adjacent smart-lock or two-wheeler prototypes rather than bicycle-lock-specific experiments**, so some design lessons are transferable but not bicycle-validated [11] [16] [34]. Bicycle-specific data on **false accept/false reject rates, anti-spoofing, unlocking force, jam tolerance, repeated-cycle battery life, and environmental failure order** are largely missing [12] [24] [44] [46]. Security claims in the literature often exceed the strength of the reported tests [15] [48] [55] [56].

Suggested Further Research

- Compare RFID, NFC, Bluetooth/app, PIN, and biometric access on the **same bicycle-lock platform** using common security and usability metrics [12] [13] [57].
- Measure **unlock time, false alarms, false accepts/rejects, jam tolerance, and repeated-cycle reliability** for the full electromechanical system [24] [25] [50] [53].

- Conduct **adversarial testing** against spoofing, relay, interception, tamper opening, and physical bypass, not just functional demonstrations [32] [34] [35].
- Quantify **battery endurance** under realistic standby sensing, alarm, communication, and lock/unlock cycles [38] [45] [58].
- Run **outdoor durability trials** for rain, humidity, sunlight, and corrosion exposure on bicycle-lock electronics and housings [42] [43] [46].

Full Report Body

Introduction and Problem Context

Conventional bicycle locks are repeatedly framed as a compromise between security and convenience: U-locks are treated as relatively strong but inconvenient, while cable locks are light yet easier to cut [47] [51]. Several sources also describe bicycle locking as a practical pain point for daily users, which motivates exploration of simpler keyless designs and app-mediated workflows [47] [48] [52]. In parallel, some prototype papers argue that conventional locks are easy to break or awkward to use, pushing design attention toward embedded or electronically enhanced anti-theft systems [47] [48].

The scope of electronic anti-theft bicycle-lock prototypes generally includes five linked elements: **authentication**, **actuation**, **tamper detection**, **communication/alerting**, and **power support** [1] [15] [27] [39]. Recent work increasingly combines these into broader connected-bike systems rather than treating the lock as a stand-alone mechanical object [15] [51] [59] [60].

Confidence level: High - The motivation and subsystem framing are consistently repeated across the retrieved synthesis and topic-specific learnings [15] [27] [47] [48].

Foundational Context

A keyless anti-theft bicycle lock prototype can be understood as a chain of decisions:

1. **Who is authorized?** - authentication by RFID, NFC, PIN, fingerprint, or app identity [1] [5] [9] [10].
2. **How is the lock physically released?** - servo, solenoid, or motorized latch under microcontroller control [15] [18] [19].
3. **How is theft or tampering detected?** - vibration, accelerometer, gyroscope, or related sensors [27] [28] [53].
4. **How is the owner informed or recovery supported?** - buzzer, SMS/GSM, Bluetooth, app, GPS, or cloud logging [23] [28] [30].
5. **Can the system survive real use?** - power management, battery availability, and environmental exposure [38] [42] [43].

This architecture matters because the literature shows that many prototypes are functionally complete at the block-diagram level, but only lightly tested as full systems under realistic cycling conditions [27] [47] [50]. Taken together, these findings suggest that the field has progressed further in **integration** than in **comparative validation** [15] [49].

Confidence level: High - This framework is a direct synthesis of the evidence themes and prototype descriptions [1] [15] [27] [39].

Keyless Authentication Architectures

RFID-based access control

RFID is repeatedly described as a low-cost access-control method in which the system reads a tag ID and unlocks when that ID matches stored data [1] [2] [3] [4]. In related lock implementations, RFID can also be paired with status reporting or local logging, as seen in an RFID/ESP-class prototype that used tag verification, a servo latch, a passive buzzer, and database logging [23].

However, the bicycle-specific evidence is thin. The retrieved set does **not** provide a bicycle-lock prototype with detailed RFID tag type, reader module, matching logic, false-accept/false-reject testing, or unauthorized-access measurements [11] [12] [61] [62]. So RFID is well supported as a **practical prototype choice**, but not yet as a **fully validated bicycle-security method** [1] [3] [12].

NFC and smartphone-mediated access

NFC is consistently described as a short-range contactless technology suitable for secure bilateral communication and mobile-device-based verification [5] [6] [7] [8]. In the retrieved NFC locking evidence, one paper used a smartphone NFC reader with a fixed lock controller and controlled access using a one-time password plus timestamp rather than a clearly documented mutual-authentication protocol [13]. This suggests stronger session logic than static ID matching, but still not a complete published security architecture [13].

App-mediated access is also common in bicycle-related prototypes. Some systems use a smartphone app and Bluetooth-connected on-bike hardware to control locking and unlocking, while adding vibration sensing, alarm functions, or GPS/GSM notifications [51] [59]. These approaches improve convenience and fit commuter workflows, but the evidence does not show robust head-to-head security or latency comparisons against RFID or NFC [14] [59].

PIN and biometric alternatives

PIN or password entry appears as an additional or fallback factor in some systems, but static credentials are explicitly noted as weaker because of low entropy and replay-style exposure risks [4] [9] [63]. One ESP32-based two-wheeler lock reported total access times of 6-8 seconds for static PIN and 9-13 seconds for rotating PIN, illustrating the convenience-security trade-off directly: stronger logic added latency [40].

Biometric authentication, especially fingerprint-based access, is proposed in several two-wheeler and dual-lock settings as a keyless replacement or supplement to passwords and keys [9] [10] [64] [65]. Yet the supplied bicycle-specific evidence does not show detailed enrollment procedures, commuter fallback design, or anti-spoofing measures for a bicycle-lock prototype [57] [66].

Authentication security limits

Across the literature, the dominant pattern is functional prototyping ahead of rigorous security validation. The sources mention threats such as brute force, relay, spoofing, impersonation, interception, and denial of service, but mostly in generic smart-lock or authentication contexts rather than bicycle-specific experiments [32] [33] [34] [35] [36]. The corpus therefore supports a cautious conclusion: **simple keyless access is common, but bicycle-specific evidence for strong anti-bypass authentication remains limited** [12] [13] [57].

Confidence level: High - The evidence strongly supports the prevalence of simple authentication methods and the lack of bicycle-specific comparative security testing [1] [5] [9] [12].

Actuation and Lock Control Design

Motorized release mechanisms

Electromechanical release mechanisms in the retrieved literature include **solenoids, DC motors, servos, and worm-gear arrangements**, controlled through PWM or cutoff logic [18] [19] [20] [21] [22]. In adjacent latch systems, one vehicle door latch used a motor and worm gear for power release, while a smart door lock used a self-latching relay and radio control [16] [17]. For bicycle-oriented rental/security work, a prototype used a servo-powered electronic lock controlled by an ESP32-based IoT module [15].

The implication is practical rather than definitive: these components are sufficient to build a working bicycle-lock prototype, but their bicycle-specific mechanical robustness is not yet well documented [15] [24].

Microcontrollers, relays, and drivers

ESP32-class controllers recur in bicycle and two-wheeler systems because they support integrated control, wireless communication, and sensor handling [15] [23] [40]. Related actuation control approaches include PWM servo drive, motor-current control, and microswitch-triggered cutoffs [18] [20] [22]. End-to-end prototypes also combine the actuator with alert peripherals such as LEDs, buzzers, and local data logging [23] [40].

Mechanical performance and reliability

This is one of the clearest gaps in the evidence. No retrieved bicycle-lock snippet reports measured **unlocking force, release time, jam tolerance, or wear-cycle reliability** [24] [25] [26]. Some adjacent embedded systems report harsh-condition verification or lab/track testing, such as an automotive power switch with self-diagnostics and a shift-by-wire actuator with performance comparisons, but these are not bicycle-lock reliability studies [67] [68].

For a strong reference paper, this means the actuation section should separate **feasibility** from **validated reliability**. Feasibility is supported; reliability remains under-characterized [15] [18] [24].

Integrated lock structures

Some bicycle anti-theft studies emphasize integrating the lock into the bicycle structure rather than treating it as an add-on device [48] [49] [69]. Another concept combines electronic locking with charging and GPS tracking, showing how the lock may become part of a multifunctional bicycle or docking ecosystem [60]. Taken together, these findings suggest a shift toward **integrated smart-bike security platforms** rather than isolated lock hardware [15] [48] [60].

Confidence level: High - The recurring toolkit and the reliability gap are both well supported across multiple actuation-related citations [15] [16] [17] [18] [24].

Anti-Theft Security Features and Alerting

Tamper detection sensors

Tamper detection is commonly implemented through accelerometers, gyroscopes, vibration sensors, and piezoelectric sensing [27] [28] [29]. One retrieved system used a BMA400 accelerometer interrupt triggered by unauthorized mechanical intrusion, while another low-power event detector aimed to keep false positives low in an outdoor setting [53] [70]. However, exact thresholds, debounce logic, and realistic bicycle-parking false-alarm rates are rarely reported [53] [70] [71].

Alarm and notification channels

The literature is strongest on alerting and recovery channels. Systems use local alarms, SMS/GSM messages, smartphone apps, and sometimes Bluetooth-linked feedback [15] [28] [30]. A smartphone-based two-wheeler theft system combined vibration sensing, SMS alerts, online database updates, and app-based lock/unlock and tracking [28]. A vision-based bicycle theft detector reportedly sent an image within 1-2 seconds and notified the owner and local authorities in real time, with field trials showing fewer theft incidents [31].

Attack resistance and bypass assumptions

The corpus explicitly mentions attack models including brute force, relay, spoofing, tampering, interception, and denial of service [32] [33] [34] [35] [36]. But there is a sharp mismatch between the **claimed** security benefits of electronic systems and the **reported** bicycle-specific evidence. No retrieved paper directly reports bicycle-lock bypass tests against cutting, tamper opening, relay, or spoofing [37]. Some adjacent smart-lock work instead argues resistance through communication security, while also noting that plaintext interception and DoS can still break systems [34].

Evidence of deterrence

Evidence for deterrence is limited but not absent. The strongest example in the set is the vision-based bicycle theft detector whose field trials reported a significant decrease in theft incidents [31]. Other alerting systems mainly provide qualitative or timing claims such as GSM alerts being sent “within a short period of time,” without quantified deterrence or human response measures [28] [30].

Confidence level: Medium-High - Sensing and alerting are strongly evidenced, but deterrence and bypass resistance remain less directly measured [27] [28] [31] [34].

Power Management, Durability, and Prototype Evaluation

Battery life and low-power operation

Low power is treated as essential because battery failure can disable the lock or make a shared bike unavailable [38] [40] [42]. Some bicycle-oriented prototypes claim low-power operation or use simplified local modes such as ESP32 SoftAP to reduce dependence on external servers and power use [39] [40]. Yet the retrieved set does not provide repeated lock/unlock battery-endurance data for portable bicycle locks [44] [45]. The best available low-power evidence comes from adjacent IoT nodes using sleep modes and low-duty-cycle sampling, which demonstrates relevant strategy but not bicycle-lock-specific runtime [45] [58].

Environmental durability

Outdoor operation exposes systems to temperature, humidity, sunlight, moisture, and corrosion [41] [42] [43]. Battery-powered rental-bike devices were specifically noted as being affected by outdoor conditions, and critical-voltage tracking was used to prevent failure [42]. However, no bicycle-security-specific test program in the evidence reports water-ingress failure order, corrosion sequence, or thermal-cycling breakdown for lock electronics [42] [46].

Usability and rider acceptance

Usability is a core motivation for keyless designs. The literature frames app-based and electronic systems as attempts to simplify the locking process and reduce the burden associated with conventional locks [47] [51] [52]. One keyless-lock paper reportedly included a customer survey on commuter preferences and lock-purchasing priorities, supporting the relevance of user-centered design [52]. Bike-share evidence also shows that multistep access procedures can be cumbersome, while smartphone integration improves convenience for shorter urban travel [72] [73].

Field testing and validation gaps

The strongest methodological pattern across the evidence is that the field is **prototype-heavy but evaluation-light** [27] [47] [48] [49]. Some riding-based validation exists, and one smart bicycle lock scheme was evaluated while riding [50]. But the retrieved set does not provide lock-specific field trials with comparable sample sizes and metrics such as unlock time, setup burden, user error rate, false-alarm rate, or long-term battery performance [74] [75] [76] [77].

Confidence level: High - The evidence consistently identifies power, durability, and validation as important but under-measured dimensions [27] [38] [42] [47].

Synthesis and Practical Design Implications

Taken together, the literature suggests that the most defensible architecture for a reference prototype is:

- **Primary keyless access:** RFID, NFC, or smartphone app [1] [5] [59]
- **Fallback access:** PIN or local override, acknowledging usability-security trade-offs [9] [40] [63]
- **Actuation:** servo or motorized latch under ESP32-class control [15] [23]
- **Tamper detection:** vibration/accelerometer sensing [27] [53]
- **Response:** buzzer plus phone/SMS/app alert, optionally GPS recovery [28] [30] [54]
- **Robustness layer:** low-power standby strategy and outdoor-protective enclosure [40] [43] [45]

Inferred: A next-generation bicycle lock would likely be stronger if it used **layered authentication** and **graduated anti-theft response**, because the literature shows overreliance on simple credentials and post-theft tracking rather than pre-theft intervention [12] [34] [78].
Confidence level: Low - This is a synthesis-driven design inference, not a directly tested finding.

Conclusion

The evidence supports using your reference paper as a study of an **integrated electronic bicycle security prototype** rather than only a lock mechanism [15] [27] [60]. The literature clearly supports discussing **simple keyless authentication**, **microcontroller-driven electromechanical locking**, and **sensor-based alert/tracking subsystems** as the current mainstream design pattern [1] [15] [28]. It also clearly shows that the field still lacks rigorous evidence on **authentication hardening, bicycle-specific bypass resistance, electromechanical reliability, battery endurance, environmental durability, and commuter-centered field testing** [12] [24] [37] [46] [74].

So the strongest academic positioning for your paper is: **the prototype is technically feasible and aligned with current smart-bike security trends, but its main scholarly value will increase substantially if it reports full-system validation rather than only successful implementation** [27] [47] [50].

Overall conclusion confidence: High - This conclusion closely matches the cross-source synthesis and repeated evidence gaps identified throughout the supplied corpus [1] [15] [27] [38].

References

1. Inamati, S.R., Sinchana, H.V., Narendra, R.N., (...), Singh, V. (2025) Automatic Door Opening System Using RFID and Arduino System. *2025 International Conference on Intelligent Control, Computing and Communications, IC3 2025*. https://doi.org/10.1109/IC363308.2025.10956406
2. Harshitha, G., Gopika, S.N., Gourinandan, B., (...), Nalinakshan, S. (2025) RFID based Access Control System. *3rd International Conference on Electronics and Renewable Systems, ICEARS 2025 - Proceedings*. https://doi.org/10.1109/ICEARS64219.2025.10941511
3. Dhari, R.R.V., Venkatesh, V. (2016) RFID based smart car parking and security system using Arduino. *Research Journal of Pharmaceutical, Biological and Chemical Sciences*. https://www.scopus.com/pages/publications/84955258681
4. Mohammed, S., Alkeelani, A.H. (2019) Locker Security System Using Keypad and RFID. *Proceedings of 2019 International Conference of Computer Science and Renewable Energies, ICCSRE 2019*. https://doi.org/10.1109/ICCSRE.2019.8807588
5. Pasquet, M., Vacquez, D., Reynaud, J., Cuozzo, F. (2009) Contactless Payment with RFID and NFC. *Ubiquitous and Pervasive Computing: Concepts, Methodologies, Tools, and Applications: Volume 1*. https://doi.org/10.4018/978-1-60566-960-1.ch009
6. Harris, D. (2007) Navigation systems to go beyond turn-by-turn directions. *Electronic Design*. https://www.scopus.com/pages/publications/34547226900
7. Yu, M.-D., Devadas, S. (2016) Pervasive, Dynamic Authentication of Physical Items. *Queue*. https://doi.org/10.1145/3028687.3047967

8. Chen, J., Hu, M. (2016) Android based smart isolation and anti-misoperation system. *59th ISA Power Industry Division Symposium 2016, POWID 2016*. https://www.scopus.com/pages/publications/85018373628

9. Dombale, A., Thakare, C., Thorve, M., (...), Zagade, S. (2024) Biometric Authentication System for Two Wheeler. *Proceedings - 2024 4th International Conference on Pervasive Computing and Social Networking, ICPCSN 2024*. https://doi.org/10.1109/ICPCSN62568.2024.00116

10. Li, C., Yang, Y.-X., Niu, X.-X. (2006) Biometric-based personal identity-authentication system and security analysis. *Journal of China Universities of Posts and Telecommunications*. https://doi.org/10.1016/S1005-8885(07)60032-6

11. Ali, Ahmad, Ahmed, Mansoor, Khan, Abid, (...), Helfert, Markus (2021) VisTAS: blockchain-based visible and trusted remote authentication system. *PeerJ Computer Science*. https://doi.org/10.7717/peerj-cs.516

12. Kang, J., Fan, K., Zhang, K., (...), Yang, Y. (2021) An ultra light weight and secure RFID batch authentication scheme for IoMT. *Computer Communications*. https://doi.org/10.1016/j.comcom.2020.12.004

13. Hung, C.-H., Bai, Y.-W., Ren, J.-H. (2016) Design and implementation of a single button operation for a door lock control system based on a near field communication of a smartphone. *5th IEEE International Conference on Consumer Electronics - Berlin, ICCE-Berlin 2015*. https://doi.org/10.1109/ICCE-Berlin.2015.7391251

14. Yang, Y., Xun, Y., Yan, Y., (...), Jin, Z. (2023) NFC-IDS: An Intrusion Detection System Based on RF Signals for NFC Security. *2023 International Wireless Communications and Mobile Computing, IWCMC 2023*. https://doi.org/10.1109/IWCMC58020.2023.10182412

15. Vijay Sathappan, M., Sujatha, S., Rathish, A., (...), Tham, M.-L. (2025) Sustainable Smart Lock for Vehicle Rentals in Controlled Environment. *5th IEEE International Conference on Innovations in Power and Advanced Computing Technologies, i-PACT 2025*. https://doi.org/10.1109/i-PACT65952.2025.11307942

16. Wang, Q., Hang, L., Wang, Y., (...), Chen, Y. (2019) Configuration synthesis of side door latch power release mechanism. *2019 IEEE 3rd International Conference on Electronic Information Technology and Computer Engineering, EITCE 2019*. https://doi.org/10.1109/EITCE47263.2019.9094953

17. Pradeepkumar, G., Rohith Bhat, C., Senthilvadivu, K., (...), Kumar, N.S. (2023) A Novel Hybrid Approach to Smart Door Locking System based on Real Time Data Transmission. *2023 14th International Conference on Computing Communication and Networking Technologies, ICCCNT 2023*. https://doi.org/10.1109/ICCCNT56998.2023.10306404

18. Morales Herrera, R., Feliu Batlle, V., Gonzalez-Rodriguez, A. (2010) Optimized obstacle avoidance trajectory generation for a reconfigurable staircase climbing wheelchair. *Robotics and Autonomous Systems*. https://doi.org/10.1016/j.robot.2009.07.020

19. Liu, Fengyu, Chen, Li, Yao, Jian, (...), Yin, Chengliang (2018) Design, modeling, and analysis of wedge-based actuator with application to clutch-to-clutch shift. *Proceedings of the Institution of Mechanical Engineers, Part D: Journal of Automobile Engineering*. https://doi.org/10.1177/0954407017727178

20. Yang, L., Wang, W., Yang, C., (...), Yang, H. (2023) An adaptive receding horizon-based flexible mode switching control strategy of parallel hybrid electric vehicles. *Control Engineering Practice*. https://doi.org/10.1016/j.conengprac.2023.105537

21. Ye, X., Xu, X., Wen, T., Han, B. (2021) Design and optimization of repeatable locking/unlocking device for magnetically suspended control moment gyro. *Acta Astronautica*. https://doi.org/10.1016/j.actaastro.2021.05.025

22. Lee, W.-B., Park, H.-C., Ahn, K.-H., Song, J.-B. (2018) Safe robot joint brake based on an elastic latch module. *Mechatronics*. https://doi.org/10.1016/j.mechatronics.2018.10.007

23. Islam, L., Al Zabir Shammo, M.B., Hossain, M.I., (...), Trapa, T.B. (2026) Real-Time RFID Authentication and Access Control System with Networked Logging. *2026 IEEE 2nd International Conference on Quantum Photonics, Artificial Intelligence and Networking, QPAIN 2026*. https://doi.org/10.1109/QPAIN69676.2026.11546467

24. Ma, Zhichao, Zhao, Hongwei, Li, Qinchao, (...), Lu, Shuai (2013) *The Review of Scientific Instruments*. https://doi.org/10.1063/1.4798545

25. Wang, Mingyuan, Hang, Lubin (2020) Research and application of variable DOF compliant five-bar mechanism based on novel compliant torsion joint in vehicle side door latch. *Proceedings of the Institution of Mechanical Engineers, Part C: Journal of Mechanical Engineering Science*. https://doi.org/10.1177/0954406220917423

26. Esteves, David Seixas, Pereira, Manuel F. C., Ribeiro, Ana, (...), Sequeiros, Elsa W. (2023) Development of MWCNT/Magnetite Flexible Triboelectric Sensors by Magnetic Patterning. *Polymers*. https://doi.org/10.3390/polym15132870

27. Cabalquinto, E.D.M., Malabayabas, L.M., Pulido, K.A.A., (...), Domingo Lopez, D.J. (2022) Anti-theft Integrated Bike Lock with Gyroscope Sensor and Accelerometer Motion Detection. *2022 IEEE 14th International Conference on Humanoid, Nanotechnology, Information Technology, Communication and Control, Environment, and Management, HNICEM 2022*. https://doi.org/10.1109/HNICEM57413.2022.10109492

28. Krishnaprasad, C., Albin Joseph, C.R., Sarath, I.S., Rahul Manohar, O. (2021) A novel low-cost theft detection system for two wheelers with minimum carbon foot print. *2021 2nd International Conference for Emerging Technology, INCET 2021*. https://doi.org/10.1109/INCET51464.2021.9456414

29. Pălăcean, A.-V., Tranca, D.-C., Contasel, C., (...), Dutescu, C. (2021) IoT Enabled Optimized Architectures for GPS Anti-Theft Tracking Devices. *Proceedings - RoEduNet IEEE International Conference*. https://doi.org/10.1109/RoEduNet54112.2021.9638274

30. Ng, C.K., Wee, K.S., Noordin, N.K., (...), Raja Abdullah, R.S.A. (2008) Theft prevention using wireless security system (WSS). *2008 IEEE International RF and Microwave Conference, RFM 2008*. https://doi.org/10.1109/RFM.2008.4897429

31. Ripa, T.S., Hasib Khan, T.F., Rokonuzzaman, M., (...), Zim, K.M. (2024) Bicycle Theft Detection by using YOLOv5s and DeepSORT algorithm. *International Conference on Recent Progresses in Science, Engineering and Technology, ICRPSET 2024*. https://doi.org/10.1109/ICRPSET64863.2024.10955901

32. Belk, M., Fidas, C., Germanakos, P., Samaras, G. (2017) The interplay between humans, technology and user authentication: A cognitive processing perspective. *Computers in Human Behavior*. https://doi.org/10.1016/j.chb.2017.06.042

33. Yang, Z., Tian, W., Li, R., (...), Xu, Z. (2025) Nis-PoW: Non-interactive secure Proof of Ownership for cloud storage. *Journal of Systems Architecture*. https://doi.org/10.1016/j.sysarc.2025.103538

34. Heiding, F., Süren, E., Olegard, J., Lagerström, R. (2023) Penetration testing of connected households. *Computers and Security*. https://doi.org/10.1016/j.cose.2022.103067

35. Kim, K., Kim, J.S., Jeong, S., (...), Kim, H.K. (2021) Cybersecurity for autonomous vehicles: Review of attacks and defense. *Computers and Security*. https://doi.org/10.1016/j.cose.2020.102150

36. Huang, Y., Xu, G., Song, X., (...), Wang, Q. (2024) A quantum-secure certificateless aggregate signature protocol for vehicular ad hoc networks. *Vehicular Communications*. https://doi.org/10.1016/j.vehcom.2024.100775

37. Rybarczyk, G., Sklar, A., Platt, L., Yan, X. (2025) E-bicyclist experiences in motor city: A mixed computational and content analysis approach for understanding sustainable micromobility. *Case Studies on Transport Policy*. https://doi.org/10.1016/j.cstp.2025.101581

38. Wilkman, V., Hautaniemi, L., Vaari, A.-M., (...), Kuosmanen, P. (2016) Electronic lock mechanism for bicycle. *Proceedings of the International Conference of DAAAM Baltic "Industrial Engineering"*. https://www.scopus.com/pages/publications/85054328956

39. Jian, Y., Ji, J. (2019) Research and Implementation of Electric Bicycle Anti-Theft System. *IOP Conference Series: Materials Science and Engineering*. https://doi.org/10.1088/1757-899X/677/3/032056

40. Painter, P., Waghmare, V., Katte, P., (...), Chavan, S. (2025) WiFi Lock for Bike Security with PIN Authentication. *International Conference on Emerging Technologies in Electronics and Green Energy, ICETEG 2025*. https://doi.org/10.1109/ICETEG66194.2025.11473153

41. Kitano, R., Miyasaka, A., Yamashita, A., Shodai, T. (2007) Charge/discharge characteristics of a backup power supply system using nickel metal hydride batteries. *INTELEC, International Telecommunications Energy Conference (Proceedings)*. https://doi.org/10.1109/INTLEC.2007.4448853

42. Mark, R., Angilletta, I. (2025) Process Mining in Battery Life Cycle. *Business Process Management Cases Vol. 3: Implementation in Practice*. https://doi.org/10.1007/978-3-031-80793-0_15

43. Parker, M.J., Novac, B.M., Smith, I.R., Louverdis, G. (2011) A low-energy, flexible pulsed-power generator for general purpose indoor and outdoor experimentation. *Digest of Technical Papers-IEEE International Pulsed Power Conference*. https://doi.org/10.1109/PPC.2011.6191464
44. Garche, J., Moséley, P.T. (2017) Lead-acid batteries for E-bicycles and E-scooters. *Lead-Acid Batteries for Future Automobiles*. https://doi.org/10.1016/B978-0-444-63700-0.00018-0
45. Fort, Ada, Landi, Elia, Mugnaini, Marco, (...), Vignoli, Valerio (2022) Performance Evaluation of an IoT Sensor Node for Health Monitoring of Artwork and Ancient Wooden Structures. *Sensors (Basel, Switzerland)*. https://doi.org/10.3390/s22249794
46. Zhang, J., Xie, D., Xu, Z., (...), Ge, X. (2025) Impact of Elevated Humidity Conditions on the Thermal and Mechanical Reliability of Silicon Carbide MOSFETs. *2025 IEEE Workshop on Wide Bandgap Power Devices and Applications in Asia, WiPDA Asia 2025*. https://doi.org/10.1109/WiPDA-Asia63772.2025.11184082
47. Ismail, I.N., Zuhair Zakariya, M.A., Azman, N.S., (...), Abd Rahman, M.S.A. (2021) Mechanical analysis for a keyless anti-theft bicycle lock system prototype. *AIP Conference Proceedings*. https://doi.org/10.1063/5.0044275
48. Huang, Y.-C., Tai-Shen, T.-S. (2017) A study for prevent theft of the bike design and analysis. *IOP Conference Series: Materials Science and Engineering*. https://doi.org/10.1088/1757-899X/241/1/012020
49. Lardón-Amat, P., De-Cózar-Macías, O.D., Castillo-Rueda, F.J., (...), Miravet-Garret, L. (2019) Multifunctional device for bicycles. *Lecture Notes in Mechanical Engineering*. https://doi.org/10.1007/978-3-030-12346-8_12
50. Arno, A., Toyoda, K., Sasase, I. (2015) Accelerometer assisted authentication scheme for smart bicycle lock. *IEEE World Forum on Internet of Things, WF-IoT 2015 - Proceedings*. https://doi.org/10.1109/WF-IoT.2015.7389108
51. Ismail, I.N., Zakariya, M.A.Z., Azman, N.S., (...), Hussin, M.S.F. (2021) Electronic development for a keyless anti-theft bicycle lock system prototype. *AIP Conference Proceedings*. https://doi.org/10.1063/5.0044264
52. Ismail, I.N., Zuhair Zakariya, M.A., Azman, N.S., (...), Abd Rahman, M.S.A. (2021) Customer survey analysis for a keyless anti-theft bicycle lock system prototype. *AIP Conference Proceedings*. https://doi.org/10.1063/5.0044270
53. https://www.sciencedirect.com/science/article/pii/S2730723926000667
54. Lee, S., Tewolde, G., Kwon, J. (2014) Design and implementation of vehicle tracking system using GPS/GSM/GPRS technology and smartphone application. *2014 IEEE World Forum on Internet of Things, WF-IoT 2014*. https://doi.org/10.1109/WF-IoT.2014.6803187

55. Ibrahim, O.A., Hussain, A.M., Oligeri, G., Di Pietro, R. (2019) Key is in the Air: Hacking Remote Keyless Entry Systems. *Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)*. https://doi.org/10.1007/978-3-030-16874-2_9

56. Maro, E., Kovalchuk, M. (2018) Bypass biometric lock systems with gelatin artificial fingerprint. *ACM International Conference Proceeding Series*. https://doi.org/10.1145/3264437.3264439

57. Binbeshr, F., Mat Kiah, M.L., Por, L.Y., Zaidan, A.A. (2021) A systematic review of PIN-entry methods resistant to shoulder-surfing attacks. *Computers and Security*. https://doi.org/10.1016/j.cose.2020.102116

58. Méndez, B., Lamo, P. (2026) IoT node for monitoring and traceability of live plants in maritime transport. *Array*. https://doi.org/10.1016/j.array.2025.100621

59. Zala, D.K. (2018) Bike Security with Theft Prevention. *Proceedings of the 3rd International Conference on Inventive Computation Technologies, ICICT 2018*. https://doi.org/10.1109/ICICT43934.2018.9034252

60. Ulinuha, A., Asy'ari, H., Efendi, T.W., Setyawan, A. (2025) Development of Electric Bicycle and Photovoltaic Powered Charging Station Complemented with Security Features. *International Journal on Energy Conversion*. https://doi.org/10.15866/irecon.v13i4.25845

61. Allen, A., Mylonas, A., Vidalis, S., Gritzalis, D. (2024) Smart homes under siege: Assessing the robustness of physical security against wireless network attacks. *Computers and Security*. https://doi.org/10.1016/j.cose.2023.103687

62. Tu, Y., Piramuthu, S. (2017) Lightweight non-distance-bounding means to address RFID relay attacks. *Decision Support Systems*. https://doi.org/10.1016/j.dss.2017.06.008

63. Naidu, B.R., Bhavani, K.V.L., Someswara Rao, Ch., Prasad Reddy, P.V.G.D. (2019) Comparative analysis of three single trait biometric authentication models. *Proceedings of the 2019 IEEE International Conference on Communication and Signal Processing, ICCSP 2019*. https://doi.org/10.1109/ICCSP.2019.8698041

64. Tshomo, K., Tshering, K., Gyeltshen, D., (...), Muramatsu, K. (2019) Dual Door Lock System Using Radio-Frequency Identification and Fingerprint Recognition. *2019 IEEE 5th International Conference for Convergence in Technology, I2CT 2019*. https://doi.org/10.1109/I2CT45611.2019.9033636

65. Matyas, V., Říha, Z. (2003) Toward reliable user authentication through biometrics. *IEEE Security and Privacy*. https://doi.org/10.1109/MSECP.2003.1203221

66. Sajjad, M., Khan, S., Hussain, T., (...), Baik, S.W. (2019) CNN-based anti-spoofing two-tier multi-factor authentication system. *Pattern Recognition Letters*. https://doi.org/10.1016/j.patrec.2018.02.015

67. Costantino, N., Serventi, R., Tinfena, F., (...), Fanucci, L. (2011) Design and test of an HV-CMOS intelligent power switch with integrated protections and self-diagnostic for harsh automotive applications. *IEEE Transactions on Industrial Electronics*. https://doi.org/10.1109/TIE.2010.2084979

68. Baronti, F., Lazzeri, A., Roncella, R., (...), Saponara, S. (2013) Design and characterization of a robotized gearbox system based on voice coil actuators for a formula sae race car. *IEEE/ASME Transactions on Mechatronics*. https://doi.org/10.1109/TMECH.2011.2162632

69. Tang, K., Liu, Y.Y., Wu, G., Liu, B.M. (2018) Research on structural integration design based on bicycle and the lock. *IPPTA: Quarterly Journal of Indian Pulp and Paper Technical Association*. https://www.scopus.com/pages/publications/85061757939

70. Smidla, József, Simon, Gyula (2013) Accelerometer-Based Event Detector for Low-Power Applications. *Sensors (Basel, Switzerland)*. https://doi.org/10.3390/s131013978

71. Jannah, A.N., Moridpour, S., Tay, R., Du, B. (2025) Cyclist safety in the digital age: A review of advanced warning technologies. *Accident Analysis and Prevention*. https://doi.org/10.1016/j.aap.2025.108069

72. Médard de Chardon, Cyrille (2021) Bicycle Sharing. *International Encyclopedia of Transportation*. https://doi.org/10.1016/B978-0-08-102671-7.10608-6

73. Pan, Lijun, Xia, Yangkun, Xing, Lining, (...), Xu, Yunbao (2022) Exploring Use Acceptance of Electric Bicycle-Sharing Systems: An Empirical Study Based on PLS-SEM Analysis. *Sensors (Basel, Switzerland)*. https://doi.org/10.3390/s22187057

74. Dubbeldam, R., Baten, C., Buurke, J.H., Rietman, J.S. (2017) SOFIE, a bicycle that supports older cyclists?. *Accident Analysis and Prevention*. https://doi.org/10.1016/j.aap.2016.09.006

75. Kim, Ye-Eun, Kim, Dong-Eun (2025) Investigating thermoplastic-elastomer-based 3D-Printed mesh and honeycomb structures for cycling gloves. *Journal of Industrial Textiles*. https://doi.org/10.1177/15280837251327737

76. Dubbeldam, R., Baten, C.T.M., Straathof, P.T.C., (...), Rietman, J.S. (2017) The different ways to get on and off a bicycle for young and old. *Safety Science*. https://doi.org/10.1016/j.ssci.2016.01.010

77. Liu, P., Jiang, Z., Li, T., (...), Xu, Z. (2021) User experience and usability when the automated driving system fails: Findings from a field experiment. *Accident Analysis and Prevention*. https://doi.org/10.1016/j.aap.2021.106383

78. Crisgar, P.V., Wijaya, P.R., Pakpahan, M.D.F., (...), Hasanuddin, M.O. (2021) GPS-based vehicle tracking and theft detection systems using google cloud IoT Core Firebase. *Proceeding - 2021 International Symposium on Electronics and Smart Devices: Intelligent Systems for Present and Future Challenges, ISESD 2021*. https://doi.org/10.1109/ISESD53023.2021.9501928