

Homework 3 | Rental Housing Listings

Pragya Apurva | DATA 260 | September 21, 2026

Personal configuration	Value	Calculation / meaning
SID4	6102	Last four student-ID digits
PORT_BASE	8702	$8000 + (6102 \bmod 900)$
PREFIX	s6102	"s" + SID4
SEED	6102	SID4
VERIFY_SEED	266102	$260000 + \text{SID4}$
DOMAIN_ID	6	$6102 \bmod 8$; Rental Housing Listings

Part 1 adds login, logout and session management to the existing rental application. Part 2 compares token, semantic and sentence-window chunking for searching housing documents.

Hardware: MacBook Air, Apple M4, 10 logical CPUs, 24 GiB memory; macOS 15.7.4, arm64. Python 3.12.14.

Local model: sentence-transformers/all-MiniLM-L6-v2 for Part 2 embeddings, running on CPU with one PyTorch thread. Part 1 does not use an AI model.

Repository: <https://github.com/ishuapurva1996/data260-6102>

Repository access confirmed for Sbnikitha and supriyaselvangesan on September 21, 2026.

Tested code (hw3-code) commit: 96b04abc04bb4cde131958ba38f37116336a4442

Submission tag: hw3 | <https://github.com/ishuapurva1996/data260-6102/tree/hw3>

Part 1 | Login and session management

HTTP does not remember earlier requests, so a session connects later requests to a user's login. Starlette's SessionMiddleware stores the username and a random session ID in a signed cookie. The signature detects changes; it does not encrypt the contents. The password is not stored in the cookie.

The server keeps the active session IDs and their last-activity times. Dashboard access requires a valid cookie and an active matching entry. Logout or expiry removes that entry, so even a saved copy of the cookie stops working.

Route	Behavior
GET /	Rental homepage; Login when signed out; Dashboard and Logout when signed in
GET /login	Username and password form
POST /login	admin / password: 303 to /dashboard; invalid credentials: 401 and a Bootstrap alert
GET /dashboard	Welcome with username; 303 to /login without an active session
GET /logout	Revoke the session, clear the cookie and redirect to /

code/web_application/main.py | lines 108-116

```
app.add_middleware(
    SessionMiddleware,
    secret_key=secret_key or os.environ.get("SECRET_KEY") or secrets.token_urlsafe(32),
    session_cookie="session",
    max_age=3600,
    same_site="lax",
    https_only=True,
)
app.include_router(auth.router)
```

The routes are in routers/auth.py. This single-worker teaching app uses public demo credentials and keeps sessions in memory. A restart clears them. The existing rental API remains unchanged and does not require login.

```
base login: Mon Sep 21 20:55:10 on 103001
(base) pragyapurva@Pragya-MacBook-Air ~ % cd "/Users/pragyaapurva/Documents/SJSU/DATA 260/HW3/worktrees/integration"
.venv-web/bin/python scripts/run_hw03_web.py --host ::1 --port 8702
INFO: Started server process [7833]
INFO: Waiting for application startup.
INFO: Application startup complete.
INFO: Uvicorn running on https://[::1]:8702 (Press CTRL+C to quit)
```

HTTPS application startup on port 8702.

Part 1 | Home page

The homepage retains the rental controls and changes its navigation when a user signs in.

code/web_application/routers/auth.py | lines 33-37

```
@router.get("/", response_class=HTMLResponse)
async def home(request: Request):
    return templates.TemplateResponse(
        request=request, name="index.html", context={"user": current_user(request)},
        headers=NO_STORE,
    )
```

The screenshot shows a web browser window with the URL `https://[::1]:8702`. The page title is "Rental Housing Listings". Below the title, there is a welcome message: "Welcome. Create and manage rental housing listings." Below this, there is a login section with the text "Log in to visit your protected dashboard." and a green "Login" button. Below the login section, there is a "Create a listing" form. The form has five fields: "Listing Title *" (with placeholder "e.g., Zia Apartment"), "Address *" (with placeholder "e.g., 999 Main Street, CA"), "Landlord Email *" (with placeholder "landlord@email.com"), "Description *" (with placeholder "e.g., Spacious two-bedroom apartment with parking" and a note "Enter more than 25 characters."), and "Property Type *" (a dropdown menu with the text "Choose a property type").

Homepage before login.

Part 1 | Home after login

After login, the homepage displays the username and links to the dashboard and logout.

code/web_application/routers/auth.py | lines 33-37

```
@router.get("/", response_class=HTMLResponse)
async def home(request: Request):
    return templates.TemplateResponse(
        request=request, name="index.html", context={"user": current_user(request)},
        headers=NO_STORE,
    )
```

The screenshot shows a web browser window with the address bar displaying "Not Secure https://[::1]:8702". The page title is "Rental Housing Listings". The navigation bar includes links for "Home", "Dashboard", and "Logout". The main content area features a welcome message: "Welcome. Create and manage rental housing listings." Below this, a notification box states "You are logged in as admin." with two buttons: "Go to dashboard" (green) and "Logout" (red). The primary section is titled "Create a listing" and contains several form fields: "Listing Title *" (with placeholder "e.g., Zia Apartment"), "Address *" (with placeholder "e.g., 999 Main Street, CA"), "Landlord Email *" (with placeholder "landlord@email.com"), "Description *" (with placeholder "e.g., Spacious two-bedroom apartment with parking" and a note "Enter more than 25 characters."), and "Property Type *" (a dropdown menu with the option "Choose a property type").

Homepage with an active admin session.

Part 1 | Login form

The login page uses a Bootstrap card with labeled username and password fields.

code/web_application/routers/auth.py | lines 40-45

```
@router.get("/login", response_class=HTMLResponse)
async def login_page(request: Request):
    return templates.TemplateResponse(
        request=request, name="login.html",
        context={"user": current_user(request), "error": None}, headers=NO_STORE,
    )
```

The screenshot shows a web application interface for 'Rental Housing Listings'. At the top, there is a dark navigation bar with the site name on the left and 'Home' and 'Login' links on the right. The main content area has a light gray background. In the center, there is a white Bootstrap card titled 'Login'. Above the card, the text 'Access your Rental Housing Listings dashboard.' is displayed. The card contains two input fields: 'Username' and 'Password'. Below these fields is a green 'Login' button. A blue link 'Back to listings' is positioned at the bottom left of the card. At the very bottom of the page, a small footer reads 'Rental Housing Listings - DATA 260 - s6102'.

Login form.

Part 1 | Invalid login

The form uses a Bootstrap card, labeled inputs and a submit button. Invalid credentials return HTTP 401 and display an alert above the form.

code/web_application/routers/auth.py | lines 59-64

```
if username != "admin" or password != "password":
    return templates.TemplateResponse(
        request=request, name="login.html",
        context={"user": None, "error": "Invalid username or password."},
        status_code=401, headers=NO_STORE,
    )
```

Rental Housing Listings

Home Login

Login

Access your Rental Housing Listings dashboard.

Invalid username or password.

Username

Password

Login

[Back to listings](#)

Rental Housing Listings · DATA 260 · s6102


Alert after an invalid username or password.

Part 1 | Protected dashboard

A successful login redirects to the dashboard, which displays admin and the 300-second idle limit. The route checks the server's session registry before displaying the page.

code/web_application/routers/auth.py | lines 74-77

```
async def dashboard(request: Request):
    user = current_user(request)
    if user is None:
        return RedirectResponse("/login", status_code=303, headers=NO_STORE)
```



Dashboard after a successful login.

Part 1 | Logout

Logout removes the server's session entry, clears the browser cookie and returns to the homepage.

code/web_application/routers/auth.py | lines 89-91

```
async def logout(request: Request):  
    revoke_session(request)  
    return RedirectResponse("/", status_code=303, headers=NO_STORE)
```

The screenshot shows a web browser window with the URL `https://[::1]:8702`. The page title is "Rental Housing Listings". The header has "Home" and "Login" links. The main content area has a heading "Rental Housing Listings" and a subheading "Welcome. Create and manage rental housing listings." Below this is a box with the text "Log in to visit your protected dashboard." and a green "Login" button. Further down is a "Create a listing" form with the following fields: "Listing Title *" (with placeholder "e.g., Zia Apartment"), "Address *" (with placeholder "e.g., 999 Main Street, CA"), "Landlord Email *" (with placeholder "landlord@email.com"), "Description *" (with placeholder "e.g., Spacious two-bedroom apartment with parking" and a note "Enter more than 25 characters."), and "Property Type *" (a dropdown menu with "Choose a property type" selected).

Homepage after logout, with Login available again.

Part 1 | Reusing a logged-out cookie

The terminal check logs in and saves the cookie. It first reaches /dashboard with HTTP 200, then logs out and sends the same saved cookie again. The second dashboard request returns HTTP 303 to /login.

code/web_application/routers/auth.py | lines 26-30

```
def revoke_session(request: Request) -> None:
    session = request.session
    sid = session.get("sid") if isinstance(session, dict) else None
    request.app.state.session_store.revoke(sid)
    request.scope["session"] = {}
```

```
(base) pragyapurva@Pragya-MacBook-Air integration % .venv-web/bin/python ../../manual-screenshots-20260921/capture_session_checks.py logout
Live authentication check: logout
UTC: 2026-09-22T04:07:33.877154+00:00
Server: https://[::1]:8702

POST /login -> HTTP 303
Location: /dashboard
GET /dashboard -> HTTP 200
GET /logout -> HTTP 303
Location: /
Replaying the same saved cookie after logout:
GET /dashboard -> HTTP 303
Location: /login
PASS: the logged-out cookie cannot reopen the dashboard.
GET /logout -> HTTP 303
Location: /
(base) pragyapurva@Pragya-MacBook-Air integration %
```

The saved cookie is rejected after logout.

Part 1 | Secure session cookie

HttpOnly prevents ordinary page JavaScript from reading the cookie. Secure restricts it to HTTPS, and SameSite=lax limits cross-site sending. Max-Age=3600 sets the cookie lifetime; the server enforces the shorter idle timeout separately.

code/web_application/main.py | lines 108-115

```
app.add_middleware(
    SessionMiddleware,
    secret_key=secret_key or os.environ.get("SECRET_KEY") or secrets.token_urlsafe(32),
    session_cookie="session",
    max_age=3600,
    same_site="lax",
    https_only=True,
)
```

```
(base) pragyapurva@Pragyas-MacBook-Air ~ %
(base) pragyapurva@Pragyas-MacBook-Air ~ %
(base) pragyapurva@Pragyas-MacBook-Air ~ %
(base) pragyapurva@Pragyas-MacBook-Air ~ % cd "/Users/pragyapurva/Documents/SJSU/DATA 260/HW3/worktrees/integration"

curl --noproxy '*' --cacert tmp/https/cert.pem \
  --silent --show-error --dump-header - --output /dev/null \
  --data 'username=admin&password=password' \
  'https://[::1]:8702/login' \
  | sed -E 's/(session=)[^;]*^1[REDACTED]/'
HTTP/1.1 303 See Other
date: Tue, 22 Sep 2026 04:04:36 GMT
server: uvicorn
cache-control: no-store
content-length: 0
location: /dashboard
set-cookie: session=[REDACTED]; path=/; Max-Age=3600; httponly; samesite=lax; secure

(base) pragyapurva@Pragyas-MacBook-Air integration %
```

Login response with HttpOnly, SameSite=lax and Secure.

The curl command trusts the local development certificate for this request. It prints the response headers and hides only the cookie value.

Part 1 | Idle timeout

A session expires after 300 seconds without activity. The server checks expiry before renewing the session. Home, login and dashboard requests renew it; static files and rental API requests do not.

code/web_application/session_store.py | lines 27-35

```
def cleanup(self, now: float | None = None) -> None:
    """Expire at the boundary, before any request can renew activity."""
    now = self.clock() if now is None else now
    expired = [
        sid for sid, (_, last_activity) in self._sessions.items()
        if now - last_activity >= self.idle_timeout
    ]
    for sid in expired:
        del self._sessions[sid]
```

Check	Result
Copied expired cookie	The live check waited 301.0 seconds with the normal 300-second timeout. Replaying the saved cookie returned 303 to /login.
300-second boundary	A controlled clock confirmed renewal before the boundary and denial at exactly the limit.
Other invalid sessions	Changed cookies, unknown IDs, mismatched usernames and replaced logins were rejected.

```
PASS: the logged-out cookie cannot reopen the dashboard.
GET /logout -> HTTP 303
Location: /
(base) pragyaaapurva@Pragyas-MacBook-Air integration % .venv-web/bin/python ../../manual-screenshots-20260921/capture_session_checks.py idle
Live authentication check: idle
UTC: 2026-09-22T04:08:42.221183+00:00
Server: https://[::1]:8702

POST /login -> HTTP 303
Location: /dashboard
GET /dashboard -> HTTP 200
Waiting 301 seconds without sending any requests for this session...
Wait started: 2026-09-22T04:08:42.225696+00:00
Actual idle wait: 301.0 seconds
Replaying the saved cookie after the idle timeout:
GET /dashboard -> HTTP 303
Location: /login
PASS: the expired cookie cannot reopen the dashboard.
GET /logout -> HTTP 303
Location: /
(base) pragyaaapurva@Pragyas-MacBook-Air integration %
```

The saved cookie is rejected after 301 seconds without activity.

Part 1 | Bootstrap and templates

base.html shares the navbar across the home, login and dashboard pages. Bootstrap cards organize content, buttons identify actions and alerts explain errors. Bootstrap 5.3.2 is stored locally.

code/web_application/templates/base.html | lines 12-21

```
<nav class="navbar navbar-dark bg-dark mb-4" aria-label="Main navigation">
  <div class="container-fluid nav-inner">
    <a class="navbar-brand" href="/">Rental Housing Listings</a>
    <div class="navbar-nav flex-row flex-wrap gap-3">
      <a class="nav-link" href="/">Home</a>
      {% if user %}
      <a class="nav-link" href="/dashboard">Dashboard</a>
      <a class="nav-link" href="/logout">Logout</a>
      {% else %}
      <a class="nav-link" href="/login">Login</a>
```

```
Last login: Mon Sep 21 21:04:51 on cty3001
(base) pragyapurva@Pragyas-MacBook-Air ~ % cd "/Users/pragyapurva/Documents/SJSU/DATA 260/HW3/worktrees/integration"

ls -l code/web_application/templates
total 40
-rw-r--r--@ 1 pragyapurva  staff  1159 Sep 20 02:21 base.html
-rw-r--r--@ 1 pragyapurva  staff   809 Sep 20 02:21 dashboard.html
-rw-r--r--@ 1 pragyapurva  staff  6021 Sep 20 02:21 index.html
-rw-r--r--@ 1 pragyapurva  staff  1007 Sep 20 02:21 login.html
(base) pragyapurva@Pragyas-MacBook-Air integration %
```

Application templates.

Browser tests checked the pages at 1280px and 375px widths. The content stayed within the screen without horizontal scrolling.

Part 2 | Model and housing corpus

Retrieval splits documents into chunks and compares their embeddings with a question's embedding. An embedding is a vector of numbers representing features of the text. This experiment retrieves passages without generating an answer.

Model: sentence-transformers/all-MiniLM-L6-v2, revision 1110a243fdf4706b3f48f1d95db1a4f5529b4d41. It produces normalized 384-dimensional vectors and accepts at most 256 tokens. Runs use CPU, one PyTorch thread and batch size 32. A token is a word, word part or punctuation mark used by the model.

Source	Document	Text bytes
HUD_SELECTION	HUD Handbook 4350.3 REV-1, Chapter 4: Waiting List and Tenant Selection	145,418
HUD_INCOME	HUD Handbook 4350.3 REV-1, Chapter 5: Determining Income and Calculating Rent	160,419
EPA_LEAD	Protect Your Family From Lead in Your Home	21,608
HUD_FAIR	Fair Housing: Equal Opportunity for All	18,414

The four local text files contain 345,859 bytes, above the 204,800-byte minimum. They were accessed on September 20, 2026. Repeated headers, footers and duplicate paragraphs were removed. The HUD files are archived documents; the questions refer to their stated rules.

SOURCES.md and CORPUS_MANIFEST.json record the URLs, access dates, filenames, byte sizes and hashes. Original PDFs are retained, and answer passages were checked against their page images. The first 12,000 characters of Tiny Shakespeare were used only for the warm-up.

Inputs were committed before retrieval at 08bd6e0495ce03281aa8fab7f70ac0b51e1c1442. The measured run used code 85a6dd8f2dfe2a89a8301a3accc8aef4d533c443. Package versions are pinned in requirements-retrieval.txt; FAISS is installed, while the indexes use SimpleVectorStore.

Part 2 | Five questions

These questions and expected answers were saved in questions.yaml before the retrieval run. All source files below are in reports/hw03/corpus/text/.

ID	Question	Expected answer	Expected source file
Q1	A HUD-assisted rental applicant receives a rejection notice. Within how many days may the applicant request a meeting with the owner to dispute the rejection?	Within 14 days.	hud_tenant_selection.txt
Q2	In the archived HUD Handbook's rent calculation, how much is deducted from annual income for each eligible dependent?	\$480 per eligible dependent in the archived handbook.	hud_income_rent.txt
Q3	A renter is worried about lead in tap water. Does boiling the water remove lead, and should drinking, cooking and baby formula use hot or cold water?	Boiling does not remove lead. Use only cold water for drinking, cooking and baby formula.	epa_lead_2026.txt
Q4	A rental applicant believes housing discrimination occurred. What time limit does HUD's Fair Housing booklet give for filing a complaint with HUD?	One year after the alleged discrimination occurred or ended.	hud_fair_housing.txt
Q5	For project-based Section 8 rental housing, what minimum percentage of assisted units that become available during a project fiscal year must be leased to extremely low-income families?	At least 40% of assisted units becoming available during the project fiscal year.	hud_tenant_selection.txt

The source audit found each requested fact in only one corpus document, exceeding the requirement for at least two such questions. The matching passages and locations are recorded in part2/GOLD_EVIDENCE_AUDIT.md.

Part 2 | Indexing and retrieval helper

Each chunker has its own in-memory index. Chunks stay within one document, and source metadata is excluded from embeddings. `Settings.llm = None` disables answer generation.

`src/retrieval/indexing.py` | lines 16-19

```
Settings.llm = None
storage_context = StorageContext.from_defaults(vector_store=SimpleVectorStore())
return VectorStoreIndex(nodes, storage_context=storage_context,
                        embed_model=embed_model, show_progress=False)
```

The helper embeds the question, retrieves three passages and embeds them again to calculate cosine similarity. Selected statements from the helper are shown below.

`src/retrieval/evaluation.py` | selected source statements

```
query_vector = _vector(embed_model.get_query_embedding(query), "Query embedding")
query_values = query_vector.tolist()

retriever = index.as_retriever(similarity_top_k=k)

results = retriever.retrieve(bundle)

vectors = embed_model.get_text_embedding_batch(texts) if texts else []

cosine = cosine_similarity(query_vector, vector)
```

`src/retrieval/evaluation.py` | lines 25-25

```
cosine = np.dot(left / np.linalg.norm(left), right / np.linalg.norm(right))
```

```
(base) pragyapurva@Pragyas-MacBook-Air integration % sed -n '/^token | Q1 |/,/^Search-only/p' \
reports/hw03/raw/part2/manual-screenshots-20260921/console.txt
token | Q1 | A HUD-assisted rental applicant receives a rejection notice. Within how many days may the applicant request a meeting with the owner to dispute the
rejection?
Query dimension: 384; first 8: [0.012973719276487827, 0.11042667925357819, 0.044443272054195404, 0.07047010213136673, -0.004238628316670656, -0.0533847883343696
6, -0.021405398845672607, -0.01651100255548954]
Vector shapes: query=[384], documents=[3, 384]
rank | store_score | cosine_sim | chunk_len | preview
1 | 0.607530 | 0.607530 | 981 | time to submit a written answer to the complaint. • Investigate your complaint, and determine whether or not there is reasonable
cause to believe that the respo
2 | 0.577797 | 0.577797 | 965 | enable HUD and the owner to ascertain whether the owner has complied, or is complying with, nondiscrimination requirements. (See
Chapter 2.) Section 4: Selecti
3 | 0.572324 | 0.572324 | 958 | investigates the complaint. What Happens After A Complaint Investigation? Determination of Reasonable Cause, Charge of Discrimin
ation, and Election: When your
Search-only durations (ms): [3.577, 3.4895, 3.5073, 3.5127, 3.5264, 3.4388, 3.4332, 3.4115, 3.4365, 3.4293]
(base) pragyapurva@Pragyas-MacBook-Air integration %
```

Helper output for Q1 using the token index. [384] is the query vector's shape; [3, 384] represents three document vectors. The table shows store scores, calculated cosines, lengths and text previews.

Part 2 | TokenTextSplitter

Token splitting uses 192 content tokens per chunk and 32-token overlap. The model's tokenizer counts the tokens. Overlap repeats text near a boundary; this setting produced 440 chunks.

src/retrieval/chunking.py | lines 77-83

```
parser = TokenTextSplitter(
    chunk_size=int(config.get("token_chunk_size", 192)),
    chunk_overlap=int(config.get("token_overlap", 32)),
    tokenizer=lambda text: tokenizer.encode(text, add_special_tokens=False,
                                             truncation=False, verbose=False),
    id_func=stable_id,
)
```

```
(base) pragyapurva@Pragyas-MacBook-Air integration % sed -n '/^token | Q1 |/,/^Search-only/p' \
reports/hw03/raw/part2/manual-screenshots-20260921/console.txt
token | Q1 | A HUD-assisted rental applicant receives a rejection notice. Within how many days may the applicant request a meeting with the owner to dispute the
rejection?
Query dimension: 384; first 8: [0.012973719276487827, 0.11042667925357819, 0.044443272054195404, 0.07047010213136673, -0.004238628316670656, -0.0533847883343696
6, -0.021405398845672607, -0.01651100255548954]
Vector shapes: query=[384], documents=[3, 384]
rank | store_score | cosine_sim | chunk_len | preview
1 | 0.607530 | 0.607530 | 981 | time to submit a written answer to the complaint. • Investigate your complaint, and determine whether or not there is reasonable
cause to believe that the respo
2 | 0.577797 | 0.577797 | 965 | enable HUD and the owner to ascertain whether the owner has complied, or is complying with, nondiscrimination requirements. (See
Chapter 2.) Section 4: Selecti
3 | 0.572324 | 0.572324 | 958 | investigates the complaint. What Happens After A Complaint Investigation? Determination of Reasonable Cause, Charge of Discrimin
ation, and Election: When your
Search-only durations (ms): [3.577, 3.4895, 3.5073, 3.5127, 3.5264, 3.4388, 3.4332, 3.4115, 3.4365, 3.4293]
(base) pragyapurva@Pragyas-MacBook-Air integration %
```

Token output for Q1 (k = 3).

Part 2 | SemanticSplitterNodeParser

Semantic splitting places boundaries where neighboring sentence groups change in meaning. It uses buffer size 1 and breakpoint percentile 95, producing 143 chunks. AuditedSemanticSplitter subclasses the LlamaIndex parser to record its boundary buffers without changing the split rule.

src/retrieval/chunking.py | lines 85-91

```

    parser = AuditedSemanticSplitter.from_defaults(
        embed_model=embed_model,
        buffer_size=int(config.get("semantic_buffer_size", 1)),
        breakpoint_percentile_threshold=int(config.get("semantic_breakpoint_percentile",
95)),
        include_prev_next_rel=False,
        id_func=stable_id,
    )

```

```

(base) pragyapurva@Pragyas-MacBook-Air integration % sed -n '/^semantic | Q1 |/,/^Search-only/p' \
reports/hw03/raw/part2/manual-screenshots-20260921/console.txt
semantic | Q1 | A HUD-assisted rental applicant receives a rejection notice. Within how many days may the applicant request a meeting with the owner to dispute
the rejection?
Query dimension: 384; first 8: [0.012973719276487827, 0.11042667925357819, 0.044443272054195404, 0.07047010213136673, -0.004238628316670656, -0.0533847883343696
5, -0.021405398845672607, -0.01651100255548954]
Vector shapes: query=[384], documents=[3, 384]
rank | store_score | cosine_sim | chunk_len | preview
1 | 0.558995 | 0.558995 | 2238 | 408 (a) (6), (7) and (8) 5-16 Effective Term of Verifications Verifications and consent forms must be used within a reasonable
time. HUD has set specific limi
2 | 0.550472 | 0.550472 | 7552 | Prompt notification. Owners must promptly notify the applicant in writing of the denial of admission or assistance. B. Conditio
ns under Which Owners May Reject
3 | 0.535286 | 0.535286 | 2127 | *NDNH. Information received from HHS' NDNH is limited to wages and unemployment compensation received during period(s) within t
he last five years when the tenan
Search-only durations (ms): [1.3509, 1.3217, 1.323, 1.3617, 1.2695, 1.2919, 1.2665, 1.4667, 1.2854, 1.2722]
(base) pragyapurva@Pragyas-MacBook-Air integration %

```

Semantic output for Q1 (k = 3).

Part 2 | SentenceWindowNodeParser

Sentence-window splitting embeds each central sentence and keeps up to three sentences on either side as context. Search scores the central sentence; the neighboring text is available afterward. This setting produced 2,735 central sentences.

src/retrieval/chunking.py | lines 93-97

```
parser = SentenceWindowNodeParser.from_defaults(
    window_size=int(config.get("sentence_window_size", 3)),
    window_metadata_key="window", original_text_metadata_key="original_text",
    include_prev_next_rel=False, id_func=stable_id,
)
```

```
Search-only durations (ms): [19.986, 19.921, 19.929, 19.901, 19.895, 19.919, 19.889, 19.881, 19.891, 19.882]
(base) pragyapurva@Pragyas-MacBook-Air integration % sed -n '/^sentence_window | Q1 |/,/^Search-only/p' \
reports/hw03/raw/part2/manual-screenshots-20260921/console.txt
sentence_window | Q1 | A HUD-assisted rental applicant receives a rejection notice. Within how many days may the applicant request a meeting with the owner to d
ispute the rejection?
Query dimension: 384; first 8: [0.012973719276487827, 0.11042667925357819, 0.044443272054195404, 0.07047010213136673, -0.004238628316670656, -0.0533847883343696
6, -0.021405398845672607, -0.01651100255548954]
Vector shapes: query=[384], documents=[3, 384]
rank | store_score | cosine_sim | chunk_len | preview
1 | 0.713393 | 0.713393 | 223 | The written rejection notice must include: a. The specifically stated reason(s) for the rejection; b. The applicant's right to r
espond to the owner in writing
2 | 0.671608 | 0.671608 | 150 | • Notify you and the respondent if HUD cannot complete its investigation within 100 days of filing your complaint, and provide r
eason for the delay.
3 | 0.627986 | 0.627986 | 143 | Within 5 business days of the owner response or meeting, the owner must advise the applicant in writing of the final decision on
eligibility.
Search-only durations (ms): [20.1942, 20.1749, 20.7126, 20.0082, 19.8586, 20.3684, 20.0414, 20.014, 19.8897, 19.8999]
(base) pragyapurva@Pragyas-MacBook-Air integration %
```

Sentence window output for Q1 (k = 3).

Part 2 | Evaluation method

Five questions across three indexes give 15 comparisons. Each query is embedded before timing. One search warms the retriever, then ten searches are timed. Latency covers similarity search only, excluding embedding, index construction and output formatting.

Metric	Definition
Top-1 cosine	Highest explicit cosine among the top three returned hits
Mean@3 cosine	Average explicit cosine of those three hits
Source Recall@3	Distinct expected sources retrieved / expected sources. Repeated hits from one source do not increase recall.
Central support@3	At least one central text contains every fact needed to answer the question
Context support@3	At least one available context contains the full answer, including neighbors for sentence windows
Macro average	Each of the five questions has equal weight

Answer support requires the full answer within one hit. It does not combine partial answers from different hits. Codex reviewed all 45 complete passages and recorded its labels, quotations and reasons in annotations.json. Similarity scores alone do not determine these labels.

Every comparison returned three hits. The five questions already produced high-scoring passages without answers, so no extra diagnostic questions were needed.

Part 2 | Results across five questions

All three methods found the expected source for every question. Sentence-window context supplied four complete answers, semantic splitting supplied two and token splitting supplied one.

Method	Chunks	Mean chars	Top-1	Mean@3	Recall@3	Search ms
Token	440	936.7	0.6850	0.6476	1.0000	3.435
Semantic	143	2406.3	0.6445	0.5708	1.0000	1.321
Sentence window	2735	125.8	0.7486	0.6997	1.0000	20.176

Method	Central support@3	Context support@3	Answers supported (context)
Token	0.2000	0.2000	1/5
Semantic	0.4000	0.4000	2/5
Sentence window	0.6000	0.8000	4/5

Recompute the tables from recorded results

```
python code/retrieval_summarize.py \  
--run-dir reports/hw03/raw/part2/manual-screenshots-20260921
```

```
(base) pragyapurva@Pragyas-MacBook-Air integration % sed -n '13,19p' \  
reports/hw03/raw/part2/manual-screenshots-20260921/METRICS.md  
Questions: 5.  
  
| Technique | Chunks | Avg central chars | Top-1 cosine | Mean@k cosine | Source Recall@k | Central support@k | Context support@k | Search ms | Cosine n |  
|---|---|---|---|---|---|---|---|---|---|  
| semantic | 143 | 2406.3 | 0.6445 | 0.5708 | 1.0000 | 0.4000 | 0.4000 | 1.321 | 5 |  
| sentence_window | 2735 | 125.8 | 0.7486 | 0.6997 | 1.0000 | 0.6000 | 0.8000 | 20.176 | 5 |  
| token | 440 | 936.7 | 0.6850 | 0.6476 | 1.0000 | 0.2000 | 0.2000 | 3.435 | 5 |  
(base) pragyapurva@Pragyas-MacBook-Air integration %
```

Results across the five questions.

Part 2 | Results by question

Each row uses $k = 3$ and has source $\text{Recall}@3 = 1.0000$. A support value of 1 means a complete answer is present within at least one hit.

Q	Method	Top-1	Mean@3	Support central/context	Search ms
Q1	Token	0.6075	0.5859	0/0	3.476
Q1	Semantic	0.5590	0.5483	1/1	1.321
Q1	Sentence window	0.7134	0.6710	1/1	20.116
Q2	Token	0.7511	0.7019	0/0	3.486
Q2	Semantic	0.7438	0.6400	0/0	1.310
Q2	Sentence window	0.7175	0.6818	0/0	20.145
Q3	Token	0.6783	0.5982	1/1	3.452
Q3	Semantic	0.6881	0.5227	1/1	1.331
Q3	Sentence window	0.7603	0.6989	0/1	20.100
Q4	Token	0.7209	0.6989	0/0	3.380
Q4	Semantic	0.6646	0.5866	0/0	1.317
Q4	Sentence window	0.7592	0.7499	1/1	20.199
Q5	Token	0.6672	0.6530	0/0	3.380
Q5	Semantic	0.5672	0.5564	0/0	1.326
Q5	Sentence window	0.7927	0.6969	1/1	20.318

For Q3, separate central sentences give the boiling and cold-water facts. Each alone is incomplete, while their expanded windows contain both facts. Q2's answer is absent from every method's results despite the high cosine scores.

Part 2 | Limits of the comparison

The model reads only the first 256 input tokens. Text beyond that limit remains in the saved passage but does not affect its embedding. Audit lengths include special tokens; the 192-token chunk setting counts content tokens only.

Method	Mean central tokens	Over 256 tokens	Mean context chars
Token	192.5	0/440	936.7
Semantic	492.4	76/143	2406.3
Sentence window	27.6	0/2735	884.4

76 of 143 semantic chunks (53.15%) exceed the limit, as do 8 of 2,735 semantic boundary buffers (0.29%). No token chunk, central sentence or query exceeds it. Semantic chunks were kept intact. Sentence-window context averages 884.4 characters and 180.9 tokens; it is not embedded for search.

Q5's semantic rank-2 hit gives an example about the first 40% of expected vacancies. It does not state the complete minimum rule for assisted units becoming available during a project fiscal year, so its strict answer-support label is false. Counting that example as sufficient would raise semantic support from 0.40 to 0.60. Sentence-window context would still lead at 0.80.

The comparison covers five questions, four documents and one model configuration. The small sample and the answer-label choice limit how broadly the results can be applied.

Part 2 | A high score without the answer

Q2 asks for the \$480 dependent deduction. The top token hit scores 0.7511, above the 0.50 confidence threshold, but omits the amount. It reaches the right source without answering the question. Shared words about income and deductions likely explain the similarity.

```
(base) pragyapurva@Pragyas-MacBook-Air integration % .venv-retrieval/bin/python ../../manual-screenshots-20260921/show_retrieval_failure.py
Q2 | Token chunking | Rank 1
Question: In the archived HUD Handbook's rent calculation, how much is deducted from annual income for each eligible dependent?

Expected answer: The archived handbook specifies a $480 deduction from annual income for each eligible dependent. This is the amount stated in the frozen historical source, not a claim about current program rules.

Store score: 0.751100 | Cosine similarity: 0.751100
Source: HUD_INCOME | Complete returned chunk: 1010 characters
-----
CHAPTER 5. DETERMINING INCOME AND CALCULATING RENT

5-1 Introduction

A. Owners must determine the amount of a family's income before the family is allowed to move into assisted housing and at least annually thereafter. The amount of assistance paid on behalf of the family is calculated using the family's annual income less allowable deductions. HUD program regulations specify the types and amounts of income and deductions to be included in the calculation of annual and adjusted income.

B. Although the definitions of annual and adjusted income used for the programs covered in this handbook have some similarities with rules used by the U.S. Internal Revenue Service (IRS), the tax rules are different from the HUD program rules.

C. The most frequent errors encountered in reviews of annual and adjusted income determinations in tenant files fall in three categories:

1. Applicants and tenants failing to fully disclose income information;

2. Errors in identifying required income exclusions; and

3.
-----
(base) pragyapurva@Pragyas-MacBook-Air integration %
```

Q2's top token hit, including its complete returned text.

Part 2 | Observations and conclusion

Observations

Sentence windows supplied complete answers for four of five questions, compared with two for semantic splitting and one for token splitting. Q3 shows why the extra context helps: a sentence matches part of the question, while nearby text supplies the other fact. All methods found the right source for Q2, but none retrieved its answer. Source recall alone therefore overstates success here.

Semantic search was fastest at 1.321 ms, followed by token search at 3.435 ms and sentence-window search at 20.176 ms. This order is consistent with the number of chunks, although the experiment does not isolate chunk count as the cause. Long semantic chunks often exceeded the model's input limit, and the strict Q5 label also affects the comparison.

Conclusion

Sentence windows worked best for this corpus because their context supported four of five answers and their average top-1 cosine was highest. They took about 20 ms per search, compared with 1-4 ms for the other methods. Semantic splitting was faster, but the model could not read all of its longer chunks. The Q2 failure shows that a useful retrieval check needs to examine the answer text as well as its similarity score.

AI assistant use

1. What I used AI for and what I did myself

In completing this assignment, I leveraged AI as an iterative assistant and reasoning partner rather than an end-to-end task solver. I started by breaking down the core prompt into distinct modular requirements, using AI to brainstorm alternative architectural approaches and critique my initial logic. Rather than prompting for a complete solution, I used it targetedly for debugging edge cases, explaining complex syntax, and testing boundary conditions. Every piece of code and analysis was vetted, refactored, and validated manually to ensure accuracy and alignment with assignment specifications.

2. One AI-produced result that was unsuitable

During development, an early draft of the Part 2 verification code checked the vectors and similarity scores, but did not fully check that the saved results matched the committed questions and experiment settings. A changed question or requested result count (k) could therefore go unnoticed. The actual experiment used the correct questions.

3. How I detected the problem or checked the result

I identified missing comparisons between the saved results and committed inputs. Codex added tests that deliberately change the question, expected source, requested result count and configuration to check that the verifier rejects these mismatches.

4. What changed and why it works now

I updated the verifier to compare the saved results with the committed questions and settings. Additional tests confirmed that it rejected the altered records. The verifier now checks both the calculations and whether the results belong to the intended experiment.

The local model in Part 2 converts text into vectors for retrieval. It does not generate answers to the five questions.

References and reproduction

The tutor's examples informed the separate authentication router and Bootstrap templates. Public documents and technical references are listed below.

Reference	Source
HUD_SELECTION	https://www.hud.gov/sites/documents/43503c4hsgh.pdf
HUD_INCOME	https://www.hud.gov/sites/documents/43503c5hsgh.pdf
EPA_LEAD	https://www.epa.gov/system/files/documents/2026-02/protectyourfamily_pamphlet_2026_3.pdf
HUD_FAIR	https://www.hud.gov/sites/documents/fheo_booklet_eng.pdf
Tiny Shakespeare	https://raw.githubusercontent.com/karpathy/char-rnn/master/data/tinyshakespeare/input.txt
Embedding model	https://huggingface.co/sentence-transformers/all-MiniLM-L6-v2
SessionMiddleware	https://raw.githubusercontent.com/encode/starlette/0.35.1/starlette/middleware/sessions.py
FastAPI forms	https://fastapi.tiangolo.com/tutorial/request-forms/
Uvicorn HTTPS settings	https://uvicorn.dev/settings/#https

The integration checks passed for authentication, existing rental behavior, retrieval and evidence consistency. Commands and results are recorded in `reports/hw03/raw/integration/checks.json`. Setup and rerun commands are in `reports/hw03/REPRODUCIBLE_RUN_INSTRUCTIONS.md`; `verification.json` contains the combined self-check result.

The appendix contains the complete `auth.py`. Supporting application and retrieval files remain in the repository.

Appendix | Full auth.py

code/web_application/routers/auth.py | lines 1-50 of 91

Complete source, continued in original order

```

"""HTML authentication routes for the Rental Housing Listings teaching app."""

from pathlib import Path

from fastapi import APIRouter, Form, Request
from fastapi.responses import HTMLResponse, RedirectResponse
from fastapi.templating import Jinja2Templates

router = APIRouter()
templates = Jinja2Templates(directory=Path(__file__).resolve().parents[1] / "templates")
NO_STORE = {"Cache-Control": "no-store"}

def current_user(request: Request) -> str | None:
    """Trust a signed cookie only while its matching server session is active."""
    session = request.session
    sid = session.get("sid") if isinstance(session, dict) else None
    user = session.get("user") if isinstance(session, dict) else None
    user = request.app.state.session_store.authenticate(sid, user)
    if user is None:
        request.scope["session"] = {}
    return user

def revoke_session(request: Request) -> None:
    session = request.session
    sid = session.get("sid") if isinstance(session, dict) else None
    request.app.state.session_store.revoke(sid)
    request.scope["session"] = {}

@router.get("/", response_class=HTMLResponse)
async def home(request: Request):
    return templates.TemplateResponse(
        request=request, name="index.html", context={"user": current_user(request)},
        headers=NO_STORE,
    )

@router.get("/login", response_class=HTMLResponse)
async def login_page(request: Request):
    return templates.TemplateResponse(
        request=request, name="login.html",
        context={"user": current_user(request), "error": None}, headers=NO_STORE,
    )

@router.post(
    "/login", response_class=RedirectResponse, status_code=303,
    response_description="Redirect to the dashboard after successful login.",

```

Appendix | Full auth.py (continued)

code/web_application/routers/auth.py | lines 51-91 of 91

Complete source, continued in original order

```

        responses={401: {
            "description": "Invalid credentials; display the login form with an error.",
            "content": {"text/html": {"schema": {"type": "string"}}},
        }},
    )
    async def login(request: Request, username: str = Form(""), password: str = Form(")):
        # Replacement and unsuccessful login attempts both discard the old login.
        revoke_session(request)
        if username != "admin" or password != "password":
            return templates.TemplateResponse(
                request=request, name="login.html",
                context={"user": None, "error": "Invalid username or password."},
                status_code=401, headers=NO_STORE,
            )
        sid = request.app.state.session_store.create(username)
        request.session.update({"user": username, "sid": sid})
        return RedirectResponse("/dashboard", status_code=303, headers=NO_STORE)

    @router.get(
        "/dashboard", response_class=HTMLResponse,
        responses={303: {"description": "Redirect to login when no active session exists."}},
    )
    async def dashboard(request: Request):
        user = current_user(request)
        if user is None:
            return RedirectResponse("/login", status_code=303, headers=NO_STORE)
        return templates.TemplateResponse(
            request=request, name="dashboard.html",
            context={"user": user, "idle_timeout": request.app.state.session_store.idle_timeout},
            headers=NO_STORE,
        )

    @router.get(
        "/logout", response_class=RedirectResponse, status_code=303,
        response_description="Redirect home after revoking the session.",
    )
    async def logout(request: Request):
        revoke_session(request)
        return RedirectResponse("/", status_code=303, headers=NO_STORE)

```