

In [1]:

```
import numpy as np

# Importing standard Qiskit libraries
from qiskit import QuantumCircuit, transpile, Aer, IBMQ
from qiskit.tools.jupyter import *
from qiskit.visualization import *
from ibm_quantum_widgets import *
from qiskit.providers.aer import QasmSimulator

# Loading your IBM Quantum account(s)
provider = IBMQ.load_account()
```

In []:

```
from qiskit import *

q=QuantumRegister(4,'q')

M=ClassicalRegister(3,'c')
#f(x1,x2,x3) = x1x2+x2x3+x3x1
#we are trying to check whether f is balanced or constant using Duetsch-Jozsa algo
rithm
DJf = QuantumCircuit(q,M)

#Now we are making circuit
DJf.x(q[3])
DJf.h(q)

#This is quantum equivalent of boolean function f(x1,x2,x3) = x1x2+x2x3+x3x1
DJf.ccx(q[0],q[1],q[3])
DJf.ccx(q[1],q[2],q[3])
DJf.ccx(q[0],q[2],q[3])

for i in range(3):
    DJf.h(q[i])
    DJf.measure(q[i], M[i])

DJf.draw()

backend = Aer.get_backend('qasm_simulator')
qjob = execute(DJf, backend, shots = 2000)

counts = qjob.result().get_counts()
print(counts)
```

In []: