

OS Logiciels - Mémo SQL w3school

1 Mots clé SQL

Keyword	Description
ADD	Adds a column in an existing table
ADD CONSTRAINT	Adds a constraint after a table is already created
ALTER	Adds, deletes, or modifies columns in a table, or changes the data type of a column in a table
ALTER COLUMN	Changes the data type of a column in a table
ALTER TABLE	Adds, deletes, or modifies columns in a table
ALL	Returns true if all of the subquery values meet the condition
AND	Only includes rows where both conditions is true
ANY	Returns true if any of the subquery values meet the condition
AS	Renames a column or table with an alias
ASC	Sorts the result set in ascending order
BACKUP DATABASE	Creates a back up of an existing database
BETWEEN	Selects values within a given range
CASE	Creates different outputs based on conditions
CHECK	A constraint that limits the value that can be placed in a column
COLUMN	Changes the data type of a column or deletes a column in a table
CONSTRAINT	Adds or deletes a constraint
CREATE	Creates a database, index, view, table, or procedure
CREATE DATABASE	Creates a new SQL database
CREATE INDEX	Creates an index on a table (allows duplicate values)
CREATE OR REPLACE VIEW	Updates a view
CREATE TABLE	Creates a new table in the database

CREATE PROCEDURE	Creates a stored procedure
CREATE UNIQUE INDEX	Creates a unique index on a table (no duplicate values)
CREATE VIEW	Creates a view based on the result set of a SELECT statement
DATABASE	Creates or deletes an SQL database
DEFAULT	A constraint that provides a default value for a column
DELETE	Deletes rows from a table
DESC	Sorts the result set in descending order
DISTINCT	Selects only distinct (different) values
DROP	Deletes a column, constraint, database, index, table, or view
DROP COLUMN	Deletes a column in a table
DROP CONSTRAINT	Deletes a UNIQUE, PRIMARY KEY, FOREIGN KEY, or CHECK constraint
DROP DATABASE	Deletes an existing SQL database
DROP DEFAULT	Deletes a DEFAULT constraint
DROP INDEX	Deletes an index in a table
DROP TABLE	Deletes an existing table in the database
DROP VIEW	Deletes a view
EXEC	Executes a stored procedure
EXISTS	Tests for the existence of any record in a subquery
FOREIGN KEY	A constraint that is a key used to link two tables together
FROM	Specifies which table to select or delete data from
FULL OUTER JOIN	Returns all rows when there is a match in either left table or right table
GROUP BY	Groups the result set (used with aggregate functions: COUNT, MAX, MIN, SUM, AVG)
HAVING	Used instead of WHERE with aggregate functions
IN	Allows you to specify multiple values in a WHERE clause
INDEX	Creates or deletes an index in a table

INNER JOIN	Returns rows that have matching values in both tables
INSERT INTO	Inserts new rows in a table
INSERT INTO SELECT	Copies data from one table into another table
IS NULL	Tests for empty values
IS NOT NULL	Tests for non-empty values
JOIN	Joins tables
LEFT JOIN	Returns all rows from the left table, and the matching rows from the right table
LIKE	Searches for a specified pattern in a column
LIMIT	Specifies the number of records to return in the result set
NOT	Only includes rows where a condition is not true
NOT NULL	A constraint that enforces a column to not accept NULL values
OR	Includes rows where either condition is true
ORDER BY	Sorts the result set in ascending or descending order
OUTER JOIN	Returns all rows when there is a match in either left table or right table
PRIMARY KEY	A constraint that uniquely identifies each record in a database table
PROCEDURE	A stored procedure
RIGHT JOIN	Returns all rows from the right table, and the matching rows from the left table
ROWNUM	Specifies the number of records to return in the result set
SELECT	Selects data from a database
SELECT DISTINCT	Selects only distinct (different) values
SELECT INTO	Copies data from one table into a new table
SELECT TOP	Specifies the number of records to return in the result set
SET	Specifies which columns and values that should be updated in a table
TABLE	Creates a table, or adds, deletes, or modifies columns in a table, or deletes a table or data inside a table
TOP	Specifies the number of records to return in the result set

TRUNCATE TABLE	Deletes the data inside a table, but not the table itself
UNION	Combines the result set of two or more SELECT statements (only distinct values)
UNION ALL	Combines the result set of two or more SELECT statements (allows duplicate values)
UNIQUE	A constraint that ensures that all values in a column are unique
UPDATE	Updates existing rows in a table
VALUES	Specifies the values of an INSERT INTO statement
VIEW	Creates, updates, or deletes a view
WHERE	Filters a result set to include only records that fulfill a specified condition

1.1 Descriptions des requêtes SQL

SQL Statement	Syntax
AND / OR	SELECT column_name(s) FROM table_name WHERE condition AND OR condition
ALTER TABLE	ALTER TABLE table_name ADD column_name datatype or ALTER TABLE table_name DROP COLUMN column_name
AS (alias)	SELECT column_name AS column_alias FROM table_name or SELECT column_name FROM table_name AS table_alias
BETWEEN	SELECT column_name(s) FROM table_name WHERE column_name BETWEEN value1 AND value2
CREATE DATABASE	CREATE DATABASE database_name
CREATE TABLE	CREATE TABLE table_name (column_name1 data_type, column_name2 data_type, column_name3 data_type, ... PRIMARY KEY (column_nameX), FOREIGN KEY (Column_nameY) REFERENCES (Column_name_Z))
CREATE INDEX	CREATE INDEX index_name ON table_name (column_name) or CREATE UNIQUE INDEX index_name ON table_name (column_name)
CREATE VIEW	CREATE VIEW view_name AS SELECT column_name(s) FROM table_name WHERE condition
DELETE	DELETE FROM table_name WHERE some_column=some_value

	or DELETE FROM table_name (Note: Deletes the entire table!!) DELETE * FROM table_name (Note: Deletes the entire table!!)
DROP DATABASE	DROP DATABASE database_name
DROP INDEX	DROP INDEX table_name.index_name (SQL Server) DROP INDEX index_name ON table_name (MS Access) DROP INDEX index_name (DB2/Oracle) ALTER TABLE table_name DROP INDEX index_name (MySQL)
DROP TABLE	DROP TABLE table_name
EXISTS	IF EXISTS (SELECT * FROM table_name WHERE id = ?) BEGIN --do what needs to be done if exists END ELSE BEGIN --do what needs to be done if not END
GROUP BY	SELECT column_name, aggregate_function(column_name) FROM table_name WHERE column_name operator value GROUP BY column_name
HAVING	SELECT column_name, aggregate_function(column_name) FROM table_name WHERE column_name operator value GROUP BY column_name HAVING aggregate_function(column_name) operator value
IN	SELECT column_name(s) FROM table_name WHERE column_name IN (value1,value2,...)
INSERT INTO	INSERT INTO table_name VALUES (value1, value2, value3,...) or INSERT INTO table_name (column1, column2, column3,...) VALUES (value1, value2, value3,...)
INNER JOIN	SELECT column_name(s) FROM table_name1 INNER JOIN table_name2

	ON table_name1.column_name=table_name2.column_name
LEFT JOIN	SELECT column_name(s) FROM table_name1 LEFT JOIN table_name2 ON table_name1.column_name=table_name2.column_name
RIGHT JOIN	SELECT column_name(s) FROM table_name1 RIGHT JOIN table_name2 ON table_name1.column_name=table_name2.column_name
FULL JOIN	SELECT column_name(s) FROM table_name1 FULL JOIN table_name2 ON table_name1.column_name=table_name2.column_name
LIKE	SELECT column_name(s) FROM table_name WHERE column_name LIKE pattern
ORDER BY	SELECT column_name(s) FROM table_name ORDER BY column_name [ASC DESC]
SELECT	SELECT column_name(s) FROM table_name
SELECT *	SELECT * FROM table_name
SELECT DISTINCT	SELECT DISTINCT column_name(s) FROM table_name
SELECT INTO	SELECT * INTO new_table_name [IN externaldatabase] FROM old_table_name or SELECT column_name(s) INTO new_table_name [IN externaldatabase] FROM old_table_name
SELECT TOP	SELECT TOP number percent column_name(s) FROM table_name
TRUNCATE TABLE	TRUNCATE TABLE table_name
UNION	SELECT column_name(s) FROM table_name1 UNION SELECT column_name(s) FROM table_name2

UNION ALL	SELECT column_name(s) FROM table_name1 UNION ALL SELECT column_name(s) FROM table_name2
UPDATE	UPDATE table_name SET column1=value, column2=value,... WHERE some_column=some_value
WHERE	SELECT column_name(s) FROM table_name WHERE column_name operator value