



CSS 3

SESSION 1

SESSION 1

SESSION 2

SESSION 3

SESSION 4

SESSION 5

TEST YOURSELF

Introduction CSS3

Introduction

- CSS3 (early 2000s): instead of one big spec, it was split into modules (Selectors, Flexbox, Grid, Transitions, Animations, etc.). **Modern CSS (today):** no CSS4 or "final version" — CSS is evolving continuously. Each module has its own level (Selectors Level 4, Media Queries Level 5, Grid Level 2, etc.).
- CSS = > Cascading Style Sheets " For Presentation And Visuals "
- Prerequisite to CSS is **HTML**

What we need ?

- Text Editor (VS Code)
- Internet Browser (Google Chrome , Firefox)

Extention file **.css** like main.css

Where can I create CSS Code ?

Inline CSS (inside the HTML tag)

You can write CSS directly inside an element using the style attribute.

```
<h1 style="color: blue; text-align: center;">Hello World</h1>
```

✓ Good for quick tests

✗ Not recommended for big projects — it's hard to manage

Internal CSS (inside the <style> tag)

You can put CSS inside your HTML file, inside the <head> section.

```
<head>
<style>
  h1 {
    color: orange;
    text-align: center;
  }
</style>
</head>
<body>
  <h1>Hello CSS!</h1>
</body>
</html>
```

✓ Good for small pages

✗ Not reusable across multiple files

External CSS (in a .css file)

You can create a separate CSS file, like style.css, and link it to your HTML.

```
body {
  background-color: #f2f2f2;
}

h1 {
  color: teal;
  text-align: center;
}
```

Then link it in your HTML file:

```
html

<link rel="stylesheet" href="style.css">
```

✓ Best and most professional way

✓ Keeps your design separate from your content

✓ Easy to reuse on multiple pages

Priority Order (Simplified)

1. Inline styles with !important
2. Internal/External styles with !important
3. Inline styles
4. Internal styles between tag <style></style>
5. External styles
6. Browser default styles (lowest)

Selector & Comment

in CSS, comments are often used to:

- Explain the code - for documentation
- Sometimes using to ignor code to test or debug

Type of Comment :

- Single Line /* */
- Multiple Line

```

1  /* single line comment */
2  /* line one */
3
4  /* ----- */
5
6  /* multi line comment */
7  /* line open
8  line two
9  line three */
10

```

Some Types of Selector :

Selector	Definition	Code
*	Universal Selector The * is called the Universal Selector in CSS. It matches all elements on the page.	<pre> 1 { 2 } 3 4 /* multi line comment */ 5 6 /* line open 7 line two 8 line three */ 9 10 </pre>
P-h1-div-span	Element Selector Selects elements by their tag-name. Note : If you type it means: "select all <p> elements on the page" and apply that style.	<pre> 1 { 2 } 3 4 /* multi line comment */ 5 6 /* line open 7 line two 8 line three */ 9 10 </pre>
.class-name	Class Selector Selects elements by class-name (with .). Note : • (class-name.class-name) mean element has two class like this <p class="highlight big">This text is red</p> • the class selector has higher priority than the element (name) selector.	<pre> 1 { 2 } 3 4 /* multi line comment */ 5 6 /* line open 7 line two 8 line three */ 9 10 </pre>
#id-name	ID Selector Selects elements by ID name (with #). Note : • the ID selector has higher priority than the class selector.	<pre> 1 { 2 } 3 4 /* multi line comment */ 5 6 /* line open 7 line two 8 line three */ 9 10 </pre>
h1, h2, p	Group Selector (,) Applies the same style to multiple elements. Note : you can make group by class and element name like (.class-name div , class-name p)	<pre> 1 { 2 } 3 4 /* multi line comment */ 5 6 /* line open 7 line two 8 line three */ 9 10 </pre>
div p	Descendant Selector Selects an element inside another element.	<pre> 1 { 2 } 3 4 /* multi line comment */ 5 6 /* line open 7 line two 8 line three */ 9 10 </pre>
div > p	Child Selector (>) Selects direct children only.	<pre> 1 { 2 } 3 4 /* multi line comment */ 5 6 /* line open 7 line two 8 line three */ 9 10 </pre>
h1 + p	Adjacent Sibling Selector (+) Selects the element immediately after another.	<pre> 1 { 2 } 3 4 /* multi line comment */ 5 6 /* line open 7 line two 8 line three */ 9 10 </pre>
h1 ~ p	General Sibling Selector (~) Selects all siblings that come after another element.	<pre> 1 { 2 } 3 4 /* multi line comment */ 5 6 /* line open 7 line two 8 line three */ 9 10 </pre>
input[required], [title], [class = "inp"], [placeholder~="name"]	Attribute Selector Selects elements based on their attributes.	<pre> 1 { 2 } 3 4 /* multi line comment */ 5 6 /* line open 7 line two 8 line three */ 9 10 </pre>

Selector	Definition	Code
[placeholder*=" "], [placeholder^="U"]		
:first-child, :last-child	<u>first child</u> Selects the first child element inside its parent. Selects the last child element inside its parent.	
:first-of-type :last-of-type	<u>first and last type</u> selects the first element of its type selects the last element of its type	
:only-child	<u>only child</u> selects an element if it is the only child of its parent.	


Background

We will take a <div> as example to implement

background-color


- The background-color property in CSS is used to set the background color of an element.
- Default value is transparent.

- background-color: red;
- background-color: rgb(107, 5, 5); or background-color: rgba(107, 5, 5, 50%);
- background-color: #eee;



- You can type color by hexadecimal like #eee, #1f1f1f
- rgba : r -> Red color g -> Green color b -> Blue color a -> Alpha
- The alpha value must be a number between (0 and 1), not a percentage.

There are many great websites for discovering and generating beautiful color palettes for your designs



linear-gradient

The linear-gradient() function in CSS is used to create smooth transition between two or more colors along a straight line (vertical, horizontal, diagonal, etc.).

background: linear-gradient(direction, color-stop1, color-stop2, ...);

Examples :

- background: linear-gradient(red, yellow);
- background: linear-gradient(to right, red, yellow);
- background: linear-gradient(45deg, red, blue, green);

background-image

- background-image: url(/img/1.jfif) ;

background-repeat

background-attachment

background-position

background-size

background-repeat

- background-repeat: no-repeat;
- background-repeat: repeat;
- background-repeat: repeat-x;
- background-repeat: repeat-y;

background-attachment

- background-attachment: scroll; => default
- background-attachment: fixed;

background-size

- background-size: auto; => default
- background-size: cover;**stretch and cut**
- background-size: contain;**fully visible**
- background-size: 100px 200px ; W H
- background-size: 50% 80% ;

background-position

- background-position: left top; => default
- background-position: left center;
- background-position: left bottom;
- background-position: center top;
- background-position: center center;
- background-position: center bottom;
- background-position: right top;
- background-position: right center;
- background-position: right bottom;
- background-position: 20px 25px;
- background-position: 50% 50%;

Font & Icon

Add font using [Google Font Online](#) :

visit website : [GOOGLE FONT](#)

- Select a font what you want as like "Roboto"
- Get font
- Get embed code
- select @import
- Copy code without <style> in your CSS file
- Add a **font-family**: "Roboto", sans-serif; in your CSS

Add Icon using [font awesome Online](#) :

visit website : [FONT AWESOME](#)

- Click on Icons
- Type Email in search
- Click on **Free**
- Select envelope
- Copy code snippet to add it in HTML file

visit website : [FONT AWESOME CDN](#)

<https://cdnjs.cloudflare.com/ajax/libs/font-awesome/7.0.1/css/all.min.css>

- create <link> in head part in your HTML file
- Add in href attribute link which you copied it from font awesome cdn => href = "https://cdnjs.cloudflare.com/ajax/libs/font-awesome/7.0.1/css/all.min.css"

Assignment

Challenge :

Help Code :

width: 50%;
height: 500px;
border: 2px solid rgb(149, 147, 147);
Note : you will use image & background-image & 2 div



Download