Static and quasi-static loading data (for a single anchor)

All data in this section applies to:

- Correct setting (See setting instruction)
- No edge distance and spacing influence
- Steel failure
- Minimum base material thickness
- Concrete C 20/25, $f_{ck,cube}$ = 25 N/mm²

Anchorage depth

Anchor size		6		8			10			14		
Type	HUS3-	H,C,A, I, P	H,C,A, I,I-flex	H,C,A,			H,C,HF			H,HF		H
Nominal embedmenth deptl	h_{nom} [mm]	h_{nom1}	h_{nom2}	h_{nom1}	h_{nom2}	h_{nom3}	h_{nom1}	h_{nom2}	h_{nom3}	h_{nom1}	h_{nom2}	h_{nom3}
		40	55	50	60	70	55	75	85	65	85	115

Characteristic resistance

Anchor size		6		8			10			14		
Type	HUS3-	H,C,A, I, P	H,C,A, I,I-flex	H,C,HF			H,C,HF			H,HF		H
Non-cracked concrete												
Tension N_{Rk}	[kN]	7,0	9,0	9,0	12,0	16,0	12,0	20,0	27,8	17,5	27,3	44,4
Shear V_{Rk}	[kN]	*12,5*	*12,5*	12,8	*19,0*	*22,0*	13,5	*30,0*	*34,0*	35,0	*54,5*	*62,0*
Cracked concrete												
Tension N_{Rk}	[kN]	2,5	6,0	6,0	9,0	12,0	9,7	16,2	19,8	12,5	19,4	31,7
Shear V_{Rk}	[kN]	*12,5*	*12,5*	9,1	*19,0*	*22,0*	9,7	*30,0*	*34,0*	24,9	*38,9*	*62,0*

Design resistance

Anchor size		6		8			10			14		
Type	HUS3-	H,C,A, I, P	H,C,A, I,	H,C,HF			H,C,HF			H,HF		H
Non-cracked concrete												
Tension N_{Rd}	[kN]	3,9	5,0	6,0	8,0	10,7	8,0	13,3	18,5	11,7	18,2	29,6
Shear V_{Rd}	[kN]	*8,3*	*8,3*	8,5	*12,7*	*14,7*	9,0	*20,0*	*22,7*	23,3	*36,3*	*41,3*
Cracked concrete												
Tension N_{Rd}	[kN]	1,4	3,3	4,0	6,0	8,0	6,4	10,8	13,2	8,3	13,0	21,1
Shear V_{Rd}	[kN]	*8,3*	*8,3*	6,1	*12,7*	*14,7*	6,4	*20,0*	*22,7*	16,6	*25,9*	*41,3*

Recommended loads[a)]

Anchor size		6		8			10			14		
Type	HUS3-	H,C,A, I, P	H,C,A, I,I-flex	H,C,HF			H,C,HF			H,HF		H
Non-cracked concrete												
Tension N_{Rec}	[kN]	2,8	3,6	4,3	5,7	7,6	5,7	9,5	13,2	8,3	13,0	21,2
Shear V_{Rec}	[kN]	*6,0*	*6,0*	6,1	*9,0*	*10,5*	6,5	*14,3*	*16,2*	16,6	*26,0*	*29,5*
Cracked concrete												
Tension N_{Rec}	[kN]	1,0	2,4	2,9	4,3	5,7	4,6	7,7	9,4	5,9	9,3	$\boxed{15,1}$
Shear V_{Rec}	[kN]	*6,0*	*6,0*	4,3	*9,0*	*10,5*	4,6	*14,3*	*16,2*	11,9	*18,5*	$\boxed{29,5}$