




PVC Board 18mm

PVC Board 18mm Technical Data:

For 1.00m wide

- $A = 100 \times (1.80) = 180.00 \text{ cm}^2$
- $I = 100 \times (1.8)^3 / 12 = 48.60 \text{ cm}^4$
- $Z = 100 \times (1.8)^2 / 6 = 54.00 \text{ cm}^3$
- (E) for PVC = 27.00 t/cm²
- (F) Bending stress = 0.175 t/cm²
- Allowable bending moment = 0.945 Kn.m



TECHNICAL PROPERTIES

Dimensions Customizable Sizes	Length: Up to 3500mm Width: Up to 1250mm Thickness: 6mm - Up to 30mm
Tolerances:	Thickness: +/- 0.5 mm
Squareness:	1±mm
Density g/cm ²	0.73 g/cm ³
Static bending (kN) for 18mm	>1.17
Modulus of Elasticity (MPa)	>= 27.00 t/cm ²
Vicat Softening Temperature °C	>70
Charpy impact strength (KJ/m ²)	>15.4
Alkali resistance	< 0.72
Shore hardness D	>72%
Water Resistance	1.24%
Water retention rate	<3%
No. of use:	Slabs: >25 times. Walls/Columns: >30 times. Panels: >40 times.
Stripping	No release agent needed
Fire retardant	Grade C2



VALUE PROPOSITION

An innovative solution which combines much more long-lasting than plywood and also offer an economical price-performance ratio.

Head Office

Factory: Wady Houf, Helwan
Tel: (+202) 23254532 / 23254519
(+20223254534
Fax: (+202) 23671 347
E-mail: sales@acrow.co

