

ACROW EURO-PROPS & ECO-PROPS LOADS

a) ACROW EURO-PROP TABLE (CLASS E):

Extension (m)	AEP E-450		AEP E-350		AEP E-300	
	inner up	outer up	inner up	outer up	inner up	outer up
4.50	36	40				
4.40	37	40				
4.30	39	40				
4.20	40	40				
4.10	40	40				
4.00	40	40				
3.90	40	40				
3.80	40	40				
3.70	40	40				
3.60	40	40				
3.50	40	40	30	36		
3.40	40	40	32	38		
3.30	40	40	34	40		
3.20	40	40	36	40		
3.10	40	40	38	40		
3.00	40	40	40	40	30	36
2.90	40	40	40	40	32	39
2.80	40	40	40	40	34	40
2.70	40	40	40	40	37	40
2.60	40	40	40	40	40	40
2.50	40	40	40	40	40	40
2.40			40	40	40	40
2.30			40	40	40	40
2.20			40	40	40	40
2.10			40	40	40	40
2.00			40	40	40	40
1.90					40	40
1.80					40	40
1.70					40	40



b) ACROW EURO-PROP TABLE (CLASS D): (1/2)

Extension (m)	AEP D-550		AEP D-500		AEP D-400	
	inner up	outer up	inner up	outer up	inner up	outer up
5.50	24	29				
5.40	25	30				
5.30	26	31				
5.20	27	33				
5.10	28	34				
5.00	29	35	23	27		
4.90	31	37	24	28		
4.80	32	38	25	30		
4.70	33	40	26	31		
4.60	35	42	27	32		
4.50	36	44	28	34		
4.40	38	46	29	35		
4.30	40	40	31	37		
4.20	40	40	32	39		
4.10	40	40	34	40		
4.00	40	40	35	40	23	27
3.90	40	40	37	40	24	29
3.80	40	40	39	40	25	30
3.70	40	40	40	40	26	32
3.60	40	40	40	40	28	34
3.50	40	40	40	40	30	36
3.40	40	40	40	40	31	38
3.30	40	40	40	40	33	40
3.20	40	40	40	40	35	40
3.10	40	40	40	40	38	40
3.00	40	40	40	40	40	40
2.90			40	40	40	40
2.80			40	40	40	40
2.70			40	40	40	40
2.60					40	40
2.50					40	40
2.40					40	40
2.30					40	40
2.20					40	40



c) ACROW EURO-PROP TABLE (CLASS D): (2/2)

Extension (m)	AEP D-250		AEP D-150	
	inner up	outer up	inner up	outer up
2.50	24	29		
2.40	26	31		
2.30	29	34		
2.20	34	41		
2.10	38	45		
2.00	40	40		
1.90	40	40		
1.80	40	40		
1.70	40	40		
1.60	40	40		
1.50	40	40	24	29
1.40	40	40	28	33
1.30			32	39
1.20			38	40
1.10			40	40
1.00			40	40
0.95			40	40



Notes:

1. These tables are based on DIN EN 1065.
2. For Class E, the permissible load for any extension is at least 30 kN.
3. For Class D, the permissible load for any extension is at least 20 kN.
4. In case of fixation at the top (prop is fixed with the head as in Tableform, Aludeck, Aero Slab or prop is working as back-propping), the permissible load for any extension is at least 40 kN for Class E & 30 kN for Class D.



d) ACROW ECO-PROP TABLE (CLASS B):

Extension (m)	ECO B-350		ECO B-300	
	inner up	outer up	inner up	outer up
3.50	13	16		
3.40	14	17		
3.30	15	18		
3.20	15	19		
3.10	17	21		
3.00	18	22	15	19
2.90	19	24	16	20
2.80	20	25	17	22
2.70	22	27	19	23
2.60	23	29	20	25
2.50	25	32	22	27
2.40	28	34	24	30
2.30	30	34	26	32
2.20	34	34	28	35
2.10			31	39
2.00			34	43
1.90			34	34



Notes:

1. These tables are based on DIN EN 1065.

