# Contents

1	Introduction									
	1.1	Introduction	4							
2	Swa	Swarm Robotics								
	2.1	Swarm Intelligence and Social animal inspiration	6							
	2.2	Swarm robotics and multi robot systems	6							
	2.3	Swarm robotics	6							
	2.4	Swarm robotics properties	7							
	2.5	Domain of application	7							
		2.5.1 Tasks that cover a region	8							
		2.5.2 Search and rescue missions	8							
		2.5.3 Cleaning of oil speals	8							
		2.5.4 Exploration	8							
		2.5.5 Agriculture	8							
	2.6	Swarm robotics basic tasks and problems	9							
		2.6.1 Aggregation	9							
		2.6.2 Dispersion	9							
		2.6.3 Pattern formation	9							
		2.6.4 Cordinated movement	9							
		2.6.5 Hole avoidance	9							
		2.6.6 Foraging	9							
3	Deep reinforcement learning									
	3.1	Introduction	.1							
	3.2	Machine learning	.1							
	3.3	Reinforcement learning	.1							
	3.4	Q learning	.2							
	3.5	Deep Q learning	.3							
	3.6	Deep Deterministic policy gradient	4							
	3.7	Related Work	.5							
4	Pro	blem formulation And Solution Conception 1	7							
	4.1	Introduction	.8							
	4.2	Goal defintion	8							
	4.3	Problem Formulation	8							
		4.3.1 Environement	.8							
		4.3.2 Shape generation	9							

4.4	State Representation	19					
	4.4.1 Introduction	19					
	4.4.2 State Representation	19					
4.5	Reward Function Design	21					
4.6	Roboting Operating system	22					
	4.6.1 Ros Basics	22					
4.7	$\label{eq:TurtleBot} \text{TurtleBot}  \dots $	23					
	4.7.1 TurtleBot3 components	23					
4.8	Talk about how we used diffrent formation from easy one to hard $$ . $$ .	25					
4.9	State Of the art	25					
4.10	DQN	25					
4.11	DDPG	25					
4.12	Thier usages in multi agent pros and cons	25					
4.13	problem formulation and solution	25					
4.14	we opt for maddpg decentrilzed excution	25					
4.15	5 we opt for maddpg for better perfomance and scalability						
4.16	ROS and gazebo						
4.17	Conception of the solution						
4.18	Rewards desgin						
4.19	Networks Desgin	25					
4.20	talk about how you choose the hyperparameters	25					
4.21	how you calculeted tha angle and how lds works	25					
4.22	implementation of the solution	25					
4.23	How other papers algorithms to train the agents	25					
4.24	basics of robotics ,turtlebot and equipments						
4.25	Networks desgin talk in detail whey the paremerrs was choses 26						
4.26	shape generation and random						
4.27	7 Multi agent systems						

1 Introduction

# 1.1 Introduction

These days, mobile robots have taken place in many fields like industry automation, planetary exploration, entertainment, and construction ..., for their ability to work in extreme environments with high precision and without fatigue[1]. Even so, a robot occasionally needs the support of other robots because it is impossible or difficult for them to perform some tasks on their own. For that, a new field has emmerged to deal with these problems, swarm robotics.

Swarm robotics is relatively a new research topic that has gained more attraction in the last few years. It is about studying how a large number of simple robots (a swarm) can collaborate and work together to achieve predefined objectives and tasks that are often difficult or impossible to do for a single robot.[2].

One of the main challgenes that swarm robotics researchs face, is pattern formation. Where the agents (robots) try to form diffrent gemoetric shapes like squeres, trinagles and circles in order to perform a specific task.

We can solve this problem using two different aproches. The first one is a Centrelized method where there exist a centel unit which controles the swarm and give global state access. However, implementing this apport can be coslty and less robust to faillures. The second aproch is a dicentrilized one, where each robot have uses local communication and have access only to his local state.[3]

Our primary objective in this thesis is to implement an RL algorithm in a system made up of a group of robots in order to form some specific geometric patterns using a decentralized method. Each robot will only have access to its local state and will interact and communicate with its neighbors in order to form the desired shapes.

2 Swarm Robotics

# 2.1 Swarm Intelligence and Social animal inspiration

Social animal and insects behavior in groups like the bees dancing, wasp's nest-building, ant's collaboration, bird flocking and fish schooling has caught the attention of researchers for their ability to archive complex tasks and working in coordination, which demonstrate some form of swarm intelligence that researchers have taken inspiration from to design and implement swarm robotics systems.[4]

They also report that social insects were able to accomplish thier goals like searching for food, alerting the presence of an enemy, or collaborate to lift heavy objects, without having access to the global state or having a leader to guide them. They were only able to accomplish this by utilizing local interactions and communication, which spread to other members and and prompted group-wide cooperation.[4]

# 2.2 Swarm robotics and multi robot systems

The early 1980s are when multi robots systems first gained popularity. As the name suggests, multi robot systems introduce the idea of teamwork in order to complete tasks that are challenging or impossible to complete alone by the robots. Seven topics of study have been identified in this feild which includes:

- Biological Inspirations;
- Communication
- Localization, mapping, and exploration;
- Object transport and manipulation;
- Motion coordination:
- Reconfigurable robots.

Swarm robotics is a subfield of multi-robot systems that differs from other multi-robot systems in some ways.[5]

### 2.3 Swarm robotics

Swarm robotics has no one definition because it is a rapidly developing area and new research is constantly being done in it. But we can take this defintion from a cited paper. "swarm robotics is the study of how large number of relatively simple physically embodied agents can be designed such that a desired collective behavior

emerges from the local interactions among agents and between the agents and the environment." [6].

The main characters of swarm robotis are:

- The robots in the swarm must be autonomous.
- The number of robots in the swarm is large.
- Homogeneity is required in robots. A small number is acceptable if not.
- Robots must be incompetent with regard to the primary task they must complete, otherwise, they will fail or perform poorly.
- Robots are limited to local communication and sensing. It makes sure that coordination is spread, making scalability one of the system's characteristics.[4]

# 2.4 Swarm robotics properties

Swarm robotics have some properties that describe the system's current condition. Bellow are some of these properties:

Robustness: the ability of the swarm to still function even with the loss of some members of the group or the faillure of some parts of the system.

**Scalability**: The ability of the system to perform well on smaller or larger group sizes without impacting the performance of the swarm.

**Flexibility** It is the capability of the swarm to adapt and manage the new changes that occur in the environment

**Autonomus**: Implys that there is no central authority controlling the behavior of the swarm and each individual is independent of the others.

**Local communication** The communication among swarm members is local since they don't have access to the swarm's overall state. [7][8]

# 2.5 Domain of application

In this section, we will list some of the significant fields domains where swarm robotics fits in, and can impact in solving the domain problem.

### 2.5.1 Tasks that cover a region

: Because of the widespread sensing capabilities that the swarm has, swarm robotics is most suited for tackling problems that cover an area of the space, such monitoring the environment of a lake or surveillance of a specific area. [6][8]

### 2.5.2 Search and rescue missions

In different types of accident or disasters that happen like earthquakes where the human intervention is difficult, swarm robots can be deployed for these type of missions. examples of such robots are: polyobot, swarm bot and M-TRAN.

### 2.5.3 Cleaning of oil speals

A swarm of robots can reduce the cost and time in such incidents. an exemple of robots that were deployed to such tasks is: Seaswarm, which was developed by the senseable group at MIT.

### 2.5.4 Exploration

To investigate Mars, swarm robots like Marsbees have been created. the same holds true for the CoCoRo swarm, which was employed for in-depth underwater investigation.

### 2.5.5 Agriculture

As they can be used to improve the agriculture and monitor the status of crops.

# 2.6 Swarm robotics basic tasks and problems

SR problems can be broken down into fundamental tasks that the swarm frequently carries out in an effort to accomplish its objective. this tasks are: aggregation,d ispersion,pattern formation, coordinated movement, hole avoidance and foraging[3][4].

# 2.6.1 Aggregation

Aggregation of the robots is performed in order to accomplish some form or to exchange information. This problem can be easy in a centralized system, but difficult in a decentralized one.

## 2.6.2 Dispersion

For exploration purposes, sometimes, the swarm must cover a wide range of area without losing the connection between the members, in order to expand the group sensing capabilities.

### 2.6.3 Pattern formation

Sometimes, the swarm must form some specific patterns like circles, squares or lines in order to lift some objects or traverse some ways corridors.

### 2.6.4 Coordinated movement

It is making an effort to coordinate the group movements by maintaining the established pattern between the robots.

### 2.6.5 Hole avoidance

As suggested by the name, the group makes an effort to avoid stepping into holes.

### 2.6.6 Foraging

The swarm aims to locate objects, pick them up, and position them where needed.

3 Deep reinforcement learning

# 3.1 Introduction

In this chapter we will provide an overview about the feild of reinforcement learning, including its applications, various techniques, and how it relates to swarm robots. Before that, we will briefly discuss machine learning since it is the foundation of RL before we move on.

# 3.2 Machine learning

Machine learning is a sub field of artificial intelligence, which focuses on developing algorithms and models that make prediction and take decisions without being explicitly programmed to do so based on the input data they receive. Generally speaking, there are three types of machine learning algorithms, suppervised algorithms which obtain labeled data and attempt to categorize or anticipate the unknown one. Unsupervised learning algorithms, where the data is unlabeled and it is the job of the ml algorithms to extract hidden patterns in it. And finally, reinforcement learning algorithms where the algorithm learns to make decisions based on trial and error and rewards, by interacting with an environment.

# 3.3 Reinforcement learning

Reinforcement learning algorithms are based on a agent that interact and observe an environment in order to take actions that maximize the reward for a given task.

The goal of the agent is to learn an optimal policy  $(\Pi)$  which maps state to actions in order to get the best possible action to take in a given situation. This can be achieved by maximizing the expected reward that the agent receive from the environment on each step he takes.[9]

Formally, RL can be described as a Markov Decision Process (MPD) where the future state depends only on the current one. An MPD consists of:

- A set of states S
- A set of actions A
- A transition dynamics  $\rho(S_{t+1}|a, S)$ . which give the probability of being in state  $S_{t+1}$  based on the current state S and the performed action A.
- A reward function  $R(S_t, A_t, S_{t+1})$  which outputs a scalar reward  $r_t \subset R$ .
- A discount factor  $\gamma \in [0,1]$  which emphasis either immediate or future rewards.

From the above definition, the policy function  $\Pi$  will a map a given state to a probabilty distribution over actions:  $\Pi: S \longrightarrow \rho(A=a|S)$ . The goal of the agent to find the optimal policy  $\Pi$  which maximize the expected return :

$$\Pi^* = argmax_{\Pi}E[R|\pi]$$

If the MPD is episodic, then the agent will accumulates a set of reward at the end of each episode which is called a return:

$$R = \sum_{t=0}^{T-1} \gamma^t r_{t+1}$$

Setting  $\gamma < 1$  will ensure the convergence of the return in case of non episodic MPDS.[9].

# 3.4 Q learning

Q-learning is a type of model free reinforcement learning algorithm based on the dynamic programming technique, where the agent tries to maximize it rewards by finding the optimale policy  $\Pi$  in an iterative manner. In order to acheive this, the agent uses a type of equation called value function that gives it the value or the reward of being in a state s and taking action according to it policy  $\Pi$ .

$$V^{\Pi}(S) = E[r(s, a) + \gamma V^{\Pi}(s')]$$

In order to find the optimal value function, hence finding the optimal policy, the equation must satisfy the bellman optimality condition which states that:

$$V^*(S) = max_a E[r(s, a) + \gamma V^*(s')]$$

The same goes for the action-value function which gives the return if the agent chooses the action a and follow the optimale policy thereafter.

$$Q^*(S, a) = E[r(s, a) + max_a \gamma Q^*(s', a)]$$

[10].

# 3.5 Deep Q learning

The problem with traditional Q-learning or Rl algorithms in general, is the inability to work in a high dimensional input states where discritization and hand-crafted features extraction is performed in order to it to work. For this, deep learning was combined with traditional Q-learning in order to overcome these challenges.[11]

Deep Q learning was firstly introduced in an article by the deepmind group, where it was tested in atari games in which the agent was given raw input images of the emulator and it was the goal of the agents to win the games by using the Q learning algorithm.

Besides using the bellmen equation to converge and calculate the loss, an experience replay memory was used to store the the experiences of the agents during the game and then sampled randomly to be fed to the neural network to learn and in order to break the correlation that apears when fedding them sequential data.[11]

```
Algorithm 1 Deep Q-learning with Experience Replay
Initialize replay memory D to capacity N
```

Initialize action-value function Q with random weights

for episode = 1, M do

Initialise sequence s1 = {x1} and preprocessed sequenced  $\phi_1$  =  $\phi(s_1)$ 

for t = 1, T do

With probability  $\epsilon$  select a random action  $a_t$  otherwise select  $a_t = max_aQ^*(\phi(s_t, a; \theta))$ 

Execute action  $a_t$  in emulator and observe reward  $r_t$  and image  $x_{t+1}$ 

Set  $s_{t+1} = s_t$ ,  $a_t$ ,  $x_{t+1}$  and preprocess  $\phi_{t+1} = \phi(s_{t+1})$ 

Store transition  $(\phi_t, a_t, r_t, \phi_{t+1})$  in D

Sample random minibatch of transitions  $(\phi_t, a_t, r_t, \phi_{t+1})$  in D set

$$y_{j} = \begin{cases} r_{j}, & \text{for terminal } \phi_{j+1}. \\ r_{j} + \gamma \max_{a} Q(\phi_{j+1}, a'; \theta), & \text{for non-terminal } Q(\phi_{j+1}). \end{cases}$$
 (1)

Perform a gradient descent step on  $(y_j - Q(\phi_j, a_j; \theta))$ 

end for

end for

# 3.6 Deep Deterministic policy gradient

One of the major problems of DQN is that he works only in discreate action spaces. For this, tasks that require continuous control, such as the linear and rotational movements of robots, require discretization. In most cases, this can result in a large action space, which slows convergence and causes instability.. [12]

For this, there is another type of DRL algorhims named Deep Deterministic policy gradient, which is a policy based method actor critic algorithm, that takes the benifites of both methods (policy based method and value based method, and useses the actor critic to reduce the bias (underfitting) that occurs ...

DDPG in composed of two neural networks: the actor and the critic. The job of the actor is to select an action based on the input state. And it is the critic who will determine if that action was suitable or not by observing the rewards returned when taking that specific action in a specific state.

The critic network is learned using bellman equation same as q-learning.

The DDPG algorhim also useses a replay buffer to store agent exepriences in order to sample from them later when training the networks.

Like in Q-learning and to enable better exploration for the agent, a noise is sampled from a process  $\eta$  then added to the output of the actor network. It is common to use the Ornstein-Uhlenbeck process to generate temporally correlated values.[12]

### Algorithm 2 Deep Deterministic Policy Gradient (DDPG)

```
1: Initialize actor network \mu(s|\theta^{\mu}) and critic network Q(s,a|\theta^{Q}) with weights \theta^{\mu}
     and \theta^Q
 2: Initialize target networks \mu'(s|\theta^{\mu'}) \leftarrow \mu(s|\theta^{\mu}) and Q'(s,a|\theta^{Q'}) \leftarrow Q(s,a|\theta^{Q}) with
     weights \theta^{\mu'} \leftarrow \theta^{\mu} and \theta^{Q'} \leftarrow \theta^{Q}
 3: Initialize replay buffer R
 4: for episode = 1 to M do
          Initialize a random process for action exploration
 5:
 6:
          Receive initial observation state s_1
          for t = 1 to T do
 7:
               Select action a_t = \mu(s_t|\theta^{\mu}) + \mathcal{N}t according to current policy and explo-
 8:
     ration noise \mathcal{N}t
 9:
               Execute action a_t and observe reward r_t and new state st + 1
               Store transition (s_t, a_t, r_t, st + 1) in R
10:
               Sample a random minibatch of N transitions (s_i, a_i, r_i, s_{i+1}) from R
11:
               Set y_i = r_i + \gamma Q'(s_{i+1}, \mu'(s_{i+1}|\theta^{\mu'})|\theta^{Q'})
12:
               Update critic by minimizing the loss: \mathcal{L} = \frac{1}{N} \sum_{i} (y_i - Q(s_i, a_i | \theta^Q))^2
13:
               Update actor policy using the sampled policy gradient: \nabla_{\theta^{\mu}} J \approx
14:
     \frac{1}{N} \sum_{i} \nabla_a Q(s, a|\theta^Q) |s = s_i, a = \mu(s_i) \nabla \theta^\mu \mu(s|\theta^\mu) |s_i|
               Update target networks: \theta^{\mu'} \leftarrow \tau \theta^{\mu} + (1-\tau)\theta^{\mu'} and \theta^{Q'} \leftarrow \tau \theta^{Q} + (1-\tau)\theta^{Q'}
15:
          end for
16:
17: end for
```

### 3.7 Related Work

In this section, we present some of the work that have applied RL algorithms in training agents and robotics systems.

The most used algorithm is Deep Q learning, where [11] have applied it in learning playing atari games by using a convolutionnal neural network by providing raw image pixels as input, where they demonstarted that the agents achived great performance even surpassing human level.

In continuous action spaces, [12] have used the ddpg algorithm, which is an extension of the DQN and the DPG algorithms. They have used an actor critic model free policy based algorithm which operate in conitous action space by applying it in several simulated physics tasks, and also shows great result achived by the agents.

In field of multi agents. [13] where they used a decentrilized approach to train multi agent to form some patterns using the DQN network with a central replay buffer that contains agents experinces in order for them to learn cooparityly.

For robotics, [14] have used the Proxiaml policy optimization algorithm (PPO) which is a policy based one, to controll in a decentrized manner a group of robot to reach their target by avoiding collison between them. Also in [15] have used the ddpg algorithm to traing mutli robots to encircle some target in a static position or

in mouvement where the agents (robots) learn to coopretivly acheve their task by using also a central replay memory.

Finnaly, in [16],[17] and [18] have applied the ddpg and dqn algorithms for path playing and postion control of robots in order to achive the target goals.

4	Problem	formulation	on And	Solution	Conception	on

# 4.1 Introduction

In this section, we'll go into detail about the objective that needs to be accomplished by our robots, the difficulties they must overcome, and then our suggested solution.

### 4.2 Goal defintion

: Our objective in this thesis is to make multi robots form geometric patterns like lines, circles, squares, and triangles while avoiding collisions and moving toward their destination in a quick and efficient manner.

### 4.3 Problem Formulation

### 4.3.1 Environement

We will describe our multi robot environemnt as an MDP where S are the set of states that each robot will reacive. A are the set of actions that it can take (left,right,towords ...). and R are the set of Rewards that each robot will get during each episode. The goal of each robot is to maximize his return by reaching the goal target and avoiding collisons with the wall and other robots. We will use the DDPG alrorithm to controll the robots in a contius manner

For the environemnt, we will Consider a scenario in which there are n (n > 2) robots moving in a 2D environment. Assuming that every robot is aware of a central point that they must form shapes around or along it.



Figure 1: formation

We'll utilize the polar coordinates  $(R,\Phi)$ , where R and  $\Phi$  are the radius and angle from the central point, respectively. After assigning each robot a goal position, we will convert it to homogeneous coordinates so it may be reached by them. The desired shapes will be formed by defining the distance and the angle from the center of the formation and by using each robot id to generate unique goal for it.

### 4.3.2 Shape generation

In order to form the different shapes, each robot will have an id = (1...n) where n is the number of robots, and he will get assigned a goal based on it using the radious and the distance from the central point. So if the target shape is a triangle the target goals will be as follow:

$$d_i = R$$
 and  $\Phi_i = \Phi$ 

where  $d_i$  and  $\Phi_i$  are the distance and the angle from the central point respectively. So if they want to form triangles ,squares, or circles this will be their positions:

$$d_i = R$$

$$\Phi_i = 2\Pi/id$$

For lines

$$d_i = R * id \Phi_i = 0$$

and we can keep modifying the distance and angle for each robot to get any shape.

And to simplify the job for the robot, we will transform the coordinates from polar to homogonous in order to calculate the distance between the robot and their target goal.

# 4.4 State Representationn

### 4.4.1 Introduction

The state and reward function must be well designed in order to generate the desired shape because how they are represented will directly impact our robot's performance towards achieving their goals and the architecture of the neural network.

### 4.4.2 State Representation

State are the inputs to our neural network. They are the inputs for our neural network and based on them, we can calulate the rewards that the robot will get when acting in the environement.

In our implementation we have defined four kind of state information, the distance to goal, angle to goal, the minimum detected object distance and it's angle for collision avoidance.

• The distance to goal: The first component in our state representation is the distance to goal, which will be calculated using the euclidean distance between the robot and the goal.

$$D(P,G) = \sqrt{(Py - Gy)^2 + (Px - Gx)^2}$$

Where P and G are the current homogeneous coordinates of the robot and the target goal respectively.

• The angle to goal: The second component is the angle to goal. And to find it we need to calculate the difference between the robot yaw, which is it's orientation around it's vertical axis, and the angle between the goal and the robot positions.

$$\theta(P,G) = yaw - arctan(P/G)$$

- The minimum detected distance: In order to detect other robots and avoid collision, we use an LDS (we will talk about it later when we describe the robot equipment) which gives us an array of 24 elements where each value is the minimum distance detected and each index is the angle of detection.
- The angle of detection: It is is the angle of the detected object relative to the robot lds.

This is a common state representation used to control a moving robot towards the goal target, as they have provide a very clear guidance for it. [18] [17]

In the next part, we will talk how we calculate the rewards of each robot to guide it in a efficient manner towards it goal based on the state input.

# 4.5 Reward Function Design

The reward function design is a critical part of any RL system. A well designed reward function will give the robot more feedback when acting in the environment thus making the task more straight forward.

The reward function was designed to engourge and reward the robot more, when he aproches the goal target, and penilize him when he collide with the wall or other robots.

The design of the function is based on the state. We have used the distance , the angle and the LDS to form the final function.

We have divided the function into three parts: The first part contains with the distance reward. We will give the robot more reward when he approaches the target goal and less when he doesn't. Formally it can be described:

$$R_D = -(D_{goal} - D_{init}) + \alpha \tag{1}$$

Where  $D_{goal}$  is the changing distance between the robot and the target goal,  $D_{init}$  is the initial distance between the robot and the target goal. and  $\alpha$  is a parameter to adjust.

The second part is to the angle of the robot to the goal. formally:

$$R_{\theta} = -(\theta_{qoal}) + +\beta \tag{2}$$

where  $\theta_{goal}$  ranges between  $-\pi$  and  $\pi$ . we added the  $\beta$  which add some reward when the angle approaches zero.

And For avoiding collion between the robots and the wall, we have set two values. The first one is set when the robot aproches the object which can lead to a collision. And the second one is when is actualy collide with it.

$$R_c = \begin{cases} -10, & \text{if } mdd < 0.5m. \\ -500, & \text{if } mdd < 0.13m \text{ (a crash ).} \\ 0 & \text{else.} \end{cases}$$
 (3)

where mdd stands for the minimum detected distance. Finally, we can add 1, 2 and 3 to form the finale reward function:

$$R = R_D + R_\theta + Rc \tag{4}$$

# 4.6 Roboting Operating system

We will use the roboting operating system (ROS), a collection of open source software and tools, to control the robots. ROS will simplify our work by giving us the necessary tools for controlling the robots, determining their positions and angles, gathering sensor data and preparing it for manipulation, and also giving the robots a way to communicate with one another.

### 4.6.1 Ros Basics

There are five concepts that ROS is built on that will allow us to implement our solution in simple and modular way.

- **Nodes**: ros is made up of noes where each node is responsible for a single giving task like moving the robot, getting sensor data, doing some processing ... nodes can communicate between the using topics and services.
- Topics: topics are a way for nodes to communicate between them. Each node can either subscribe to a topic thus reactiving informations from other nodes, or publish to some topic to send information to other nodes.
  - For example: a node can subscribe to a topic that publish the position of the robot from another node which is responsible for providing this information.
- Services: They are the same as topics but they differ in that data is received when requested by a client in contrast to topics where there are a stream of data updated continuously.

For example: We can have a service that generate goals or reset the simulation.




Figure 2: Ros

# 4.7 TurtleBot

We will be using the turtlebot robot which is developed by open robotics. They same organization behind ros and the gazebo similator.

This robot is used for educational, reaserch and prototyping purpuses, where multiple version have been developed. In this thesis, we will be using the turblebot3-burger version.

### 4.7.1 TurtleBot3 components

TurtleBot3 is a two wheeled, small size robot composed of many parts that generally robots have like Gyroscope, Accelerometer and Programmable LEDs ..., and he uses Raspberry Pi as the core computer board.

# Scalable Structure Single Board Computer (Raspberry Pi) OpenCR (32-bit ARM Cortex®-M7) DYNAMIXEL x 2 for Wheels Sprocket Wheels for Tire and Caterpillar Li-Po Battery

# TurtleBot3 Burger

Figure 3: TurtleBot3 [ref:https://emanual.robotis.com/]]

But the most important component, and what we will relay on in this project is the Laser Distance Sensor or (LDS) which gives a 360 degree sensing of ob objects in the environment with a maximum distance of 3.5m

The (LDS) was the main source of data to train our neural networks besides the robots positions. we have used it to detect other robots and to avoid collisions during the navigation.




Figure 4: Lds

- 4.8 Talk about how we used diffrent formation from easy one to hard
- 4.9 State Of the art
- 4.10 DQN
- 4.11 DDPG
- 4.12 Thier usages in multi agent pros and cons
- 4.13 problem formulation and solution
- 4.14 we opt for maddpg decentrilzed excution
- 4.15 we opt for maddpg for better perfomance and scalability
- 4.16 ROS and gazebo
- 4.17 Conception of the solution
- 4.18 Rewards desgin
- 4.19 Networks Desgin
- 4.20 talk about how you choose the hyperparameters
- 4.21 how you calculeted tha angle and how lds works
- 4.22 implementation of the solution
- 4.23 How other papers algorithms to train the agents
- 4.24 basics of robotics , turtlebot and equipments

•

4.25 Networks desgin talk in detail whey the paremerrs was choses

.

4.26 shape generation and random

.

4.27 Multi agent systems

•

# References

- [1] F. Rubio, F. Valero, and C. Llopis-Albert, "A review of mobile robots: Concepts, methods, theoretical framework, and applications," *International Journal of Advanced Robotic Systems*, vol. 16, no. 2, p. 1729881419839596, 2019.
- [2] L. Bayındır, "A review of swarm robotics tasks," *Neurocomputing*, vol. 172, pp. 292–321, 2016.
- [3] L. Bayindir and E. Şahin, "A review of studies in swarm robotics," *Turkish Journal of Electrical Engineering and Computer Sciences*, vol. 15, no. 2, pp. 115–147, 2007.
- [4] I. Navarro and F. Matía, "An introduction to swarm robotics," *Isrn robotics*, vol. 2013, pp. 1–10, 2013.
- [5] T. Arai, E. Pagello, L. E. Parker, et al., "Advances in multi-robot systems," IEEE Transactions on robotics and automation, vol. 18, no. 5, pp. 655–661, 2002.
- [6] E. Şahin, "Swarm robotics: From sources of inspiration to domains of application," in Swarm Robotics: SAB 2004 International Workshop, Santa Monica, CA, USA, July 17, 2004, Revised Selected Papers 1, pp. 10–20, Springer, 2005.
- [7] M. Brambilla, E. Ferrante, M. Birattari, and M. Dorigo, "Swarm robotics: a review from the swarm engineering perspective," *Swarm Intelligence*, vol. 7, pp. 1–41, 2013.
- [8] I. Olaronke, I. Rhoda, I. Gambo, O. Ojerinde, and O. Janet, "A systematic review of swarm robots," 2020.
- [9] K. Arulkumaran, M. P. Deisenroth, M. Brundage, and A. A. Bharath, "A brief survey of deep reinforcement learning," arXiv preprint arXiv:1708.05866, 2017.
- [10] C. J. Watkins and P. Dayan, "Q-learning," *Machine learning*, vol. 8, pp. 279–292, 1992.
- [11] V. Mnih, K. Kavukcuoglu, D. Silver, A. Graves, I. Antonoglou, D. Wierstra, and M. Riedmiller, "Playing atari with deep reinforcement learning," arXiv preprint arXiv:1312.5602, 2013.
- [12] T. P. Lillicrap, J. J. Hunt, A. Pritzel, N. Heess, T. Erez, Y. Tassa, D. Silver, and D. Wierstra, "Continuous control with deep reinforcement learning," arXiv preprint arXiv:1509.02971, 2015.

- [13] E. A. O. Diallo and T. Sugawara, "Multi-agent pattern formation: a distributed model-free deep reinforcement learning approach," in 2020 International Joint Conference on Neural Networks (IJCNN), pp. 1–8, IEEE, 2020.
- [14] P. Long, T. Fan, X. Liao, W. Liu, H. Zhang, and J. Pan, "Towards optimally decentralized multi-robot collision avoidance via deep reinforcement learning," in 2018 IEEE international conference on robotics and automation (ICRA), pp. 6252–6259, IEEE, 2018.
- [15] J. Ma, H. Lu, J. Xiao, Z. Zeng, and Z. Zheng, "Multi-robot target encirclement control with collision avoidance via deep reinforcement learning," *Journal of Intelligent & Robotic Systems*, vol. 99, pp. 371–386, 2020.
- [16] Y. Dong and X. Zou, "Mobile robot path planning based on improved ddpg reinforcement learning algorithm," in 2020 IEEE 11th International Conference on software engineering and service science (ICSESS), pp. 52–56, IEEE, 2020.
- [17] H. Gong, P. Wang, C. Ni, and N. Cheng, "Efficient path planning for mobile robot based on deep deterministic policy gradient," Sensors, vol. 22, no. 9, p. 3579, 2022.
- [18] F. Quiroga, G. Hermosilla, G. Farias, E. Fabregas, and G. Montenegro, "Position control of a mobile robot through deep reinforcement learning," *Applied Sciences*, vol. 12, no. 14, p. 7194, 2022.