

Local Development Setup - Secrets Configuration

⚠ Important: Do NOT commit real secrets to Git!

This guide helps you set up local secrets for development without exposing them in version control.

📁 Files You Need to Create

1. `appsettings.Development.json`

Copy from `appsettings.json.example` and update with your actual values:

```
cp appsettings.json.example appsettings.Development.json
```

Then edit `appsettings.Development.json` with your actual credentials:

```
{
  "ConnectionStrings": {
    "DefaultConnection": "Server=ism-
sandbox.database.windows.net;Database=ISMSponsor;User
Id=ISMSponsorUser;Password=YOUR_ACTUAL_PASSWORD;TrustServerCertificate=true;MultipleActiveResultSets=true"
  },
  "Authentication": {
    "Google": {
      "ClientId": "YOUR_ACTUAL_GOOGLE_CLIENT_ID",
      "ClientSecret": "YOUR_ACTUAL_GOOGLE_CLIENT_SECRET"
    }
  }
}
```

2. `appsettings.AzureMigration.json` (if needed)

```
cp appsettings.AzureMigration.json.example appsettings.AzureMigration.json
```

Update with your actual Azure database credentials.

🔑 Where to Get Credentials

Database Connection String

- **Server:** Your Azure SQL Server hostname
- **Database:** ISMSponsor
- **User ID:** Database username

- **Password:** Database password (ask your DBA or check Azure Portal)

Google OAuth Credentials

1. Go to [Google Cloud Console](#)
2. Select your project (or create one)
3. Navigate to: **APIs & Services** → **Credentials**
4. Find your OAuth 2.0 Client ID
5. Copy **Client ID** and **Client Secret**

Authorized Redirect URIs must include:

- <http://localhost:5001/Account/GoogleCallback> (Development)
- https://YOUR_APP.azurewebsites.net/Account/GoogleCallback (Production)

For Azure Deployment

Don't use config files! Use the Azure CLI script instead:

```
# Edit with your actual values
nano scripts/configure-azure-app-service.sh

# Update these lines with real credentials:
RESOURCE_GROUP="your-resource-group"
APP_NAME="your-app-name"

# Also update the Google OAuth credentials in the script
```

Then run:

```
bash scripts/configure-azure-app-service.sh
```

Verify Your Setup

These files should be ignored by Git (check [.gitignore](#)):

-  [appsettings.Development.json](#)
-  [appsettings.AzureMigration.json](#)
-  [appsettings.json](#) (custom local settings)

These files are safe to commit (no secrets):

-  [appsettings.json.example](#)
-  [appsettings.AzureMigration.json.example](#)
-  [appsettings.Production.json](#) (uses placeholders)
-  [appsettings.Pilot.json](#)

Check What Files Are Tracked

```
# See what's staged for commit
git status

# Make sure no files with secrets are listed!
# If you see appsettings.Development.json or similar, DO NOT commit!
```

If You Accidentally Committed Secrets

1. **Immediately rotate all exposed credentials** (change passwords, regenerate OAuth secrets)
2. Remove from Git history:

```
git rm --cached appsettings.Development.json
git commit -m "Remove sensitive config file"
```

3. Add to **.gitignore** (already done)
4. Update credentials in:
 - Google Cloud Console (OAuth)
 - Azure SQL Server (database password)
 - Azure App Service settings

Need Help?

Contact your team lead or check:

- [AZURE_APP_SERVICE_CONFIGURATION.md](#) - Azure deployment guide
- [AZURE_DEPLOYMENT_FIX.md](#) - Troubleshooting guide