


GENERAL PURPOSE APPLICATION.

FEATURES

- Low Saturation Voltage
: $V_{CE(sat)}=1.0V(\text{Max.})$ at $I_C=2A$, $I_B=0.2A$.
- Complementary to KTB1366.

MAXIMUM RATING ($T_a=25^\circ\text{C}$)






CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Base Voltage	V_{CBO}	60	V
Collector-Emitter Voltage	V_{CEO}	60	V
Emitter-Base Voltage	V_{EBO}	7	V
Collector Current	I_C	3	A
Base Current	I_B	0.5	A
Collector Power Dissipation	$T_a=25^\circ\text{C}$	2	W
	$T_c=25^\circ\text{C}$	25	
Junction Temperature	T_j	150	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	-55 ~ 150	$^\circ\text{C}$



ELECTRICAL CHARACTERISTICS ($T_a=25^\circ\text{C}$)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current	I_{CBO}	$V_{CB}=60V$, $I_E=0$	-	-	100	μA
Emitter Cut-off Current	I_{EBO}	$V_{EB}=7V$, $I_C=0$	-	-	100	μA
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C=50mA$, $I_B=0$	60	-	-	V
DC Current Gain	$h_{FE}(\text{Note})$	$V_{CE}=5V$, $I_C=0.5A$	60	-	200	
Collector Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=2A$, $I_B=0.2A$	-	0.25	1.0	V
Base-Emitter Voltage	V_{BE}	$V_{CE}=5V$, $I_C=0.5A$	-	0.7	1.0	V
Transition Frequency	f_T	$V_{CE}=5V$, $I_C=0.5A$	-	3.0	-	MHz
Collector Output Capacitance	C_{ob}	$V_{CB}=10V$, $I_E=0$, $f=1\text{MHz}$	-	35	-	pF
Switching Time	Turn-on Time	t_{on}	-	0.65	-	μS
	Storage Time	t_{stg}	-	1.3	-	
	Fall Time	t_f	-	0.65	-	

Note : h_{FE} Classification O:60 ~ 120, Y:100 ~ 200



This datasheet has been download from:

www.datasheetcatalog.com

Datasheets for electronics components.