

Indoor Air Quality and Health

Knowledge towards indoor air quality

* Required

1. Gender *

Mark only one oval.

- ☐ Male
☐ Female

2. Age *

Please insert your age in years format (e.g. 24)

3. Race *

Mark only one oval.

- ☐ Malay
☐ Chinese
☐ Indian
☐ Bumiputera

Knowledge of IAQ

Please choose the following statement based on the scale given, indicate by number 1 - 5.

4. Please tick the appropriate answer based on your understanding *

Strongly Disagree	Disagree	Neutral	Agree	Strongly Agree
1	2	3	4	5

Mark only one oval per row.

	1	2	3	4	5
1. Standard of IAQ is the basis on the IAQ Hong Kong Standard	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
2. Ventilation calculation for centralize air-conditioning was based on the air-change per hours	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
3. Occupants can bring the pollutants through the shirt	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
4. Staircase are one of the example that influence the pathway of the pollutant	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
5. Carbon monoxide was associated with the exposure to the high occupant	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
6. Total fungus more than 500 CFU/m3 are consider safe	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
7. OSH Act 1994 indicate that the risk of the IAQ for prescribe activity will be control fully by the building managers	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
8. Carbon dioxide can be used as indicator for ventilation effectiveness	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
9. Negative pressure usually created inside the office to avoid any pollutants coming inside the work areas	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
10. Road that are closely to the windows can influence the particulate to be impacted on the AHU if the bird screen are not install	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
11. Chemical exposure to the formaldehyde can come from the furniture	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
12. Double door system are one of the mechanism to limit the thermal comfort setting within the centralized building system	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
13. Photocopied machine can be used within the open space provided with the local exhaust ventiation system	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
14. sick building syndrome was separated into two major component namely mucosal and dermal symptoms	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
15. Building related illness was due to the exposure of non-specific agent of microbes that possible to influence human health	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>

This content is neither created nor endorsed by Google.

Google Forms