

---

# Network Applications: Network Programming: UDP, TCP

Qiao Xiang

<https://qiaoxiang.me/courses/cnns-xmuf21/index.shtml>

10/12/2021

# Outline

---

- ❑ Admin. and recap
- ❑ Network application programming
  - UDP sockets
  - TCP sockets

# Admin.

---

- ❑ Lab assignment 1 due on Oct. 14
  - ❑ By email or in class

# Recap: Connectionless UDP: Big Picture (Java version)

## Server (running on `serv`)

create socket,  
port=`x`, for  
incoming request:  
`serverSocket =`  
`DatagramSocket( x )`

read request from  
`serverSocket`

generate reply, create  
datagram using client  
host address, port number

write reply to  
`serverSocket`


## Client

create socket,  
`clientSocket =`  
`DatagramSocket()`

Create datagram using (`serv`,  
`x`) as (`dest addr. port`),  
send request using `clientSocket`

read reply from  
`clientSocket`

close  
`clientSocket`



# Recap: UDP Sockets

## server

Public address: 128.36.59.2

Local address: 127.0.0.1

UDP socket space

address: {127.0.0.1:9876}  
snd/rcv buf:

address: {128.36.59.2:9876}  
snd/rcv buf:

address: {\*:6789}  
snd/rcv buf:

⋮

address: {128.36.232.5:53}  
snd/rcv buf:

```
InetAddress sIP1 =  
    InetAddress.getByName("localhost");  
DatagramSocket ssock1 =  
    new DatagramSocket(9876, sIP1);
```

```
InetAddress sIP2 =  
    InetAddress.getByName("128.36.59.2");  
DatagramSocket ssock2 =  
    new DatagramSocket(9876, sIP2);
```

```
DatagramSocket serverSocket =  
    new DatagramSocket(6789);
```

UDP demultiplexing is based on matching (dst address, dst port)

# Java Server (UDP): Processing

A simple upper-case UDP echo service is among the simplest network service. Are there any problems with the processing?

```
class UDPServer {  
    public static void main(String args[]) throws Exception {  
  
        ...  
        DatagramPacket receivePacket = new DatagramPacket(receiveData, receiveData.length);  
        serverSocket.receive(receivePacket);  
  
        // process  
        String sentence = new String(receivePacket.getData(),  
                                     0, receivePacket.getLength());  
        String capitalizedSentence = sentence.toUpperCase();  
        sendData = capitalizedSentence.getBytes();  
  
        // send  
        DatagramPacket sendPacket = new DatagramPacket(sendData, sendData.length,  
                                                         IPAddress, port);  
        serverSocket.send(sendPacket);  
    }  
}
```

# Example: Java client (UDP)

```
import java.io.*;  
import java.net.*;
```

```
class UDPClient {  
    public static void main(String args[]) throws Exception  
    {
```

Create  
input stream

```
        BufferedReader inFromUser =  
            new BufferedReader(new InputStreamReader(System.in));  
        String sentence = inFromUser.readLine();  
        byte[] sendData = sentence.getBytes();
```

Create  
client socket

```
        DatagramSocket clientSocket = new DatagramSocket();
```

Translate  
hostname to IP  
address using DNS

```
        InetAddress sIPAddress = InetAddress.getByName("servname");
```

# Example: Java client (UDP), cont.

Create datagram  
with data-to-send,  
length, IP addr, port

Send datagram  
to server

Read datagram  
from server

```
DatagramPacket sendPacket =  
    new DatagramPacket(sendData, sendData.length, sIPAddress, 9876);  
  
clientSocket.send(sendPacket);  
  
byte[] receiveData = new byte[1024];  
DatagramPacket receivePacket =  
    new DatagramPacket(receiveData, receiveData.length);  
  
clientSocket.receive(receivePacket);  
  
String modifiedSentence =  
    new String(receivePacket.getData());  
  
System.out.println("FROM SERVER:" + modifiedSentence);  
clientSocket.close();  
}  
}
```



# Demo

---

%ubuntu: java UDPServer

%netstat to see buffer

%ubuntu: java UDPClient <server>

%wireshark to capture traffic


# Discussion on Example Code

---

- ❑ A simple upper-case UDP echo service is among the simplest network service.
- ❑ Are there any problems with the program?


# Data Encoding/Decoding

- ❑ Rule: *ALWAYS* pay attention to encoding/decoding of data



# Example: Endianness of Numbers

□ `int var = 0x0A0B0C0D`




ARM, Power PC, Motorola 68k, IA-64

Intel x86

□ `sent != received`: take an int on a big-endian machine and send a little-endian machine

# Example: String and Chars

Will we always get back the same string?



Depends on default local platform char set :  
`java.nio.charset.Charset.defaultCharset()`

# Example: Charset Troubles

---

## □ Try

- java EncodingDecoding US-ASCII UTF-8


# Encoding/Decoding as a Common Source of Errors

- ❑ Please read chapter 2 (Streams) of Java Network Programming for more details
  - Java stream, reader/writer can always be confusing, but it is good to finally understand
  
- ❑ Common mistake even in many (textbook) examples:
  - <http://www.java2s.com/Code/Java/Network-Protocol/UseDatagramSocketToSendOutAndReceiveDatagramPacket.htm>

# Exercise: UDP/DNS Server Pseudocode

- ❑ Modify the example UDP server code to implement a local DNS server.


Identification	Flags	
Number of questions	Number of answer RRs	12 bytes
Number of authority RRs	Number of additional RRs	
Questions (variable number of questions)		Name, type fields for a query
Answers (variable number of resource records)		RRs in response to query
Authority (variable number of resource records)		Records for authoritative servers
Additional information (variable number of resource records)		Additional "helpful" info that may be used





# UDP/DNS Implementation

- ❑ Standard UDP demultiplexing (find out return address by `src.addr/src.port` of UDP packet) does not always work
- ❑ DNS solution: identification: remember the mapping




# Outline


---

- ❑ Admin. and recap
- ❑ Network application programming
  - Overview
  - UDP
  - *Basic TCP*

# TCP Socket Design: Starting w/ UDP



# BSD TCP Socket API Design



Q: How to decide where to put a new TCP packet?


A: Packet demultiplexing is based on **four tuples**:  
(dst addr, dst port, src addr, src port)

# TCP Connection-Oriented Demux

- ❑ TCP socket identified by 4-tuple:
  - source IP address
  - source port number
  - dest IP address
  - dest port number
  
- ❑ recv host uses all four values to direct segment to appropriate socket
  - different connections/sessions are automatically separated into different sockets

- Welcome socket: the waiting room
- connSocket: the operation room

# TCP Socket Big Picture



# Client/server Socket Workflow: TCP

Server (running on `hostid`)

Client

create socket,  
port=`x`, for  
incoming request:  
`welcomeSocket =`  
`ServerSocket(x)`

wait for incoming  
connection request  
`connectionSocket =`  
`welcomeSocket.accept()`

read request from  
`connectionSocket`

write reply to  
`connectionSocket`

close  
`connectionSocket`


**TCP  
connection setup**

create socket,  
connect to `hostid`, port=`x`  
`clientSocket =`  
`Socket()`



send request using  
`clientSocket`

read reply from  
`clientSocket`

close  
`clientSocket`



# Server Flow



- Welcome socket: the waiting room
- connSocket: the operation room



# ServerSocket

- ❑ **ServerSocket()**
  - creates an unbound server socket.
- ❑ **ServerSocket(int port)**
  - creates a server socket, bound to the specified port.
- ❑ **ServerSocket(int port, int backlog)**
  - creates a server socket and binds it to the specified local port number, with the specified backlog.
- ❑ **ServerSocket(int port, int backlog, InetAddress bindAddr)**
  - creates a server with the specified port, listen backlog, and local IP address to bind to.
- ❑ **bind(SocketAddress endpoint)**
  - binds the ServerSocket to a specific address (IP address and port number).
- ❑ **bind(SocketAddress endpoint, int backlog)**
  - binds the ServerSocket to a specific address (IP address and port number).
- ❑ **Socket accept()**
  - listens for a connection to be made to this socket and accepts it.
- ❑ **close()**
  - closes this socket.


# (Client) Socket

- ❑ **Socket(InetAddress address, int port)**
  - creates a stream socket and connects it to the specified port number at the specified IP address.
- ❑ **Socket(InetAddress address, int port, InetAddress localAddr, int localPort)**
  - creates a socket and connects it to the specified remote address on the specified remote port.
- ❑ **Socket(String host, int port)**
  - creates a stream socket and connects it to the specified port number on the named host.
- ❑ **bind(SocketAddress bindpoint)**
  - binds the socket to a local address.
- ❑ **connect(SocketAddress endpoint)**
  - connects this socket to the server.
- ❑ **connect(SocketAddress endpoint, int timeout)**
  - connects this socket to the server with a specified timeout value.
- ❑ **InputStream **getInputStream()****
  - returns an input stream for this socket.
- ❑ **OutputStream **getOutputStream()****
  - returns an output stream for this socket.
- ❑ **close()**
  - closes this socket.

# Simple TCP Example

## Example client-server app:

- 1) client reads line from standard input (`inFromUser` stream), sends to server via socket (`outToServer` stream)
- 2) server reads line from socket
- 3) server converts line to uppercase, sends back to client
- 4) client reads, prints modified line from socket (`inFromServer` stream)



# Example: Java client (TCP)

```
import java.io.*;
import java.net.*;
class TCPClient {
```

```
    public static void main(String argv[]) throws Exception
    {
```

```
        String sentence;
        String modifiedSentence;
```

Create  
input stream

```
        BufferedReader inFromUser =
            new BufferedReader(new InputStreamReader(System.in));
        sentence = inFromUser.readLine();
```

Create  
client socket,  
connect to server

```
        Socket clientSocket = new Socket("server.name", 6789);
```

Create  
output stream  
attached to socket

```
        DataOutputStream outToServer =
            new DataOutputStream(clientSocket.getOutputStream());
```

# OutputStream

---

- ❑ public abstract class OutputStream
  - public abstract void write(int b) throws IOException
  - public void write(byte[] data) throws IOException
  - public void write(byte[] data, int offset, int length) throws IOException
  - public void flush( ) throws IOException
  - public void close( ) throws IOException

# InputStream

---

- ❑ public abstract class InputStream
  - public abstract int read( ) throws IOException
  - public int read(byte[] input) throws IOException
  - public int read(byte[] input, int offset, int length) throws IOException
  - public long skip(long n) throws IOException
  - public int available( ) throws IOException
  - public void close( ) throws IOException

# Example: Java client (TCP), cont.

Send line  
to server

```
outToServer.writeBytes(sentence + '\n');
```

Create  
input stream  
attached to socket

```
BufferedReader inFromServer =  
    new BufferedReader(new  
        InputStreamReader(clientSocket.getInputStream()));
```

Read line  
from server

```
modifiedSentence = inFromServer.readLine();
```

```
System.out.println("FROM SERVER: " + modifiedSentence);
```

```
clientSocket.close();
```

```
}
```

```
}
```

# Example: Java server (TCP)

```
import java.io.*;  
import java.net.*;
```


```
class TCPServer {
```

```
    public static void main(String argv[]) throws Exception  
    {
```

```
        String clientSentence;  
        String capitalizedSentence;
```

Create  
welcoming socket  
at port 6789

```
        ServerSocket welcomeSocket = new ServerSocket(6789);
```





# Demo

---



% on MAC

start TCPServer

wireshark to capture our TCP traffic


tcp.srcport==6789 or tcp.dstport==6789

# Under the Hood: After Welcome (Server) Socket





%netstat -p tcp -n -a

# After Client Initiates Connection




%ubuntu java TCPClient <server> 6789

# Example: Client Connection Handshake Done



# Example: Client Connection Handshake Done



Packet demultiplexing is based on (dst addr, dst port, src addr, src port)

Packet sent to the socket with **the best match!**

# Demo

---

- ❑ What if more client connections than backlog allowed?
  - We continue to start java TCPClient

# Example: Java server (TCP)

```
import java.io.*;  
import java.net.*;
```

```
class TCPServer {
```

```
    public static void main(String argv[]) throws Exception  
    {
```


```
        String clientSentence;  
        String capitalizedSentence;
```

```
        ServerSocket welcomeSocket = new ServerSocket(6789);
```


```
        while(true) {
```

```
            Socket connectionSocket = welcomeSocket.accept();
```

Wait, on welcoming  
socket for contact  
by client



# Example: Server accept()





# Example: Java server (TCP): Processing

Create input stream, attached to socket

→

```
BufferedReader inFromClient =  
    new BufferedReader(new  
        InputStreamReader(connectionSocket.getInputStream()));
```

Read in line from socket

→

```
clientSentence = inFromClient.readLine();  
  
capitalizedSentence = clientSentence.toUpperCase() + '\n';
```

```
    }  
}
```

# Example: Java server (TCP): Output

