

---

# Network Applications: Overview, EMail

Y. Richard Yang

<http://zoo.cs.yale.edu/classes/cs433/>

9/12/2017

# Outline

---


- Admin and recap
- ❑ ISO/OSI Layering and Internet Layering
- ❑ Application layer overview
- ❑ Network applications
  - Email

# Admin

---

- ❑ Questions on Assignment One

# Recap: Summary of the Taxonomy of Communication Networks




# Recap: Statistical Multiplexing

A simple model to compare bandwidth efficiency of

- reservation/dedication (aka circuit-switching) and
- no reservation (aka packet switching)

setup

- a single bottleneck link with rate  $R$  ( $L/R$  to trans.  $L$  bits)
- $n$  flows; each flow has an arrival rate of  $a/n$



- no reservation: all arrivals into the single link with rate  $R$ , the queueing delay + transmission delay:


$$\frac{L}{R} \frac{1}{1 - \rho}$$

- reservation: each flow uses its own reserved (sub)link with rate  $R/n$ , the queueing delay + transmission delay:

$$\textcircled{n} \frac{L}{R} \frac{1}{1 - \rho}$$


# Recap: Layering

- Why layering
  - reference model
  - modularization
- Concepts
  - service, interface, and protocol
  - physical vs logical communication
- Key design decision
  - end-to-end arguments to place functions in layers




# Some Implications of Layered Architecture


- A packet as a stack container



- Each layer needs multiplexing and demultiplexing to serve layer above



Has a field to indicate which higher layer requires the service



# Outline


---

- ❑ Recap
  - *ISO/OSI Layering and Internet Layering*
- ❑ Application layer overview




# ISO/OSI Reference Model

- Seven layers
  - highest four layers are implemented in host



# Internet Layering


- ❑ Five layers
  - highest two layers are implemented in host




# Internet Protocol Layers

## □ Five layers

- **Application:** applications
  - ftp, smtp, http, p2p, IP telephony, ...
- **Transport:** host-host data transfer
  - tcp (reliable), udp (not reliable)
- **Network:** routing of datagram from source to destination
  - ipv4, ipv6
- **Link:** data transfer between neighboring network elements
  - ethernet, 802.11, cable, DSL, ...
- **Physical:** bits “on the wire”
  - cable, wireless, optical fiber




# The Hourglass Architecture of the Internet




# Link Layer (Ethernet)

- ❑ Services (to network layer)
  - multiplexing/demultiplexing
    - from/to the network layer
  - error detection
  - multiple access control
    - arbitrate access to shared medium
- ❑ Interface
  - send frames to a directly reachable peer




# Link Layer: Protocol Header (Ethernet)




# Network Layer: IP

- ❑ Services (to transport layer)
  - **multiplexing/demultiplexing** from/to the transport
  - **fragmentation and reassembling**: partition a fragment into smaller packets
    - removed in IPv6
  - **error detection**
  - **routing**: best-effort to send packets from source to destination
  - **certain QoS/CoS**
  - **does not provide** reliability or reservation
- ❑ Interface:
  - send a packet to a (transport-layer) peer at a specified global destination, with certain QoS/CoS




# Network Layer: IPv4 Header





# Transport Layer: UDP


- ❑ A connectionless service
- ❑ Does not provide: connection setup, reliability, flow control, congestion control, timing, or bandwidth guarantee
  - why is there a UDP?




# Transport Services and APIs

- ❑ Multiple services and APIs proposed in history
  - XTI (X/Open Transport Interface), a slight modification of the Transport Layer Interface (TLI) developed by AT&T.
- ❑ Commonly used transport-layer service model and API: Socket
  - sometimes called "Berkeley sockets" acknowledging their heritage from Berkeley Unix
  - a socket has a transport-layer local port number
    - e.g., email (SMTP) port number 25, web port number 80
  - Application can send data into socket, read data out of socket
  - an application process binds to a socket (-a all; -u udp; -n number)
    - %netstat -aun


# Socket Service Model and API



# Multiplexing/Demultiplexing



# Transport Layer: UDP Header




# Transport Layer: TCP

## □ Services


- multiplexing/demultiplexing
- reliable transport
  - between sending and receiving processes
  - setup required between sender and receiver: a **connection-oriented service**
- flow control: sender won't overwhelm receiver
- congestion control: throttle sender when network overloaded
- error detection
- does not provide timing, minimum bandwidth guarantees

## □ Interface:


- send a packet to a (app-layer) peer



# Transport Layer: TCP Header



# Secure Socket Layer Architecture






# SSL Record-Layer Packet Format


20: change\_cipher  
21: alert  
22: handshake  
23: application

encrypted







# Summary: The Big Picture of the Internet

- ❑ Hosts and routers:
  - ~ 1 bil. hosts
  - autonomous systems organized roughly hierarchical
  - backbone links at 100 Gbps
- ❑ Software:
  - datagram switching with virtual circuit support at backbone
  - layered network architecture
    - use end-to-end arguments to determine the services provided by each layer
  - the hourglass architecture of the Internet



# Protocol Formats



# Outline

---

- ❑ Recap
- ❑ ISO/OSI Layering and Internet Layering
  - *Application layer overview*

# Application Layer: Goals

- ❑ Conceptual + implementation aspects of network application protocols
  - client server paradigm
  - peer to peer paradigm
  - network app. programming
- ❑ Learn about applications by examining common applications
  - smtp/pop
  - dns
  - http (1, 1.1, /2)
  - content distribution
  - peer-to-peer


# Network Applications vs. Application-layer Protocols

## Network application: communicating, distributed processes

- a **process** is a program that is running within a host
  - a **user agent** is a process serving as an interface to the user
    - web: browser
    - streaming audio/video: media player
- processes communicate by an **application-layer protocol**
  - e.g., email, Web

## Application-layer protocols

- one “piece” of an app
- define messages exchanged by apps and actions taken
- implementing services by using the service provided by the lower layer, i.e., the transport layer



# App. and Trans.: App. Protocols and their Transport Protocols

- An application needs to choose the transport protocol

<u>Application</u>	<u>Application layer protocol</u>	<u>Underlying transport protocol</u>
e-mail	smtp [RFC 821]	TCP/SSL
remote terminal access	telnet [RFC 854]	TCP
Web	http [RFC 2068]	TCP/SSL
file transfer	ftp [RFC 959]	TCP
Internet telephony	proprietary (e.g., Vocaltec)	typically UDP
remote file server	NFS	TCP or UDP
streaming multimedia	proprietary	typically UDP but moving to http

# Client-Server Paradigm


Typical network app has two pieces: *client* and *server*

## Client (C):

- ❑ initiates contact with server (“speaks first”)
- ❑ typically requests service from server
- ❑ for Web, client is implemented in browser; for e-mail, in mail reader

## Server (S):

- ❑ provides requested service to client
- ❑ e.g., Web server sends requested Web page; mail server delivers e-mail






# Client-Server Paradigm: Key Questions

Key questions to ask about a C-S application

- Is the application **extensible**?
- Is the application **scalable**?
- How does the application handle server failures (being **robust**)?
- How does the application handle **security**?



# Outline

---

- ❑ Admin and recap
- ❑ ISO/OSI Layering and Internet Layering
- ❑ Application layer overview
- ❑ Network applications
  - Email

# Electronic Mail


---

- ❑ Still active
  - 80B emails/day
  - 3.9B active email boxes
  
- ❑ A highly recommended reading: a history of Email development
  - linked on the Schedule page

# Recall: SMTP


```
S: 220 mr1.its.yale.edu
C: HELO cyndra.yale.edu
S: 250 Hello cyndra.cs.yale.edu, pleased to meet you
C: MAIL FROM: <spoof@cs.yale.edu>
S: 250 spoof@cs.yale.edu... Sender ok
C: RCPT TO: <yry@yale.edu>
S: 250 yry@yale.edu ... Recipient ok
C: DATA
S: 354 Enter mail, end with "." on a line by itself
C: Date: Wed, 23 Jan 2008 11:20:27 -0500 (EST)
C: From: "Y. R. Yang" <yry@cs.yale.edu>
C: To: "Y. R. Yang" <yry@cs.yale.edu>
C: Subject: This is subject
C:
C: This is the message body!
C: Please don' t spoof!
C:
C: .
S: 250 Message accepted for delivery
C: QUIT
S: 221 mr1.its.yale.edu closing connection
```

# Electronic Mail: Components



## Three major components:

- User agents
- Mail servers
- Protocols
  - Mail transport protocol
    - SMTP
  - Mail access protocols
    - POP3: Post Office Protocol [RFC 1939]
    - IMAP: Internet Mail Access Protocol [RFC 1730]



# Email Transport Architecture

**MUA:** User Agent

**Mediator:** User-level Relay


**MHS:** Mail Handling (transit) Service

**MSA:** Submission


**MTA:** Transfer

**MDA:** Delivery

**Bounce:** Returns




# SMTP: Mail Transport Protocol Messages (Envelop Messages)



```

S: 220 mr1.its.yale.edu
C: HELO cyndra.yale.edu
S: 250 Hello cyndra.cs.yale.edu, pleased to meet you
C: MAIL FROM: <spoof@cs.yale.edu>
S: 250 spoof@cs.yale.edu... Sender ok
C: RCPT TO: <yry@yale.edu>
S: 250 yry@yale.edu ... Recipient ok
C: DATA
S: 354 Enter mail, end with "." on a line by itself
C: Date: Wed, 23 Jan 2008 11:20:27 -0500 (EST)
C: From: "Y. R. Yang" <yry@cs.yale.edu>
C: To: "Y. R. Yang" <yry@cs.yale.edu>
C: Subject: This is subject
C:
C: This is the message body!
C: Please don' t spoof!
C:
C: .
S: 250 Message accepted for delivery
C: QUIT
S: 221 mr1.its.yale.edu closing connection
    
```



Email txt diff from  
SMTP protol msg



# Mail Message Data

SMTP: protocol for exchanging email msgs


RFC 822: standard for text message format:

- Header lines, e.g.,

- To:
- From:
- Subject:

- Body

- the “message”, ASCII characters only




Benefit of separating protocol and msg: easier extensibility



# Message Format: Multimedia Extensions

- ❑ MIME: multimedia mail extension, RFC 2045, 2056
- ❑ Additional lines in msg header declare MIME content type



Benefit of MIME type: self describing data type, adding extensibility.

# Multipart Type: How Attachment Works

From: yry@cs.yale.edu

To: cs433@cs.yale.edu

Subject: Network map.

MIME-Version: 1.0

Content-Type: multipart/mixed; boundary=98766789

--98766789

Content-Transfer-Encoding: quoted-printable

Content-Type: text/plain

Hi,

Attached is network topology map.

--98766789

Content-Transfer-Encoding: base64

Content-Type: image/jpeg

base64 encoded data .....

.....

.....base64 encoded data


--98766789--

# POP3 Protocol: Mail Retrieval

## Authorization phase

- ❑ client commands:
  - user: declare username
  - pass: password


- ❑ server responses
  - +OK
  - -ERR



```
S: +OK POP3 server ready
C: user alice
S: +OK
C: pass hungry
S: +OK user successfully logged on
```

## Transaction phase, client:

- ❑ list: list message numbers
- ❑ retr: retrieve message by number
- ❑ dele: delete
- ❑ quit



```
C: list
S: 1 498
S: 2 912
S: .
C: retr 1
S: <message 1 contents>
S: .
C: dele 1
C: retr 2
S: <message 1 contents>
S: .
C: dele 2
C: quit
S: +OK POP3 server signing off
```

```
%openssl s_client -connect pop.gmail.com:995
```

# Exercise


---

- ❑ Send email to yalecs433533 with attachment
- ❑ Retrieve using pop

# Evaluation of SMTP/POP/IMAP

Key questions to ask about a C-S application

- extensible?
- scalable?
- robust?
- security?




# Email Security: Spam

## □ Spam (Google)



# Email Security Issue: Spam



© Statista 2017

Source: <https://www.statista.com/statistics/420400/spam-email-traffic-share-annual/>

# Discussion: How May One Handle Email Spams?

---



# Detection Methods Used by GMail

- ❑ Known phishing scams
- ❑ Message from unconfirmed sender identity
- ❑ Message you sent to Spam/similarity to suspicious messages
- ❑ Administrator-set policies

<https://support.google.com/mail/answer/1366858?hl=en>