

SMART BUS FOR SMART CITY

12M CITY BUS



52

SEATS

8 YEARS

BATTERY WARRANTY

330

KM RANGE

Product Configuration List for EQ6120GPBEV New Energy Pure Electric Bus (12m)

BASIC INFORMATION

Vehicle Brand	DONGFENG YUNNAN
Vehicle Model	EQ6120GPBEV
Driving Type	Right-hand drive
Seating Capacity (seats)	51+1

VEHICLE SPECIFICATIONS

Total Length (MM)	11980
Total Width (MM)	2520
Total Height (MM)	3280, Overall height with AC (Actual height may vary depending on the AC manufacturer)
Wheelbase (MM)	6200
Front Overhang/Rear Overhang (MM)	2620/3160
Approach Angle/Departure Angle°	7/7.5 (Tentative)
Maximum Climbing Gradient %	20
Maximum Gross Vehicle Weight (KG)	11300
Ground Clearance (MM)	≥320
Maximum Speed	85 km/hr (Software speed limited to 69 km/hr)

POWERTRAIN PARAMETERS

Motor Type	Permanent Magnet Synchronous (Direct Drive)
Peak Power (KW)	275
Rated/Maximum Torque (NM)	1200/2800
Maximum Speed (RPM)	3500
Cooling Method	Water cooling
Layout Type	Rear-engine, rear-wheel drive
Remaining Range (KM)	≥330 (Isokinetic Method)
Energy Storage Device Type	269.37 kWh, LFP, Dual-circuit 8-box, 69.37 kWh, EVE
Thermal Management System (TMS) for Energy Storage Systems	Integrated with the AC system

Charge	1 China National Standard DC charging (GBT) 2 20kW+AC charging, 20kW On-Board Charger (OBC) + charging cable
--------	---

CHASSIS

Front Axle	7T, 7T, disc brakes
Rear Axle	11T, 11T, disk brakes
Suspension	Front 11, rear 12 Multi-leaf springs
Turn	Hydraulic power steering, right-hand drive
Brake	ABS Air pressure dual-circuit air brakes, Front disc and rear disc brakes, ABS system
Tires/Wheels	275/70 R22.5, 275/70 R22.5, tubeless radial tire

LOW-PRESSURE SYSTEM

Battery	2 units of 12V, 120Ah, maintenance-free lead-acid batteries
Instrument	CAN CAN bus instrument
Wiper	Scraper type
Monitoring System	1 / 1 reversing sensor, Display on a separate monitor
Electric Drive Cooling System	ATS / ATS water-cooled radiator, electronic fan

HIGH-PRESSURE SYSTEM

Electronic Control System	All-in-one
Air Conditioning System	Cooling-only air conditioner, integrated with the power battery thermal management system
Heating System	Front windshield electric defrost, none for others
High-pressure Air Pump	Oil-free piston type
High-pressure Fuel Pump	Electric power steering pump

BODY AND INTERIOR

Vehicle Body Structure	Frame and skin construction
Car Door and Door Pump	Front double and center double pneumatic inner swing doors
Handrail	Standard configuration, citybus handrail, 20 gymnastic rings
Car Window, Windshield	5mm Side window 5mm tempered glass, with built-in sliding window (Clear Glass); Front windshield: laminated glass; rear windshield: 5mm tempered glass (Clear Glass)
Rearview System	Interior and exterior rear view mirrors, reverse voice alarm
Dashboard	Standard configuration, foam dashboard
Front Top/Back Top	ABS ABS Blister Part
Air Duct	PU/Integral PU Foam Air Duct
Side Wall Panel	3mm 3mm composite board
Middle Roof Panel	3mm 3mm composite board
Passenger Seat	Individual bus seat
Driver's Seat	Mechanical suspension, with three-point seat belt, seat belt unfastened warning function
Safety Skylight	With exhaust fan
Wiring Harness	Complete vehicle wiring harness
Flooring and Linoleum	Flat floor in the central passenger area, PVC plywood+ vinyl flooring
Paint	Solid color paint
Billboard	Photo of warning signs/advertising locations inside the carriage
LED Road Sign	Front, back, top, and middle
Stop Announcement Device	Can play Nepali audio; audio file package installed by the owner after vehicle arrives in Nepal
Others	Driver Sunshade; 2kg fire extinguisher; 2 safety hammers; onboard tools, etc.
Warranty Period	Battery: 8 years or 500,000 km Motor, electronic control: 5 years or 200,000 km\ (whichever comes first)

**Specifications are subject to change due to technological improvements. The company reserves the right of final interpretation.*

Authorized Dealer:



Authorized Importer/Distributor:

AAYAM INTERCONTINENTAL PVT. LTD.

Head Office: Gairidhara chowk, Naxal, Kathmandu

Branch Office: Pokhara-14, Chautha