

SMART BUS FOR SMART CITY

9M CITY BUS



38/40

SEATS

300

KM RANGE

8 YEARS

BATTERY WARRANTY

Product Configuration List for EQ6900GPBEV New Energy Pure Electric Bus (9m)

BASIC INFORMATION

Vehicle Brand	DONGFENG YUNNAN
Vehicle Model	EQ6900GPBEV
Driving Type	Right-hand drive
Seating Capacity (Seats)	37+1 / 39+1

VEHICLE SPECIFICATIONS

Total Length (MM)	8990
Total Width (MM)	2365
Total Height (MM)	3250 With A/C: Overall height may vary by A/C brand
Wheelbase (MM)	4400
Front Overhang/Rear Overhang (MM)	1860/2730
Approach Angle/Departure Angle°	11/1011/10 (Tentative)
Maximum Climbing Gradient%	20
Maximum Gross Vehicle Weight (KG)	12000
Ground Clearance	≥320 (mm)
Maximum Speed	85 km/hr (Software speed limited to 69 km/hr)

POWERTRAIN PARAMETERS

Motor Type	Permanent Magnet Synchronous (Direct Drive)
Peak Power (KW)	260
Rated/Maximum Torque (NM)	870/2130
Maximum Speed (RPM)	3500
Cooling Method	Water cooling
Layout Type	Rear-engine, rear-wheel drive
Remaining Range (KM)	Air conditioner off ≥300 (Isokinetic Method) Air conditioner on ≥240 (Isokinetic Method)
Energy Storage Device Type	LFP 140.15 kWh EVE
Thermal Management of Energy Storage Systems	Integrated with the AC system
Charge	1 China National Standard DC charging 2 charging, 13kW on-Board Charger (OBC) + charging cable

CHASSIS

Front Axle / Rear Axle	4.5T, Disc Brakes / 7.5T, Drum Brakes
Suspension	Front 9, rear 11 Multi-leaf springs
Turn	Hydraulic power steering, right-hand drive
Brake	Air pressure dual-circuit air brakes, Front disc and rear drum brakes, ABS system
Tires/Wheels	245/70 R19.5, tubeless radial tire

LOW-PRESSURE SYSTEM

Battery	2 units of 12V, 100Ah, maintenance-free lead-acid batteries
Instrument / Wiper	CAN bus instrument / Scraper type
Monitoring System	1 reversing sensor, Integrated Instrument Display
Electric Drive Cooling System	ATS water-cooled radiator, electronic fan

HIGH-PRESSURE SYSTEM

Electronic Control System	All-in-one
Air Conditioning System	Cooling-only air conditioner, integrated with the power battery thermal management system
Heating System	Front windshield electric defrost, none for others
High-pressure Air Pump	Oil-free piston type
High-pressure Fuel Pump	Electric power steering pump

BODY AND INTERIOR

Vehicle Body Structure	Frame and skin construction
Car Door and Door Pump	Front and center doors ,Front single-leaf and middle double-leaf pneumatic inward-swinging doors
Handrail	Standard configuration, City bus handrail, 10 gymnastic rings
Car Window, Windshield	Side windows: 5mm tempered glass; Front windshield: laminated glass; rear windshield: 5mm tempered glass
Rearview System	Interior and exterior rear view mirrors, reverse voice alarm
Dashboard	Standard configuration, foam dashboard
Front Back Top / Airflow channel	ABS Blister Part / PU integral foam air duct
Side Wall & Middle Roof Panel	3mm composite board
Passenger Seat	Individual bus seat
Driver's Seat	Mechanical suspension with three-point seat belt seat belt unfastened warning function
Safety Skylight	With exhaust fan
Wiring Harness	Complete Vehicle wiring harness
Flooring and Linoleum	Flat floor in the central passenger area, PVC plywood+ vinyl flooring
Paint	Solid color paint
Billboard	Photo of warning signs/advertising locations inside the carriage
LED Road Sign	Front, back, top, and middle
Stop Announcement Device	Can play Nepali/English Audio file package installed by the owner after vehicle delivery.
Others	Driver Sunshade; one 2kg fire extinguisher; two safety hammers; onboard tools, etc.
Warranty Period	Battery: 8 years or 500,000 km Motor, electronic control: 5 years or 200,000 km (whichever comes first)

**Specifications are subject to change due to technological improvements. The company reserves the right of final interpretation.*

Authorized Dealer:



Authorized Importer/Distributor:

AAYAM INTERCONTINENTAL PVT. LTD.

Head Office: Gairidhara chowk, Naxal, Kathmandu

Branch Office: Pokhara-14, Chautha