
Hashed-factor-base ECDL tensor implementation

2026-10-29 · Native implementation report · Correctness evidence only

The compact encoder, exact contraction machinery and Figure 2 relation reduction are implemented in both isogeny-labs/crypto and cryptanalysis. The source is Akshima et al., *A Subexponential Time Algorithm for Elliptic Curve Discrete Logarithm*, v0.2, revision `1ee44e562b1b9a50ea339f3b8f81112b5a24b96f`. Bochum source. The external contraction algorithm is OpenAI's October 25 manuscript, Appendix D.1/D.4, revision `7ef5c0cc5ca4b0e072b7a050fca09ab24bc6fa3a`. External source.



Public interface

The shared crate is `hashed_ecdl_tensor`. Both repository APIs export it as `hashed_ecdl::tensor`; the earlier bounded generic reference is preserved. The native runner reads a public JSON problem, writes an exclusive new receipt, and independently replays a receipt. OS randomness is the default; seeded fixtures provide reproducibility, not ideal-uniform runtime guarantees.

Compact encoding and general inputs

Ripple addition, comparison and zero tests compose with two-stage Fourier integer multiplication over the paper’s canonical residue words. Quotient and carry identities implement canonical modular products. Point predicates cover identity, inverse, ordinary addition and doubling; affine hash membership uses coordinate bits, without a factor-base lookup. Constant-degree equality trees distribute shared bits into ordinary graph edges.

Integers are arbitrary precision. Exact AKS prime certification, with a fixed small trial-division prefix, and Tonelli–Shanks replace the earlier field bound and root table. Curve construction certifies the subgroup and full cardinality c*r through the Hasse interval or exact counting in ambiguous cases. Cofactor clearing projects free Si to Ai=[c]Si. Counts retain preimage multiplicities; the projected witness language remains the requested subgroup decompositions. The paper’s unchanged asymptotic extension assumes fixed c.

Exact contraction

The implementation includes the unramified coefficient ring modulo powers of two, conditional-expectation packet packing, integral Cauchy deformation, streamed weighted modes, implicit packet tensors, depth-first contraction and tapered Hermite recovery. Retained entries are evaluated at their immutable creation precision before canonical lifting. Interpolation uses residue-distinct points; reconstruction uses exact rational arithmetic and checks integrality.

Literal admission guards matter. The source has u=floor(ceil(log2(s))/131072), where s is its network-size parameter. It is zero for all practically addressable graphs. Those inputs use exact finite-size fallback. Private built-in metadata permits enumerating free input bits with uniquely determined auxiliaries. Caller predicates cannot assert such metadata. Execution counters report Direct, Functional or Recursive. Forced small recursion tests bypass admission/shrink size bounds only; their outputs are compared with direct contraction. They do not measure asymptotic behavior.

Reduction and replay

Factor bases are enumerated by inverse hashes and root extraction. Each slot/point has its own matrix column. Tensor search receives only a target and seed. A trial collects N+1 relations within 20(N+1) attempts; deterministic modular elimination chooses a dependency without u/v, and V=0 restarts. Replay rebuilds the bases and independently checks every membership, group equation, slot-column cancellation, nonzero dependency and scalar extraction. Execution counters are informational and do not attest discarded trials.

Validation and limits

The 25 core controls include arbitrary graph truth tables and prefix witnesses, parallel edges, exact ring units/interpolation, creation-precision retention, Cauchy kernels, tapered Hermite recovery, weighted tuples and a full forced packet recursion versus independent direct contraction. Arithmetic products are checked independently through 513-bit input words, with explicit edge and degree inequalities. Point networks cover every pair on two small curves, including infinity, inverses, doubling and two-torsion. Hash enumeration is compared with a subgroup scan.

The full tiny relation pipeline recovers a public scalar and rejects corrupted relations, dependencies and scalar certificates. Cofactor projection is checked separately. The cryptanalysis binding additionally cross-checks all 199 scalars of a small curve against its independent C arithmetic. The current validation receipt records the actual final-source tests, lint, minimum compiler, CLI, source parity and broad-root regression outcomes; pending work is not a pass.

The native runner caps input files at 16 MiB and refuses to overwrite receipts. Caller bounds govern steps, vectors, precision, columns and trials. Exhaustion returns an error: it is not a zero count or a proof of nonexistence. Practical input sizes can exhaust these policies long before cryptographic sizes.

Requirement status

Code replication now includes the encoder, contraction backend and reduction, with public integration in both repositories. General correctness and complexity audit of the external theorem remains open in the canonical problem record. No conditional theorem was independently proved, no deployed-curve run or security consequence was established, and no IC/rho performance experiment was launched. No new mathematical result or Lean proof is claimed. Passing bounded tests or merging code does not prove the general algorithm.

The historical first-reference receipt remains intact. No frozen evidence, validation gate, leaderboard, curve route or benchmark is changed. See `docs/hashed-ecdl.md`, `docs/hashed-ecdl-tensor-validation.md`, and crypto's `problems/hashed-ecdl-tensor-backend.md` for source links and remaining review obligations. Prior literature/code review is recorded there; no novelty claim is inferred from finding no prior executable implementation.