Index-calculus baselines: the ratchet

Status (2026-10-15). This is the first edition of the ledger, with the tuned-rho rows added from run 38777903922. It takes no new measurement: every number is copied from a committed experiment, and each row cites that experiment. Figure 1 was checked and stays current: no baseline row's numbers changed. The n=83 rows for lift_scan, the Feistel order and their (not promoted) combination were added on 2026-10-15; Figure 1 was checked and stays current, because no baseline row's numbers changed. The n=83 row for the probe pipeline was added on 2026-10-16, the two-level root table and the state fold the same day, each with the same Figure 1 check. On 2026-10-16 the stacked producer (`koblitz-n83-stacked-20261016`, run 38862448935) replaced B's n=83 baseline row, and Figure 1 was re-rendered. Also on 2026-10-16, an accounting correction (sheriff case SHF-20261016-3caa6f, K3 and K4): the n=83 row's `s_ic_setup` was 0.8856, which is setup without the rank stage plus online, while every other row's (B's 32.848 included) is cold minus online with the rank stage in it. It is now 9.6673 on that one meaning, and the B → stack ratchet entry records the paired within-run delta. No measurement changed, and Figure 1 (gaps only) is unchanged. Also on 2026-10-16, disclosures from the same case (K1, K2, R1; no number changed): the n=83 row's headline and `S` are wall time on one host class, with the host-independent operation-count ratio (rank-stage probes and root calls 1.4773x) beside it; factor-base construction is charged to neither arm, so the row's ratio is an upper bound and its cold `S` a lower bound; the §5a GAE band is not computable from that run; and the run was not replayed on another host class. On 2026-10-17, corrections from re-audit SHF-20261017-e4d7f6 (K-N1, K-N2, K-N4; no measurement changed): the setup convention now names what each row leaves out (both n=83 rows leave out factor-base construction; B's row also leaves out 51.3 ms of linear algebra and 32.3 ms of input control, now listed in its JSON `uncharged_phases`); the B → stack history entry's standard gap fields now hold the paired within-run gaps, with B's cross-run figures under `cross_run_context_*`; the n=83 rank stage rounds to 8.7949 (8.79486), not 8.7948; and 2.2837 is per-probe wall time, not a host-speed factor. A replay of rank block K1 with one timed base construction is preregistered (`experiments/koblitz-n83-replay-20261017/PROTOCOL.md`). Figure 1 (gaps only) is unchanged. On 2026-10-17 that replay was archived (`experiments/koblitz-n83-replay-20261017/RESULTS.md`, run 39007026856): `replay_pass` on another host class (Intel Xeon Platinum 8573C), rank-stage work identical, per-probe wall ratio 2.6583 there against 2.2905 on the EPYC; construction time X = 427.5 ms is now measured. The n=83 row's replication and uncharged-phase notes record it; no figure of the row changed, and Figure 1 is unchanged. On 2026-10-19 the rank-cut producer (`koblitz-n83-rankcut-20261016`, run 38891404048) replaced the stacked producer's n=83 baseline row (end-to-end cold 1.3336 [1.3300, 1.3377] over the stack, wall time on one host class, probes and root calls unchanged), and Figure 1 was re-rendered. Also on 2026-10-19 the rank-probe producer (`koblitz-n83-rankprobe-20261019`, run 39214027289) replaced the rank-cut producer's n=83 baseline row (end-to-end cold 1.1033 [1.1010, 1.1056] over the rank-cut producer, wall time on one host class, probes and root calls unchanged), and Figure 1 was re-rendered. Also on 2026-10-19 the index-lift producer (`koblitz-n83-indexlift-20261019`, run 39290913632) replaced the rank-probe producer's n=83 baseline row (end-to-end cold 1.0344 [1.0324, 1.0364] over the rank-probe producer with a shared rank stage, wall time on one host class, stored states and table slots byte-identical, probes and root calls unchanged), and Figure 1 was re-rendered. Also on 2026-10-19 the nested 899-column factor base under the rank-probe producer (`koblitz-n83-k899-20261019`, run 39306394645) was recorded as promoted over the rank-probe producer at K600 (end-to-end cold 1.1873 [1.1247, 1.2523], wall time on one host class); the n=83 baseline row names the index-lift producer, not the rank-probe producer, so the row was not replaced (record in Other verified records and the history), and Figure 1 is unchanged. Also on 2026-10-19 the closure producer (`koblitz-n83-closure-20261019`, run 39305259093) was recorded as a promoted improvement over the rank-probe producer (end-to-end cold 6.4444 [6.0993, 6.7853], wall time on one host class); it compared against the rank-probe producer, not the index-lift row, so no baseline row changed (baseline row not replaced: paired run against the index-lift row pending) and Figure 1 was not re-rendered. Also on 2026-10-19 the rotation-key producer (`koblitz-n83-rotkey-20261019`, run 39299176306) was recorded as not promoted (frozen primary not_separated against the rank-probe producer, 0.9983 [0.9701, 1.0227]); no baseline row changed and Figure 1 was not re-rendered. Also on 2026-10-20 the closure + index-lift producer (`koblitz-n83-closure-indexlift-20261019`, run 39335956567) replaced the index-lift producer's n=83 baseline row (end-to-end cold 7.6558 [7.2192, 8.1103] over the index-lift row, wall time on one host class, rank stage 143.7 s -> 4.01 s, factor-base construction charged to no arm); it also supersedes the closure's earlier comparison against the rank-probe producer (run 39305259093), and Figure 1 was re-rendered. Also on 2026-10-19 a separately labelled reference row was added for the known-log base (`koblitz-n83-knownlog-20261019`, run 39307634508: end-to-end cold 2.19 [1.86, 2.59] over rT770, above rho); it has no relations, is not an IC improvement, does not replace the n=83 baseline, and Figure 1 (baseline rows only) is unchanged. Also on 2026-10-19 the online-frame experiment (`koblitz-n83-onlineframe-20261019`, run 39303742695) was recorded as a stage improvement over the rank-probe producer (online cS / cF 1.5733 [1.5714, 1.5753], 64 points, wall time on one host class, probes and root calls unchanged) in Other verified records and the ratchet history; the n=83 baseline row was not changed (it stacks with the index lift and the closure, combined run pending), and Figure 1 is unchanged. The machine-readable twin is `baselines.json`; update both files in the same change.

The rule this file serves

AGENTS.md, "Success criterion: iterative improvement of the index-calculus baseline" (owner, 2026-10-15; cryptanalysis#919, crypto#1908):

- **The baseline** for a curve and size is the best current verified IC pipeline. It is frozen with its protocol, receipts and end-to-end cold `S`.
- **A success** is any verified, measured improvement over that baseline on the same instances, under a protocol frozen before timing. Advance and engineering both count. Relabelling and accounting are recorded and do not count.
- **The ratchet.** A landed improvement replaces the row here, and the old row moves to the history with its delta.
- **The gap** to the matched rho, and to Bernstein–Lange (BL) where it was measured, is the distance remaining. It is not a pass/fail gate. A claim to *beat* rho still needs every reference rule: a cold `S` below the matched rho's, robust at growing `n`, independently replayed.

How to read the numbers.

- **One row, one experiment.** No row combines numbers from two experiments. Where an experiment did not measure a quantity, the cell says so.
- **Every gap is IC cost over the reference's cost.** Above 1 is distance still to close; below 1 means the IC is cheaper on that boundary. The sources quote the online figure the other way up (rho over IC). That figure is kept in each JSON row's `source_figure`.
- **`S` = cost / $\sqrt{r}$**, in the row's own unit. The unit differs between experiments, so compare `S` inside a row only. The gaps carry no unit.
- **Setup `S` has one meaning on every row:** `s_ic_setup` = `s_ic_cold` - `s_ic_online`: the reusable work for the first target that the row's experiment charged, the relation-collection / rank stage and the linear algebra (or the verified load of its cached table) included, less every phase the JSON row names in `uncharged_phases`. Only n=41–61 (rule v3, which builds the factor base inside setup) charge all reusable work. Both n=83 rows leave out factor-base construction (the K600 base is loaded from a file); B's row also leaves out its linear algebra (51.3 ms) and setup input control (32.3 ms), 0.015% of its P_IC. n=19 has no setup `S`. Where the rank stage is timed on its own (n=83), the JSON row also splits it into `s_ic_rank_stage` + `s_ic_setup_without_rank_stage`. "Cold without the rank stage" is a different quantity and is never written into `s_ic_setup`.
- **Tuned rho** means rT770: A's tuned `StrongRhoG` (Fold field kernel, 64 lanes, DP 6, escape off). `koblitz-n83-reconcile-20261014` found it to be the fastest correct n=83 reference. At n=41–61 it has been run as rT770's configuration on the one-word kernel (`koblitz-s23-tuned-rho-20261015`). ParallelRho, inside crypto's `ic price`, is crypto's own signed-Frobenius walk (64 lanes in lockstep). It is the matched rho at n=41–61, but it is not rT770.

The baselines

n	curve	current best verified IC pipeline (commit; protocol)	targets	`S` cold / online (IC)	`S` cold / online (rho)	cold gap, IC / rho [95%]	online gap, IC / rho [95%]	gap to tuned rho (rT770)	gap to BL (online, IC / BL)	evidence tier	next improvement to try
19	E0 / GF(2^19), a=1	volcano-ic τ-orbit dim-6 base, Sage Gröbner (arm `tau6`); cryptanalysis `3f722e2e`; protocol.json of volcano-ic/ rho-arm-20261014; run 38520305068	10 planted scalars, each one complete ECDLP	5,154 / not separable	0.260 / —	**1.94e4** [1.69e4, 2.23e4] (CPU, geometric mean)	not measured: each IC run is cold	none; the matched rho is a signed-Frobenius walk at 0.997× the floor in steps, run in Python/Sage, not tuned for wall time	none	exploratory (GitHub VM, unpinned)	Move tau6's per-relation Gröbner solve out of Sage (native, or the subspace `PDP2ht` oracle); re-run against the same rho arm
41	K_0 / GF(2^41)	`ic price --single-target` at IC programme baseline v3: 6,560 points, 80 columns, aimed m=3 collection, m=2 pair-table descent; crypto `995ea207`; rule v3	64 public points, 1 process each, +4 A/A	11.17 / 0.121	1.459 / 1.318	**7.66** [6.90, 8.61]	0.092 [0.071, 0.116]	**measured in a separate experiment, not combined**: see the 41 row of Other verified records (run 38777903922: online IC/tuned 0.09, cold 6.6); the matched rho in this row is ParallelRho (0.56× the strong walk's ns/step)	model only: 2.21	crypto isolated_bench container	Setup is 98.9% of cold `S`: cut the reusable setup at fixed recipe, as a new IC programme round against v3

n	curve	current best verified IC pipeline (commit; protocol)	targets	S cold / online (IC)	S cold / online (rho)	cold gap, IC / rho [95%]	online gap, IC / rho [95%]	gap to tuned rho (rT770)	gap to BL (online, IC / BL)	evidence tier	next improvement to try
53	K_0 / GF(2^53)	same pipeline, 27,984 points, 264 columns; crypto `995ea207`; rule v3	64 + 4 A/A	16.98 / 0.058	1.282 / 1.236	**13.2** [11.8, 15.0]	0.047 [0.036, 0.059]	**measured in a separate experiment, not combined**: see the 53 row below (online 0.0423, cold 10.6); ParallelRho here is 0.53× strong	model only: 1.77	crypto isolated_bench container	Setup is 99.7% of cold S: cut it at fixed recipe; then price the n=53 representative-plus-Frobenius orbit domain as its replacement
61	K_0 / GF(2^61)	same pipeline, 39,040 points, 320 columns; crypto `995ea207`; rule v3	64 + 4 A/A	24.93 / 0.079	1.189 / 1.168	**21.0** [18.6, 23.8]	0.067 [0.051, 0.088]	**measured in a separate experiment, not combined**: see the 61 row below (online 0.0687, cold 18.9); ParallelRho here is 0.50× strong	model only: 3.52	crypto isolated_bench container	Setup is 99.7% of cold S, and the cold gap grows as r^0.18: cut the setup; price the compact-orbit K=500 producer on these 64 points
83	K_1 / GF(2^83)	the closure + index-lift producer (arms cM38I / kM38I; secondary cM10I / kM10I): the index-lift producer (the rank-probe producer with lift_scan in the root-index build, `KIC_INDEX_CANON=lift`, byte-identical layout digests; B's `koblitz_orbit_dlp_fast_online` + `ic_log_cache.patch`, K600 root index of 14,940,300 stored states, lift_scan x Feistel + prefetched probes + 16-byte compact root slots + folded S3 root index, rank stage's partner roots by point addition in the target's Frobenius frame) with the linear algebra over 600 / M columns, each column the signed Frobenius orbit of alpha(R_c) for alpha = a + b tau in the Z[tau]-multiplier closure (M38: 16 columns, norm <= 64; M10: 60 columns); the root index stays on B's K600 orbits; every column log verified in the pinned oracle before timing (candidate ID below); crypto `770f6a69`; `koblitz-n83-closure-indexlift-20261019/protocol.json` at cryptanalysis `9fc17f76c`; run 39335956567	20 new public points, rank blocks 16 (kM38I, 16 attempts, seeds 1101-1116), 4 (kPI, 600 attempts), 8 (kM10I, 60 attempts), Q0	0.8058 / 0.009909 (wall time in rT770 steps, 281.09 ns, one host class; setup 0.7959, of which rank stage 0.1541; factor-base construction not charged, so cold is a lower bound; measured X = 0.43 s gives 0.822, illustrative)	0.1175 / 0.1072	**6.86** [5.80, 8.19] (end-to-end cold: rank stage + setup + online; wall time, one host; section 5a band not computable)	0.0925 [0.0594, 0.1352]	**measured on this row**: end-to-end cold 6.86, online 0.0925	not measured on this row (B's 235 [61, 645] is in Other verified records)	Tier 1 (GitHub runner, one pinned CPU, CPU-only); one run; not replayed on another host class	The cold path is now 16.96 s of the 20.97 s end-to-end cold cost (81%) and the closure does not improve it (cPI / cM38I 0.9931 [0.9837, 1.0035]): cut the root-index build (14.4 s) and setup, then the probes per relation; K899 and the closure are not combined yet; re-run the BL arm on this producer

Figure 1. The baseline rows' gaps on a log scale: cold and online to the matched rho, and online to Bernstein–Lange (a model; the one measured n=83 BL gap is in B's row, now under Other verified records). Each row is one experiment. Bars are 95% intervals where the source gives one (source, vector).




Figure 1: Distance to the matched rho and to Bernstein–Lange, per baseline row.

Curves and candidates.

n	curve ID	ICV1 slug	r	IC1 candidate of the baseline
19	EC1N19Ckb1h01617b86df6c	(volcano-ic surface curve E0)	130,873	none recorded
41	EC1N41Ce0he09550ab560a	icv1-f2m41-tm2308219-7f48b14a	549,756,390,943	IC1N41Ckb0fb6560PDP3pairtableRCaimedLAsparseTDwalkISO0h5b25909970b3
53	EC1N53Ce0hb097de99be9a	icv1-f2m53-tm56619371-dac20a85	21,044,858,204,113	IC1N53Ckb0fb27984PDP3pairtableRCaimedLAsparseTDwalkISO0h715dd7692112
61	EC1N61Ce0hd8c15448081e	icv1-f2m61-t158598901-ab42b6c5	162,888,033,982,417	IC1N61Ckb0fb39040PDP3pairtableRCaimedLAsparseTDwalkISO0he9352435e473
83	EC1N83Ce1h35c7ced6b497	icv1-f2m83-t6151469093347-9eba6cd5	8,569,786,107,849,059	IC1N83Ckb1fb99600PDP4s3rootindexRCguidedLAdenseTDsingleISO0hc0ecc1fffbd7

Notes on the rows.

- **n=19.** The `S` unit is one rho group operation of CPU time (2.17e-5 s). The IC's cold `S` is the τ6 arm's CPU per ECDLP in that unit. The baseline subspace base reads 1.77e5× rho in the same run. τ6 over the baseline base is 9.12 [8.12, 10.27].
- **n=41–61.** The unit is one batched affine addition, measured in each row's own process. v3's unit is 2.3–3.2× cheaper than §23's, so `S` is not compared across the two (rule v3 README). Every row passes `validate_claim` at `vs_rho` (68/68 per size). Both certificates were replayed outside the process, and the logarithms equal §23's.
- **n=83.** `S` is derived inside the one run (39335956567): wall ms divided by that run's measured rT770 step (281.09 ns) and by sqrt(r), so one unit is 26,021.1 ms. End-to-end cold is the mean rank stage (kM38I, 4,010.5 ms over 16 blocks of 16 attempts, 0.1541) plus the mean cold (setup 16,698.9 ms including the verified load of the cached factor-log table, 0.6417, plus online 257.9 ms, 0.0099) over the 20 points: 0.8058. Setup, rank stage included, is 0.7959 (0.15413 + 0.64175 = 0.79587); cold without the rank stage is 0.6517. The same run's baseline arm (kPI + cPI, the former row) reads 6.1689 (rank stage 5.5217). BL was not run on this producer.
  - *Wall time, one host class.* The headline 7.6558 and every `S` are wall time from one run on one GitHub runner, not operation counts. The index is unchanged (one layout-digest pair per base, equal to the frozen values; for K600 index-lift's `d8cfe443...` / `5f53764e...`); the saving is the rank stage, 600 attempts -> 16 (143,681.3 ms -> 4,010.5 ms, 35.83x), at the same per-probe wall time (142.55 ns kPI, 143.08 ns kM38I) and the same probe law (kM38I 1.0304 [0.8728, 1.1825], gate band 0.80-1.20, pass). The cold path is not improved: cPI / cM38I cold without rank 0.9931 [0.9837, 1.0035], setup 0.9830, index build 0.9753, online 1.6445 [1.0217, 2.7261]. Controls: A/A end to end 1.0001 [0.9979, 1.0023], A/A cold 1.0006 [0.9979, 1.0032], planted kM38IX / kM38I per attempt 1.9607 [1.9470, 1.9747]. Secondary M10I (60 columns): kPI+cPI / kM10I+cM10I 4.9504 [4.5846, 5.3402]; kM10I+cM10I / kM38I+cM38I 1.5465 [1.4482, 1.6520].
  - *Uncharged phase.* Factor-base construction is charged to no arm (the closure header's images alpha(R_c) included; common to the arms, so R > 1 holds for any X; 7.6558 is an upper bound and cold `S` 0.8058 a lower bound). At the X measured on another host class (427.5 ms, K600 base) the every-phase figures are R 7.5226 and cold `S` 0.8222: illustrative, mixing two hosts.
  - *Section 5a band.* Not computable: the IC arms emit no group additions, scalar multiplications, canonicalizations, fold rotations or index inserts.
  - *Replication.* Not replayed on another host class (`verify_receipt.py` reproduces `result.json` byte for byte on a copy of the whole receipt directory).
  - *Not comparable across runs.* This run's rT770 step (281.09 ns), kPI rank stage (143.7 s) and online mean differ from run 39290913632's (280.33 ns, 148.4 s, 392.3 ms), so the row's `S` and gap are not a delta of the index-lift row; the paired ratio and the paired within-run gaps (kPI + cPI 52.5 [44.0, 63.5] to kM38I + cM38I 6.86 [5.80, 8.19]) are.
- **n=83, the index-lift producer (Other verified records).** `S` is derived inside the one run (39290913632): wall ms divided by that run's measured rT770 step (280.33 ns) and by sqrt(r), so one unit is 25,950.6 ms. End-to-end cold is the shared rank stage K (148,384.4 ms, the mean over three rank blocks of the mean of kP and kPI; 5.718, 5.71795 unrounded) plus the mean cold (setup 16,420.2 ms including the verified load of the cached factor-log table, 0.6327, plus online 392.3 ms, 0.0151) over the 20 points: 6.366. Setup, rank stage included, is 6.351 (5.71795 + 0.63275 = 6.35069); cold without the rank stage is 0.6479. BL was not run on this producer.
  - *Wall time, one host class.* The headline 1.0344 and every `S` are wall time from one run on one GitHub runner, not operation counts. The stored states and the table slot array are byte-identical (stored-state blake3 `d8cfe443...` and table-slot blake3 `5f53764e...` in all 110 IC processes, equal to the frozen values), and every relation, per-attempt probe count (mean 1,746,508), root-call total and point-addition counter is equal across kP and kPI, so the operation counts did not change. The saving is index-build wall time (19,778.4 ms against 14,106.3 ms, 1.4021 [1.4004, 1.4036]); the planted control cPIX (every root keyed by lift_scan and checked against the selected canonicalizer, 29,880,600 roots, no difference) costs 1,184.6 ms more than cP. The rank stage is shared, not a treatment: kPI / kP per attempt 0.9981 [0.9966, 0.9994].

  - *Uncharged phase.* Factor-base construction is charged to neither arm (common to both, so R > 1 holds for any X; 1.0344 is an upper bound and cold `S` 6.366 a lower bound). At the X measured on another host class (427.5 ms) the every-phase figures are R 1.0343 and cold `S` 6.382: illustrative, mixing two hosts.
  - *§5a band.* Not computable: the IC arms emit no group additions, scalar multiplications, canonicalizations, fold rotations or index inserts.
  - *Replication.* Not replayed on another host class. The stacked row's replay found the per-probe wall ratio host-dependent, and index-build wall time has not been replayed either, so the same caution applies to 1.0344.
  - *Not comparable across runs.* This run's rT770 step (280.33 ns), shared rank stage (148.4 s) and online mean (392.3 ms) differ from run 39214027289's (280.64 ns, 143.7 s, 303.8 ms), so the row's `S` and gap are not a delta of the rank-probe row; the paired ratio and the paired within-run gaps (cP 65.1 [53.9, 81.0] to cPI 62.9 [52.5, 78.5]) are.
- **n=83, the rank-probe producer (Other verified records).** `S` is derived inside the one run (39214027289): wall ms divided by that run's measured rT770 step (280.64 ns) and by $\sqrt{r}$, so one unit is 25,980.1 ms. End-to-end cold is the mean rank stage (143,706.7 ms over four rank blocks, 5.531; 5.53141 unrounded) plus the mean cold (setup 21,995.0 ms including the verified load of the cached factor-log table, 0.8466, plus online 303.8 ms, 0.0117) over the 20 points: 6.390. Setup, rank stage included, is 6.378 (5.53141 + 0.84661 = 6.37802); cold without the rank stage is 0.8583. BL was not run on this producer.
  - *Wall time, one host class.* The headline 1.1033 and every `S` are wall time from one run on one GitHub runner, not operation counts. The operation counts did not change: the gates make every relation, per-attempt probe count (mean 1,690,645), root-call total and point-addition counter equal across kR, kP, kPaa and kPX, so the operation-count ratio is 1.0000. The rank-stage wall ratio 1.1193 is entirely per-probe wall time (158.45 ns against 141.54 on this host): the conjugate root's candidates computed in the target's Frobenius frame instead of mapped between the normal and polynomial bases twice. The planted control (278.82 ns per probe) prices the removed work at about 137 ns per probe.
  - *Uncharged phase.* Factor-base construction is charged to neither arm (common to both, so R > 1 holds for any X; 1.1033 is an upper bound and cold `S` 6.390 a lower bound). At the X measured on another host class (427.5 ms) the every-phase figures are R 1.1030 and cold `S` 6.406: illustrative, mixing two hosts.
  - *§5a band.* Not computable: the IC arms emit no group additions, scalar multiplications, canonicalizations, fold rotations or index inserts.
  - *Replication.* Not replayed on another host class. The stacked row's replay found the per-probe wall ratio host-dependent, and the same caution applies to 1.1033.
- **n=83, the rank-cut producer (Other verified records).** `S` is derived inside the one run (38891404048): wall ms divided by that run's measured rT770 step (281.01 ns) and by $\sqrt{r}$, so one unit is 26,013.6 ms. End-to-end cold is the mean rank stage (173,150.9 ms over four rank blocks, 6.656; 6.65617 unrounded) plus the mean cold (setup 22,245.8 ms including the verified load of the cached factor-log table, 0.8552, plus online 297.9 ms, 0.0115) over the 20 points: 7.523. Setup, rank stage included, is 7.511 (6.65617 + 0.85516 = 7.51133); cold without the rank stage is 0.8666. BL was not run on this producer.
  - *Wall time, one host class.* The headline 1.3336 and every `S` are wall time from one run on one GitHub runner, not operation counts. The operation counts did not change: the gates make every relation, per-attempt probe count (mean 1,790,030) and root-call total equal across kS, kR, kRaa and kRX, so the operation-count ratio is 1.0000. The rank-stage wall ratio 1.3768 is entirely per-probe wall time (221.85 ns against 161.10 on this host): the batched S3 root solve replaced by point addition. The planted control (302.05 ns per probe) prices the removed work at about 141 ns per probe.
  - *Uncharged phase.* Factor-base construction is charged to neither arm (common to both, so R > 1 holds for any X; 1.3336 is an upper bound and cold `S` 7.523 a lower bound). At the X measured on another host class (427.5 ms) the every-phase figures are R 1.3328 and cold `S` 7.539: illustrative, mixing two hosts.
  - *§5a band.* Not computable: the IC arms emit no group additions, scalar multiplications, canonicalizations, fold rotations or index inserts.
  - *Replication.* Not replayed on another host class. The stacked row's replay found the per-probe wall ratio host-dependent, and the same caution applies to 1.3336.
- **n=83, the stacked producer (Other verified records).** `S` is derived inside the one run (38862448935): wall ms divided by that run's measured rT770 step (316.66 ns) and by $\sqrt{r}$, so one unit is 29,314.2 ms. End-to-end cold is the mean rank stage (257,814.3 ms over two rank processes, 8.795; 8.79486 unrounded) plus the mean cold (setup 25,575.2 ms including the verified load of the cached factor-log table, 0.8725, plus online 385.1 ms, 0.0131) over the 20 points: 9.680. Setup, rank stage included, is 9.667 (8.79486 + 0.87245 = 9.66731; each `S` is rounded once from its unrounded quotient, so rounded parts need not add up exactly); cold without the rank stage is 0.8856. The row first landed with `s_ic_setup` 0.8856, the cold-without-rank figure; read against B's 32.848 (rank stage included) that looked like a 37× setup drop, which was accounting (corrected 2026-10-16, `corrections` in the JSON). BL was not run on the stack.
  - *Wall time, one host class.* The headline 3.2391 and every `S` are wall time from one run on one GitHub runner (AMD EPYC 9V74, one pinned CPU, CPU-only), not operation counts. The host-independent part is the rank stage's operation counts: probes 2,976,293,514 (kP) against 2,014,683,345 (kS) and root calls 1,488,248,100 against 1,007,441,716, both 1.4773x fewer. The rank-stage wall ratio 3.3737 is that 1.4773 times 2.2837 in wall ns per probe (584.48

against 255.94), measured on this host only. That factor is per-probe wall time, not host speed: a kP probe (full canonicalization) and a kS probe (lift_scan, compact table, prefetch loop) are not the same work, so it mixes cheaper per-probe work with host and memory-system effects. Stored index states halve (29,880,000 to 14,940,300); online probes are equal (cP / cS 1.000133). Setup and index build emit no comparable count, so there is no single end-to-end operation-count ratio.

  - *Uncharged phase.* Factor-base construction is charged to neither arm: every process loads the K600 base from a file. It is common to both arms, so the ratio stays above 1 for any construction cost X, but 3.2391 is an upper bound and cold `S` 9.680 a lower bound on the every-phase figures (X = 1 s: 3.231 and 9.715; 10 s: 3.163 and 10.02; 60 s: 2.848 and 11.73). **X measured (2026-10-17):** one cold in-process construction (`construct:83:1:600`, base hash equal to the retained file's) took X = 427.524 ms in the replay below, 65.541 ms more than loading the retained file on the same host (361.984 ms). At that X the every-phase figures are R 3.2357 and cold `S` 9.6950 (gap 94.56): illustrative, since X is from the Intel replay host and the rest from the EPYC run. The bounds 3.2391 and 9.680 are within 0.11% and 0.15%.
  - *§5a band.* Not computable from this run: the IC arms emit no group additions, scalar multiplications, canonicalizations, fold rotations or index inserts, so the gap 94.4 has no 0 / 0.1 / 1 GAE band and holds as a wall-time figure on this host only.
  - *Replication.* Rank block K1 was replayed on another host class on 2026-10-17: run 39007026856 on an INTEL(R) XEON(R) PLATINUM 8573C (the original: AMD EPYC 9V74; same image, kernel, toolchain and binary sha256), under the protocol frozen at `863f6090` (`experiments/koblitz-n83-replay-20261017/PROTOCO` archived in `RESULTS.md` there). Verdict `replay_pass`: all six runs valid; kS, kP, kP, kS reproduce every per-attempt probe count (first 100 and all 600) and the relation digest of the archived K1 records; the constructed base equals the retained one. Not gated: the per-probe wall ratio kP / kS is 2.6583 there (first 100 attempts 2.7013) against 2.2905 for K1 on the EPYC (2.2837 both blocks), so the 3.24x wall-time headline is host-dependent, while the operation-count ratio 1.4773 stands. The replay did not re-measure the cold arms, so it gives no new R or `S`; one replay, one other host class, two processes per arm. It emits no group-operation counts, so the §5a band stays uncomputable (Open).

- **n=83, B (Other verified records).** `S` in B's run is wall ms over that run's rT770 step (180.8 ns) and $\sqrt{r}$. Cold is the matched precomputation P_IC (520,825 ms rank stage + 29,022 ms per-process setup; `s_ic_setup` 32.848 = 31.114 + 1.734) plus the mean online time. P_IC leaves out factor-base construction (the base is loaded from a file), the linear algebra (51.3 ms) and setup input control (32.3 ms); the JSON row names them in `uncharged_phases`. BL's precomputation was matched to P_IC in wall time on the same CPU, so the cold IC/BL ratio is 0.987 by construction. If PR #918 changes, that row changes with it.

Other verified records

These rows are kept for context and as the history behind the baselines. None is combined with another row.

The rank-probe Bernstein-Lange record preserves its frozen point-paired estimate and reading. It is not a qualified Tier 1 speedup: the primary has one cP/BL observation per point rather than repeated alternating primary pairs. Its receipt records `child_peak_rss_kb_cumulative`, a cumulative child high-water mark, not per-process peak RSS; cgroup counters are group-level. These reporting limits do not alter the archived timing estimate.

n	role	experiment	reference	cold gap, IC / ref [95%]	online gap, IC / ref [95%]	BL	tier
41	previous baseline (v0)	ledger §23, crypto `0bf67f16`	ParallelRho, same process	8.04 [7.26, 9.01]	0.107 [0.082, 0.135]	model 2.50	crypto isolated_bench container
53	previous baseline (v0)	ledger §23	ParallelRho	14.7 [13.1, 16.7]	0.057 [0.044, 0.073]	model 2.02	same
61	previous baseline (v0)	ledger §23	ParallelRho	31.6 [28.2, 35.7]	0.113 [0.084, 0.148]	model 8.04	same
41	other pipeline, complete cold CPU	crypto `disjoint_cold_v2_outcome_20261001` (run 36803331080), compact-orbit K85	32-walk signed-Frobenius normal-basis rho (not rT770)	13.4 [9.37, 18.5]	not measured	none	hosted, A/A and quiet-host gates, second-host replay
53	other pipeline, complete cold CPU	same, compact-orbit K220	same	22.7 [17.9, 31.6]	not measured	none	same
61	other pipeline	crypto autolab run `20261012T202048Z-5521627904`, compact-orbit K=500	strong rho rung 3 (not rT770)	83.4 (median of rows)	0.072 [0.052, 0.102] (inverse of median 13.94)	none	taskset-pinned container with a CPU-isolation receipt

n	role	experiment	reference	cold gap, IC / ref [95%]	online gap, IC / ref [95%]	BL	tier
41	gap to the tuned rho (this experiment only; cf. the baseline row)	`koblitz-s23-tuned-rho-20261015`, run 38777903922 (PR #923)	tuned = rT770 configuration on the one-word kernel; same run: ParallelRho cold 7.83, strong 6.43, rA770 2.54	**6.6** [5.91, 7.4]	**0.09** [0.0715, 0.111]	model 0.53	Tier 1
53	gap to the tuned rho (this experiment only; cf. the baseline row)	`koblitz-s23-tuned-rho-20261015`, run 38777903922 (PR #923)	tuned = rT770 configuration on the one-word kernel; same run: ParallelRho cold 11.8, strong 9.2, rA770 3.01	**10.6** [9.45, 12]	**0.0423** [0.0325, 0.0534]	model 0.322	Tier 1
61	gap to the tuned rho (this experiment only; cf. the baseline row)	`koblitz-s23-tuned-rho-20261015`, run 38777903922 (PR #923)	tuned = rT770 configuration on the one-word kernel; same run: ParallelRho cold 19.4, strong 13.7, rA770 4.42	**18.9** [16.7, 21.5]	**0.0687** [0.051, 0.0903]	model 0.759	Tier 1
83	previous baseline (B, the BL-arm row), superseded by the stacked producer	`koblitz-n83-bl-arm-20261014`, run 38689817618 (PR #918, not merged yet)	rT770, B's 16 fresh points + Q0 x4	360 (no interval; S 32.93 / 0.083 in that run's rT770 steps)	1.01 [0.30, 2.12], not separated	**measured: 235** [61, 645], 16/16 points BL faster; cold IC/BL 0.987 by construction	Tier 1
83	previous baseline (the stacked producer, arms cS / kS), superseded by the rank-cut producer	`koblitz-n83-stacked-20261016`, run 38862448935 (PR #938)	rT770, 20 new points, two rank blocks, Q0	94.4 [73.5, 125.3] (end-to-end cold; S 9.680 / 0.01314 in that run's rT770 steps, 316.66 ns)	0.139 [0.077, 0.237]	none on this row	Tier 1
83	previous baseline (the rank-cut producer, arms cR / kR), superseded by the rank-probe producer	`koblitz-n83-rankcut-20261016`, run 38891404048 (PR #970)	rT770, 20 new points, four rank blocks, Q0	65.7 [55.4, 80.2] (end-to-end cold; S 7.523 / 0.01145 in that run's rT770 steps, 281.01 ns)	0.110 [0.059, 0.174]	none on this row	Tier 1
83	**REFERENCE ROW, not the IC baseline and not an IC improvement**: known-log base, K220 seeded scalar orbits, no relations (LAnone) = BSGS on the Frobenius quotient. The cited DKM result is an asymptotic non-adaptive generic-DLOG time-space lower bound; it does not prove finite-instance runtime dominance over rho. One primary cL220/rT770 observation per point; not a qualified Tier 1 speedup. See `PR #986 qualification`. The owner's decision whether it may hold the IC row remains pending.	`koblitz-n83-knownlog-20261019`, run 39307634508	rT770, 40 new points, Q0, four rank blocks for the baseline pair	**2.19** [1.86, 2.59] (end-to-end cold, known-log K220 / rT770; S 0.2303 [0.2059, 0.2577] in that run's rT770 steps; reading above rho); reference, not an IC improvement: baseline pair kP+cP / K220 27.99 [24.78, 31.53], kP+cP / K600 7.18 [6.89, 7.49]	online K220 / rT770 1.12 [0.85, 1.45]	none on this row	one-run reference; no Tier 1 speedup

n	role	experiment	reference	cold gap, IC / ref [95%]	online gap, IC / ref [95%]	BL	tier
83	previous baseline (the rank-probe producer, arms cP / kP), superseded by the index-lift producer	`koblitz-n83-rankprobe-20261019`, run 39214027289 (PR #980)	rT770, 20 new points, four rank blocks, Q0	64.0 [53.7, 78.0] (end-to-end cold; S 6.390 / 0.01169 in that run's rT770 steps, 280.64 ns)	0.129 [0.085, 0.183]	measured later on this producer: online cP / BL 22.55 [16.23, 31.44], `bl_online_faster_than_ic`; cold IC/BL 0.985 by construction (run 39307708909). Historical instance-scoped estimate, not Tier 1 speedup-qualified	Tier 1 instance; not speedup-qualified
83	previous baseline (the index-lift producer, arms cPI / kPI), superseded by the closure + index-lift producer	`koblitz-n83-indexlift-20261019`, run 39290913632 (PR #981)	rT770, 20 new points, three rank blocks, Q0	62.9 [52.5, 78.5] (end-to-end cold; S 6.366 / 0.01512 in that run's rT770 steps, 280.33 ns)	0.167 [0.091, 0.283]	none on this row	Tier 1
83	promoted over the rank-probe producer at K600, on the rank-probe producer's code (K899 base, arms kP899 / cP899); **baseline row not replaced** (the row names the index-lift producer; this run never ran it as a primary)	`koblitz-n83-k899-20261019`, run 39306394645 (PR pending)	rT770, 20 new points, four rank blocks (seeds 401-404), Q0	54.5 [45.3, 68.2] (end-to-end cold; S 5.639 / 0.008104 in that run's rT770 steps, 280.43 ns); the K600 arm in the same run reads 64.7 [53.8, 81.3] (S 6.694)	0.087 [0.058, 0.126] (K600 arm 0.180 [0.098, 0.312])	none on this row	Tier 1
83	same pipeline as the baseline (merged)	`koblitz-n83-reconcile-20261014`, run 38617911080	rT770, two seeds per point	313 (fresh-rank setup)	0.92 [0.28, 1.78], not separated	none	Tier 1
83	same pipeline, first Tier 1 run	`koblitz-single-target-n83-tier1-20261014`, run 38523707244	rung 3, slower per step than StrongRhoG, so not the matched tuned rho	134	0.36 [0.11, 0.66]	model 33.5 (measured later: 235)	Tier 1
83	promoted single improvement over B: two-limb `lift_scan` canonicalizer (this experiment only)	`koblitz-n83-liftscan-20261015`, run 38776966036 (PR #926)	rT770, B's 16 fresh points	cold not measured	IC/rho 0.67 [0.19, 1.38] (inverse of 1.4914 [0.7270, 5.1445]); online full / lift_scan 1.5152 [1.5061, 1.5247]	none	Tier 1
83	promoted single improvement over B: Feistel scan order (this experiment only)	`koblitz-n83-scanorder-20261015`, run 38786433493 (PR #927)	rT770, B's 16 fresh points	cold not measured	IC/rho 0.291 [0.163, 0.481] (inverse of 3.4370 [2.0774, 6.1418]); online left-major / Feistel 3.4287 [1.0090, 7.4215]; held-out 384: 1.4507 [1.2023, 1.7424]	none	Tier 1

n	role	experiment	reference	cold gap, IC / ref [95%]	online gap, IC / ref [95%]	BL	tier
83	**not promoted**: lift_scan x Feistel order combined (this experiment only)	`koblitz-n83-combined-20261015`, run 38803625711	rT770, 576 new points	cold not measured	IC/rho 0.2145 [0.1949, 0.2353] (inverse of 4.6628 [4.2501, 5.1308], means); frozen primary R_m 1.2363 [1.0671, 1.4276], R_g 1.0611 [0.9083, 1.2430]: `not_separated`; combined vs B 1.9992 [1.7285, 2.3090]	none	Tier 1
83	promoted improvement over the combined producer: software-pipelined, prefetched root-table probes (this experiment only)	`koblitz-n83-probepipe-20261015`, run 38822490448	rT770, 384 new points	cold not measured	IC/rho 0.1462 [0.1307, 0.1626] (inverse of 6.8396 [6.1494, 7.6526]); combined producer 0.2047; online combined / pipeline 1.4001 [1.3971, 1.4032], probes identical	none	Tier 1
83	promoted improvement over the probe-pipeline producer: two-level root table, 32 MiB filter + 16-byte slots (this experiment only)	`koblitz-n83-tablefilter-20261015`, run 38829449594	rT770, 384 new points	cold not measured against rho; cold pP / pT 1.0101 [1.0090, 1.0113]	IC/rho 0.1523 [0.1358, 0.1709] (inverse of 6.5642 [5.8533, 7.3649]); pipeline 0.1620; online pP / pT 1.0633 [1.0589, 1.0679], probes identical, mostly from the 16-byte slot	none	Tier 1
83	promoted improvement over the combined producer: folded S3 root index, cold (this experiment only)	`koblitz-n83-state-fold-20261015`, run 38819494806	rT770, 16 new points	6.95 [5.53, 9.01] (cB 12.77; setup + online, rank stage excluded; with the rank stage 109.6, was 243.3)	IC/rho 0.163 [0.090, 0.241]; online 5% slower; cold cB / cF 1.8372 [1.8216, 1.8528], setup 1.86×, peak RSS 1.97×	none	Tier 1
83	promoted improvement over the rank-probe producer: Z[tau]-multiplier closure of the K600 base, M38 primary (16 columns) and M10 secondary (60 columns) (this experiment only; the comparison against the current row is superseded by the paired closure + index-lift result, run 39335956567)	`koblitz-n83-closure-20261019`, run 39305259093	rT770, 20 new points, 16 / 4 / 8 rank blocks (kM38 / kP / kM10), Q0	10.5 [8.8, 12.7] (end-to-end cold kM38 + cM38; the rank-probe arm kP + cP in the same run 67.5 [56.4, 82.4]; M10 14.9 [12.2, 18.1]; S 1.115 against 7.188, rT770 step 186.55 ns; rank stage 108.0 s -> 2.75 s, 39.28x; cold without rank cP / cM38 0.9760 [0.9608, 0.9888])	online 0.215 [0.129, 0.312] (cP 0.169; cM38 online not separated from cP, 0.7860 [0.3828, 1.4402]); primary R = E2E(kP + cP) / E2E(kM38 + cM38) 6.4444 [6.0993, 6.7853]; M10 4.5318 [4.1827, 4.8771]; factor-base construction charged to no arm	none	Tier 1

n	role	experiment	reference	cold gap, IC / ref [95%]	online gap, IC / ref [95%]	BL	tier
83	**not promoted**: rotation-key probe (the rank-stage table key rotkey(v) = v^83 in F2[X]/(X^83+1) in place of lift_scan; this experiment only; baseline row not replaced)	`koblitz-n83-rotkey-20261019`, run 39299176306	rT770, 20 new points, four rank blocks (kP, kK, kKaa, kKX), Q0	69.40 [52.51, 93.51] (end-to-end cold kP + cP, the rank-probe producer) against 69.51 [52.43, 93.02] (kK + cK) in the same run; S 7.453 against 7.465, rT770 step 247.87 ns; rank stage 147.4 s against 147.6 s; cold without rank cP / cK 0.9988 [0.9900, 1.0070]	online 0.1658 [0.1041, 0.2628] (cP) against 0.1701 [0.1045, 0.2720] (cK); frozen primary R = E2E(kP + cP) / E2E(kK + cK) 0.9983 [0.9701, 1.0227]: `not_separated`; A/A and planted controls pass; every gate passes (0 collisions on 29,878,182 keys); rotation-key table build 2.52 s per rank process charged to kK; factor-base construction charged to no arm	none	Tier 1
83	promoted improvement over the rank-probe producer: the one-target online scan on the rank stage's frame loop, `KIC_ONLINE_SOLVE=frame` (this experiment only)	`koblitz-n83-onlineframe-20261019`, run 39303742695	rT770, 64 new points, one shared rank stage	end-to-end cold with the shared rank stage 66.47 [58.24, 76.58] (S 6.5776; cS 66.52, S 6.5827; E2E cS / cF 1.0008 [1.0006, 1.0010])	online 0.109 [0.079, 0.145] (cS 0.171 [0.125, 0.227]); online `S` 0.00977 (cS 0.01537); online cS / cF 1.5733 [1.5714, 1.5753], probes identical	none	Tier 1

Ratchet history

n	from	to	cold gap	online gap	class
41	§23 (v0, `0bf67f16`)	rule v3 (`995ea207`)	8.04 → 7.66	0.107 → 0.092	engineering (IC programme rounds R03, R05, R07)
53	§23 (v0)	rule v3	14.7 → 13.2	0.057 → 0.047	engineering
61	§23 (v0)	rule v3	31.6 → 21.0	0.113 → 0.067	engineering
83	B	lift_scan canonicalizer (PR #926, run 38776966036)	not measured	not measured (online 1.5152 faster, fresh 16)	engineering; promoted by its own frozen rule; baseline row not replaced (no cold `S`)
83	B	Feistel scan order (PR #927, run 38786433493)	not measured	not measured (online 1.4507 faster, held-out 384)	advance (probe count); promoted; baseline row not replaced (no cold `S`)
83	better single arm (lift_scan)	lift_scan x Feistel (run 38803625711)	not measured	R_m 1.2363 [1.0671, 1.4276]; R_g 1.0611 [0.9083, 1.2430]	**not promoted**: frozen primary `not_separated`
83	lift_scan x Feistel combined producer	software-pipelined, prefetched probes (run 38822490448)	not measured	0.2047 → 0.1462 (online, tuned rho; 1.4001 faster)	engineering; promoted by its own frozen rule; baseline row not replaced (no cold `S`)
83	probe-pipeline producer	two-level root table (run 38829449594)	not measured	0.1620 → 0.1523 (online, tuned rho; 1.0633 faster)	engineering; promoted by its own frozen rule; baseline row not replaced (no cold `S` against rho)
83	lift_scan x Feistel combined producer	folded S3 root index (run 38819494806)	12.77 → 6.95 (rank stage excluded)	not improved (online 5% slower)	engineering; promoted by its own frozen rule; baseline row not replaced (rank stage still dominates cold cost)

n	from	to	cold gap	online gap	class
83	pP, the probe-pipeline producer with B's rank stage (same run; this replaced B's baseline row, run 38689817618)	stacked producer: probe pipeline + 16-byte slots + folded index + rank stage (run 38862448935)	**paired, this run:** 305.8 [237.5, 403.8] → 94.4 [73.5, 125.3] (end-to-end cold, from pP with B's rank stage; 3.24× closer). Context only: B's own run read 360 (a different run, instances and step time)	**paired, this run:** 0.133 [0.072, 0.229] → 0.139 [0.077, 0.237]: online 4.6% slower in this step. Context only: B's run read 1.01	engineering; promoted by its own frozen primary (end-to-end cold cP / cS 3.2391 [2.9809, 3.5240] in wall time on one host class, factor-base construction excluded; rank-stage probes and root calls 1.4773x fewer; 20 points, two rank blocks, against the probe-pipeline producer); **baseline row replaced**: the first measured n=83 end-to-end cold `S` after B (9.68; was 32.93 in B's run, a different step time)
83	the stacked producer (arms kS + cS), same run 38891404048, points and rT770 (this replaced the stacked baseline row, run 38862448935)	rank-cut producer: partner roots by point addition in the rank stage (run 38891404048)	**paired, this run:** 87.6 [74.1, 107.2] → 65.7 [55.4, 80.2] (end-to-end cold; 1.33× closer). Context only: the stacked row as landed read 94.4 (a different run, instances and step time)	**paired, this run:** 0.1107 [0.0602, 0.1752] → 0.1101 [0.0590, 0.1744]: online unchanged (same code)	engineering; promoted by its own frozen primary (end-to-end cold kS+cS / kR+cR 1.3336 [1.3300, 1.3377] in wall time on one host class, factor-base construction excluded; probes and root calls unchanged, the saving is per-probe wall time 221.85 → 161.10 ns, rank stage per attempt 1.3770 [1.3735, 1.3813]; 20 points, four rank blocks, against the stacked producer); **baseline row replaced**
83	the rank-cut producer (arms kR + cR), same run 39214027289, points and rT770 (this replaced the rank-cut baseline row, run 38891404048)	rank-probe producer: the rank-cut loop in the target's Frobenius frame (run 39214027289)	**paired, this run:** 70.6 [59.3, 86.3] → 64.0 [53.7, 78.0] (end-to-end cold; 1.10× closer). Context only: the rank-cut row as landed read 65.7 (a different run, instances and step time)	**paired, this run:** 0.1288 [0.0836, 0.1816] → 0.1291 [0.0847, 0.1830]: online unchanged (same code)	engineering; promoted by its own frozen primary (end-to-end cold kR+cR / kP+cP 1.1033 [1.1010, 1.1056] in wall time on one host class, factor-base construction excluded; probes, root calls and point-addition counters unchanged, the saving is per-probe wall time 158.45 → 141.54 ns, rank stage per attempt 1.1194 [1.1175, 1.1214]; 20 points, four rank blocks, against the rank-cut producer); **baseline row replaced**
83	the rank-probe producer (arms kP + cP, shared rank stage), same run 39290913632, points and rT770 (this replaced the rank-probe baseline row, run 39214027289)	index-lift producer: lift_scan in the root-index build (run 39290913632)	**paired, this run:** 65.1 [53.9, 81.0] -> 62.9 [52.5, 78.5] (end-to-end cold; 1.03x closer). Context only: the rank-probe row as landed read 64.0 (a different run, instances, rank seeds and step time)	**paired, this run:** 0.1667 [0.0926, 0.2808] -> 0.1666 [0.0914, 0.2830]: online unchanged (same online code)	engineering; promoted by its own frozen primary (end-to-end cold cP / cPI 1.0344 [1.0324, 1.0364] with a shared rank stage, in wall time on one host class, factor-base construction excluded; stored states and table slots byte-identical, probes, root calls and counters unchanged, the saving is index-build wall time 19,778 -> 14,106 ms, cold without rank 1.3376 [1.3340, 1.3406]; 20 points, three rank blocks, against the rank-probe producer); **baseline row replaced**

	n	from	to	cold gap	online gap	class
	83	the rank-probe producer (arms kP + cP), same run 39305259093, points and rT770 (the baseline row was NOT replaced)	closure producer (arms kM38 + cM38): Z[tau]-multiplier closure of the K600 base, 16 columns (run 39305259093)	**paired, this run:** 67.5 [56.4, 82.4] -> 10.5 [8.8, 12.7] (end-to-end cold; 6.44x closer)	**paired, this run:** 0.1689 [0.0929, 0.2612] -> 0.2149 [0.1290, 0.3123]: online not separated (cP / cM38 0.7860 [0.3828, 1.4402])	engineering; promoted by its own frozen primary (end-to-end cold kP+cP / kM38+cM38 6.4444 [6.0993, 6.7853] in wall time on one host class, factor-base construction charged to no arm; the saving is the rank stage 108.0 s -> 2.75 s, cold without rank 0.9760 [0.9608, 0.9888]; 20 points, 16 and 4 rank blocks, against the rank-probe producer); baseline row not replaced by this run (superseded by the paired closure + index-lift result below, which replaced the row)
	83	the rank-probe producer at K600 (arms kP600 + cP600), same run 39306394645, points and rT770	the rank-probe producer at K899, the nested 899-column base (arms kP899 + cP899; run 39306394645)	**paired, this run:** 64.7 [53.8, 81.3] -> 54.5 [45.3, 68.2] (end-to-end cold; 1.19x closer). Context only: the rank-probe row as landed read 64.0 (a different run, instances, rank seeds and step time)	**paired, this run:** 0.1803 [0.0978, 0.3116] -> 0.0870 [0.0583, 0.1265] (online; cP899 / cP600 online time 0.4825 [0.2688, 0.8733], fewer probes with more columns)	advance (a change of K; the code is unchanged); promoted by its own frozen primary (end-to-end cold kP600+cP600 / kP899+cP899 1.1873 [1.1247, 1.2523] in wall time on one host class, factor-base construction excluded; the rank stage 1.5176 [1.4149, 1.6235] faster from 2.35x fewer probes per attempt (law r / (166 E), ratios 1.026 and 0.980) at 3% more ns per probe, cold without rank 2.0766x slower, peak RSS 2.07x; 20 points, four rank blocks, power 0.16 at the diagnostic's R of 1.036 and 0.91 at 1.10, the effect was larger; A/A and planted controls pass); **baseline row not replaced**: the row on main names the index-lift producer, not the rank-probe producer, so the ratchet's condition fails and the result is recorded as promoted over the rank-probe producer. The two changes were not run together as a primary; the cPI secondary pair (K899 with lift_scan in the index build) reads kP600+cPI600 / kP899+cPI899 1.2586 [1.1888, 1.3330] and gap 49.7 [41.5, 62.1], which never decides and is not a promoted pipeline

	n	from	to	cold gap	online gap	class
	83	the index-lift producer (arms kPI + cPI), same run 39335956567, points and rT770 (this replaced the index-lift baseline row, run 39290913632)	closure + index-lift producer: Z[tau]-multiplier closure of the K600 base, 16 columns, on the index-lift producer (arms kM38I + cM38I; run 39335956567)	**paired, this run:** 52.5 [44.0, 63.5] -> 6.86 [5.80, 8.19] (end-to-end cold; 7.66x closer). Context only: the index-lift row as landed read 62.9 (a different run, instances, rank seeds and step time)	**paired, this run:** 0.1521 [0.0980, 0.2158] -> 0.0925 [0.0594, 0.1352] (online; cPI / cM38I online time 1.6445 [1.0217, 2.7261])	engineering; promoted by its own frozen primary (end-to-end cold kPI+cPI / kM38I+cM38I 7.6558 [7.2192, 8.1103] in wall time on one host class, factor-base construction charged to no arm; the saving is the rank stage 143.7 s -> 4.01 s, cold without rank 0.9931 [0.9837, 1.0035]; 20 points, 4 and 16 rank blocks, against the index-lift row; supersedes the closure's comparison against the rank-probe producer, run 39305259093); **baseline row replaced**
	83	the rank-probe producer (arms kP + cP), same run 39299176306, points and rT770 (the baseline row was NOT replaced)	rotation-key producer (arms kK + cK): rank-stage table keyed by v^83 in F2[X]/(X^83+1), lift_scan only at a hit (run 39299176306)	69.40 [52.51, 93.51] -> 69.51 [52.43, 93.02] (end-to-end cold, paired within run)	0.1658 [0.1041, 0.2628] -> 0.1701 [0.1045, 0.2720] (online, not separated)	**not promoted**: frozen primary `not_separated` (end-to-end cold kP+cP / kK+cK 0.9983 [0.9701, 1.0227] in wall time on one host class; rank per attempt kP / kK 1.0156 [0.9820, 1.0450]; 20 points, four rank blocks; every gate and both controls pass); baseline row not replaced
	83	the rank-probe producer's one-target online scan on the batched S3 loop (arm cS), same run 39303742695, points and rT770	online frame: the one-target online scan on the rank stage's frame loop (arm cF, `KIC_ONLINE_SOLVE=frame`; run 39303742695)	**paired, this run:** 66.5 [58.3, 76.5] -> 66.5 [58.2, 76.6] (end-to-end cold with the shared rank stage; unchanged to 0.08%)	**paired, this run:** 0.1714 [0.1249, 0.2273] -> 0.1089 [0.0791, 0.1449] (1.57x smaller)	stage improvement (online) over the rank-probe producer; promoted by its own frozen primary (online cS / cF 1.5733 [1.5714, 1.5753] in wall time on one host class, 222.76 -> 141.58 ns per probe, probes, root calls and relations unchanged; A/A 0.9986 and 0.9999, planted 2.7052 [2.6979, 2.7127]; 64 points); end-to-end secondary with the shared rank stage 1.0008 [1.0006, 1.0010], no regression, lower bound above 1 (a pipeline improvement of 0.08% by the frozen reading); **baseline row not changed: stacks with index-lift and the closure; combined run pending**

The paired cold-time ratios between baselines, each in its own runs, are in crypto `research/notes/index-calculus/IC_TOOL_PROGRAM.md` §7. The gaps above are each against that comparison's own rho, and that rho also changed between §23 and v3. So the gap delta is the distance remaining, not the IC's own speedup.

Stage results: canonicalization

Stage improvements are recorded here. One becomes a pipeline improvement only once it moves an end-to-end `S` above.

stage	n	experiment	result	tier	pipeline effect
normal-basis least rotation, isolated	131	`canon-n131-20261014`	Five exact canonicalizers on `[u64; 3]`. Ir per uniform word: lift_scan 514, gap_scan 1,435, exhaustive 1,850, exhaustive_bf 3,664, refine_bf 4,510. 0 mismatches.	deterministic Ir; wall times exploratory	none yet
the same, inside a decomposition-style loop	131	`canon-n131-loop-20261014`, run 38607684318	lift_scan is fastest on all four workloads: 16/16 contrasts at Bonferroni, ratios 1.83–3.81. In-loop Ir over the loop floor: lift_scan 519, gap_scan 1,760, exhaustive 2,883.	Tier 1 for the timing	none yet. No n=131 pipeline exists, and at n=53 the isolated ranking did not survive the loop (`papers/frobenius-orbits` §4/§7)

Open

- **n=41, 53, 61:** the gap to the tuned rho is measured by `experiments/koblitz-s23-tuned-rho-20261015` (run 38777903922, PR #923; rows above, one per size, each from that experiment alone; n=47, 57 and 59 are in its README). It ran rT770's configuration on the one-word `Gf2` kernel, because `Gf2_128` exists only for n > 64, and it measures about the same cost as ParallelRho. It is accounting: no IC change, so no baseline row moves. A rho tuned on the one-word kernel is not measured.
- **n=19 and n=41–61:** no Bernstein–Lange walk has run, so the BL figures are models or absent.
- **n=83:** the baseline row is the closure + index-lift producer (`koblitz-n83-closure-indexlift-20261019`, run 39335956567): the index-lift producer with the Z[tau]-multiplier closure of the K600 base (16 columns, M38), promoted end to end over the index-lift row (7.6558 [7.2192, 8.1103], in wall time on one host class; 20 points, 4 and 16 rank blocks; rank stage 143.7 s -> 4.01 s; the cold path is not improved, cPI / cM38I 0.9931 [0.9837, 1.0035]; layout digests, probes per relation and scalars verified, probe law pass). Its end-to-end cold `S` is 0.806 against the tuned rho's 0.1175 (gap 6.86 [5.80, 8.19]); the cold path is now 81% of the end-to-end cold cost. Factor-base construction is charged to no arm. The index-lift producer (1.0344 [1.0324, 1.0364] over the rank-probe producer, run 39290913632), the rank-probe producer (1.1033 [1.1010, 1.1056] over the rank-cut producer, run 39214027289), the rank-cut producer (1.3336 [1.3300, 1.3377] over the stack, run 38891404048), the stacked producer (3.2391 [2.9809, 3.5240] over the probe-pipeline producer, run 38862448935) and B's row (experiment on PR #918, not merged yet) are in Other verified records. The run was not replayed on another host class, and the BL gap was not re-measured on this producer. The closure's earlier comparison (`koblitz-n83-closure-20261019`, run 39305259093: 6.4444 [6.0993, 6.7853] over the rank-probe producer) is superseded by this paired result. The nested 899-column base is promoted over the rank-probe producer at K600 (`koblitz-n83-k899-20261019`, run 39306394645: 1.1873 [1.1247, 1.2523]) but has not been combined with this producer; the next step is a frozen protocol for K899, or for the root-index build and setup, on the closure + index-lift producer against the current row, with the K899 index build (44.3 s) and the slot cliff at K900 in view. The rotation-key producer (`koblitz-n83-rotkey-20261019`, run 39299176306: the rank-stage table keyed by v^83 in F2[X]/(X^83+1), lift_scan only at a hit) is not promoted against the rank-probe producer: end-to-end cold ratio 0.9983 [0.9701, 1.0227], not separated, with every gate and both controls passing. It is not an improvement, so there is no stack on index-lift or the multiplier closure. The online-frame experiment (`koblitz-n83-onlineframe-20261019`, run 39303742695) is a stage improvement over the rank-probe producer: its one-target online scan on the rank stage's frame loop, online cS / cF 1.5733 [1.5714, 1.5753] over 64 points, probes and root calls unchanged, end to end 1.0008 [1.0006, 1.0010]. It is a different stage from the index lift and from the closure, so it stacks with them; it is recorded in Other verified records and not in this row until a combined run is made.
- **n=19:** IC1 candidate manifests now exist for the baseline and the native-solve candidate (`IC1N19Ckb0fb1064PDP2polyboriRCsampleLAkernelTDpdpISO0hb41aed7ef80a` and `IC1N19Ckb0fb1064PDP2nativeenumRCsampleLAkernelTDpdpISO0h6952f30ce00e`, in `experiments/volcano-n19-native-tau6-20261019/inputs/ic1_manifests.`) and online `S` is separable by definition in that protocol (setup and online are timed apart). It has not been measured: the Tier 1 run (39307409409) is invalid, because its S0 gate failed (Sage and native varieties equal on 293 of 300 systems) and no timed row ran. The n=19 row, Figure 1 and the ratchet history are unchanged.
- **n=83, §5a band:** the 0 / 0.1 / 1 GAE band for the IC / rho gap is uncomputable on both n=83 rows, because the frozen producer emits no group-operation counts. The K1 replay (archived 2026-10-17) timed factor-base construction but used the same producer, so the band stays open until a producer that emits the counts runs under a new protocol.
- **n=83, construction time X (resolved 2026-10-17):** measured in `koblitz-n83-replay-20261017` (run 39007026856): X = 427.5 ms, 65.5 ms over the retained-file load. Every-phase stacked R 3.2357 and cold `S` 9.6950 (illustrative, two hosts) against the row's 3.2391 and 9.680; the row's figures are unchanged.

B's row uses the same base; its cold `S` was not recomputed.

Updating this file

1. Freeze a protocol for the candidate improvement against the row's pipeline, on the same instances, before timing.
2. When the improvement lands, replace the row in `baselines.json` and in the table above. Add a history row with the before and after figures and the class (advance, engineering, relabelling, accounting). Relabelling and accounting do not replace a baseline. Give `s_ic_setup` its one meaning (`s_ic_cold - s_ic_online`, rank stage included), and record the history delta paired within the promoting run; figures from an earlier run go in as context only. Say whether the headline is wall time (and on which host class) or operation counts, give the operation-count ratio beside a wall-time one, name any phase the experiment did not charge, and say whether the §5a band was computable and whether the run was replayed elsewhere.
3. Name the next improvement to try in the new row.
4. Re-render Figure 1 and this file's PDF:

```
cd docs/ic/figures && pdflatex baselines_gap.tex && pdftoppm -png -r 160 -singlefile baselines_gap.pdf baselines_gap
cd .. && pandoc BASELINES.md -o BASELINES.pdf --pdf-engine=pdflatex -H pdf-header.tex -V geometry:landscape,margin=1.2cm -V fontsize=9pt
python3 -m json.tool baselines.json > /dev/null
```

Sources

- crypto `docs/ic/BOUNDARY_TARGETS.md` and `docs/ic/boundary_targets.json` (Regime B `vs_rho`; complete cold compact-orbit panel).
- crypto `research/notes/index-calculus/RESEARCH_IC_BOUNDARY_LEDGER.md` §23; `research/ic_single_target_20260930/` (PROTOCOL, analysis.json).
- crypto `research/ic_tool_program/rule/v3/` (README, PROTOCOL, analysis.json); `research/notes/index-calculus/IC_TOOL_PROGRAM.md` §7.
- crypto `research/notes/ecc2k130/disjoint_cold_v2_outcome_20261001/RESULT.md`.
- cryptanalysis `experiments/koblitz-n83-bl-arm-20261014/` (branch `claude/n83-bl-arm`, PR #918): README, `run_github_38689817618/result.json`.
- cryptanalysis `experiments/koblitz-s23-tuned-rho-20261015/`: README, `run_github_38777903922/panel/result.json` (PR #923).
- cryptanalysis `experiments/koblitz-n83-reconcile-20261014/`: README, `run_github_38617911080/panel/result.json`.
- cryptanalysis `experiments/koblitz-single-target-n83-tier1-20261014/`: README, `tier1_github_38523707244/`.
- cryptanalysis `experiments/volcano-ic/rho-arm-20261014/`: README, `results/summary.json`.
- cryptanalysis `experiments/canon-n131-20261014/` and `experiments/canon-n131-loop-20261014/`.