Held-out confirmation: GLV table budget constant 48 → 12

`PROTOCOL.md` was frozen in commit f630cc3 together with the `src/curve.c` change, before any data on seed 20261023 existed. `sha256sum -c PROTOCOL.sha256` passes on the committed protocol, scripts and source.

Run

- **Arms:** `main` (`7cb3dce`) and `c12` (`7cb3dce` + this PR's one-constant change).
- **Sample:** j = 1728 and j = 0, r at 26–40 bits, 200 curves × 25 targets per family and size.
- **Seed:** 20261023, held out.
- **Rho reference:** the negation-map rho on every target.
- **Total:** 160,000 `curve_solve` rows plus 80,000 rho rows. Four processes on one 4-core host took 31 minutes.
- **Raw rows:** `rows_main.jsonl.gz` and `rows_c12.jsonl.gz`.

Invariants (all pass)

- **Correctness:** every answer is correct, in both arms and in the rho reference.
- **Grid:** the grids are identical, with no duplicate rows.
- **Identity control:** wherever c = 12 and c = 48 pick the same table, the counts are identical. That covers 45,700 rows, 0 differing, and includes all of 26 bits and 36–40 bits.

Primary result: confirmed for both families

The statistic is the geometric mean of the c12 / main `curve_solve` group-operation ratios at 28, 30, 32 and 34 bits. Intervals are 97.5% (2 families), bootstrapped over curves within each cell.

family	held-out ratio	97.5% interval	selection-round estimate (in-sample)
j = 1728	**0.957**	[0.948, 0.965]	0.959
j = 0	**0.967**	[0.958, 0.976]	0.954



Cells (descriptive; intervals 99.69%, Bonferroni over 16)

family	bits	table main → c12	c12 / main	interval	main / rho	c12 / rho
j1728	26	8 → 8	1.000	identical	0.536	0.536
j1728	28	8 → 16	0.938	[0.916, 0.959]	0.520	0.487
j1728	30	8 → 32	0.917	[0.893, 0.943]	0.726	0.665
j1728	32	8/16 → 32	0.980	[0.952, 1.008]	0.691	0.677
j1728	34	16/32 → 32	0.994	[0.982, 1.005]	0.689	0.685
j1728	36–40	32 → 32	1.000	identical	0.695–0.748	same
j0	26	8 → 8	1.000	identical	0.435	0.435
j0	28	8 → 8/16	0.998	[0.978, 1.019]	0.407	0.407
j0	30	8 → 16/32	0.949	[0.924, 0.975]	0.589	0.559
j0	32	8/16 → 32	0.942	[0.916, 0.970]	0.593	0.559
j0	34	16/32 → 32	0.980	[0.959, 1.002]	0.562	0.550
j0	36–40	32 → 32	1.000	identical	0.566–0.605	same

Where the two rules choose different tables:

- **Resolved fewer:** j = 1728 at 28 and 30 bits (6–8%), and j = 0 at 30 and 32 bits (5–6%), even at the per-cell Bonferroni level.
- **Not resolved alone:** j = 1728 at 32 and 34 bits, and j = 0 at 28 and 34 bits. Their point estimates are 0.980–0.998.
- **Never resolved worse:** no cell.

Against the matched negation-map rho, `curve_solve` on j = 1728 at 30 bits goes from 0.726 to 0.665, and j = 0 at 32 bits from 0.593 to 0.559.

Decision (from the frozen rule)

Both families are confirmed. The PR proposes the change as an operation-count improvement of about 4% (j = 1728) and 3% (j = 0) in geometric mean over 28–34-bit subgroups. Individual sizes gain up to 8%. There is no change at 26 bits or from 36 bits up, where both rules pick the same table.

Limits

- **Measure:** operation counts, not wall time. Setup operations are counted, so a larger table's extra setup is included.
- **Sizes:** 26–40 bits only. Above 36 bits the rule is unchanged by construction.
- **Scope:** `glv_rho_solve` only. The covariant walk's own table rule is unchanged and still not dispatched on `main` (#1059, #1061).

Reproduce

Build both arms as in `PROTOCOL.md`, then:

```
for fam in j1728 j0; do
  CRYPTANALYSIS_LIB=b-main/libcryptanalysis.so python3 run.py --arm main --families $fam --rho --out rows_main_$fam.jsonl
&
  CRYPTANALYSIS_LIB=b-c12/libcryptanalysis.so  python3 run.py --arm c12  --families $fam --out rows_c12_$fam.jsonl &
done; wait
cat rows_main_j1728.jsonl rows_main_j0.jsonl | gzip -9 > rows_main.jsonl.gz
cat rows_c12_j1728.jsonl rows_c12_j0.jsonl | gzip -9 > rows_c12.jsonl.gz
python3 analyze.py && python3 chart.py
```