# Index-calculus baselines: the ratchet

**Status (2026-10-15).** This is the first edition of the ledger, with the tuned-rho rows added from run 38777903922. It takes no new measurement: every number is copied from a committed experiment, and each row cites that experiment. Figure 1 was checked and stays current: no baseline row's numbers changed. The n=83 rows for lift_scan, the Feistel order and their (not promoted) combination were added on 2026-10-15; Figure 1 was checked and stays current, because no baseline row's numbers changed. The n=83 row for the probe pipeline was added on 2026-10-16, the two-level root table and the state fold the same day, each with the same Figure 1 check. On 2026-10-16 the stacked producer (`koblitz-n83-stacked-20261016`, run 38862448935) replaced B's n=83 baseline row, and Figure 1 was re-rendered. Also on 2026-10-16, an accounting correction (sheriff case SHF-20261016-3caa6f, K3 and K4): the n=83 row's `s_ic_setup` was 0.8856, which is setup without the rank stage plus online, while every other row's (B's 32.848 included) is cold minus online with the rank stage in it. It is now 9.6673 on that one meaning, and the B → stack ratchet entry records the paired within-run delta. No measurement changed, and Figure 1 (gaps only) is unchanged. Also on 2026-10-16, disclosures from the same case (K1, K2, R1; no number changed): the n=83 row's headline and `S` are wall time on one host class, with the host-independent operation-count ratio (rank-stage probes and root calls 1.4773x) beside it; factor-base construction is charged to neither arm, so the row's ratio is an upper bound and its cold `S` a lower bound; the §5a GAE band is not computable from that run; and the run was not replayed on another host class. On 2026-10-17, corrections from re-audit SHF-20261017-e4d7f6 (K-N1, K-N2, K-N4; no measurement changed): the setup convention now names what each row leaves out (both n=83 rows leave out factor-base construction; B's row also leaves out 51.3 ms of linear algebra and 32.3 ms of input control, now listed in its JSON `uncharged_phases`); the B → stack history entry's standard gap fields now hold the paired within-run gaps, with B's cross-run figures under `cross_run_context_*`; the n=83 rank stage rounds to 8.7949 (8.79486), not 8.7948; and 2.2837 is per-probe wall time, not a host-speed factor. A replay of rank block K1 with one timed base construction is preregistered (`experiments/koblitz-n83-replay-20261017/PROTOCOL.md`). Figure 1 (gaps only) is unchanged. On 2026-10-17 that replay was archived (`experiments/koblitz-n83-replay-20261017/RESULTS.md`, run 39007026856): `replay_pass` on another host class (Intel Xeon Platinum 8573C), rank-stage work identical, per-probe wall ratio 2.6583 there against 2.2905 on the EPYC; construction time X = 427.5 ms is now measured. The n=83 row's replication and uncharged-phase notes record it; no figure of the row changed, and Figure 1 is unchanged. On 2026-10-19 the rank-cut producer (`koblitz-n83-rankcut-20261016`, run 38891404048) replaced the stacked producer's n=83 baseline row (end-to-end cold 1.3336 [1.3300, 1.3377] over the stack, wall time on one host class, probes and root calls unchanged), and Figure 1 was re-rendered. Also on 2026-10-19 the rank-probe producer (`koblitz-n83-rankprobe-20261019`, run 39214027289) replaced the rank-cut producer's n=83 baseline row (end-to-end cold 1.1033 [1.1010, 1.1056] over the rank-cut producer, wall time on one host class, probes and root calls unchanged), and Figure 1 was re-rendered. Also on 2026-10-19 the index-lift producer (`koblitz-n83-indexlift-20261019`, run 39290913632) replaced the rank-probe producer's n=83 baseline row (end-to-end cold 1.0344 [1.0324, 1.0364] over the rank-probe producer with a shared rank stage, wall time on one host class, stored states and table slots byte-identical, probes and root calls unchanged), and Figure 1 was re-rendered. Also on 2026-10-19 the nested 899-column factor base under the rank-probe producer (`koblitz-n83-k899-20261019`, run 39306394645) was recorded as promoted over the rank-probe producer at K600 (end-to-end cold 1.1873 [1.1247, 1.2523], wall time on one host class); the n=83 baseline row names the index-lift producer, not the rank-probe producer, so the row was not replaced (record in Other verified records and the history), and Figure 1 is unchanged. Also on 2026-10-19 the closure producer (`koblitz-n83-closure-20261019`, run 39305259093) was recorded as a promoted improvement over the rank-probe producer (end-to-end cold 6.4444 [6.0993, 6.7853], wall time on one host class); it compared against the rank-probe producer, not the index-lift row, so no baseline row changed (baseline row not replaced: paired run against the index-lift row pending) and Figure 1 was not re-rendered. Also on 2026-10-19 the rotation-key producer (`koblitz-n83-rotkey-20261019`, run 39299176306) was recorded as not promoted (frozen primary not_separated against the rank-probe producer, 0.9983 [0.9701, 1.0227]); no baseline row changed and Figure 1 was not re-rendered. Also on 2026-10-20 the closure + index-lift producer (`koblitz-n83-closure-indexlift-20261019`, run 39335956567) replaced the index-lift producer's n=83 baseline row (end-to-end cold 7.6558 [7.2192, 8.1103] over the index-lift row, wall time on one host class, rank stage 143.7 s -> 4.01 s, factor-base construction charged to no arm); it also supersedes the closure's earlier comparison against the rank-probe producer (run 39305259093), and Figure 1 was re-rendered. Also on 2026-10-19 a separately labelled reference row was added for the known-log base (`koblitz-n83-knownlog-20261019`, run 39307634508: end-to-end cold 2.19 [1.86, 2.59] over rT770, above rho); it has no relations, is not an IC improvement, does not replace the n=83 baseline, and Figure 1 (baseline rows only) is unchanged. Also on 2026-10-19 the online-frame experiment (`koblitz-n83-onlineframe-20261019`, run 39303742695) was recorded as a stage improvement over the rank-probe producer (online cS / cF 1.5733 [1.5714, 1.5753], 64 points, wall time on one host class, probes and root calls unchanged) in Other verified records and the ratchet history; the n=83 baseline row was not changed (it stacks with the index lift and the closure, combined run pending), and Figure 1 is unchanged. Also on 2026-10-20 the index-build producer (`koblitz-n83-indexbuild-20261020`, run 39383739494, Tier 1 repeated alternating pairs) replaced the closure + index-lift producer's n=83 baseline row (end-to-end cold 1.7406 [1.7129, 1.7676] over 36 alternating pairs, wall time on one host class, root-index build 17,084.8 -> 7,247.2 ms, rank stage and online unchanged, factor-base construction charged to no arm); the superseded row, with its Tier 1 qualification from run 39359922687, moved to Other verified records, and Figure 1 was re-rendered. Also on 2026-10-20 the round-2 index-build producer (`koblitz-n83-indexbuild2-20261020`, run 39464544962, Tier 1 repeated

alternating pairs) replaced the index-build producer's n=83 baseline row (end-to-end cold 1.1169 [1.1110, 1.1231] over 36 alternating pairs, wall time on one host class, root-index build 6,501.9 -> 5,170.8 ms, rank stage and online running the same source, factor-base construction charged to no arm); the superseded row, with its Tier 1 qualification from its own promoting run 39383739494, moved to Other verified records, and Figure 1 was re-rendered. Also on 2026-10-21 the rank-finder producer (`koblitz-n83-rankfinder-20261021`, run 39527997793, Tier 1 repeated alternating pairs) replaced the round-2 index-build producer's n=83 baseline row (end-to-end cold 1.0196 [1.0147, 1.0255] over 36 alternating pairs, wall time on one host class, rank stage 1.0467 [1.0399, 1.0534], stored states, probes and root calls unchanged, factor-base construction charged to no arm); the superseded row, with its Tier 1 qualification from its own promoting run 39464544962, moved to Other verified records, and Figure 1 was re-rendered. The machine-readable twin is `baselines.json`; update both files in the same change. On 2026-10-20 the native-solve producer (run 39387473809, cold CPU B / N 141.02 [136.75, 144.95]) replaced the n=19 row, the old row moved to Other verified records, and Figure 1 was re-rendered.

## The rule this file serves

AGENTS.md, "Success criterion: iterative improvement of the index-calculus baseline" (owner, 2026-10-15; cryptanalysis#919, crypto#1908):

- **The baseline** for a curve and size is the best current verified IC pipeline. It is frozen with its protocol, receipts and end-to-end cold `S`.
- **A success** is any verified, measured improvement over that baseline on the same instances, under a protocol frozen before timing. Advance and engineering both count. Relabelling and accounting are recorded and do not count.
- **The ratchet.** A landed improvement replaces the row here, and the old row moves to the history with its delta.
- **The gap** to the matched rho, and to Bernstein–Lange (BL) where it was measured, is the distance remaining. It is not a pass/fail gate. A claim to *beat* rho still needs every reference rule: a cold `S` below the matched rho's, robust at growing `n`, independently replayed.

**How to read the numbers.**

- **One row, one experiment.** No row combines numbers from two experiments. Where an experiment did not measure a quantity, the cell says so.
- **Every gap is IC cost over the reference's cost.** Above 1 is distance still to close; below 1 means the IC is cheaper on that boundary. The sources quote the online figure the other way up (rho over IC). That figure is kept in each JSON row's `source_figure`.
- **`S` = cost / $\sqrt{\mathbf{r}}$**, in the row's own unit. The unit differs between experiments, so compare `S` inside a row only. The gaps carry no unit.
- **Setup `S` has one meaning on every row:** `s_ic_setup` = `s_ic_cold` - `s_ic_online`: the reusable work for the first target that the row's experiment charged, the relation-collection / rank stage and the linear algebra (or the verified load of its cached table) included, less every phase the JSON row names in `uncharged_phases`. Only n=41–61 (rule v3, which builds the factor base inside setup) charge all reusable work. Both n=83 rows leave out factor-base construction (the K600 base is loaded from a file); B's row also leaves out its linear algebra (51.3 ms) and setup input control (32.3 ms), 0.015% of its P_IC. n=19 has no setup `S`. Where the rank stage is timed on its own (n=83), the JSON row also splits it into `s_ic_rank_stage` + `s_ic_setup_without_rank_stage`. "Cold without the rank stage" is a different quantity and is never written into `s_ic_setup`.
- **Tuned rho** means rT770: A's tuned `StrongRhoG` (Fold field kernel, 64 lanes, DP 6, escape off). `koblitz-n83-reconcile-20261014` found it to be the fastest correct n=83 reference. At n=41–61 it has been run as rT770's configuration on the one-word kernel (`koblitz-s23-tuned-rho-20261015`). ParallelRho, inside crypto's `ic price`, is crypto's own signed-Frobenius walk (64 lanes in lockstep). It is the matched rho at n=41–61, but it is not rT770.

## The baselines

| n | curve | current best verified IC pipeline (commit; protocol) | targets | S cold / online (IC) | S cold / online (rho) | cold gap, IC / rho [95%] | online gap, IC / rho [95%] | gap to tuned rho (rT770) | gap to BL (online, IC / BL) | evidence tier | next improvement to try |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 19 | E0 / GF(2^19), a=1 | volcano-ic tau-orbit dim-6 base with the per-shift Groebner solve in native code (arm N: `tauDlp` with `tauRelationNative`; base, shifts, relations and linear algebra are the tau6 arm's; candidate `IC1N19Ckb0fb1064PDP2nativeenum2RC3aNpTeLAkernelTDpdpISO0h6952f30ce00e`); cryptanalysis `4ef371544` (workflow-only fix over the frozen `92d85f14`); `volcano-n19-native-tau6-v3-20261020/protocol.json` (sha256 `db9089bb...`); run 39387473809 | 20 new held-out scalars, 60 alternating B/N pairs (3 per point), +60 N/Naa and 2B/C pairs, 20 rho processes | 31.42 / 21.40 (CPU in this run's rho group operation, 3.0095e-5 s; setup 10.02) | 0.2661 / not separable | **117.9** [113.4, 122.6] (CPU, geometric mean of 60 pairs; the previous row read 1.94e4 in another run, host and unit) | not computed: online S 21.40 against the rho's 0.2661 cold is about 80 (point estimates, no interval) | none; the matched rho is a signed-Frobenius walk at 0.997x the floor in steps, run in Python/Sage, not tuned for wall time | none | Tier 1 (one GitHub-hosted Hyper-V runner, AMD EPYC 9V74, one pinned vCPU, CPU only; cold B/N 141.02 [136.75, 144.95], A/A 1.0003, planted 140.8 [136.6, 144.6], 24/24 gates; not replayed) | The Groebner solve is 15.4% of N's cold CPU; setup is 31.9% and the rest of the online stage 52.7%. Move those out of Sage and re-run against the same rho arm |
| 41 | K_0 / GF(2^41) | `ic price --single-target` at IC programme baseline v3: 6,560 points, 80 columns, aimed m=3 collection, m=2 pair-table descent; crypto `995ea207`; rule v3 | 64 public points, 1 process each, +4 A/A | 11.17 / 0.121 | 1.459 / 1.318 | **7.66** [6.90, 8.61] | 0.092 [0.071, 0.116] | **measured in a separate experiment, not combined**: see the 41 row of Other verified records (run 38777903922: online IC/tuned 0.09, cold 6.6); the matched rho in this row is ParallelRho (0.56× the strong walk's ns/step) | model only: 2.21 | crypto isolated_bench container | Setup is 98.9% of cold S: cut the reusable setup at fixed recipe, as a new IC programme round against v3 |
| 53 | K_0 / GF(2^53) | same pipeline, 27,984 points, 264 columns; crypto `995ea207`; rule v3 | 64 + 4 A/A | 16.98 / 0.058 | 1.282 / 1.236 | **13.2** [11.8, 15.0] | 0.047 [0.036, 0.059] | **measured in a separate experiment, not combined**: see the 53 row below (online 0.0423, cold 10.6); ParallelRho here is 0.53× strong | model only: 1.77 | crypto isolated_bench container | Setup is 99.7% of cold S: cut it at fixed recipe; then price the n=53 representative-plus-Frobenius orbit domain as its replacement |
| 61 | K_0 / GF(2^61) | same pipeline, 39,040 points, 320 columns; crypto `995ea207`; rule v3 | 64 + 4 A/A | 24.93 / 0.079 | 1.189 / 1.168 | **21.0** [18.6, 23.8] | 0.067 [0.051, 0.088] | **measured in a separate experiment, not combined**: see the 61 row below (online 0.0687, cold 18.9); ParallelRho here is 0.50× strong | model only: 3.52 | crypto isolated_bench container | Setup is 99.7% of cold S, and the cold gap grows as r^0.18: cut the setup; price the compact-orbit K=500 producer on these 64 points |

| n | curve | current best verified IC pipeline (commit; protocol) | targets | S cold / online (IC) | S cold / online (rho) | cold gap, IC / rho [95%] | online gap, IC / rho [95%] | gap to tuned rho (rT770) | gap to BL (online, IC / BL) | evidence tier | next improvement to try |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 83 | K_1 / GF(2^83) | the rank-finder producer (arms cM38RF / kM38RF; secondary cM10RF): the round-2 index-build producer (arms cM38IC / kM38IC, the previous row) with the rank stage's probe loop computing its probe keys with round 2's linear run finder, eight keys in lock step (`KIC_RANK_SOLVE=frame`; `rank_probe_pipeline linear_canon_lanes8`), instead of lift_scan per key, exact: every probe key, probe count, relation, root call, counter and rank table equals the previous row's per rank seed (gated per process), and every other stage, the index and its layout digests included, is the previous row's code (6 counted, invertible edits of the derived source `4008a47a...`, derived source `301615b3...`, binary `ic_online_rankfinder_r770`; candidate ID below is the previous row's: same base and recipe, no new IC1 manifest); crypto `770f6a69`; `koblitz-n83-rankfinder-20261021/protocol.json` (sha256 `3209eee1...`) at cryptanalysis `69d48f86`; run 39527997793 | 12 new public points (3 alternating primary pairs each, 36 pairs; 2 A/A pairs and 1 planted pair per point), rank blocks 36 of kM38IC and 72 of kM38RF (16 attempts, seeds 1801-1836; 24 A/A, 12 planted at control seed 7), Q0 | 0.4466 / 0.009735 (wall time in rT770 steps, 175.95 ns, one host class; setup 0.4368, of which rank stage 0.1723; factor-base construction not charged, so cold is a lower bound; measured X = 0.43 s gives 0.473, illustrative) | 0.1138 / 0.1044 | **3.924** (end-to-end cold: rank stage + setup + online; point estimate, no interval computed in this run; the previous row's arms in the same run read 4.001, but the previous row as landed read 4.416 in its own run: a cross-run artifact of host class and rT770 step, see the notes; wall time, one host; section 5a band not computable) | 0.0933 (point estimate; the previous row's arms in the same run read 0.0935: online code unchanged) | **measured on this row**: end-to-end cold 3.924, online 0.0933 (point estimates, one run) | not measured on this row (B's 235 [61, 645] is in Other verified records) | Tier 1 (GitHub runner, one pinned CPU, CPU-only), **qualified in the promoting run** (repeated alternating pairs, run 39527997793: 1.0196 [1.0147, 1.0255] over 36 alternating pairs, A/A 0.9998 and 0.9982, planted rank stage 1.8688 [1.8541, 1.8845], 282/282 rows valid; instance scope, no host-wide exclusivity; not replayed on another host class | The cold path is still 4.47 s of the 7.27 s end-to-end cold cost (61.4%): setup 4.31 s, of which the root-index build is 3.25 s and the self-test 0.84 s; the rank stage is 2.81 s (38.6%). Cut the remaining index build, the self-test, then the rest of the rank stage and the 3 probes per relation; K899 is not combined yet; re-run the BL arm on this producer |

*Figure 1. The baseline rows' gaps on a log scale: cold and online to the matched rho, and online to Bernstein–Lange (a model; the one measured n=83 BL gap is in B's row, now under Other verified records). Each row is one experiment. Bars are 95% intervals where the source gives one (the n=83 gaps are point estimates: the promoting run computed no interval for them) (source, vector).*

**Curves and candidates.**

| n | curve ID | ICV1 slug | r | IC1 candidate of the baseline |
|---|---|---|---|---|
| 19 | `EC1N19Ckb1h01617b86df6c` | (volcano-ic surface curve E0) | 130,873 | none recorded |
| 41 | `EC1N41Ce0he09550ab560a` | `icv1-f2m41-tm2308219-7f48b14a` | 549,756,390,943 | `IC1N41Ckb0fb6560PDP3pairtableRCaimedLAsparseTDwalkISO0h5b25909970b3` |
| 53 | `EC1N53Ce0hb097de99be9a` | `icv1-f2m53-tm56619371-dac20a85` | 21,044,858,204,113 | `IC1N53Ckb0fb27984PDP3pairtableRCaimedLAsparseTDwalkISO0h715dd7692112` |
| 61 | `EC1N61Ce0hd8c15448081e` | `icv1-f2m61-t158598901-ab42b6c5` | 162,888,033,982,417 | `IC1N61Ckb0fb39040PDP3pairtableRCaimedLAsparseTDwalkISO0he9352435e473` |
| 83 | `EC1N83Ce1h35c7ced6b497` | `icv1-f2m83-t6151469093347-9eba6cd5` | 8,569,786,107,849,059 | `IC1N83Ckb1fb99600PDP4s3rootindexRCguidedLAdenseTDsingleISO0hc0ecc1fffbd7` |

**Notes on the rows.**

- **n=19.** The S unit is one rho group operation of CPU time in the promoting run (3.0095e-5 s on its AMD EPYC 9V74 host; the previous row's 2.17e-5 s was another host, so the two S are not compared). The IC's cold S is the native-solve arm's CPU per ECDLP in that unit, with setup (10.02) and online (21.40) timed





Figure 1: Distance to the matched rho and to Bernstein–Lange, per baseline row.

apart. The same run measured the previous pipeline (arm B) at cold 4,429.3, which is 141.02 [136.75, 144.95] times N's CPU in the 60 alternating pairs. The rho is Python/Sage and not wall-time tuned, so the gap of 117.9 is a native IC against a non-native rho.

- **n=41–61.** The unit is one batched affine addition, measured in each row's own process. v3's unit is 2.3–3.2× cheaper than §23's, so `S` is not compared across the two (rule v3 README). Every row passes `validate_claim` at `vs_rho` (68/68 per size). Both certificates were replayed outside the process, and the logarithms equal §23's.
- **n=83.** `S` is derived inside the one run (39527997793): wall ms divided by that run's measured rT770 step (175.95 ns) and by sqrt(r), so one unit is 16,288.0 ms. End-to-end cold is the mean rank stage (kM38RF, 2,806.5 ms over the 36 primary blocks of 16 attempts, 0.1723) plus the mean cold (setup 4,308.5 ms including the verified load of the cached factor-log table, 0.2645, plus online 158.6 ms, 0.009735) over the 12 points: 0.4466. Setup, rank stage included, is 0.4368 (0.17230 + 0.26452 = 0.43682); cold without the rank stage is 0.2743. The same run's previous-row arms (kM38IC + cM38IC, the former row) read 0.4553 (rank stage 0.1803, cold without rank 0.2750). BL was not run on this producer.
  - *Wall time, one host class.* The headline 1.0196 and every `S` are wall time from one run on one GitHub runner, not operation counts. The index is unchanged (one layout-digest set per base, equal to the frozen values), and per rank seed every relation, probe vector, root call and counter is equal across kM38IC, kM38RF, kM38RFaa and kM38RFX. The saving is the rank stage, 2,937.5 -> 2,806.5 ms (1.0467 [1.0399, 1.0534], a labelled stage ratio; 99.14 -> 94.53 ns per probe; 91.8% of the 142.6 ms end-to-end saving). The cold path is unchanged code and every cold-path interval contains 1: setup 1.0026 [0.9962, 1.0099], index build 1.0031 [0.9956, 1.0116], self-test 0.9967 [0.9882, 1.0063], cold 1.0026 [0.9961, 1.0100], online 1.0030 [0.9970, 1.0113]. The probe law is the same for both arms (1.0892, gate band 0.80-1.20, pass; the smoke on 3 seeds read 1.30). Controls: A/A end to end 0.9998 [0.9955, 1.0040], A/A cold 0.9982 [0.9928, 1.0036], planted rank stage kM38RFX / kM38RF 1.8688 [1.8541, 1.8845] (12,853,712 rank-stage inputs checked per planted process, frozen rank table kept).
  - *Small effect.* 1.0196 is below the design's minimal effect of interest (1.03) and its modelled 1.066; the rank-stage ratio read 1.0467 against a modelled 1.204 (the profile was taken on the shared cloud-agent VM, this host is an AMD EPYC 9V45; the cause is not tested). The frozen rule's verdict is improvement. Per-pair spread: 0.9894 to 1.0547 (median 1.0185), one pair below 1; order effect (A first 1.0159, B first 1.0233) 0.73%.
  - *Uncharged phase.* Factor-base construction is charged to no arm (the K600 base and each closure header are loaded from file; common to the arms, so R > 1 holds for any X; 1.0196 is an upper bound and cold `S` 0.4466 a lower bound). At the X measured on another host class (427.5 ms, K600 base) the every-phase figures are R 1.0185 and cold `S` 0.4728: illustrative, mixing two hosts.
  - *Section 5a band.* Not computable: the IC arms emit no group additions, scalar multiplications, canonicalizations, fold rotations or index inserts.
  - *Replication.* The run is itself a Tier 1 repeated-alternating-pair measurement (36 pairs, instance scope; isolation gaps in the experiment's README: no host-wide exclusivity, SMT sibling not excluded, microcode unreadable, frequency not recorded in this guest, the runner smaller than advertised, one instance). Not replayed on another host class (`verify_receipt.py` reproduces `result.json` and `result_table.md` byte for byte on a copy of the whole receipt directory).
  - *Not comparable across runs (cross-run rho-gap artifact).* This run's rT770 step (175.95 ns), runner (an AMD EPYC 9V45 with AVX-512 exposed) and online mean (158.6 ms) differ from run 39464544962's (275.04 ns, an Intel Xeon Platinum 8370C, 332.4 ms), so the row's `S` and gaps are not a delta of the round-2 row. The previous row as landed read gap 4.416 and online 0.1422; its arms read 4.001 and 0.0935 in this run. The landed-to-new drop (4.416 to 3.924, 1.13x) therefore overstates the change: only the paired ratio and the paired within-run gaps (the former arms 4.001 [point estimate] to 3.924, online 0.0935 to 0.0933) are a delta.
- **n=83, the round-2 index-build producer (Other verified records).** `S` is derived inside the one run (39464544962): wall ms divided by that run's measured rT770 step (275.04 ns) and by sqrt(r), so one unit is 25,460.9 ms. End-to-end cold is the mean rank stage (kM38IC, 4,216.1 ms over the 36 primary blocks of 16 attempts, 0.1656) plus the mean cold (setup 6,989.0 ms including the verified load of the cached factor-log table, 0.2745, plus online 332.4 ms, 0.01305) over the 12 points: 0.4531. Setup, rank stage included, is 0.4401 (0.16559 + 0.27450 = 0.44009); cold without the rank stage is 0.2876. The same run's previous-row arms (kM38IB + cM38IB, the former row) read 0.5061 (rank stage 0.1664, cold without rank 0.3398). BL was not run on this producer.
  - *Wall time, one host class.* The headline 1.1169 and every `S` are wall time from one run on one GitHub runner, not operation counts. The index is unchanged (one layout-digest set per base, equal to the frozen values), and per rank seed every relation, probe vector, root call and counter is equal across kM38IB, kM38IC and kM38ICaa. The saving is the root-index build, 6,501.9 -> 5,170.8 ms (1.2574 [1.2563, 1.2586]; 98.7% of the 1,348.8 ms end-to-end saving), setup 1.1898 [1.1844, 1.1954], cold 1.1816 [1.1746, 1.1891]. The self-test is unchanged (0.9979 [0.9750, 1.0214]). The rank stage (1.0046 [1.0033, 1.0059]; 148.59 and 147.95 ns per probe) and online (1.0082 [1.0068, 1.0098]) run the same source in both arms: their intervals exclude 1 by under 1%, an offset this run does not explain and that is not a gate; with both set to 1 the ratio would be 1.1148. The probe law is the same for both arms (1.0479, gate band 0.80-1.20, pass). Controls: A/A end to end 0.9996 [0.9968, 1.0024], A/A cold 0.9993 [0.9953, 1.0036], planted index build cM38ICX / cM38IC 2.5856 [2.5830, 2.5883]

(30,682,720 roots checked, frozen layout kept).
  - *Uncharged phase.* Factor-base construction is charged to no arm (the K600 base and each closure header are loaded from file; common to the arms, so R > 1 holds for any X; 1.1169 is an upper bound and cold `S` 0.4531 a lower bound). At the X measured on another host class (427.5 ms, K600 base) the every-phase figures are R 1.1127 and cold `S` 0.4699: illustrative, mixing two hosts.
  - *Section 5a band.* Not computable: the IC arms emit no group additions, scalar multiplications, canonicalizations, fold rotations or index inserts.
  - *Replication.* The run is itself a Tier 1 repeated-alternating-pair measurement (36 pairs, instance scope; isolation gaps in the experiment's README). Not replayed on another host class (`verify_receipt.py` reproduces `result.json` and `result_table.md` byte for byte on a copy of the whole receipt directory).
  - *Not comparable across runs (cross-run rho-gap artifact).* This run's rT770 step (275.04 ns), runner (an Intel Xeon Platinum 8370C with AVX-512 exposed) and online mean (332.4 ms) differ from run 39383739494's (317.40 ns, an AMD EPYC 9V74 without AVX-512, 586.7 ms), so the row's `S` and gaps are not a delta of the index-build row. The previous row as landed read gap 4.158 and online 0.1845; its arms read 4.933 and 0.1434 in this run. The new row's 4.416 is therefore numerically larger than the old row's landed 4.158 although it is the faster producer: only the paired ratio and the paired within-run gaps (the former arms 4.933 [point estimate] to 4.416, online 0.1434 to 0.1422) are a delta.
- **n=83, the index-build producer (Other verified records).** `S` is derived inside the one run (39383739494): wall ms divided by that run's measured rT770 step (317.40 ns) and by sqrt(r), so one unit is 29,382.9 ms. End-to-end cold is the mean rank stage (kM38IB, 4,429.9 ms over 36 blocks of 16 attempts, 0.1508) plus the mean cold (setup 9,195.0 ms including the verified load of the cached factor-log table, 0.3129, plus online 586.7 ms, 0.01997) over the 12 points: 0.4837. Setup, rank stage included, is 0.4637 (0.15076 + 0.31294 = 0.46370); cold without the rank stage is 0.3329. The same run's previous-row arms (kM38I + cM38I, the former row) read 0.8419 (rank stage 0.1509, cold without rank 0.6910). BL was not run on this producer.
  - *Wall time, one host class.* The headline 1.7406 and every `S` are wall time from one run on one GitHub runner, not operation counts. The index is unchanged (one layout-digest set per base, equal to the frozen values), and per rank seed every relation, probe vector, root call and counter is equal across kM38I, kM38IB and kM38IBaa. The saving is the cold path: root-index build 17,084.8 -> 7,247.2 ms (2.3574 [2.3539, 2.3611]), self-test 2,233.6 -> 1,531.6 ms (1.4583 [1.4480, 1.4708]), setup 2.1446 [2.1404, 2.1493], cold 2.0756 [2.0299, 2.1139]. The rank stage is unchanged (1.0008 [0.9982, 1.0032]; 164.02 and 163.94 ns per probe) with the same probe law (0.9937 for both arms, gate band 0.80-1.20, pass), and online is unchanged (0.9947 [0.9888, 1.0006]). Controls: A/A end to end 0.9998 [0.9984, 1.0011], A/A cold 0.9994 [0.9977, 1.0010], planted index build cM38IBX / cM38IB 2.0847 [2.0812, 2.0876] (30,682,720 roots checked, frozen layout kept).
  - *Uncharged phase.* Factor-base construction is charged to no arm (the K600 base and each closure header are loaded from file; common to the arms, so R > 1 holds for any X; 1.7406 is an upper bound and cold `S` 0.4837 a lower bound). At the X measured on another host class (427.5 ms, K600 base) the every-phase figures are R 1.7190 and cold `S` 0.4982: illustrative, mixing two hosts.
  - *Section 5a band.* Not computable: the IC arms emit no group additions, scalar multiplications, canonicalizations, fold rotations or index inserts.
  - *Replication.* The run is itself a Tier 1 repeated-alternating-pair measurement (36 pairs, instance scope; isolation gaps in the experiment's README). Not replayed on another host class (`verify_receipt.py` reproduces `result.json` byte for byte on a copy of the whole receipt directory).
  - *Not comparable across runs.* This run's rT770 step (317.40 ns), runner (no AVX-512 exposed, transparent hugepages `always`) and online mean (586.7 ms) differ from run 39335956567's (281.09 ns, 257.9 ms) and from run 39359922687's (246.64 ns), so the row's `S` and gaps, including the online gap 0.1845 against the former row's 0.0925, are not a delta of the closure + index-lift row. The paired ratio and the paired within-run gaps (the former arms 7.238 [point estimate] to 4.158, online 0.1836 to 0.1845) are.
- **n=83, the closure + index-lift producer (Other verified records).** `S` is derived inside the one run (39335956567): wall ms divided by that run's measured rT770 step (281.09 ns) and by sqrt(r), so one unit is 26,021.1 ms. End-to-end cold is the mean rank stage (kM38I, 4,010.5 ms over 16 blocks of 16 attempts, 0.1541) plus the mean cold (setup 16,698.9 ms including the verified load of the cached factor-log table, 0.6417, plus online 257.9 ms, 0.0099) over the 20 points: 0.8058. Setup, rank stage included, is 0.7959 (0.15413 + 0.64175 = 0.79587); cold without the rank stage is 0.6517. The same run's baseline arm (kPI + cPI, the former row) reads 6.1689 (rank stage 5.5217). BL was not run on this producer.
  - *Wall time, one host class.* The headline 7.6558 and every `S` are wall time from one run on one GitHub runner, not operation counts. The index is unchanged (one layout-digest pair per base, equal to the frozen values; for K600 index-lift's `d8cfe443...` / `5f53764e...`); the saving is the rank stage, 600 attempts -> 16 (143,681.3 ms -> 4,010.5 ms, 35.83x), at the same per-probe wall time (142.55 ns kPI, 143.08 ns kM38I) and the same probe law (kM38I 1.0304 [0.8728, 1.1825], gate band 0.80-1.20, pass). The cold path is not improved: cPI / cM38I cold without rank 0.9931 [0.9837, 1.0035], setup 0.9830, index build 0.9753, online 1.6445 [1.0217, 2.7261]. Controls: A/A end to end 1.0001 [0.9979, 1.0023], A/A cold 1.0006 [0.9979, 1.0032], planted kM38IX / kM38I per attempt 1.9607 [1.9470, 1.9747]. Secondary M10I (60 columns): kPI+cPI / kM10I+cM10I 4.9504 [4.5846, 5.3402]; kM10I+cM10I / kM38I+cM38I 1.5465 [1.4482,

1.6520].
  - *Uncharged phase.* Factor-base construction is charged to no arm (the closure header's images alpha(R_c) included; common to the arms, so R > 1 holds for any X; 7.6558 is an upper bound and cold `S` 0.8058 a lower bound). At the X measured on another host class (427.5 ms, K600 base) the every-phase figures are R 7.5226 and cold `S` 0.8222: illustrative, mixing two hosts.
  - *Section 5a band.* Not computable: the IC arms emit no group additions, scalar multiplications, canonicalizations, fold rotations or index inserts.
  - *Replication.* Not replayed on another host class (`verify_receipt.py` reproduces `result.json` byte for byte on a copy of the whole receipt directory).
  - *Not comparable across runs.* This run's rT770 step (281.09 ns), kPI rank stage (143.7 s) and online mean differ from run 39290913632's (280.33 ns, 148.4 s, 392.3 ms), so the row's `S` and gap are not a delta of the index-lift row; the paired ratio and the paired within-run gaps (kPI + cPI 52.5 [44.0, 63.5] to kM38I + cM38I 6.86 [5.80, 8.19]) are.
- **n=83, the index-lift producer (Other verified records).** `S` is derived inside the one run (39290913632): wall ms divided by that run's measured rT770 step (280.33 ns) and by sqrt(r), so one unit is 25,950.6 ms. End-to-end cold is the shared rank stage K (148,384.4 ms, the mean over three rank blocks of the mean of kP and kPI; 5.718, 5.71795 unrounded) plus the mean cold (setup 16,420.2 ms including the verified load of the cached factor-log table, 0.6327, plus online 392.3 ms, 0.0151) over the 20 points: 6.366. Setup, rank stage included, is 6.351 (5.71795 + 0.63275 = 6.35069); cold without the rank stage is 0.6479. BL was not run on this producer.
  - *Wall time, one host class.* The headline 1.0344 and every `S` are wall time from one run on one GitHub runner, not operation counts. The stored states and the table slot array are byte-identical (stored-state blake3 `d8cfe443...` and table-slot blake3 `5f53764e...` in all 110 IC processes, equal to the frozen values), and every relation, per-attempt probe count (mean 1,746,508), root-call total and point-addition counter is equal across kP and kPI, so the operation counts did not change. The saving is index-build wall time (19,778.4 ms against 14,106.3 ms, 1.4021 [1.4004, 1.4036]); the planted control cPIX (every root keyed by lift_scan and checked against the selected canonicalizer, 29,880,600 roots, no difference) costs 1,184.6 ms more than cP. The rank stage is shared, not a treatment: kPI / kP per attempt 0.9981 [0.9966, 0.9994].
  - *Uncharged phase.* Factor-base construction is charged to neither arm (common to both, so R > 1 holds for any X; 1.0344 is an upper bound and cold `S` 6.366 a lower bound). At the X measured on another host class (427.5 ms) the every-phase figures are R 1.0343 and cold `S` 6.382: illustrative, mixing two hosts.
  - *§5a band.* Not computable: the IC arms emit no group additions, scalar multiplications, canonicalizations, fold rotations or index inserts.
  - *Replication.* Not replayed on another host class. The stacked row's replay found the per-probe wall ratio host-dependent, and index-build wall time has not been replayed either, so the same caution applies to 1.0344.
  - *Not comparable across runs.* This run's rT770 step (280.33 ns), shared rank stage (148.4 s) and online mean (392.3 ms) differ from run 39214027289's (280.64 ns, 143.7 s, 303.8 ms), so the row's `S` and gap are not a delta of the rank-probe row; the paired ratio and the paired within-run gaps (cP 65.1 [53.9, 81.0] to cPI 62.9 [52.5, 78.5]) are.
- **n=83, the rank-probe producer (Other verified records).** `S` is derived inside the one run (39214027289): wall ms divided by that run's measured rT770 step (280.64 ns) and by $\sqrt{r}$, so one unit is 25,980.1 ms. End-to-end cold is the mean rank stage (143,706.7 ms over four rank blocks, 5.531; 5.53141 unrounded) plus the mean cold (setup 21,995.0 ms including the verified load of the cached factor-log table, 0.8466, plus online 303.8 ms, 0.0117) over the 20 points: 6.390. Setup, rank stage included, is 6.378 (5.53141 + 0.84661 = 6.37802); cold without the rank stage is 0.8583. BL was not run on this producer.
  - *Wall time, one host class.* The headline 1.1033 and every `S` are wall time from one run on one GitHub runner, not operation counts. The operation counts did not change: the gates make every relation, per-attempt probe count (mean 1,690,645), root-call total and point-addition counter equal across kR, kP, kPaa and kPX, so the operation-count ratio is 1.0000. The rank-stage wall ratio 1.1193 is entirely per-probe wall time (158.45 ns against 141.54 on this host): the conjugate root's candidates computed in the target's Frobenius frame instead of mapped between the normal and polynomial bases twice. The planted control (278.82 ns per probe) prices the removed work at about 137 ns per probe.
  - *Uncharged phase.* Factor-base construction is charged to neither arm (common to both, so R > 1 holds for any X; 1.1033 is an upper bound and cold `S` 6.390 a lower bound). At the X measured on another host class (427.5 ms) the every-phase figures are R 1.1030 and cold `S` 6.406: illustrative, mixing two hosts.
  - *§5a band.* Not computable: the IC arms emit no group additions, scalar multiplications, canonicalizations, fold rotations or index inserts.
  - *Replication.* Not replayed on another host class. The stacked row's replay found the per-probe wall ratio host-dependent, and the same caution applies to 1.1033.
- **n=83, the rank-cut producer (Other verified records).** `S` is derived inside the one run (38891404048): wall ms divided by that run's measured rT770 step (281.01 ns) and by $\sqrt{r}$, so one unit is 26,013.6 ms. End-to-end cold is the mean rank stage (173,150.9 ms over four rank blocks, 6.656; 6.65617 unrounded) plus the mean cold (setup 22,245.8 ms including the verified load of the cached factor-log table, 0.8552, plus online 297.9 ms, 0.0115) over the 20 points: 7.523. Setup, rank

stage included, is 7.511 (6.65617 + 0.85516 = 7.51133); cold without the rank stage is 0.8666. BL was not run on this producer.

- *Wall time, one host class.* The headline 1.3336 and every `S` are wall time from one run on one GitHub runner, not operation counts. The operation counts did not change: the gates make every relation, per-attempt probe count (mean 1,790,030) and root-call total equal across kS, kR, kRaa and kRX, so the operation-count ratio is 1.0000. The rank-stage wall ratio 1.3768 is entirely per-probe wall time (221.85 ns against 161.10 on this host): the batched S3 root solve replaced by point addition. The planted control (302.05 ns per probe) prices the removed work at about 141 ns per probe.
- *Uncharged phase.* Factor-base construction is charged to neither arm (common to both, so R > 1 holds for any X; 1.3336 is an upper bound and cold `S` 7.523 a lower bound). At the X measured on another host class (427.5 ms) the every-phase figures are R 1.3328 and cold `S` 7.539: illustrative, mixing two hosts.
- *§5a band.* Not computable: the IC arms emit no group additions, scalar multiplications, canonicalizations, fold rotations or index inserts.
- *Replication.* Not replayed on another host class. The stacked row's replay found the per-probe wall ratio host-dependent, and the same caution applies to 1.3336.

- **n=83, the stacked producer (Other verified records).** `S` is derived inside the one run (38862448935): wall ms divided by that run's measured rT770 step (316.66 ns) and by $\sqrt{r}$, so one unit is 29,314.2 ms. End-to-end cold is the mean rank stage (257,814.3 ms over two rank processes, 8.795; 8.79486 unrounded) plus the mean cold (setup 25,575.2 ms including the verified load of the cached factor-log table, 0.8725, plus online 385.1 ms, 0.0131) over the 20 points: 9.680. Setup, rank stage included, is 9.667 (8.79486 + 0.87245 = 9.66731; each `S` is rounded once from its unrounded quotient, so rounded parts need not add up exactly); cold without the rank stage is 0.8856. The row first landed with `s_ic_setup` 0.8856, the cold-without-rank figure; read against B's 32.848 (rank stage included) that looked like a 37× setup drop, which was accounting (corrected 2026-10-16, `corrections` in the JSON). BL was not run on the stack.
  - *Wall time, one host class.* The headline 3.2391 and every `S` are wall time from one run on one GitHub runner (AMD EPYC 9V74, one pinned CPU, CPU-only), not operation counts. The host-independent part is the rank stage's operation counts: probes 2,976,293,514 (kP) against 2,014,683,345 (kS) and root calls 1,488,248,100 against 1,007,441,716, both 1.4773x fewer. The rank-stage wall ratio 3.3737 is that 1.4773 times 2.2837 in wall ns per probe (584.48 against 255.94), measured on this host only. That factor is per-probe wall time, not host speed: a kP probe (full canonicalization) and a kS probe (lift_scan, compact table, prefetch loop) are not the same work, so it mixes cheaper per-probe work with host and memory-system effects. Stored index states halve (29,880,000 to 14,940,300); online probes are equal (cP / cS 1.000133). Setup and index build emit no comparable count, so there is no single end-to-end operation-count ratio.
  - *Uncharged phase.* Factor-base construction is charged to neither arm: every process loads the K600 base from a file. It is common to both arms, so the ratio stays above 1 for any construction cost X, but 3.2391 is an upper bound and cold `S` 9.680 a lower bound on the every-phase figures (X = 1 s: 3.231 and 9.715; 10 s: 3.163 and 10.02; 60 s: 2.848 and 11.73). **X measured (2026-10-17):** one cold in-process construction (`construct:83:1:600`, base hash equal to the retained file's) took X = 427.524 ms in the replay below, 65.541 ms more than loading the retained file on the same host (361.984 ms). At that X the every-phase figures are R 3.2357 and cold `S` 9.6950 (gap 94.56): illustrative, since X is from the Intel replay host and the rest from the EPYC run. The bounds 3.2391 and 9.680 are within 0.11% and 0.15%.
  - *§5a band.* Not computable from this run: the IC arms emit no group additions, scalar multiplications, canonicalizations, fold rotations or index inserts, so the gap 94.4 has no 0 / 0.1 / 1 GAE band and holds as a wall-time figure on this host only.
  - *Replication.* Rank block K1 was replayed on another host class on 2026-10-17: run 39007026856 on an INTEL(R) XEON(R) PLATINUM 8573C (the original: AMD EPYC 9V74; same image, kernel, toolchain and binary sha256), under the protocol frozen at `863f6090` (`experiments/koblitz-n83-replay-20261017/PROTOCOL` archived in `RESULTS.md` there). Verdict `replay_pass`: all six runs valid; kS, kP, kP, kS reproduce every per-attempt probe count (first 100 and all 600) and the relation digest of the archived K1 records; the constructed base equals the retained one. Not gated: the per-probe wall ratio kP / kS is 2.6583 there (first 100 attempts 2.7013) against 2.2905 for K1 on the EPYC (2.2837 both blocks), so the 3.24x wall-time headline is host-dependent, while the operation-count ratio 1.4773 stands. The replay did not re-measure the cold arms, so it gives no new R or `S`; one replay, one other host class, two processes per arm. It emits no group-operation counts, so the §5a band stays uncomputable (Open).
- **n=83, B (Other verified records).** `S` in B's run is wall ms over that run's rT770 step (180.8 ns) and $\sqrt{r}$. Cold is the matched precomputation P_IC (520,825 ms rank stage + 29,022 ms per-process setup; `s_ic_setup` 32.848 = 31.114 + 1.734) plus the mean online time. P_IC leaves out factor-base construction (the base is loaded from a file), the linear algebra (51.3 ms) and setup input control (32.3 ms); the JSON row names them in `uncharged_phases`. BL's precomputation was matched to P_IC in wall time on the same CPU, so the cold IC/BL ratio is 0.987 by construction. If PR #918 changes, that row changes with it.

## Other verified records

These rows are kept for context and as the history behind the baselines. None is combined with another row.

The rank-probe Bernstein-Lange record preserves its frozen point-paired estimate and reading. It is not a qualified Tier 1 speedup: the primary has one cP/BL observation per point rather than repeated alternating primary pairs. Its receipt records `child_peak_rss_kb_cumulative`, a cumulative child high-water mark, not per-process peak RSS; cgroup counters are group-level. These reporting limits do not alter the archived timing estimate.

| n | role | experiment | reference | cold gap, IC / ref [95%] | online gap, IC / ref [95%] | BL | tier |
|---|---|---|---|---|---|---|---|
| 19 | previous baseline (the tau6 arm, Sage Groebner per-shift solve), superseded by the native-solve producer | `volcano-ic/rho-arm-20261014`, run 38520305068 (cryptanalysis `3f722e2e`); the same pipeline's B arm was measured in run 39387473809: S cold 4,429.3 in that run's unit | matched signed-Frobenius rho, same scalars (S 0.2603 as landed; unit 2.17e-5 s) | 1.94e4 [1.69e4, 2.23e4] (CPU, geometric mean; S 5,154 as landed) | not measured | none | exploratory (GitHub VM, unpinned) |
| 41 | previous baseline (v0) | ledger §23, crypto `0bf67f16` | ParallelRho, same process | 8.04 [7.26, 9.01] | 0.107 [0.082, 0.135] | model 2.50 | crypto isolated_bench container |
| 53 | previous baseline (v0) | ledger §23 | ParallelRho | 14.7 [13.1, 16.7] | 0.057 [0.044, 0.073] | model 2.02 | same |
| 61 | previous baseline (v0) | ledger §23 | ParallelRho | 31.6 [28.2, 35.7] | 0.113 [0.084, 0.148] | model 8.04 | same |
| 41 | other pipeline, complete cold CPU | crypto `disjoint_cold_v2_outcome_20261001` (run 36803331080), compact-orbit K85 | 32-walk signed-Frobenius normal-basis rho (not rT770) | 13.4 [9.37, 18.5] | not measured | none | hosted, A/A and quiet-host gates, second-host replay |
| 53 | other pipeline, complete cold CPU | same, compact-orbit K220 | same | 22.7 [17.9, 31.6] | not measured | none | same |
| 61 | other pipeline | crypto autolab run `20261012T202048Z-5521627904`, compact-orbit K=500 | strong rho rung 3 (not rT770) | 83.4 (median of rows) | 0.072 [0.052, 0.102] (inverse of median 13.94) | none | taskset-pinned container with a CPU-isolation receipt |
| 41 | gap to the tuned rho (this experiment only; cf. the baseline row) | `koblitz-s23-tuned-rho-20261015`, run 38777903922 (PR #923) | tuned = rT770 configuration on the one-word kernel; same run: ParallelRho cold 7.83, strong 6.43, rA770 2.54 | **6.6** [5.91, 7.4] | **0.09** [0.0715, 0.111] | model 0.53 | Tier 1 |
| 53 | gap to the tuned rho (this experiment only; cf. the baseline row) | `koblitz-s23-tuned-rho-20261015`, run 38777903922 (PR #923) | tuned = rT770 configuration on the one-word kernel; same run: ParallelRho cold 11.8, strong 9.2, rA770 3.01 | **10.6** [9.45, 12] | **0.0423** [0.0325, 0.0534] | model 0.322 | Tier 1 |
| 61 | gap to the tuned rho (this experiment only; cf. the baseline row) | `koblitz-s23-tuned-rho-20261015`, run 38777903922 (PR #923) | tuned = rT770 configuration on the one-word kernel; same run: ParallelRho cold 19.4, strong 13.7, rA770 4.42 | **18.9** [16.7, 21.5] | **0.0687** [0.051, 0.0903] | model 0.759 | Tier 1 |
| 83 | previous baseline (B, the BL-arm row), superseded by the stacked producer | `koblitz-n83-bl-arm-20261014`, run 38689817618 (PR #918, not merged yet) | rT770, B's 16 fresh points + Q0 x4 | 360 (no interval; S 32.93 / 0.083 in that run's rT770 steps) | 1.01 [0.30, 2.12], not separated | **measured: 235** [61, 645], 16/16 points BL faster; cold IC/BL 0.987 by construction | Tier 1 |
| 83 | previous baseline (the stacked producer, arms cS / kS), superseded by the rank-cut producer | `koblitz-n83-stacked-20261016`, run 38862448935 (PR #938) | rT770, 20 new points, two rank blocks, Q0 | 94.4 [73.5, 125.3] (end-to-end cold; S 9.680 / 0.01314 in that run's rT770 steps, 316.66 ns) | 0.139 [0.077, 0.237] | none on this row | Tier 1 |
| 83 | previous baseline (the rank-cut producer, arms cR / kR), superseded by the rank-probe producer | `koblitz-n83-rankcut-20261016`, run 38891404048 (PR #970) | rT770, 20 new points, four rank blocks, Q0 | 65.7 [55.4, 80.2] (end-to-end cold; S 7.523 / 0.01145 in that run's rT770 steps, 281.01 ns) | 0.110 [0.059, 0.174] | none on this row | Tier 1 |

| n | role | experiment | reference | cold gap, IC / ref [95%] | online gap, IC / ref [95%] | BL | tier |
|---|---|---|---|---|---|---|---|
| 83 | **REFERENCE ROW, not the IC baseline and not an IC improvement**: known-log base, K220 seeded scalar orbits, no relations (LAnone) = BSGS on the Frobenius quotient. The cited DKM result is an asymptotic non-adaptive generic-DLOG time-space lower bound; it does not prove finite-instance runtime dominance over rho. One primary cL220/rT770 observation per point; not a qualified Tier 1 speedup. See `PR #986 qualification`. The owner's decision whether it may hold the IC row remains pending. | `koblitz-n83-knownlog-20261019`, run 39307634508 | rT770, 40 new points, Q0, four rank blocks for the baseline pair | **2.19** [1.86, 2.59] (end-to-end cold, known-log K220 / rT770; S 0.2303 [0.2059, 0.2577] in that run's rT770 steps; reading above rho); reference, not an IC improvement: baseline pair kP+cP / K220 27.99 [24.78, 31.53], kP+cP / K600 7.18 [6.89, 7.49] | online K220 / rT770 1.12 [0.85, 1.45] | none on this row | one-run reference; no Tier 1 speedup |
| 83 | previous baseline (the rank-probe producer, arms cP / kP), superseded by the index-lift producer | `koblitz-n83-rankprobe-20261019`, run 39214027289 (PR #980) | rT770, 20 new points, four rank blocks, Q0 | 64.0 [53.7, 78.0] (end-to-end cold; S 6.390 / 0.01169 in that run's rT770 steps, 280.64 ns) | 0.129 [0.085, 0.183] | measured later on this producer: online cP / BL 22.55 [16.23, 31.44], `bl_online_faster_than_ic`; cold IC/BL 0.985 by construction (run 39307708909). Historical instance-scoped estimate, not Tier 1 speedup-qualified | Tier 1 instance; not speedup-qualified |
| 83 | previous baseline (the index-lift producer, arms cPI / kPI), superseded by the closure + index-lift producer | `koblitz-n83-indexlift-20261019`, run 39290913632 (PR #981) | rT770, 20 new points, three rank blocks, Q0 | 62.9 [52.5, 78.5] (end-to-end cold; S 6.366 / 0.01512 in that run's rT770 steps, 280.33 ns) | 0.167 [0.091, 0.283] | none on this row | Tier 1 |
| 83 | previous baseline (the closure + index-lift producer, arms cM38I / kM38I; secondary cM10I / kM10I), superseded by the index-build producer | `koblitz-n83-closure-indexlift-20261019`, run 39335956567 (PR #997); Tier 1 qualified by run 39359922687 (PR #1002) | rT770, 20 new points, 4 and 16 rank blocks, Q0 | 6.86 [5.80, 8.19] (end-to-end cold; S 0.8058 / 0.009909 in that run's rT770 steps, 281.09 ns) | 0.0925 [0.0594, 0.1352] | none on this row | Tier 1, qualified by replication: 7.4133 [7.1999, 7.6362] over 30 alternating pairs (run 39359922687); the same arms were also the A side of run 39383739494 (7.238 over rT770 there) |

| n | role | experiment | reference | cold gap, IC / ref [95%] | online gap, IC / ref [95%] | BL | tier |
|---|---|---|---|---|---|---|---|
| 83 | previous baseline (the index-build producer, arms cM38IB / kM38IB; secondary cM10IB), superseded by the round-2 index-build producer | `koblitz-n83-indexbuild-20261020`, run 39383739494 (PR #1006) | rT770, 12 new points, 36 and 60 rank blocks, Q0 | 4.158 (end-to-end cold, point estimate; S 0.4837 / 0.01997 in that run's rT770 steps, 317.40 ns); the same arms read 4.933 as the A side of run 39464544962 (275.04 ns step, another host class) | 0.1845 | none on this row | Tier 1, qualified in its own promoting run (repeated alternating pairs): 1.7406 [1.7129, 1.7676] over 36 alternating pairs (run 39383739494) |
| 83 | previous baseline (the round-2 index-build producer, arms cM38IC / kM38IC; secondary cM10IC), superseded by the rank-finder producer | `koblitz-n83-indexbuild2-20261020`, run 39464544962 (PR #1009) | rT770, 12 new points, 36 and 60 rank blocks, Q0 | 4.416 (end-to-end cold, point estimate; S 0.4531 / 0.01305 in that run's rT770 steps, 275.04 ns); the same arms read 4.001 as the A side of run 39527997793 (175.95 ns step, another host class) | 0.1422 | none on this row | Tier 1, qualified in its own promoting run (repeated alternating pairs): 1.1169 [1.1110, 1.1231] over 36 alternating pairs (run 39464544962) |
| 83 | promoted over the rank-probe producer at K600, on the rank-probe producer's code (K899 base, arms kP899 / cP899); **baseline row not replaced** (the row names the index-lift producer; this run never ran it as a primary) | `koblitz-n83-k899-20261019`, run 39306394645 (PR pending) | rT770, 20 new points, four rank blocks (seeds 401-404), Q0 | 54.5 [45.3, 68.2] (end-to-end cold; S 5.639 / 0.008104 in that run's rT770 steps, 280.43 ns); the K600 arm in the same run reads 64.7 [53.8, 81.3] (S 6.694) | 0.087 [0.058, 0.126] (K600 arm 0.180 [0.098, 0.312]) | none on this row | Tier 1 |
| 83 | same pipeline as the baseline (merged) | `koblitz-n83-reconcile-20261014`, run 38617911080 | rT770, two seeds per point | 313 (fresh-rank setup) | 0.92 [0.28, 1.78], not separated | none | Tier 1 |
| 83 | same pipeline, first Tier 1 run | `koblitz-single-target-n83-tier1-20261014`, run 38523707244 | rung 3, slower per step than StrongRhoG, so not the matched tuned rho | 134 | 0.36 [0.11, 0.66] | model 33.5 (measured later: 235) | Tier 1 |
| 83 | promoted single improvement over B: two-limb `lift_scan` canonicalizer (this experiment only) | `koblitz-n83-liftscan-20261015`, run 38776966036 (PR #926) | rT770, B's 16 fresh points | cold not measured | IC/rho 0.67 [0.19, 1.38] (inverse of 1.4914 [0.7270, 5.1445]); online full / lift_scan 1.5152 [1.5061, 1.5247] | none | Tier 1 |
| 83 | promoted single improvement over B: Feistel scan order (this experiment only) | `koblitz-n83-scanorder-20261015`, run 38786433493 (PR #927) | rT770, B's 16 fresh points | cold not measured | IC/rho 0.291 [0.163, 0.481] (inverse of 3.4370 [2.0774, 6.1418]); online left-major / Feistel 3.4287 [1.0090, 7.4215]; held-out 384: 1.4507 [1.2023, 1.7424] | none | Tier 1 |
| 83 | **not promoted**: lift_scan x Feistel order combined (this experiment only) | `koblitz-n83-combined-20261015`, run 38803625711 | rT770, 576 new points | cold not measured | IC/rho 0.2145 [0.1949, 0.2353] (inverse of 4.6628 [4.2501, 5.1308], means); frozen primary R_m 1.2363 [1.0671, 1.4276], R_g 1.0611 [0.9083, 1.2430]: `not_separated`; combined vs B 1.9992 [1.7285, 2.3090] | none | Tier 1 |

| n | role | experiment | reference | cold gap, IC / ref [95%] | online gap, IC / ref [95%] | BL | tier |
|---|---|---|---|---|---|---|---|
| 83 | promoted improvement over the combined producer: software-pipelined, prefetched root-table probes (this experiment only) | `koblitz-n83-probepipe-20261015`, run 38822490448 | rT770, 384 new points | cold not measured | IC/rho 0.1462 [0.1307, 0.1626] (inverse of 6.8396 [6.1494, 7.6526]); combined producer 0.2047; online combined / pipeline 1.4001 [1.3971, 1.4032], probes identical | none | Tier 1 |
| 83 | promoted improvement over the probe-pipeline producer: two-level root table, 32 MiB filter + 16-byte slots (this experiment only) | `koblitz-n83-tablefilter-20261015`, run 38829449594 | rT770, 384 new points | cold not measured against rho; cold pP / pT 1.0101 [1.0090, 1.0113] | IC/rho 0.1523 [0.1358, 0.1709] (inverse of 6.5642 [5.8533, 7.3649]); pipeline 0.1620; online pP / pT 1.0633 [1.0589, 1.0679], probes identical, mostly from the 16-byte slot | none | Tier 1 |
| 83 | promoted improvement over the combined producer: folded S3 root index, cold (this experiment only) | `koblitz-n83-state-fold-20261015`, run 38819494806 | rT770, 16 new points | 6.95 [5.53, 9.01] (cB 12.77; setup + online, rank stage excluded; with the rank stage 109.6, was 243.3) | IC/rho 0.163 [0.090, 0.241]; online 5% slower; cold cB / cF 1.8372 [1.8216, 1.8528], setup 1.86×, peak RSS 1.97× | none | Tier 1 |
| 83 | promoted improvement over the rank-probe producer: Z[tau]-multiplier closure of the K600 base, M38 primary (16 columns) and M10 secondary (60 columns) (this experiment only; the comparison against the current row is superseded by the paired closure + index-lift result, run 39335956567) | `koblitz-n83-closure-20261019`, run 39305259093 | rT770, 20 new points, 16 / 4 / 8 rank blocks (kM38 / kP / kM10), Q0 | 10.5 [8.8, 12.7] (end-to-end cold kM38 + cM38; the rank-probe arm kP + cP in the same run 67.5 [56.4, 82.4]; M10 14.9 [12.2, 18.1]; S 1.115 against 7.188, rT770 step 186.55 ns; rank stage 108.0 s -> 2.75 s, 39.28x; cold without rank cP / cM38 0.9760 [0.9608, 0.9888]) | online 0.215 [0.129, 0.312] (cP 0.169; cM38 online not separated from cP, 0.7860 [0.3828, 1.4402]); primary R = E2E(kP + cP) / E2E(kM38 + cM38) 6.4444 [6.0993, 6.7853]; M10 4.5318 [4.1827, 4.8771]; factor-base construction charged to no arm | none | Tier 1 |
| 83 | **not promoted**: rotation-key probe (the rank-stage table key rotkey(v) = v^83 in F2[X]/(X^83+1) in place of lift_scan; this experiment only; baseline row not replaced) | `koblitz-n83-rotkey-20261019`, run 39299176306 | rT770, 20 new points, four rank blocks (kP, kK, kKaa, kKX), Q0 | 69.40 [52.51, 93.51] (end-to-end cold kP + cP, the rank-probe producer) against 69.51 [52.43, 93.02] (kK + cK) in the same run; S 7.453 against 7.465, rT770 step 247.87 ns; rank stage 147.4 s against 147.6 s; cold without rank cP / cK 0.9988 [0.9900, 1.0070] | online 0.1658 [0.1041, 0.2628] (cP) against 0.1701 [0.1045, 0.2720] (cK); frozen primary R = E2E(kP + cP) / E2E(kK + cK) 0.9983 [0.9701, 1.0227]: `not_separated`; A/A and planted controls pass; every gate passes (0 collisions on 29,878,182 keys); rotation-key table build 2.52 s per rank process charged to kK; factor-base construction charged to no arm | none | Tier 1 |

| n | role | experiment | reference | cold gap, IC / ref [95%] | online gap, IC / ref [95%] | BL | tier |
|---|---|---|---|---|---|---|---|
| 83 | promoted improvement over the rank-probe producer: the one-target online scan on the rank stage's frame loop, `KIC_ONLINE_SOLVE=frame` (this experiment only) | `koblitz-n83-onlineframe-20261019`, run 39303742695 | rT770, 64 new points, one shared rank stage | end-to-end cold with the shared rank stage 66.47 [58.24, 76.58] (S 6.5776; cS 66.52, S 6.5827; E2E cS / cF 1.0008 [1.0006, 1.0010]) | online 0.109 [0.079, 0.145] (cS 0.171 [0.125, 0.227]); online `S` 0.00977 (cS 0.01537); online cS / cF 1.5733 [1.5714, 1.5753], probes identical | none | Tier 1 |

## Ratchet history

| n | from | to | cold gap | online gap | class |
|---|---|---|---|---|---|
| 41 | §23 (v0, `0bf67f16`) | rule v3 (`995ea207`) | 8.04 → 7.66 | 0.107 → 0.092 | engineering (IC programme rounds R03, R05, R07) |
| 53 | §23 (v0) | rule v3 | 14.7 → 13.2 | 0.057 → 0.047 | engineering |
| 61 | §23 (v0) | rule v3 | 31.6 → 21.0 | 0.113 → 0.067 | engineering |
| 83 | B | lift_scan canonicalizer (PR #926, run 38776966036) | not measured | not measured (online 1.5152 faster, fresh 16) | engineering; promoted by its own frozen rule; baseline row not replaced (no cold `S`) |
| 83 | B | Feistel scan order (PR #927, run 38786433493) | not measured | not measured (online 1.4507 faster, held-out 384) | advance (probe count); promoted; baseline row not replaced (no cold `S`) |
| 83 | better single arm (lift_scan) | lift_scan x Feistel (run 38803625711) | not measured | R_m 1.2363 [1.0671, 1.4276]; R_g 1.0611 [0.9083, 1.2430] | **not promoted**: frozen primary `not_separated` |
| 83 | lift_scan x Feistel combined producer | software-pipelined, prefetched probes (run 38822490448) | not measured | 0.2047 → 0.1462 (online, tuned rho; 1.4001 faster) | engineering; promoted by its own frozen rule; baseline row not replaced (no cold `S`) |
| 83 | probe-pipeline producer | two-level root table (run 38829449594) | not measured | 0.1620 → 0.1523 (online, tuned rho; 1.0633 faster) | engineering; promoted by its own frozen rule; baseline row not replaced (no cold `S` against rho) |
| 83 | lift_scan x Feistel combined producer | folded S3 root index (run 38819494806) | 12.77 → 6.95 (rank stage excluded) | not improved (online 5% slower) | engineering; promoted by its own frozen rule; baseline row not replaced (rank stage still dominates cold cost) |
| 83 | pP, the probe-pipeline producer with B's rank stage (same run; this replaced B's baseline row, run 38689817618) | stacked producer: probe pipeline + 16-byte slots + folded index + rank stage (run 38862448935) | **paired, this run:** 305.8 [237.5, 403.8] → 94.4 [73.5, 125.3] (end-to-end cold, from pP with B's rank stage; 3.24× closer). Context only: B's own run read 360 (a different run, instances and step time) | **paired, this run:** 0.133 [0.072, 0.229] → 0.139 [0.077, 0.237]: online 4.6% slower in this step. Context only: B's run read 1.01 | engineering; promoted by its own frozen primary (end-to-end cold cP / cS 3.2391 [2.9809, 3.5240] in wall time on one host class, factor-base construction excluded; rank-stage probes and root calls 1.4773x fewer; 20 points, two rank blocks, against the probe-pipeline producer); **baseline row replaced**: the first measured n=83 end-to-end cold `S` after B (9.68; was 32.93 in B's run, a different step time) |

| n | from | to | cold gap | online gap | class |
|---|---|---|---|---|---|
| 83 | the stacked producer (arms kS + cS), same run 38891404048, points and rT770 (this replaced the stacked baseline row, run 38862448935) | rank-cut producer: partner roots by point addition in the rank stage (run 38891404048) | **paired, this run:** 87.6 [74.1, 107.2] → 65.7 [55.4, 80.2] (end-to-end cold; 1.33× closer). Context only: the stacked row as landed read 94.4 (a different run, instances and step time) | **paired, this run:** 0.1107 [0.0602, 0.1752] → 0.1101 [0.0590, 0.1744]: online unchanged (same code) | engineering; promoted by its own frozen primary (end-to-end cold kS+cS / kR+cR 1.3336 [1.3300, 1.3377] in wall time on one host class, factor-base construction excluded; probes and root calls unchanged, the saving is per-probe wall time 221.85 → 161.10 ns, rank stage per attempt 1.3770 [1.3735, 1.3813]; 20 points, four rank blocks, against the stacked producer); **baseline row replaced** |
| 83 | the rank-cut producer (arms kR + cR), same run 39214027289, points and rT770 (this replaced the rank-cut baseline row, run 38891404048) | rank-probe producer: the rank-cut loop in the target's Frobenius frame (run 39214027289) | **paired, this run:** 70.6 [59.3, 86.3] → 64.0 [53.7, 78.0] (end-to-end cold; 1.10× closer). Context only: the rank-cut row as landed read 65.7 (a different run, instances and step time) | **paired, this run:** 0.1288 [0.0836, 0.1816] → 0.1291 [0.0847, 0.1830]: online unchanged (same code) | engineering; promoted by its own frozen primary (end-to-end cold kR+cR / kP+cP 1.1033 [1.1010, 1.1056] in wall time on one host class, factor-base construction excluded; probes, root calls and point-addition counters unchanged, the saving is per-probe wall time 158.45 → 141.54 ns, rank stage per attempt 1.1194 [1.1175, 1.1214]; 20 points, four rank blocks, against the rank-cut producer); **baseline row replaced** |
| 83 | the rank-probe producer (arms kP + cP, shared rank stage), same run 39290913632, points and rT770 (this replaced the rank-probe baseline row, run 39214027289) | index-lift producer: lift_scan in the root-index build (run 39290913632) | **paired, this run:** 65.1 [53.9, 81.0] -> 62.9 [52.5, 78.5] (end-to-end cold; 1.03x closer). Context only: the rank-probe row as landed read 64.0 (a different run, instances, rank seeds and step time) | **paired, this run:** 0.1667 [0.0926, 0.2808] -> 0.1666 [0.0914, 0.2830]: online unchanged (same online code) | engineering; promoted by its own frozen primary (end-to-end cold cP / cPI 1.0344 [1.0324, 1.0364] with a shared rank stage, in wall time on one host class, factor-base construction excluded; stored states and table slots byte-identical, probes, root calls and counters unchanged, the saving is index-build wall time 19,778 -> 14,106 ms, cold without rank 1.3376 [1.3340, 1.3406]; 20 points, three rank blocks, against the rank-probe producer); **baseline row replaced** |
| 83 | the rank-probe producer (arms kP + cP), same run 39305259093, points and rT770 (the baseline row was NOT replaced) | closure producer (arms kM38 + cM38): Z[tau]-multiplier closure of the K600 base, 16 columns (run 39305259093) | **paired, this run:** 67.5 [56.4, 82.4] -> 10.5 [8.8, 12.7] (end-to-end cold; 6.44x closer) | **paired, this run:** 0.1689 [0.0929, 0.2612] -> 0.2149 [0.1290, 0.3123]: online not separated (cP / cM38 0.7860 [0.3828, 1.4402]) | engineering; promoted by its own frozen primary (end-to-end cold kP+cP / kM38+cM38 6.4444 [6.0993, 6.7853] in wall time on one host class, factor-base construction charged to no arm; the saving is the rank stage 108.0 s -> 2.75 s, cold without rank 0.9760 [0.9608, 0.9888]; 20 points, 16 and 4 rank blocks, against the rank-probe producer); baseline row not replaced by this run (superseded by the paired closure + index-lift result below, which replaced the row) |

| n | from | to | cold gap | online gap | class |
|---|---|---|---|---|---|
| 83 | the rank-probe producer at K600 (arms kP600 + cP600), same run 39306394645, points and rT770 | the rank-probe producer at K899, the nested 899-column base (arms kP899 + cP899; run 39306394645) | **paired, this run:** 64.7 [53.8, 81.3] -> 54.5 [45.3, 68.2] (end-to-end cold; 1.19x closer). Context only: the rank-probe row as landed read 64.0 (a different run, instances, rank seeds and step time) | **paired, this run:** 0.1803 [0.0978, 0.3116] -> 0.0870 [0.0583, 0.1265] (online; cP899 / cP600 online time 0.4825 [0.2688, 0.8733], fewer probes with more columns) | advance (a change of K; the code is unchanged); promoted by its own frozen primary (end-to-end cold kP600+cP600 / kP899+cP899 1.1873 [1.1247, 1.2523] in wall time on one host class, factor-base construction excluded; the rank stage 1.5176 [1.4149, 1.6235] faster from 2.35x fewer probes per attempt (law r / (166 E), ratios 1.026 and 0.980) at 3% more ns per probe, cold without rank 2.0766x slower, peak RSS 2.07x; 20 points, four rank blocks, power 0.16 at the diagnostic's R of 1.036 and 0.91 at 1.10, the effect was larger; A/A and planted controls pass); **baseline row not replaced**: the row on main names the index-lift producer, not the rank-probe producer, so the ratchet's condition fails and the result is recorded as promoted over the rank-probe producer. The two changes were not run together as a primary; the cPI secondary pair (K899 with lift_scan in the index build) reads kP600+cPI600 / kP899+cPI899 1.2586 [1.1888, 1.3330] and gap 49.7 [41.5, 62.1], which never decides and is not a promoted pipeline |
| 83 | the index-lift producer (arms kPI + cPI), same run 39335956567, points and rT770 (this replaced the index-lift baseline row, run 39290913632) | closure + index-lift producer: Z[tau]-multiplier closure of the K600 base, 16 columns, on the index-lift producer (arms kM38I + cM38I; run 39335956567) | **paired, this run:** 52.5 [44.0, 63.5] -> 6.86 [5.80, 8.19] (end-to-end cold; 7.66x closer). Context only: the index-lift row as landed read 62.9 (a different run, instances, rank seeds and step time) | **paired, this run:** 0.1521 [0.0980, 0.2158] -> 0.0925 [0.0594, 0.1352] (online; cPI / cM38I online time 1.6445 [1.0217, 2.7261]) | engineering; promoted by its own frozen primary (end-to-end cold kPI+cPI / kM38I+cM38I 7.6558 [7.2192, 8.1103] in wall time on one host class, factor-base construction charged to no arm; the saving is the rank stage 143.7 s -> 4.01 s, cold without rank 0.9931 [0.9837, 1.0035]; 20 points, 4 and 16 rank blocks, against the index-lift row; supersedes the closure's comparison against the rank-probe producer, run 39305259093); **baseline row replaced** |
| 83 | the rank-probe producer (arms kP + cP), same run 39299176306, points and rT770 (the baseline row was NOT replaced) | rotation-key producer (arms kK + cK): rank-stage table keyed by v^83 in F2[X]/(X^83+1), lift_scan only at a hit (run 39299176306) | 69.40 [52.51, 93.51] -> 69.51 [52.43, 93.02] (end-to-end cold, paired within run) | 0.1658 [0.1041, 0.2628] -> 0.1701 [0.1045, 0.2720] (online, not separated) | **not promoted**: frozen primary `not_separated` (end-to-end cold kP+cP / kK+cK 0.9983 [0.9701, 1.0227] in wall time on one host class; rank per attempt kP / kK 1.0156 [0.9820, 1.0450]; 20 points, four rank blocks; every gate and both controls pass); baseline row not replaced |
| 83 | the index-lift producer (arms kPI + cPI), same run 39359922687 | closure + index-lift producer: Tier 1 replication of #997 (run 39359922687, repeated alternating pairs) | 62.53 -> 8.43 (point estimates, same run) | 0.1488 -> 0.1475 (not separated) | replication; baseline row not replaced, row gains its Tier 1 qualification: 7.4133 [7.1999, 7.6362] over 30 alternating pairs |

| n | from | to | cold gap | online gap | class |
|---|---|---|---|---|---|
| 83 | the closure + index-lift producer (arms kM38I + cM38I), same run 39383739494, points and rT770 (this replaced the closure + index-lift baseline row, run 39335956567) | index-build producer: batched-inverse state loop, prefetched insert loop, lane-wise self-test, on the closure + index-lift producer (arms kM38IB + cM38IB; run 39383739494) | **paired, this run:** 7.238 -> 4.158 (point estimates, end-to-end cold; 1.74x closer). Context only: the closure + index-lift row as landed read 6.86 (a different run, instances, rank seeds and step time) | **paired, this run:** 0.1836 -> 0.1845 (point estimates; online unchanged, same online code, A / B 0.9947 [0.9888, 1.0006]) | engineering; promoted by its own frozen primary (end-to-end cold kM38I+cM38I / kM38IB+cM38IB 1.7406 [1.7129, 1.7676] over 36 alternating pairs in wall time on one host class, factor-base construction charged to no arm; stored states and table slots byte-identical, relations, probes, root calls and counters unchanged, the saving is the root-index build 17,084.8 -> 7,247.2 ms and the self-test 2,233.6 -> 1,531.6 ms, cold 2.0756 [2.0299, 2.1139], rank stage 1.0008 [0.9982, 1.0032]; 12 points, 36 rank blocks, against the closure + index-lift row; Tier 1 repeated alternating pairs in the promoting run, so the new row is qualified by its own run); **baseline row replaced** |
| 83 | the index-build producer (arms kM38IB + cM38IB), same run 39464544962, points and rT770 (this replaced the index-build baseline row, run 39383739494) | round-2 index-build producer: state roots from the inverses of l, r and l+r (7 field products per state instead of 11) and the linear run finder for the index keys (8 roots in lock step), on the index-build producer (arms kM38IC + cM38IC; run 39464544962) | **paired, this run:** 4.933 -> 4.416 (point estimates, end-to-end cold; 1.12x closer). Context only, and a cross-run rho-gap artifact: the index-build row as landed read 4.158 (a different run, host class, instances, rank seeds and step time), lower than the new row's 4.416 although the new producer is paired-faster | **paired, this run:** 0.1434 -> 0.1422 (point estimates; online code unchanged, A / B 1.0082 [1.0068, 1.0098]) | engineering; promoted by its own frozen primary (end-to-end cold kM38IB+cM38IB / kM38IC+cM38IC 1.1169 [1.1110, 1.1231] over 36 alternating pairs in wall time on one host class, factor-base construction charged to no arm; stored states and table slots byte-identical, relations, probes, root calls and counters unchanged, the saving is the root-index build 6,501.9 -> 5,170.8 ms (1.2574 [1.2563, 1.2586]), setup 1.1898 [1.1844, 1.1954], cold 1.1816 [1.1746, 1.1891], self-test 0.9979 [0.9750, 1.0214], rank stage 1.0046 and online 1.0082 on unchanged code; 12 points, 36 rank blocks, against the index-build row; Tier 1 repeated alternating pairs in the promoting run, so the new row is qualified by its own run); **baseline row replaced** |

| | n | from | to | cold gap | online gap | class |
|---|---|---|---|---|---|---|
| | 83 | the round-2 index-build producer (arms kM38IC + cM38IC), same run 39527997793, points and rT770 (this replaced the round-2 index-build baseline row, run 39464544962) | rank-finder producer: the rank stage's probe keys from round 2's linear run finder, eight keys in lock step, instead of lift_scan per key, on the round-2 index-build producer (arms kM38RF + cM38RF; run 39527997793) | **paired, this run:** 4.001 -> 3.924 (point estimates, end-to-end cold; 1.02x closer). Context only, and a cross-run rho-gap artifact: the round-2 row as landed read 4.416 (a different run, host class, instances, rank seeds and step time), so the landed-to-new drop (1.13x) overstates the paired change | **paired, this run:** 0.0935 -> 0.0933 (point estimates; online code unchanged, A / B 1.0030 [0.9970, 1.0113]) | engineering; promoted by its own frozen primary (end-to-end cold kM38IC+cM38IC / kM38RF+cM38RF 1.0196 [1.0147, 1.0255] over 36 alternating pairs in wall time on one host class, factor-base construction charged to no arm; stored states, relations, probes, root calls and counters unchanged, the saving is the rank stage 2,937.5 -> 2,806.5 ms (1.0467 [1.0399, 1.0534]), setup 1.0026 [0.9962, 1.0099], cold 1.0026 [0.9961, 1.0100], self-test 0.9967 and online 1.0030 on unchanged code; 12 points, 36 rank blocks, against the round-2 index-build row; an effect below the design's minimal effect of interest 1.03; Tier 1 repeated alternating pairs in the promoting run, so the new row is qualified by its own run); **baseline row replaced** |
| | 83 | the rank-probe producer's one-target online scan on the batched S3 loop (arm cS), same run 39303742695, points and rT770 | online frame: the one-target online scan on the rank stage's frame loop (arm cF, `KIC_ONLINE_SOLVE=frame`; run 39303742695) | **paired, this run:** 66.5 [58.3, 76.5] -> 66.5 [58.2, 76.6] (end-to-end cold with the shared rank stage; unchanged to 0.08%) | **paired, this run:** 0.1714 [0.1249, 0.2273] -> 0.1089 [0.0791, 0.1449] (1.57x smaller) | stage improvement (online) over the rank-probe producer; promoted by its own frozen primary (online cS / cF 1.5733 [1.5714, 1.5753] in wall time on one host class, 222.76 -> 141.58 ns per probe, probes, root calls and relations unchanged; A/A 0.9986 and 0.9999, planted 2.7052 [2.6979, 2.7127]; 64 points); end-to-end secondary with the shared rank stage 1.0008 [1.0006, 1.0010], no regression, lower bound above 1 (a pipeline improvement of 0.08% by the frozen reading); **baseline row not changed: stacks with index-lift and the closure; combined run pending** |
| | 19 | tau6, Sage Groebner per-shift solve (arm B in the promoting run; the row as landed was run 38520305068) | native per-shift solve (arm N), run 39387473809 | **paired, this run:** 16,647 (B, the ratio of mean cold S, no interval) -> 117.9 [113.4, 122.6] (N; CPU, 141x closer). Context only: the row as landed read 1.94e4 [1.69e4, 2.23e4] (another run, host and unit) | not computed (online S now measured: N 21.40) | engineering (the per-shift Groebner solve moved from Sage to native code); promoted by its own frozen primary (cold CPU B / N 141.02 [136.75, 144.95] over 60 alternating pairs, CPU time on one host class, not replayed); online B/N 206.7 [203.3, 209.8], setup B/N 1.29 [1.279, 1.297], A/A 1.0003 [0.9964, 1.0035], planted NX/N 140.8 [136.6, 144.6]; 24 of 24 gates |

The paired cold-time ratios between baselines, each in its own runs, are in crypto `research/notes/index-calculus/IC_TOOL_PROGRAM.md` §7. The gaps above are each against that comparison's own rho, and that rho also changed between §23 and v3. So the gap delta is the distance remaining, not the IC's own speedup.

## Stage results: canonicalization

Stage improvements are recorded here. One becomes a pipeline improvement only once it moves an end-to-end `S` above.

| stage | n | experiment | result | tier | pipeline effect |
|---|---|---|---|---|---|
| normal-basis least rotation, isolated | 131 | `canon-n131-20261014` | Five exact canonicalizers on `[u64; 3]`. Ir per uniform word: lift_scan 514, gap_scan 1,435, exhaustive 1,850, exhaustive_bf 3,664, refine_bf 4,510. 0 mismatches. | deterministic Ir; wall times exploratory | none yet |
| the same, inside a decomposition-style loop | 131 | `canon-n131-loop-20261014`, run 38607684318 | lift_scan is fastest on all four workloads: 16/16 contrasts at Bonferroni, ratios 1.83–3.81. In-loop Ir over the loop floor: lift_scan 519, gap_scan 1,760, exhaustive 2,883. | Tier 1 for the timing | none yet. No n=131 pipeline exists, and at n=53 the isolated ranking did not survive the loop (`papers/frobenius-orbits` §4/§7) |

## Open

- **n=41, 53, 61:** the gap to the tuned rho is measured by `experiments/koblitz-s23-tuned-rho-20261015` (run 38777903922, PR #923; rows above, one per size, each from that experiment alone; n=47, 57 and 59 are in its README). It ran rT770's configuration on the one-word `Gf2` kernel, because `Gf2_128` exists only for $n > 64$, and it measures about the same cost as ParallelRho. It is accounting: no IC change, so no baseline row moves. A rho tuned on the one-word kernel is not measured.
- **n=19 and n=41–61:** no Bernstein–Lange walk has run, so the BL figures are models or absent.
- **n=83:** the baseline row is the rank-finder producer (koblitz-n83-rankfinder-20261021, run 39527997793): the round-2 index-build producer with the rank stage's probe keys computed by round 2's linear run finder, eight in lock step, instead of lift_scan per key (same keys, probes, relations, root calls, counters and rank table per rank seed; the index and every other stage unchanged), promoted end to end over the round-2 index-build row at Tier 1 by 1.0196 [1.0147, 1.0255] (wall time on one host class; 36 alternating pairs, 12 points; rank stage 1.0467 [1.0399, 1.0534]; setup 1.0026, cold 1.0026, self-test 0.9967 and online 1.0030 on unchanged code, every interval containing 1; layout digests, probes per relation and scalars verified, probe law 1.0892 pass, A/A 0.9998 and 0.9982, planted rank stage 1.8688). The effect is small: below the design's minimal effect of interest, 1.03, and its modelled 1.066, with the rank-stage ratio at 1.0467 against a modelled 1.204 on this AMD EPYC 9V45 host; the frozen rule's verdict is improvement, and it has not been replayed on another host class. Its end-to-end cold S is 0.4466 against the tuned rho's 0.1138 (gap 3.924, a point estimate); the cold path is still 61.4% of the end-to-end cold cost (setup 4.31 s, the root-index build 3.25 s of it; the rank stage 2.81 s). Factor-base construction is charged to no arm. Cross-run rho-gap artifact: the previous row read gap 4.416 in its own run (275.04 ns rT770 step, Intel Xeon Platinum 8370C) and 4.001 as the A side of this run (175.95 ns step, AMD EPYC 9V45), so only the paired within-run gap (4.001 to 3.924) is a delta. The round-2 index-build producer (1.1169 [1.1110, 1.1231] over the index-build row, run 39464544962, its own Tier 1 run) and the index-build producer (1.7406 [1.7129, 1.7676] over the closure + index-lift row, run 39383739494, its own Tier 1 run) are in Other verified records. The closure + index-lift producer (7.6558 [7.2192, 8.1103] over the index-lift row, run 39335956567; Tier 1 qualified, 7.4133 [7.1999, 7.6362], run 39359922687), the index-lift producer (1.0344 [1.0324, 1.0364] over the rank-probe producer, run 39290913632), the rank-probe producer (1.1033 [1.1010, 1.1056] over the rank-cut producer, run 39214027289), the rank-cut producer (1.3336 [1.3300, 1.3377] over the stack, run 38891404048), the stacked producer (3.2391 [2.9809, 3.5240] over the probe-pipeline producer, run 38862448935) and B's row (experiment on PR #918, not merged yet) are in Other verified records. The run was not replayed on another host class, and the BL gap was not re-measured on this producer. The closure's earlier comparison (`koblitz-n83-closure-20261019`, run 39305259093: 6.4444 [6.0993, 6.7853] over the rank-probe producer) is superseded by the paired closure + index-lift result (run 39335956567). The nested 899-column base is promoted over the rank-probe producer at K600 (`koblitz-n83-k899-20261019`, run 39306394645: 1.1873 [1.1247, 1.2523]) but has not been combined with this producer; the next step is a frozen protocol for K899, or for the remaining root-index build, self-test and setup, on the rank-finder producer against the current row, with the K899 index build (44.3 s) and the slot cliff at K900 in view. The rotation-key producer (`koblitz-n83-rotkey-20261019`, run 39299176306: the rank-stage table keyed by v^83 in F2[X]/(X^83+1), lift_scan only at a hit) is not promoted against the rank-probe producer: end-to-end cold ratio 0.9983 [0.9701, 1.0227], not separated, with every gate and both controls passing. It is not an improvement, so there is no stack on index-lift or the multiplier closure. The online-frame experiment (`koblitz-n83-onlineframe-20261019`, run 39303742695) is a stage improvement over the rank-probe producer: its one-target online scan on the rank stage's

frame loop, online cS / cF 1.5733 [1.5714, 1.5753] over 64 points, probes and root calls unchanged, end to end 1.0008 [1.0006, 1.0010]. It is a different stage from the index lift and from the closure, so it stacks with them; it is recorded in Other verified records and not in this row until a combined run is made.

- **n=19:** online `S` is now measured, by the v3 run (39387473809, repeated alternating pairs, Sage smoke gate): the native-solve producer's cold `S` is 31.42, with setup 10.02 and online 21.40, against the matched rho's 0.2661; the cold gap is 117.9 [113.4, 122.6]. No interval was computed for an online gap, and there is no BL measure. IC1 candidate manifests exist for the baseline and the native-solve candidate (`IC1N19Ckb0fb1064PDP2polyboriRCsampleLAkernelTDpdpISO0hb41aed7ef80a` and `IC1N19Ckb0fb1064PDP2nativeenumRCsampleLAkernelTDpdpISO0h6952f30ce00e`, in `experiments/volcano-n19-native-tau6-20261019/inputs/ic1_manifests.jso`. The earlier runs were invalid: v1 (39307409409, S0 failed), v2 (39376405326, every timed IC row crashed in the relation digest with a `TypeError`: the v3 smoke job reproduced it in Sage, a Sage `Integer` that `json.dumps` refuses) and the first v3 run (39384735073, a workflow defect, `KeyError: 'N19_RD'`, nothing timed). Gaps that remain: one hosted runner and one host class, not replayed on another machine; CPU only; the smoke and timed jobs ran on different hosts (EPYC 9V45 and 9V74); microcode unreadable; the rho is not wall-time tuned.
- **n=83, §5a band:** the 0 / 0.1 / 1 GAE band for the IC / rho gap is uncomputable on both n=83 rows, because the frozen producer emits no group-operation counts. The K1 replay (archived 2026-10-17) timed factor-base construction but used the same producer, so the band stays open until a producer that emits the counts runs under a new protocol.
- **n=83, construction time X (resolved 2026-10-17):** measured in `koblitz-n83-replay-20261017` (run 39007026856): X = 427.5 ms, 65.5 ms over the retained-file load. Every-phase stacked R 3.2357 and cold `S` 9.6950 (illustrative, two hosts) against the row's 3.2391 and 9.680; the row's figures are unchanged. B's row uses the same base; its cold `S` was not recomputed.

## Updating this file

1. Freeze a protocol for the candidate improvement against the row's pipeline, on the same instances, before timing.
2. When the improvement lands, replace the row in `baselines.json` and in the table above. Add a history row with the before and after figures and the class (advance, engineering, relabelling, accounting). Relabelling and accounting do not replace a baseline. Give `s_ic_setup` its one meaning (`s_ic_cold` - `s_ic_online`, rank stage included), and record the history delta paired within the promoting run; figures from an earlier run go in as context only. Say whether the headline is wall time (and on which host class) or operation counts, give the operation-count ratio beside a wall-time one, name any phase the experiment did not charge, and say whether the §5a band was computable and whether the run was replayed elsewhere.
3. Name the next improvement to try in the new row.
4. Re-render Figure 1 and this file's PDF:

```
cd docs/ic/figures && pdflatex baselines_gap.tex && pdftoppm -png -r 160 -singlefile baselines_gap.pdf baselines_gap
cd .. && pandoc BASELINES.md -o BASELINES.pdf --pdf-engine=pdflatex -H pdf-header.tex -V geometry:landscape,margin=1.2cm -V fontsize=9pt
python3 -m json.tool baselines.json > /dev/null
```

## Sources

- crypto `docs/ic/BOUNDARY_TARGETS.md` and `docs/ic/boundary_targets.json` (Regime B `vs_rho`; complete cold compact-orbit panel).
- crypto `research/notes/index-calculus/RESEARCH_IC_BOUNDARY_LEDGER.md` §23; `research/ic_single_target_20260930/` (PROTOCOL, analysis.json).
- crypto `research/ic_tool_program/rule/v3/` (README, PROTOCOL, analysis.json); `research/notes/index-calculus/IC_TOOL_PROGRAM.md` §7.
- crypto `research/notes/ecc2k130/disjoint_cold_v2_outcome_20261001/RESULT.md`.
- cryptanalysis `experiments/koblitz-n83-bl-arm-20261014/` (branch `claude/n83-bl-arm`, PR #918): README, `run_github_38689817618/result.json`.
- cryptanalysis `experiments/koblitz-s23-tuned-rho-20261015/`: README, `run_github_38777903922/panel/result.json` (PR #923).
- cryptanalysis `experiments/koblitz-n83-reconcile-20261014/`: README, `run_github_38617911080/panel/result.json`.
- cryptanalysis `experiments/koblitz-single-target-n83-tier1-20261014/`: README, `tier1_github_38523707244/`.
- cryptanalysis `experiments/volcano-ic/rho-arm-20261014/`: README, `results/summary.json`.
- cryptanalysis `experiments/canon-n131-20261014/` and `experiments/canon-n131-loop-20261014/`.