G3 continuation: actual receipts and CI repair

2026-11-13 · additive report · all standing unsigned

The completed component remains nativec162f3,CLI188d44,integrated2d6fec:four unfiltered tests,all1828 source points,twelve geometric branch controls,nine CLI points,twenty native+tee pairs[0,0],eleven named Lean bindings. The workflow correction changes no arithmetic,fixture,test or proof statement. [pcc:unverified]

First GitHub run43379511138 on sourcea719 fails before creating any job or check run. Independent official actionlint1.7.7,after published-release checksum verification, identifies runner.temp at job-level env as unavailable. The primary GitHub context table confirms runner is available in step env. Scope correctiona6d76b precedes the edit. Current actionlint,bash syntax and343 portable hash checks pass,b02647. The original340-entry reference is immutable;reference02 also pins both original trusted-native manifests. Actual new full CI remains pending publication. [pcc:unverified]

Both broad root regression attempts are retained:cold01 times out124 before tests;warm02 times out124 after its6330-test suite begins,with all2133 selected hashes unchanged. Whole warm02 is d99199/8,950,824-byte standard tar/XZ. A60-second exact diagnostic of the first failed test exits101 with6329 tests filtered and2133 guards unchanged;823054 preserves its complete original record. It reports a missing original ecbench records.jsonl,not a G3 test failure. The canonical original object has2,293,097 bytes/SHA8970667e…;original artifact pull exits2 because aws CLI is absent. Fixture availability and the global suite remain unresolved,2364e3. [pcc:unverified]

Actual latest publication920f04:trusted-base43379515719/job131733754230 replaysEIGHT remote objects before normalbotbb6e,parenta719,exact16paths. Seven whole archives and the complete95,052-byte lossless member index match the original Git blob sizes/hashes. Exact local fast-forward,artifact and wiring checks exit0;all owned dirty bytes and2133 native inputs are preserved. Whole428,067-byte UTF8 log,43,776-byte standard XZ and complete34-file publication archive66,532 bytes are retained. The collector archive itself is a separate pending data object. [pcc:unverified]

The entire original root four-job and consumer six-job workflows remain unchanged. Current source control edits are the workflow environment placement and the thin driver reference filename;the old reference is retained. Whole CI-control raw tree76ec36 includes original API,original and corrected validator output,primary documentation and installation fallback. Each raw boundary keeps every member,raw/archive digests and exact standard tar/XZ roundtrip. New oversized objects use the genuine trusted-base route. Main ledger/signing/review/merge requirements remain separate. [pcc:unverified]

Evidence pointers

evidence/genus3-ci-definition-failure-01;genus3-ci-scope-correction-01;genus3-root-regression-02;genus3-root-fixture-diagnosis-01;genus3-latest-publication-raw-01. Previous three-page native report and one-page integration report remain immutable.

Next lead: actual norm on canonical classes



This is a source-reviewed proposal88d09a,not a new norm implementation or execution. The next cryptanalysis component will accept valid canonical Jacobian classes of the same three fixtures and evaluate the actual quotient norm into E(Fq³),without recovering a source scalar. Reuse the original field,polynomial,linear algebra,elliptic and Picard engines. [pcc:unverified]

For a typical class,its three conics define a degree-three divisor D. Recover the dimension-three quotient algebra from R2 and R4. Select a prime-field linear form L whose squared multiplication is invertible,then represent functions as F2/L². Find a monogenic coordinate T with basis1,T,T². Its degree-three polynomial carries multiplicity. Split it with the original Fp6 polynomial engine and evaluate the completed Ciani cover at each support point,weighted by the polynomial multiplicity. Validate the curve equation in the algebra,including nilpotents. [pcc:unverified]

Subtract a separately computed image sum for an actual plane line section through P0 minus P0,representing Dinf~K-P0. Every rational line choice must agree;no shift fitting. For an exceptional class[P0-P],use pi(P0)-pi(P). All output coordinates must be fixed by q³-Frobenius and projected through an explicit K→Fp6 embedding. This norm oracle openly uses support roots;its eventual cost is charged separately from the root-free forward map. [pcc:unverified]

Independently count C overq,q²,q³ with one-coordinate polynomial-root enumeration and projective boundaries. The original Picard source uses zeta_c3=(N1³+3N1N2+2N3)/6;RR gives#Jac=zeta_c3-q*N1. Predicted point-count triples are(6,26,192),(8,50,380),(12,122,1308),giving148,356,1324 classes. These are predictions for native recomputation. Prove a deterministic generating BFS reaches the independently counted order before claiming full-domain acceptance. [pcc:unverified]

Require every Jacobian class,every generating edge,both actual compositions norm(phi(P))=[2]P andphi(norm(J))=[2]J,all odd-subgroup scalar images/recovery and explicit exceptional,multiplicity,infinity,origin,field/model and malformed-input controls. Report observed even kernels. Freeze the consumer protocol/source catalog and ready child PR under1520 before implementation. Original sources are the W1 README/Picard source,G3 derivation/proof map and original FpR/poly/curve/series APIs. KB tools remain absent;earlier six127 receipts and primary fallback are retained. No novelty or computational advantage is asserted. [pcc:unverified]