Nonempty matrix cloud recovery

Observations only. All four actual rows passed: source/publication and distinct-pod restore for two nonempty states of the fixed generic n=7 Boolean fixture. The seed-phase snapshot has rank 2 at sequence 2; the checkpoint after closure round 1 has rank 12 at sequence 22. Each resumed computation reproduces the frozen reference certificate bytes. Independent generic quotient conditions, constant survival and full-space oracle dimension checks pass; every row has codimension 63 and exhaustive solution count 64.

- Seed checkpoint: rank 2 — source and restore passed
- Closure checkpoint: rank 12 — source and restore passed
- All four rows: reference bytes, oracle and count agree
- Frontier disk admission and degree-six result: outstanding

This extends the previous real-cloud Semaev controls, which transported empty relation matrices. It establishes recovery of these nonempty seed and closure states only. It does not establish a Semaev frontier result, a new LFD lower bound, or large-worker resource admission. The frontier requires an explicit certificate-export disk guard: its conservative output bound exceeds the worker disk limit. The original Semaev controls and prior failed source attempt remain preserved.

Source pod: 3748e2c9-205a-42e7-aa7f-3aa8c249b75e.

Restore pod: 7f8ba690-b0ff-4ffb-af73-920740fca59d.

All 110 archive file hashes verified; export validation: True. No canonical mathematical graph changes.