Checkpoint transport controls

14 of 14 fixed local fake-S3 controls passed. The archive contains 283 hash-verified files. This is not actual cloud permission or durability evidence and establishes no LFD bound.

Export is incomplete: the frozen protocol declares separate arms but the harness recorded composite candidate cases. Missing arm rows are not fabricated. A prospective corrected-protocol replay is required for a valid export.

Local fake-S3 controls: 14/14 passed

Actual cloud recovery and frontier bound: not established

Case	Passed	Steps
object_put	True	3
object_get	True	3
object_corrupt_get	True	3
manifest_put	True	3
manifest_get	True	3
manifest_corrupt_get	True	3
wrong_snapshot_context	True	1
idempotent_publication	True	2
prune_after_readback	True	2
fallback_corrupt_object	True	3
fallback_corrupt_manifest	True	3
wrong_restore_context	True	3
truncated_listing	True	3
restore_newest_and_replay	True	4

The workload uses a filesystem-only fake AWS executable. Controls cover interrupted PUT/GET, corruption, idempotence, verified pruning, fallback, context mismatch, incomplete listing, and native replay against retained reference certificate bytes. Child commands and their original stdout/stderr are in the evidence archive. Each child has a 1 GiB cap and 120-second watchdog; timings are L0 telemetry only. Inputs, code and native binary hashes are in plan.json. The source revision is pinned in protocol.json. Actual cloud publish, replacement-worker restore and independent certificate checking remain required. No canonical mathematical graph changes; this diagram records software-control status only.