Checkpoint transport controls

28 of 28 fixed local fake-S3 controls passed. The archive contains 553 hash-verified files. This is not actual cloud permission or durability evidence and establishes no LFD bound.

Export validation passed for the composite case rows.

Local fake-S3 controls: 28/28 passed

Actual cloud recovery and frontier bound: not established

Mode	Case	Passed	Steps
retain	object_put	True	3
retain	object_get	True	3
retain	object_corrupt_get	True	3
retain	manifest_put	True	3
retain	manifest_get	True	3
retain	manifest_corrupt_get	True	3
retain	wrong_snapshot_context	True	1
retain	idempotent_publication	True	2
retain	prune_after_readback	True	2
retain	fallback_corrupt_object	True	3
retain	fallback_corrupt_manifest	True	3
retain	wrong_restore_context	True	3
retain	truncated_listing	True	3
retain	restore_newest_and_replay	True	4
prune	object_put	True	3
prune	object_get	True	3
prune	object_corrupt_get	True	3
prune	manifest_put	True	3
prune	manifest_get	True	3
prune	manifest_corrupt_get	True	3
prune	wrong_snapshot_context	True	1
prune	idempotent_publication	True	2
prune	prune_after_readback	True	2
prune	fallback_corrupt_object	True	3
prune	fallback_corrupt_manifest	True	3
prune	wrong_restore_context	True	3
prune	truncated_listing	True	3
prune	restore_newest_and_replay	True	4

The workload uses a filesystem-only fake AWS executable. Controls cover interrupted PUT/GET, corruption, idempotence, verified pruning, fallback, context mismatch, incomplete listing, and native replay against retained reference certificate bytes. Child commands and their original stdout/stderr are in the evidence archive. Each child has a 1 GiB cap and 120-second watchdog; timings are L0 telemetry only. Inputs, code and native binary hashes are in plan.json. The source revision is pinned in protocol.json. Actual cloud publish, replacement-worker restore and independent certificate checking remain required. No canonical mathematical graph changes; this diagram records software-control status only.