Historical D4 acceptance reuse controls

Observations only. Two actual local worker paths passed on the retained n6 fixture: fresh original D4 checking and reuse of historical D4 acceptance. Both produced the same retained D5 certificate, passed the original independent D5 checker, and freshly counted three solutions. Accepted codimension is also three. No new LFD bound follows.

Two worker paths, one retained n6 fixture

Fresh D4 check	D5 checked • count 3 • reference bytes match
Historical D4 acceptance	D5 checked • count 3 • reference bytes match

Reuse binding controls: 12 / 12 altered inputs rejected

Local qualification only; no new LFD bound

All twelve altered bindings were rejected: capsule digest, seed bytes, target, checker source, failed step, timeout, acceptance transcript, invocation, original request, worker source, transfer receipt, and escaping evidence path. Inner tests re-pin outer hashes so each intended binding is exercised. They are assertions within the reuse row, not independent mathematical instances.

The custody verifier does not replay the algebra. It binds trusted historical acceptance to identical seed bytes and target. Final D5 checking and fresh enumeration remain mandatory. Storage here is local fake AWS; unchanged checkpoint components have separate retained cloud qualification. This is not frontier success or a timing comparison.

Two requested rows completed once each, with no retry or exclusion. Raw artifacts, protocol, exact commands, certificate bytes and rejection receipts accompany the report. The archive contains 247 individually verified files. The source commit is 3b14f358bcb49d83c483b0c4cf772320d6d3d2b2. No mathematical-bound graph changes.