Export admission guard controls

Observations only. All 20 actual local software controls passed, ten fresh and ten restored. This rendering supplements the immutable export-guard-001 report; no trial was rerun.

Allowed exports match the retained reference certificate. Fresh refusal preserves a published, verified checkpoint; restored refusal prevents native execution. Exact-capacity and one-byte-short cases use the common prelaunch path in both configurations. Corrupt state, mismatched identity, and existing output paths are rejected.

Export guard: 20 / 20 fixed software controls passed

	Fresh	Restored
native_allow	PASS	PASS
native_refuse	PASS	PASS
phase1	PASS	PASS
wrong_request	PASS	PASS
wrong_dimensions	PASS	PASS
corrupt_snapshot	PASS	PASS
output_exists	PASS	PASS
boundary_exact	PASS	PASS
boundary_short	PASS	PASS
word_counts	PASS	PASS

Local fake storage; no new LFD bound; no performance claim.

All 169 archived files were verified against sizes and SHA-256 hashes. The twenty-row experiment export validates with zero findings. Source report: export-guard-001/report.md. Protocol SHA: d8686cd06e99f7b4d73efc099673e767ea3a4cb4dd4b4cbef3e7c7beade9805e.

These are local fake-storage controls. No cloud resource qualification, performance result, or new LFD bound follows. Worker integration remains required.