# Weak-class calibration of the numeric structure instruments

Lead: LEAD-EXO-weak-class-instrument-calibration. Protocol protocol.json, WEAKCLASS-20261104, was frozen before data (sha256 472123ace16b..., commit 3d36b1a3). Scripts are pinned by hash.

**Question.** Do the instruments this program uses to rule out structure see curves whose DLP is *known* to be easy? A NULL from a blind instrument excludes only structure of that statistic's own type.

## Design

- **Classes.** All curves have prime order n.
  - A, anomalous: n = p, solved in polynomial time by Smart's attack.
  - B, small embedding degree: ord_n(p) = 3–6, so MOV gives a subexponential attack.
  - C, j = 0 (a = 0, p ≡ 1 mod 3), with a factor base made of whole ζ-orbits.
  - D, ordinary: one curve **paired with each weak curve over the same p**, excluding j = 0, j = 1728, small k, anomalous orders and orders already used at that p.
- **Sizes.** p ∈ [2^(L−1), 2^L) for L = 10, 12, 14, with 3 weak curves per class per size, giving 54 curves in all.
- **Instruments.** Each is scored as the percentile u of the curve's statistic within its own 40-draw null.
  - I1, character-sum maximum of the factor base's log set. The null is negation-closed random log sets (round-2 lesson D1).
  - I2, m = 2 yield |F + F|/n in log space, with the same null.
  - I3, QTT parameter count of the transfer matrix M (holant step b), at L = 10 only. The null is random relabellings.

  The low-degree rank instrument is omitted, because at full rank it does not depend on the curve (LOWDEG-RANK-20261104).
- **Positive controls.** A negation-closed log-AP set for I1 and I2, and the discrete-log labelling for I3.
- **Rule.** A cell is DETECTS iff all 3 class curves fall beyond the null's 5–95% band in the same direction, at ≥ 2 sizes (QTT: at L = 10), while the paired ordinary curves do not. Otherwise it is BLIND. An instrument whose controls fail is INVALID.

## Results (frozen rule)

| instrument | anomalous (A) | small k (B) | j = 0, ζ-stable FB (C) |
|---|---|---|---|
| I1 character sum | INVALID (mean u 0.61) | INVALID (mean u 0.41) | INVALID (mean u 0.12) |
| I2 m=2 sumset yield | BLIND (mean u 0.56) | BLIND (mean u 0.44) | BLIND (mean u 0.64) |
| I3 QTT, p  2^10 | BLIND (mean u 0.36) | BLIND (mean u 0.44) | BLIND (mean u 0.60) |




Figure 1: u per curve

- **I2 and I3 are BLIND to all three weak classes.** Their positive controls sit at u = 0.00 on every curve, so the instruments work. They simply do not see Smart- or MOV-weak curves, or ζ-stability. Every NULL from these instruments should carry the scope note "blind to anomalous and small-embedding-degree curves".
- **I1 is INVALID under the frozen rule.** The fault lies in my A/A gate, not in the instrument. Its positive control is perfect (u = 1.00 everywhere). But the gate required the even and odd null-draw means to agree within 5% on every

curve, while with 20 + 20 draws the sampling error alone is about 2%. 5 of 54 curves exceed 5% (median 2.3%, 95th percentile 6.6%), which is consistent with chance. The gate was miscalibrated.

## Descriptive observations (not decisions)

1. **I1 versus j = 0.** The ζ-stable class lies at u = 0.00, 0.00, 0.00 at L = 10 and 0.00, 0.05, 0.03 at L = 14, below its paired ordinary curves. This is the "small downward shift" the memo predicted from fewer independent frequencies, because a ζ-stable log set is closed under multiplication by λ. It is the only class-specific pattern seen. It reflects how the factor base was built, not the DLP's ease.
2. **I1 versus anomalous and small k.** There is no consistent pattern (u from 0.05 to 1.00 in both classes).
3. **I1 is overdispersed on ordinary curves.** 10 of 27 paired ordinary curves fall at or beyond the 5%/95% marks, against 14.6% expected (3.95 curves; exact rate for 40 draws with mid-ranks), P(X ≥ 10) = 0.0035, if the small-x log set behaved like a random negation-closed set. So at these small sizes (n ≤ 2^14, |F| ≈ 2√n), the character-sum maximum of the small-x set is more variable than the matched null's. The small-x factor base is exactly negation-closed here (n odd, so no 2-torsion), so this is not a construction artifact. It deserves its own check before I1 nulls are read at small n. See also the H-PSEUDO re-read in this round.

## Consequences

- I2 and I3: scope notes (blind to Smart- and MOV-weak classes).
- I1: **rerun done** (../weakclass-i1-20261104). With a calibrated A/A gate on fresh curves, I1 is valid and BLIND to all three classes. The overdispersion was not reproduced on 90 independently picked ordinary curves, but the rerun's 27 *paired* ordinary curves again sit low. That is an unexplained anomaly; see that report. The j = 0 cell did not replicate under the cell rule, but the direction partly did.
- I3 caveat (validation): 8 of the 18 L = 10 curves have a degenerate QTT null (statistic equal to the null constant, so u = 0.5 by the tie rule). At p ≈ 2^10 the QTT instrument sits at its rank ceiling for random labellings, so its BLIND verdict has little dynamic range.
- Not a cost claim. BLIND does not mean a class is not weak.

## Deviations

- No S3 checkpoint, because there is no upload token. With the owner's approval (session 2026-11-04), the pushed branch is the resume record.
- The run shared the container's 4 cores with two other runs. The values are exact, so this affects only wall time.

## Reproduce

python3 weakclass.py --protocol-sha 472123ace16b54bf0cc2f3fa4dd855ca326805b4aac6a560a69046e491436665 --out rows.jsonl
python3 analyze_weakclass.py rows.jsonl verdict.json
python3 figures.py; ./build_pdf.sh