Direct polynomial replay: source and runtime-binding review

Reviewer authored helper runner ancestor and direct mathematical note; direct Lean candidate authored by renew_materializer and independently source-reviewed by renew_norm. This is a nonblind runner delta/import review, not an independent runtime replay.

Actual replay/launcher source differs from helper runner only in fresh workspace, unit, lane and release-schema names. Ownership, process cleanup, deadline and post-custody control flow are unchanged.

Four calls match frozen module order. Eighteen printed names exactly match names.json, with no duplicates. Readback and expected-failure source bytes equal independently reviewed source packet.

Direct candidate and fixed controls byte-match independent source review. Ten explicit import edges resolve to earlier fresh outputs, the retained Nonbranch artifact, or exact baseline-bound .olean entries; no unresolved direct import.

All 26 retained entries match helper reviewed set and current hashes. Artifact hashes are separate from source hashes; only 13 successful modules are copied into private cache. Failed BranchRootMultiplicity is excluded.

Private retained cache rejects symlinks, extra files and name collisions; verifies original/copied bytes before and after compilation and postcheck. New workspace precedes private cache then baseline roots; failure stops before subsequent calls.

Shared 16736-file baseline/runtime pre/post verification retained. Compiler failures still enter post phase only after captured terminal ownership; unresolved custody stops progression.

Limits 900/600/900 = 2400 seconds, 1 CPU, 8 GiB, no swap, 128 tasks, one attempt/no retry and unchanged absolute deadline. Ledger remains null, release false; coordinator must bind current serial/admission/publication.

No blocking source finding in this reviewed scope. No execution occurred; final launch bindings remain pending.

Direct branch replay: source review

13 retained compiled imports / 10 resolved import edges

candidate → controls → 18-name readback → negative

2400-second protocol; release and ledger unset

Source-only diagram; no candidate runtime measurements.