Offline lock gate v4: two generated locks

Native result: generated pending publication. This report retains the single completed attempt.

Offline two-workspace resolution: driver exit 0 → adapter exit 0

Actual locks: driver 2952 bytes / adapter 2999 bytes; hashes verified

Native 0.869217 s; caller 1.186748 s; full 60 s reservation charged

Both offline resolutions exited zero. The driver lock contains 2952 bytes with SHA256: 41829631b1c402e6bec2ea0c91327d557d5160bcb71b92bd10d8eba82ecfdde3 The standalone adapter lock contains 2999 bytes with SHA256: 0748a4bcf82a638dc393117a9256b828bd1a5b21f32972962abc29184d9ff6a1 Both actual files are retained separately as small source-bindable artifacts. The native receipt reports no compiler invocation and no network access. This gate did not run the combined qualification panel.

Timing, custody and charge

Native elapsed time was 0.8692167460103519 seconds; caller elapsed time was 1.1867481969529763 seconds. These are distinct observations. Pre-stop status was success with exit zero, and terminal ownership reports an empty owned cgroup. The full 60-second reservation is charged, bringing campaign cumulative charge to 3720 seconds and remaining allowance to 125880 seconds. All native and caller files are archived, with file hashes and byte counts. The canonical remote archive is downloaded and hash-verified. Originals are untouched. Publication and exact lock binding remain necessary before any combined qualification attempt; this result supplies the two generated locks only.