Prospective runtime-only assembly recovery

Preserve the original uncertain receipt unchanged. The base Docker build completed with native client exit0 and client_unknown=false; failure occurred only on the unprivileged Python read of root-owned mode0600 base.iid. Scoped sudo cat now returns sha256:347667d6ecc9294ab7bfcc83411fb47f7548c8d1ca5f7d315cca23fc4b115476. It matches the retained exact owner-tag readback and successful build stdout. No base rebuild is required.

Root can prepare a narrow additive supervisor from the reviewed assemble.py, admitting exactly one runtime build and zero base builds. Keep its source/binary/archive validation, context reconstruction, bounds, deferred interruption, client reaping and failure reconciliation. The original packet and owner UUID remain bound; use a new receipt directory and preserve all failures.

Before mutation, require:
1. Exact original receipt/binding/base-command/context-inventory/Dockerfile hashes. Require the sole original attempted phase is base, command exit0, client_unknown=false, iid path equals the original base.iid, command tag/labels/source revision/context paths match the frozen original binding. Do not infer terminal build success from image presence alone.
2. Adopt the original owner467e8502-46d8-4ab9-a13b-8d2375dd2ca2, exact base ID347667d6ecc9294ab7bfcc83411fb47f7548c8d1ca5f7d315cca23fc4b115476, and original runtime tag. Preserve base attempt1 as completed/adopted via separate evidence rather than editing it.
3. Read original IID through a bounded scoped sudo cat and validate SHA256 format; require regular non-symlink single-link root-owned0600 file and exact fixed path. Do not chmod/chown it. Require same daemon identity. Inspect both exact base ID and original base tag, matching ID, linux/amd64, owner/base/revision labels, User1000:1000, empty Entrypoint, no OnBuild, and retained RootFS layer list. Check relevant recipe Cmd/WorkingDir as recorded. Validate parent presence under original pinned receipt without a pull.
4. Require original runtime tag absent with exact No such image evidence. On presence/error, stop and reconcile; never replace it. Reconstruct context from the original artifact bindings and require its complete relative inventory equals the original context-inventory. Check both Dockerfile bytes and final binary/buildinfo/fresh-owner joins.

The sole build command remains the original reviewed legacy route with --pull=false --network=none --platform=linux/amd64, original owner/phase runtime labels and runtime tag, exact Dockerfile.runtime, staged overlay, and BASE_IMAGE=sha256:347667d6ecc9294ab7bfcc83411fb47f7548c8d1ca5f7d315cca23fc4b115476. No base phase loop executes. Keep original per-command240s and total600s supervision, with reserve for readback. These are software assembly bounds, not additional scientific worker authorization.

Minimal IID correction: after successful runtime build, use the same bounded scoped sudo cat path to read its newly created root-owned IID, with path/type/link/owner/mode checks and a receipt. This avoids repeating the exact PermissionError. Do not use unsupervised subprocess.check_output. The existing run helper may accept an explicit fixed prefix for only this cat command while retaining its deadlines/output cap/client ownership; Docker commands retain the existing env-i/no-credential prefix. Do not widen this helper to arbitrary privileged commands.

Post-build require terminal0 plus IID and exact runtime tag/ID agreement, original owner/runtime/revision labels, linux/amd64, User0:0, empty Entrypoint, no OnBuild, context unchanged and runtime layers extending the adopted base layer list. Preserve runtime command/IID/readback receipts. Failure or timeout records uncertain state and exact-tag readback only; it does not authorize a retry or removal. No push, image removal, container execution, pull or publication is included. Runtime qualification still verifies actual archive bytes, modes and payload behavior separately.

Source-review note: assemble.py currently sanitizes Config.Env but preserves ContainerConfig.Env in saved image inspection. The retained base contains only inherited PATH/HOME, so this failure does not expose a credential; any additive inspector should sanitize both lists before saving generic image metadata. The independently reviewed recovery must bind its exact source and filled recovery record before root execution.

Proposed recovery: adopt completed base, build runtime once

Base command exit0 + root0600 IID + matching owned image

Revalidate custody / daemon / exact base / runtime tag absence

One runtime build → privileged scoped IID read → exact readback

Proposal only: no base retry, publication or container execution