Executed archival audit: fixed 420-case results

Coverage and dispositions

420 / 420 source identities in exact order; 60 targets, 7 cases each, selected by p=739 from a 180-record archive. Recomputed: 218 collector-ineligible; 202 eligible = 174 first occurrences + 28 redundant duplicates; 0 informative candidates. Native exit0. No missing, failed or post-terminal disposition.

The preserved pattern

All 28 duplicates are case6 versus case3 within the same target: designed -(G+Q) versus G+Q. Their canonically signed coefficient difference is (0,0). Across all60 targets the original case6 labels and divisors negate case3. Graph forwarding:174 edges,28 suppressions,0 cycles,0 terminal answers. These are coordinate-validation fixtures, not sampled collector paths.

Setup accounting: aggregate each target once

All60 ledger entries agree across their seven row copies.

Setup checks:3904 Jacobian operations;438198 M;8436 S;14252 I;760038 field additions.

Constructor:2640 Jacobian operations;299213 M;5631 S;9823 I;519770 field additions.

Reference, eligibility, adapter and graph phases remain separate; scalar and field counters are not conflated.

Independent review and exclusions

Reviewer independently recomputed coverage, split-root eligibility, signed normalization, duplicate classifications and the once-per-target ledger. Frozen source/control hashes matched. No native rerun: admission permitted one attempt. Native label checks verify D=aG+bQ and Q=kG against public known answers; controls include deliberately planted informative labels.

Hashing, comparisons, memory, primality arithmetic, dense reference arithmetic, internal expansion and complete runtime work are not fully priced. No comparative clock, natural-yield estimate, cost ratio or ranking is reported.

Scope retained

The original four-lead and five-followup criteria remain unchanged, including the full1,260-target requirement and separate18-slot upper gate. This snapshot adds component evidence and an archival correctness audit; previous aggregate snapshots are preserved. index.json binds exact producer and independent-review paths and hashes.