Second-host re-execution of holdout-P20 (PROTOCOL.md §13), 2026-10-29

This is the second-host replay that PROTOCOL.md

§13 requires before the 20-bit result of this study (README) is promoted to the leaderboard.

It re-executes the frozen holdout-P20 spec on a different host class with a different ecbench build, and

checks every original record against its counterpart on the second host.

Outcome

- **Reproduced exactly.** Each of the 1,008 records of the original session `ECBS1h685271327a8a` has a partner on the second host with the same arm, workload, round and algorithm seed. All 1,008 partners are identical in every deterministic field: outcome and recovered scalar, `cost`, `counters`, `boundaries`, `field_ops` and `solver`, plus each phase's adds, doubles, scalar multiplications, GAE and `native` map. The band reads `counters` and the phase `native` maps (`src/cryptanalysis/ecbench/band.rs`, `unpriced_counts`). So S at w = 0, 0.1 and 1 is reproduced exactly. Source: `analysis/match-original.json`, written by `tools/match_records.py`.

- **Second-host session audit passes.** `ecbench verify` on the EKS worker (`eks-results/audit.json`) reports 2,016 of 2,016 records verified and regraded, with the session complete. The L2 gate (`eks-results/l2-gate.json`) admitted all 2,016 executions at L2.

- **Same decision on more data.** The second-host session has 5 measured rounds, so 240 pairs instead of 96. On it, `ecbench compare --weight` gives *recorded* paired ratios for sel/inc and sel/rho-neg:

w	Σ S_sel / Σ S_inc, second host (240 pairs)	original (96 pairs)	Σ S_sel / Σ S_rho-neg, second host	original
0	0.836 [0.806, 0.866]	0.818 [0.773, 0.866]	7.95 [7.31, 8.64]	7.75 [6.92, 8.70]
0.1	0.817 [0.786, 0.847]	0.798 [0.752, 0.847]	8.24 [7.56, 8.97]	8.02
1	0.746 [0.714, 0.779]	0.726 [0.677, 0.778]	9.62 [8.77, 10.55]	9.35 [8.27, 10.60]

`inc-aa/inc` is exactly 1.000 at every weight. `ecbench band --ranks` (`analysis/band.md`) ranks `sel < inc` and `rho-neg < sel` at every weight. Rounds 3–5 use seeds the original session never ran, but the same curve and targets. They add target-round pairs, not curves.




Figure. Paired ratios with cluster-bootstrap 95% intervals. Blue is the original host (`ECBS1h685271327a8a`, 96 pairs); red is the second host (`ECBS1h517504d65837`, 240 pairs). Values come from the saved `ecbench compare --weight` JSON; `figures/plot.py` does layout only.

What ran

- **Spec:** the frozen `specs/holdout-P20.json` of this study, with exactly two fields changed for EKS admission: `measurement.rounds` 2 → 5 (the lab requires at least 5) and `measurement.isolation_required` L0 → L2. Curve, targets, arms, warm-up, order and seed are unchanged. `src/cryptanalysis/ecbench/spec.rs` derives the algorithm seed of a round from (seed, workload, round) only, so measured rounds 1–2 equal the original executions.

- **Request:** `launch/request.json`, sha256 `4cf9306c…c7cd6e`. The launcher stored it as `launch/validated-request.json`, request sha256 `cc72e6be…8944ff`.

- **Route:** isolab-eks, using the AWS launcher (`taskq/deploy/eks-karpenter/remote/launch-remote`).

- Frozen task card `launch/card.md` (CARD-…-xhost-02), written by the experiment director and run by the mechanical executor.

- Card -01 failed on the client before any request was sent: the venv's awscli v1 reads only `AWS_DEFAULT_REGION`. The launcher's CodeBuild build list held no build carrying its request key, so -02 is not a resubmission.

- **Identity:**

- Launcher build `isolab-experiment-launcher:7569b7f7-fc24-4096-a62a-7a76bf46947e`.

- Job `pbo-p20-xhost-20261029`, Job UID `b3207fe0-32b1-47b5-a9fb-da09e7ea8282`, Pod UID `e2064a35-dae6-4576-b8b8-883baa19858b`.

- Launcher result: `launch/result.json`, state `succeeded`.

- S3 results: `s3://isolab-results-104186811093-us-east-2/runs/pbo-p20-xhost-20261029/e2064a35-dae6-4576-b8b8-883baa19858b/`. The 19 files in `eks-results/SHA256SUMS` all verify after download.

- **Host and binary:**

	original	second host
env class	`ECBENV3hc4d998f5ae3f`	`ECBENV2h3a51beea0bc2`
host	4-vCPU Intel Xeon @ 2.10 GHz container, one pinned core, L0	EKS Spot c8a.2xlarge, AMD EPYC 9R45, 4 exclusive CPUs (cpuset 1-4), L2
ecbench sha256	`bf5eec6d…3807d9`	`583e62f0…c6a5a9`
ecbench source commit	`0e124fb1b207`	`cb2ec6873f30` (image built 2026-10-19)

The second host's binary is an older build, and it does not emit the newer bitop/v1 `work` or phase `work_native` fields. The match therefore excludes them, and they are named in `match-original.json`. No counted or band-priced field is excluded.

Limits

- **One curve:** this is one 20-bit holdout curve. The replay establishes that the recorded counts reproduce on another host class and build. It adds no curve and makes no claim at other sizes.

- **Counted unit only:** wall times in `eks-results/` are L2 records but are not analysed here.

- **Not an independent implementation:** both hosts run ecbench. The original validator's own `[d]G = Q` check remains the only implementation-independent check.

Files

- `launch/`: request, validated request, card, launcher log and CodeBuild receipts.

- `eks-results/`: every file the worker uploaded, with `session/records.jsonl` (2,016 records, sha256 `a9bce342…5924`) stored in the artifact store.

- `analysis/`: second-host `compare` JSON at w = 0, 0.1 and 1, `band.md`, and `match-original.json`.

- `tools/match_records.py` and `figures/`.