Independent machine review: pivot renewal

Retained run status: failed

The retained receipts are internally consistent with a bounded run. Pre-custody passed; the first module compiled; the second module failed at source line 59; and post-custody passed. The three later modules were not attempted.

Stage	Result	Observed time
Pre-custody	passed	45.61097849800717 s
Compiler	failed	42.47305457800394 s
Post-custody	passed	40.05902259401046 s
Overall	failed	128.24891154497163 s

Module outcomes

- `EliminationField`: exit 0; `EliminationField.olean` retained.
- `PivotSwap`: exit 1; the equal-row branch of `swap_involutive` remained unsolved.
- `Controls`, `Readback`, `ExpectedFailure`: not attempted.

Both compiler child groups were reaped with no remaining members. All three outer phase owners are terminal; no outer wait timed out.

Custody

The pre and post scans each checked 16,736 files totaling 3,111,892,318 bytes. The maps are byte-identical at:

`bd79b0566f9d19dbf1bdecbc1e94cd5dd119bffcf3f0bb639b9d921ff41ed2ad`

The native receipt notes that shared-cache equality does not exclude transient concurrent changes between the two scans.

Binding note

The admission receipt binds repository release SHA-256:

`b3acbb8650a1f370579e067fa89874d6348278a63517adb9cb1ee54aae8eecff`

The retained outer copy is semantically equal JSON but was reserialized, so its byte digest differs. The original bound release remains present.

Scope

This review recomputed hashes and checked retained receipts and source bytes. It did not rerun Lean or independently prove any statement. The supported component result is the `EliminationField` compilation; the full five-module replay did not complete.