Timed IC vs rho on RunPod, std vs fast hasher (2026-11-12)

Timed IC vs rho on a RunPod CPU pod, std vs fast hasher: the IC is faster up to 2^28 and slower at 2^32

Protocol: `PROTOCOL.md` (frozen in fde73fb405 before data; amendment A1 after a failed first attempt that produced
no measurement). Host: one RunPod Secure Cloud `cpu5c` pod (AMD EPYC 9575F 64-core, 128 threads; the container
may use CPUs 27, 56, 91, 120; every execution pinned to CPU 91), image `runpod/base:1.0.2-ubuntu2404`, pod
yt43r1gavrm8w3 (created, payload uploaded and deleted by `launch.py`; receipts in `launch/`). **3672 executions
(2 builds x 36 configurations x 17 keys x 3 interleaved repeats), 0 errors, every target verified.** Data:
`results/holdout/runs.jsonl`, `opcost.jsonl`, `host.json`, `job.log`, `analysis.txt`, `summary.json`; compact table
`runs.json` (`mk_runs.py`). Every number here is [pcc:unverified] until the claim is signed. The seconds are
diagnostic: a shared cloud host (load average 40-89 on 128 threads during the run; steal 0), not an isolated lab node.

Result (solve-phase wall time, fastest IC key / fastest rho key per configuration; median of 4 per cell)

bits	T	std: IC/rho [95%]	fast: IC/rho [95%]	IC fast/std	rho fast/std	IC/BSGS std / fast
24	1024	0.884 [0.861, 0.984] faster	0.893 [0.809, 0.974] faster	0.892	0.878	1.52 / 1.53
24	4096	0.733 [0.718, 0.825] faster	0.776 [0.765, 0.799] faster	0.890	0.845	1.47 / 1.46
24	16384	0.700 [0.697, 0.712] faster	0.712 [0.704, 0.726] faster	0.900	0.886	1.46 / 1.41
28	1024	0.791 [0.766, 0.824] faster	0.739 [0.719, 0.754] faster	0.918	0.981	1.44 / 1.46
28	4096	0.833 [0.819, 0.835] faster	0.779 [0.751, 0.794] faster	0.926	0.989	1.48 / 1.50
28	16384	0.953 [0.936, 0.995] faster	0.944 [0.929, 0.975] faster	0.946	0.961	1.54 / 1.62
32	1024	1.053 [1.029, 1.083] slower	1.011 [0.996, 1.031] unranked	0.963	1.003	1.52 / 1.60
32	4096	1.170 [1.136, 1.195] slower	1.108 [1.076, 1.145] slower	0.938	0.986	1.60 / 1.62
32	16384	1.179 [1.161, 1.192] slower	1.148 [1.110, 1.171] slower	0.949	0.975	1.58 / 1.60

- **Size pattern, both builds.** std: the IC is faster in 12 of 12 configurations at 2^24 (0.70-0.98x) and at 2^28
  (0.77-0.99x) and slower in 12 of 12 at 2^32 (1.03-1.20x). fast: faster in 12 of 12 at 2^24 and 2^28, slower in
  11 of 12 at 2^32 (1.00-1.17x; 32 b T = 1024 is unranked at 1.011 [0.996, 1.031]).
- **Host replication (std build vs the session VM of `../mt_timed_20261112/`).** 2^24 and 2^32 reproduce in direction
  (VM: 0.78-0.83 and 1.11-1.29). 2^28, unranked or fragile on the VM, is faster in all three cells here
  (0.79-0.95), so the crossover lies between 2^28 and 2^32 on this host.
- **Fast hasher.** It makes both sides faster: the fastest IC by 4-11% (fast/std 0.89-0.96) and the fastest rho by
  0-15% (0.85-1.00), more for rho at 2^24 and more for the IC at 2^28-2^32. It narrows the IC's deficit at 2^32
  (1.05-1.18 to 1.01-1.15) but does not reverse it. The size pattern does not depend on the std hasher.
- **Fixed-key control** (each side's key chosen on repeat 0, scored on repeats 1-2): std faster in the six cells up to
  2^28 and slower in the three at 2^32 (0.69-1.18); fast the same except unranked at 32 b T = 1024 (0.72-1.13).
- **Distance to BSGS:** the IC takes 1.41-1.62x the time of the fastest paired BSGS in every cell of both builds.
- Fastest arms: rho side `rho2xks` at 24 b (all three cells in the fast build, T = 1024 and 4096 in the std build)
  and `rhodpu` elsewhere; IC side `ic5` or `ic5w`
  (the retention variants never win in time).

Controls and their limits

- **A/A is not clean.** The rho side's repeat-0/repeat-1 ratio is 0.97-1.14 (std) and 1.01-1.11 (fast) and its
  interval contains 1 in only 4 of 9 (std) and 3 of 9 (fast) cells: the first round ran about 3% slower than rounds
  2 and 3 (median key time relative to its median: 1.032, 1.000, 1.000), with a drop in host load late in the run.
  Within each round the order of all keys of both builds was a single shuffle, so the drift applies to both sides
  of every comparison; the median |log(repeat/median)| over all keys is 0.008 (95th percentile 0.11). The IC/rho
  effects at 2^24 (12-30%) and 2^32 (5-20%) are larger than the drift, but single-cell magnitudes should be read
  with it in mind.
- With n = 4 configurations per cell the bootstrap interval of the median equals the range: each cell decision is a
  4-of-4 sign rule; the size-level counts above (12 of 12) are the strongest evidence.

Measured prices (`opcost`, std binary, before and after, curve 0 of each size)

One affine addition (1 GAE): 98-140 ns (about 2x faster than the session VM) [pcc:unverified]; I/M 23-27; a canonicalisation plus
one hash of x (two counted native operations): 0.006-0.007 GAE; a std HashMap lookup: 0.06-0.11 GAE at 2^10-2^16
entries, 0.74-1.45 GAE at 2^22-2^24 (relative to the faster field arithmetic, lookups at large tables cost more GAE
here than on the VM). These are microbenchmark loops (independent probes), not the solvers' access patterns.

Answer (interpretation)


On both hosts and with both hashers, this harness's multi-target index calculus is faster than its multi-target rho
on small groups and slower at 2^32 [pcc:unverified]; on the RunPod host the crossover lies between 2^28 and 2^32 (on the session VM
near 2^28). A faster hash table helps both sides and does not move the crossover past 2^32. The trend runs against
the IC as the group grows, so these measurements give no sign that it beats rho at cryptographic sizes; BSGS remains
faster than the IC everywhere.


Pre-registered predictions vs outcome

prediction	outcome
std on RunPod: size pattern reproduces (faster at 2^24, slower at 2^32), magnitudes within about 10% of the VM	holds in direction; 2^24 0.70-0.88 (VM 0.78-0.83), 2^3
fast: hash-heavy arms gain most; ic5 and rhodpu change little; IC/rho falls at every size	partly: the fastest IC gains 4-11%, the fastest rho 0-15%; IC/rho falls at
IC slower than BSGS everywhere in both builds	holds (1.41-1.62x)

Limits

One shared cloud host (load average 40-89 of 128 threads; the pinned CPU's SMT sibling was idle apart from the
pod's own job server); one implementation per build; 4 configurations per cell, the 12 curves and seed of the
earlier timed study (a host replication, not new configurations); A/A drift as above; the counted operations are
identical across builds, so the build comparison isolates the hasher; nothing here is about single-target ECDLP or
about ECC2K-130 / m = 83.


RunPod cpu5c (EPYC 9575F), one pinned CPU
std hasher: IC / rho
fast hasher: IC / rho
solve-time ratio (median, 95% CI)
1.2
1.1
1.0
0.9
0.8
0.7
24b T=1024
24b T=4096
24b T=16384
28b T=1024
28b T=4096
28b T=16384
32b T=1024
32b T=4096
32b T=16384


Effect of the fast hasher on each side
1.00
0.98
0.96
0.94
0.92
0.90
0.88
0.86
0.84
fastest IC: fast / std
fastest rho: fast / std
24b T=1024
24b T=4096
24b T=16384
28b T=1024
28b T=4096
28b T=16384
32b T=1024
32b T=4096
32b T=16384