
Saved-tape pruning audit: native software gate passes

The required stronger square obstruction and independent integer replay passed before this owner compiled its native runner. This report records the software gate only; the 21 scientific case receipts are separate.



fp-pruning-audit-v1: a software pass does not establish useful pruning or a lower IC price.

Actual execution and retained evidence

Managed owner: twist-joint-fp-pruning-audit-v1.service, started at 06:07 UTC. Driver: run-fp-pruning-audit.sh. Its metadata records source commit 64276f78721878ad637f52cc39225a7a19de2b0b and actual source hashes; the hashes retain the compiled source state independently of the commit label. Compilation, native tests and runner build all exit zero.

The native suite reports 77 passed, zero failed and zero ignored. Its added actual-point control verifies that the finite-residual rule must retain infinity, where a CM triangle can occur with distinct factors. This is a meaningful exception control, not a timing comparison.

The immutable runner SHA-256 is f610684f4ce5e33c10e80fe087a06c0c647e3ac906b883542a8c04eaa686d6d7. The build/copy and checksum were inspected before another native module was registered. Later edits cannot change this runner's bytes.

Evidence: runs/fp-pruning-audit-v1/metadata/ contains the executed script, commands, source hashes, test stdout, exit receipts and runner checksum. The compiled suite runs serially with one thread, an 8 GiB address-space limit and a 1,200-second watchdog. Heavy phases use the shared busy lock; compilation is separate. Queue delay and the test log's elapsed duration are not admitted solver timings. No isolation tier or speedup is claimed.

Scientific boundary

The subsequent audit reuses all 9,658 saved historical residuals and the existing phi, doubling and pure group-reference sets. It verifies every saved physical presentation, distinct tuple, projective row, independent RREF, first full-rank query and recovered point. It does not repeat a polynomial collector or BSGS oracle. A software pass establishes none of the final rejection counts, rank preservation or complete-cost gain. No filter has been deployed and no benchmark or leaderboard row changes.