Norm successor: independent prospective review

Source amendment supported; ready after authenticated serial coordinator release. No source blocking finding. Exact GitHub API readback returned `b3eeef70af3c`; source inspection followed the preread plan. No compiler, test or payload ran.

Replay retained. Replay differs from V3 only in workspace. Producer, readback, negative source, names, runtime and tactic bindings are unchanged. Corrected IndependentControls matches `448d5ab6...`. Four ordered calls and 30 exact axiom names remain. Negative control requires the intended single False-goal rejection and rejects syntax, environment and resource failures.

Custody retained. Fresh full pre and post checks cover 16,736 files and 3,111,892,318 bytes, requiring identical dictionaries. Closure and baseline manifest bytes matched their pins; this source review did not rehash the imported payload. Captured phase ownership, bounded cleanup and trusted manager-journal fallback are unchanged. Post remains required after compiler failure when terminal custody and budget permit.

Conditional accounting. Current 42,300 seconds is not silently replaced by 41,400. The latter requires terminal materializer custody and its 900-second conservative debit, making total prior debit 5,400. The proposed norm 2,400 leaves 39,000. Any intervening charge requires prospective reconciliation or amendment. Historical three-of-three consumption remains recorded.

Release trust boundary. A release hash proves byte identity, not provenance. The launcher validates fields, balances and hashes of five receipts. The coordinator must authenticate their publication, independent-review, ledger, materializer-terminal and live-lease contents and maintain the lease throughout. This is explicit trusted coordinator responsibility, not a cryptographic or independent authentication claim.

Finite limits. One new attempt, no retry, 1 CPU, 8 GiB, zero swap and128 tasks; pre900/compiler600/post900 within2,400 seconds. Original deadline remains2026-11-06 04:00UTC. Fresh workspace, output and phase unit identities prevent accidental reuse; actual absence and no overlap must be rechecked before release.

Scope and next step. Later finite nonbranch, branch norm and root-multiplicity declarations are outside this replay. Publish this review, authenticate and bind actual serial receipts, allocate the attempt, establish a fresh runtime lease and issue the concrete hash-pinned coordinator release. Existing user authorization applies; no new user permission is needed.