Multi-target IC vs rho in wall time (2026-11-12)

```
# Multi-target IC vs rho in wall time: the IC is faster on 2^24 groups and slower on 2^32 groups

Protocol: `PROTOCOL.md` (frozen in a992ed6c80 before data). **1836 executions (36 configurations x 17 keys x 3
interleaved repeats), 0 errors, every target of every run verified**, sequential and pinned to one CPU of the
session host (4-vCPU cloud VM, Intel Xeon @ 2.10 GHz). Data: `results/holdout/runs.jsonl`, `opcost.jsonl`,
`analysis.txt`, `summary.json`. Every number here is [pcc:unverified] until the claim is signed.

**Host caveat.** The lab's default route (Iso Lab on EKS, L2 isolation) was unavailable: this session's AWS
identity is a placeholder that AWS rejects. The seconds below are from a shared cloud VM without a hardware PMU
and are diagnostic, not lab-admitted; the study's own controls (pinning, interleaved repeats, A/A, a selection-bias
control) are reported with them.

## Result (solve-phase wall time, median of 4 configurations per cell, bootstrap 95%)

| bits | T | ic/rho solve [95%] | ic/rho incl. verify [95%] | ic/bsgs solve | A/A rep0/rep1 (rho side) [95%] | fixed-key ic/rho solve [95%] | winners ic / rho |
|---|---|---|---|---|---|---|---|
| 24 | 1024 | 0.778 [0.765, 0.922] cheaper | 0.818 [0.791, 0.943] | 1.537 | 0.863 [0.667, 1.145] | 0.825 [0.637, 0.961] | {'ic5w': 2, 'ic5': 2} / {'rho2xks 0.5': 2, 'rho
| 24 | 4096 | 0.792 [0.753, 0.821] cheaper | 0.852 [0.816, 0.878] | 1.326 | 0.985 [0.832, 1.358] | 0.818 [0.731, 0.847] | {'ic5': 3, 'ic5w': 1} / {'rhodpu 0.0': 3, 'rho2
| 24 | 16384 | 0.829 [0.811, 0.872] cheaper | 0.922 [0.885, 0.944] | 1.438 | 1.113 [0.975, 1.421] | 0.752 [0.655, 1.211] | {'ic5': 1, 'ic5w': 3} / {'rhodpu 0.0': 3, 'rho
| 28 | 1024 | 0.932 [0.869, 0.967] cheaper | 0.929 [0.858, 0.966] | 1.374 | 0.992 [0.830, 1.042] | 0.975 [0.884, 1.137] | {'ic5': 3, 'ic5w': 1} / {'rhodpu 0.0': 4} |
| 28 | 4096 | 1.053 [0.987, 1.101] unranked | 1.046 [0.989, 1.094] | 1.544 | 0.990 [0.809, 1.001] | 1.031 [0.967, 1.143] | {'ic5w': 2, 'ic5': 2} / {'rhodpu 0.0': 4} |
| 28 | 16384 | 1.007 [0.954, 1.193] unranked | 1.025 [0.976, 1.159] | 1.443 | 0.890 [0.725, 1.150] | 1.017 [0.940, 1.077] | {'ic5w': 3, 'ic5': 1} / {'rhodpu 0.0': 4} |
| 32 | 1024 | 1.114 [1.049, 1.211] dearer | 1.115 [1.048, 1.203] | 1.456 | 1.034 [0.894, 1.344] | 1.096 [0.972, 1.351] | {'ic5': 2, 'ic5w': 2} / {'rhodpu 0.0': 4} |
| 32 | 4096 | 1.203 [1.116, 1.303] dearer | 1.195 [1.105, 1.294] | 1.421 | 0.933 [0.812, 1.110] | 1.180 [1.052, 1.305] | {'ic5': 2, 'ic5w': 2} / {'rhodpu 0.0': 4} |
| 32 | 16384 | 1.289 [1.269, 1.319] dearer | 1.268 [1.252, 1.300] | 1.590 | 0.975 [0.846, 1.056] | 1.284 [1.218, 1.374] | {'ic5': 4} / {'rhodpu 0.0': 3, 'rhodpu 0.25': 1

- **2^24 groups: the IC is faster in all three cells (0.78-0.83x)** [pcc:unverified]; 2^28: faster at T = 1024 (0.93x), unranked at
  T = 4096 and 16384; **2^32: slower in all three cells (1.11-1.29x)**. The IC's relative speed falls as the group
  grows, and the trend runs against the IC toward cryptographic sizes.
- With the shared verification pass included the ratios are 0.82-1.27x, the same pattern.
- Selection-bias control (each side's key fixed on repeat 0, scored on repeats 1-2): 0.75-1.28x, the same pattern.
- A/A: the rho-side repeat-0/repeat-1 ratio's interval contains 1 in all 9 cells (widest 24 b T = 1024: 0.863
  [0.667, 1.145]); over all keys the median |log(repeat/median)| is
  0.028 (2.8%) and the 95th percentile 0.28 (dominated by the short 24-bit runs). The 2^32 differences (11-29%)
  are well above the median noise, and their intervals exclude 1.
- Distance to BSGS: the IC is 1.33-1.59x slower than the fastest paired BSGS in every cell.
- Fastest arms: rho side `rhodpu` (kappa 0) in 29 of 36 configurations, `rho2xks` (kappa 0.25-0.5) in 7; IC side
  `ic5` 20, `ic5w` 16. Retention (`ic5ks`, `ic5rw`, the hash-heavy variants) never wins in time.

## Measured operation prices (`opcost`, before and after, curve 0 of each size)

- One affine addition (1 GAE): 214-294 ns. Inversion: I = 23-31 M (the section 5a band's c_I = 30 is the matching
  price; c_I = 3 and 10 are far from this implementation).
- A native operation (canonicalisation + one hash of x, or a step index): 0.005-0.009 GAE, at the loop baseline:
  **in practice h_native is about 0**.
- A std HashMap lookup (SipHash, the harness's table): 0.04-0.15 GAE at 2^10-2^16 entries, 0.12-0.42 at 2^18-2^20,
  0.27-0.85 at 2^22-2^24 (cache misses). A fast multiplicative hasher is 2-5x cheaper (`opcost.jsonl`).

## Answer to the v5 question (interpretation)


v5 priced native work and hash-table operations at the same h. On this host they differ by one to two orders of
magnitude: native work is nearly free (h_native about 0) while lookups cost h_hash about 0.05-0.85 depending on
table size. That combination favours the distinguished-point rho, which does many native operations and few
lookups, and it is the rho that wins in time (29 of 36 configurations), although it never won in v5's counted
model. At small groups the IC still wins (its tables are small and cache-resident, and its per-target work is
lower); at 2^32 its table and trials are larger, lookups miss cache, and the distinguished-point rho is faster by
11-29% [pcc:unverified]. So in this implementation on this host the multi-target IC does not beat Pollard rho at the largest size
tested, and the trend is against it as the group grows.


## Pre-registered predictions vs outcome

| prediction | outcome |
|---|---|
| I/M about 23-28; native about 0.005-0.01 GAE; std lookup 0.05-0.1 at 2^10-2^16, 0.4-0.6 at 2^22-2^24; fast hasher 2-5x cheaper | holds (I/M 23-31; lookups 0.04-0.15 at
| IC faster than rho in most cells (0.8-0.95), most clearly at large tables (32 b, large T) | wrong in direction of size: faster at 24 b (0.78-0.83), slower at 32 b (1.1
| IC slower than BSGS everywhere | holds (1.33-1.59x) |

## Limits

One shared cloud VM (possible steal time; no PMU), not an isolated L2 node, and one CPU of it; one implementation
(std HashMap with SipHash, counting cells in the field layer, u64 field arithmetic with u128 reductions); 4 curves
per size and one seed (4 configurations per cell); the comparison is per target in a batch of T on one curve,
memory unbounded; it says nothing about single-target ECDLP, about other implementations or hardware, or about
ECC2K-130 / m = 83. A rerun on EKS L2 with the same `run.py` and binary is the follow-up.
```


Timed head-to-head, one core of the session VM
wall-time ratio, solve phase (median, 95% CI)
IC / rho (best of each side)
IC / rho (keys fixed on repeat 0)
A/A: rho repeat 0 / repeat 1
0.6
0.7
0.8
0.9
1.0
1.1
1.2
1.3
1.4
24b T=1024
24b T=4096
24b T=16384
28b T=1024
28b T=4096
28b T=16384
32b T=1024
32b T=4096
32b T=16384


Measured operation prices (grey: native op)
price in GAE (one affine addition)
std HashMap lookup, 24 b
fast hasher, 24 b
std HashMap lookup, 28 b
fast hasher, 28 b
std HashMap lookup, 32 b
fast hasher, 32 b
0.0
0.2
0.4
0.6
0.8
10
12
14
16
18
20
22
24
log2 table entries