`bitop/v1`: the unpriced counters decided, and the open `bitop/v2` choices measured

2026-11-07 · branch `claude/bitop-audit-and-pricing` · class: **accounting** (no algorithm changed and no cost fell; not an improvement under the success criterion). Rules: `docs/units/BITOPS.md`, "Extensions → 2026-11-07" and "bitop/v2 → Open definition choices". Companion instruction audits: `research/ic_acct1_cover_bitop_20261021/AUDIT_IR.md`, `research/ic_acct3_hec_ecbench_20261021/AUDIT_IR.md`.

Task B: each counter left unpriced on purpose

Each decision reads what the code executes per increment.

- **Priced (2):**
  - `abscissae_enumerated_uncharged` is now $C(\text{atoms}, w) \cdot (w \cdot \text{field_add} + \text{hash_probe})$, read from the factor-base parameter: every w-subset is summed and inserted, and the counter is only the deduplicated set's size.
  - A binary-field `sqrt_solves` is now the Artin–Schreier lift attempt `field_sqr + field_inv + field_mul + 2·field_add + as_solve`: no square root is taken on $y^2 + xy = x^3 + ax^2 + b$.

  Each adds a `known_uncounted` item for the work beside it that no counter sees.
- **Kept unpriced, with reasons:**
  - F_{p^4} square roots: a randomised Tonelli–Shanks.
  - SAT conflicts: no constant per conflict; see Figure 2.
  - The d4 and PKM "multiplication" units: modelled or mixed counts, not products executed.
  - The CM-folded backend's gap: `power` calls, string signatures and pivots with no counter.

No primitive weight and no vector changed.




Figure 1: Archive before/after (`examples/ic_acct6_archive.rs`; 84,687 verified records of the 709-session archive checkout of 2026-10-26). Complete, incomplete and error totals are unchanged (58,277 / 24,682 / 1,728): every record a decision touched is incomplete for another reason too.




Figure 2: The 8 smallest committed SAT records re-executed on the counted engine reproduce their conflicts and propagations exactly. Word operations per conflict are 3,092–3,185 on one arm and 4,595–4,712 on the other, so no per-conflict rule exists. A re-run prices such a record exactly.

Task C: the eight open `bitop/v2` choices

The evidence is `examples/bitop_v2_choices.rs` on the 12,080 hold-out records of `research/bitop_ladder_20261019` and the archive's 477 CM-folded records. Every recommendation is **pending owner sign-off**, and none is implemented.

#	**evidence**	**recommendation**
1 sum/max	IC sum/max 1.37 median, [1.03, 1.61]; no ranking changes	keep the sum
2 dense/sparse	matrix 23.7× smaller sparse; IC total 1.29× (max 1.48×); IC is 3.9–193× the generic arms in gates	keep dense (the measured `incremental-gauss` builds dense rows); report sparse beside it
3 attempts	attempts ≤ 3.1% of the 2^{κ} keys; collisions $\lesssim 2\%$	keep attempts
4 kangaroo width	$2\kappa + w + 1$ moves 2 of 25 BSGS/kangaroo pairs to "trade"	adopt $2\kappa + w + 1$
5 `at` and ranking	204/204 IC-versus-generic pairs rank; true trades stay unranked	keep
6 bound fit	memory slopes differ from gate slopes (rho 0.30 against 0.57; IC 0.65 against 0.71)	fit memory and `at` exponents too
7 walk state	rho walk state 13% median, up to 3.4×; kangaroo up to 12×; no ranking changes	include the jump table
8 native backends	477/477 CM-folded records are memory-incomplete	backends declare per-structure bytes




Figure 3: The choices on the hold-out: how much the declared memory moves (C1, C2), the walk state left out (C7), which pairs the rule ranks under the frozen rule and two alternatives (C5, C4, C7), and the gate, memory and `at` exponents (C6).

Limits

- **The archive.** It is the host's newest full checkout (2026-10-26); the artifact-store records on `main`'s tip were unreachable without store credentials.
- **The hold-out's scope.** It covers prime-field generic arms and `ic.pipeline` only.
- **No checkpoint.** No S3 checkpoint could be pushed (no upload token). The runs were local re-executions of committed seeds.