Run report: ecbench session `ECBS1hd81d73afe25e` (e-m16), 2026-10-27T05:53Z

Part E, `m = 16`, two targets, IC and rho (checkpointing binary). Spec `specs/SPEC-E-m16.json`. Binary sha256 `ad1dd91a…`, commit `1b15f8b35` (clean). Host: Xeon @ 2.10 GHz, 4 vCPU, one core per session (isolation level L1 or L0, recorded per run: wall time is descriptive only). The session completed: every planned run was recorded.

arm	workload	m	status	S	GAE	trials	relations	wall (h)
rho-neg	`Wa1b3b10e6968`	16	verified	0.8992	2.731e+09	–	–	0.815
ic-wied	`Wa1b3b10e6968`	16	verified	1.482	4.5e+09	3108064	16019	5.078
rho-neg	`W37a8388076b0`	16	verified	2.235	6.789e+09	–	–	2.353
ic-wied	`W37a8388076b0`	16	verified	1.49	4.524e+09	3124998	15980	4.931

All values are recorded fields (`S` = `cost.s`, GAE = `cost.total_gae`, trials and relations from `counters`, wall = `time.solve_wall_ns` ÷ $3.6{\cdot}10^{12}$); no run here is a replay. Records: `sessions/e-m16/records.jsonl`. Audit receipts: `audits/`.




Figure 1: Recorded `S` per run, session `ECBS1hd81d73afe25e`.