Symbolic signed-graph reduction for pencil relations

Mathematical implementation and development checks

28 October 2026 (America/Los_Angeles)

The existing pencil cohort has 543 verified candidate targets out of 1,260. This packet adds a native algebraic component, with no new cohort or performance measurement. Its candidate/rho cost ratio is unknown.

Algebraic interface

An input row is $\sum a_i X_i + \sum b_j S_j = 0$ over a prime field. At most two large-variable terms survive canonicalization; the S_j remain symbolic. The forest stores $X_i = s_i X_{\mathrm{parent}(i)} + u_i(S)$ and uses union by size. Root substitution leaves zero, one or two free roots. Zero emits a constraint, one anchors a root, and two join components by an invertible pivot. An unbalanced signed cycle anchors its root; it does not immediately yield an additional relation involving only small variables.

Recorded development checks

The Rust suite compares the emitted small-row space with independent dense row reduction after every prefix: 40 prefixes, 128 deterministic streams and five prime fields (2, 3, 5, 7 and 101), totaling 25,600 checks. Additional cases cover signed cycles, duplicate terms, rejected inputs, composites and a prime near the 64-bit limit. The test log is retained. The four Lean declarations cover pivot equivalence, substitution, balanced cycles and unbalanced cycles. Their direct compiler result and axiom report are retained separately. They do not formalize the full forest invariant or prove correspondence with Rust. The retained residual basis is now also compared with the independent reference at all 25,600 prefixes. Seven native tests pass. Explicit working and retained coefficient caps leave the basis unchanged on rejection; callers must stop or retain that rejected row. Logical counters include failed attempts but omit map comparisons, allocation, setup and exponentiation internals. These are coefficient limits, not process-memory guarantees or a complete cost model.

Next integration gates

Requirement	Status
Prime-field row kernel and independent prefix tests	Implemented and tested
Forest-state induction and Rust correspondence	Open
Pencil adapter, fixed small-base selection and admission accounting	Open
Full symbolic-vector, memory and residual elimination costs	Unmeasured
Remaining 717 frozen candidate targets	No new results
End-to-end cost against matched rho	Unknown

Sources and limitations

The graph construction follows the mathematical distinction between full relations and cycles leaving a large prime in Gaudry, Theriault and Thome, double large prime variation, sections 2.3 and 3.1 (2005 version). Its genus-at-least-three complexity result is not asserted for this genus-2 pencil stream. Existing repository graph and large-prime eliminators informed the implementation. The editable graph is `reduction.svg`; the machine-readable check table is `checks.csv`. All results are development checks; no runtime, memory improvement or full-cohort completion is inferred from them.