N83 spike29 fixed-base first-fall run

48 certificates, fresh replays, and S3 readbacks

Outcome

The same complete spike29 factor bases were reused for m=2–9. Koblitz and general-binary systems each had exact first-fall degree 2 in all 16 cases. Prime systems had certified lower bound at least 5 in all 16 cases, with no exact first-fall found. These labels do not vary by candidate.

Counts

Family	Cases	Exact FFD 2	FFD ≥ 5	Exact LFD	Affine Dreg
Koblitz	16	16	0	0	0
General binary	16	16	0	0	0
Prime	16	0	16	0	0

Scope

This is a first-fall dataset only. No exact LFD or affine degree-of-regularity labels were measured, so the run cannot rank bases for those targets. The independent validator was filed after data collection and checked source/certificate/replay/readback linkage without changing the run.

Custody

Protocol N83-FACTOR-BASE-PDP-FFD-LFD-20261031-V2; protocol SHA-256 50cd6f8213789de2dfd54a3b33a067ed87cc0def761b7c98769be3e19aee47a9. Archive s3://setec-astronomy-artifacts/runs/n83-ffd-lfd-factorbase-panel-20261105/v2/spike29/attempt-01/panel-complete.tar.gz; 118893 bytes; SHA-256 031210e42946033daa78a04066cfaa6d01c07621d0da3eabda65561ffe4615d2.

Execution and cost

Limits: 1 CPU, 8 GiB, 60 seconds per case and replay, 2-hour wall deadline, zero retries. Cost ceiling: USD 2.00 compute plus USD 0.25 artifact storage. At observed Spot price USD 0.5321/hour, about 3.5 minutes corresponds to estimated USD 0.031 compute (not a billing measurement).

Reproduction

The S3 archive contains attempts, certificates, readbacks, summary, and file layout. Source systems and fixed bases remain content-addressed in Git. See the run README and plot.csv / plot.svg.