
External follow-up: duplicate terminal audit stopped and reconciliation fixed

The first follow-up owner has an orchestration defect: it reuses completed audit summaries but fails to recognize a completed timeout without a summary. The original basis and input did not change. The duplicate was identified and stopped; every partial artifact and the original timeout are retained.



An owner stop or a successful external process does not establish complete physical roots.

Actual sequence

twist-joint-external-audit-completion-v1.service starts at 05:39 UTC and waits for the two original external owners. After the external msolve inventory finishes, it copies existing successful audit records and starts another l0-peel-variant-geometric root audit. That identical computation already has native exit 124 after its original 1,200-second cap in external-audit-v3. The missing summary is a timeout, not an unaudited input.

At inspection, the duplicate is running with a native child; it is not merely waiting for the lock. The service is stopped before further retries. The before-stop receipt records 132,461,232,000 ns of whole-service CPU. That is unadmitted service accounting, including orchestration, not a solver timer or a new scientific result. No native completion verdict exists for the stopped retry. Systemd's successful stop is not an audit pass.

The original timeout, executed scripts, duplicate command and partial outputs remain under their original run IDs. The reconciliation and exact before/after service observations are in runs/external-audit-completion-v1/metadata/duplicate-reconciliation.json and the adjacent stop receipts. No msolve or BSGS process is repeated by the correction. The unnecessary native-root retry itself is explicitly recorded here rather than omitted from consumed work.

Corrected version

Commit 0fd82a7287 adds a separate terminal-failure reuse branch. It requires the exact original argv, with public-input, system and basis hashes and the frozen runner/output paths, to match before reusing the failed receipt. The actual unchanged timeout command matches; a changed basis-hash argument is rejected. The earlier inline corruption check changed the reference argument; the corrected control changes the actual basis-hash position. These infrastructure checks run no native audit.

New owner twist-joint-external-audit-completion-v2.service preserves that timeout as reused-native-terminal-failure, with native exit 124 and external exit zero. Its remaining audits cover only newly available terminal bases. All 21 expected positions, including missing and failed outputs, remain in its inventory. A zero external exit supplies no complete root, physical-yield or rank claim by itself. The existing one-worker, 8 GiB, 1,200-second native cap and busy reservation remain unchanged. Read its own eventual terminal report for its outcomes; none is inferred from this correction. No benchmark or leaderboard result is promoted.