Retained signed-duplicate archival audit

420 retained cases · 60 separate targets

28 redundant duplicates: case6 -(G+Q) paired with case3 G+Q

All normalized differences: Delta a = Delta b = 0

174 graph edges · 0 cycles · 0 informative duplicate candidates

Fixed archived coordinate fixtures. No new trajectory. Costs counted by audit phase.

All420 retained case dispositions were produced and checked against the frozen input index. Native exit0; audit_pass=true. The selected60 p739 records are a fixed subset of the180-record pinned archive. Their labels, signs, target identities and seeds were preserved. One admitted run was executed, without retry.

There were218 collector-ineligible cases and202 eligible logical adapter ingests. These comprised174 first occurrences and28 redundant duplicates. Each duplicate was archived case6 versus case3 within the same target: the designed -(G+Q) versus G+Q pair. After canonical sign normalization both coefficient differences were zero. No informative duplicate candidate, invariant error, rejected candidate or noncanonical-label failure occurred.

The native graph received174 first-occurrence edges across60 separate target contexts, and had zero cycles. The28 duplicate edges were suppressed. There were no terminal returns, so no post-terminal diagnostic comparisons occurred. All420 rows remain available; zero missing/unexpected identities or parse errors were found. These are retained coordinate-validation fixtures, not naturally generated collector paths.

Setup and constructor counters were reconciled in a unique ledger keyed by physical archive row. All60 targets were present and repeated copies agreed. Setup validation totals:3904 Jacobian operations,438198 M,8436 S,14252 I,760038 field additions. Constructor totals:2640 Jacobian operations,299213 M,5631 S,9823 I,519770 field additions. These phases are deliberately separate; repeated setup metadata on each case was not summed seven times.

phase-counts.json preserves separate label-reference, eligibility, canonical-key reference, adapter, graph-processing, graph-factor-verification and terminal-reference totals. Scalar counters remain separate from field counters. Initialization/order checks and the repeated eligibility work belong to this audit schedule. Hashing, memory, comparisons, primality arithmetic, internal exponentiation expansion and full runtime work are not completely priced. Whole-cost and timing ratios are null.

The frozen helper verifies valid signed divisors and D=aG+bQ against each retained public target, with exact prime-order conditions and Q=kG checked in setup. Only canonicalized table entries negate both coefficients; graph forwarding preserves the original signed divisor and original label pair. Invalid labels or inconsistent nested adapter outcomes would fail the audit. No such failure occurred in this archive subset.

The source and prospective independent review were committed at191a0210a7e150c922bc848b37fb639daacd89e1 before root admission. The native run used its own cache under a120second cap with5second termination grace, concurrently with unrelated root validation; no comparison clock is reported. The dead-code compiler warning is retained. The earlier input-preparation assertion failure remains in the frozen packet; it was corrected prospectively by selecting p==739 rather than assuming the entire archive had60 records.

This result characterizes the recorded coefficient differences in this fixed archive. The natural-trajectory arm remains inventory-only. Machine-readable status, all420 raw JSONL records, a flattened420-row CSV, exact source/input bindings, native receipt and counters accompany this report. Independent review of this terminal evidence is pending.