F4 trace for `pkm-semaev`: learn once per branch system, replay per target

Protocol: PROTOCOL.md (frozen before data, unchanged since). Scope of every statement below: **k = 20 miniature, isogeny form, m = 2, mode full, t in {6, 7, 8}, G in {0, 2, 4}, 100 subgroup targets per cell, seeds 2026111400 + t**, in the unit **F4 elimination multiply-adds** (the oracle's unit). Nothing is claimed for other k, m, t, G, the bits form, wall time, or against rho (distance to rho is lead A's, a different unit).

What was built

`pkm-semaev:...,trace=1` (and `curve25519_family f4cost ... <lifts> <trace>`, argument 12; `trace=0` is byte for byte lead 4's code path).

- `f4_fp_tower.rs`: `TowerF4Options::record_trace` / `replay`, `F4Trace`. A recording run keeps, per F4 step, the S-rows `(multiplier, element)` whose residue gave a new pivot, the S-rows promoted to reducers, and the sorted leads of the new elements. A replay forms only those S-rows, forms the reduced reducer block `B'` only for the reducers those rows reach, and stops at the first step whose new leads differ from the trace's (unless it already holds `1`). Only a refutation is a result of a replay: every row lies in the ideal, so `1` is a sound certificate whatever the trace was learned on; the result is never "this is a Groebner basis".
- `pkm_semaev.rs`: at `prepare`, one trace per branch system (`2^G` of them), learned by plain F4 with recording on `x_R` from a fixed splitmix stream (at most 8 tries, until one refutes; in every cell the first try did). Per target and branch: replay; if it does not refute, plain F4 on the same system (the fallback), as before. The grid reading, lift and verdict code after F4 is unchanged.
- Ledger: learning is setup native work (`pkm_trace_learn_muladds`), charged once per branch shape, not in `f4_muladds`. `f4_muladds` = replay work (every attempt, including the ones that fail) + plain work after a failed replay; the test asserts the identity.
- Design choice, with the alternative rejected, is in PROTOCOL.md.

Validity checks


- `cargo test --release --lib pkm_semaev`: `test result: ok. 12 passed; 0 failed; 0 ignored; 0 measured; 6075 filtered out; finished in 471.89s` (11 existing plus the new test, listed in the output). New test `trace_agrees_with_plain_f4_and_grid` (isogeny t = 4 at G = 0, 1, 2 and the bit form at G = 1, 32 random and planted targets each): trace verdict == plain-F4 verdict == grid verdict == exact decomposable set, relations sum to the target, zero crosscheck disagreements, replays refute, the fallback is exercised (planted targets are consistent systems) and charged, ledger identity holds. All pre-existing tests pass.
- `cargo clippy --release --lib --bin curve25519_family -- -D warnings`: exit 0, only the environmental unknown-lint warning (`chunks_exact_to_as_chunks`). rustfmt applied to the three changed `.rs` files.
- Self-check (uncharged diagnostic in `prepare`, counter `pkm_trace_selfcheck_refuted`): each learned trace replayed on its own `x_R` must refute. It equals the number of branches in all 9 trace cells (1, 4, 16). It is what exposed the one bug found (below).
- Binary identity: frozen copy `/home/user/frozen-bin/curve25519_family_leadC`, sha256 `621055521e98edb4f1cb0685b5f2e072bc3b8da1cc2216d4f132799c82c149c1` (`analysis/binary.sha256`), built after `touch` of the changed sources inside the `flock` call (the shared-target hazard), and checked before the data with a 3-target smoke run whose JSON contains `"trace":true` and the `pkm_trace_*` counters, which only this branch's code emits.
- The `trace=0` cells reproduce lead 4's numbers: multiply-adds per target 7.1e5 (t = 6, G = 4), 9.7e6 (t = 7, G = 4), 8.64e7 (t = 8, G = 4), 6.98e9 (t = 8, G = 0), identical to its README; hits 4/4 at t = 8, else 0.

Measurement

Driver `analysis/run_cells.sh` (shell + jq), 18 cells, sequential, trace 0 then trace 1 per (t, G), each under `ulimit -v 3500000` and `timeout 900`, cap 600 s. Raw: `analysis/f4trace.jsonl` (sha256 `7fa5d4a040c7293377a52f3efa8738761a85333f66dffca1071c85a4973acd6e`, 18 lines, 18 ok, 0 failed, all stderr files empty), status with the load average before each cell in `analysis/f4trace.jsonl.status`. **No cell hit the cap**, so every pair is paired target for target (same 100 targets). Run locally on a shared 4-core box; `elapsed_s` and the load are recorded in the JSON but **wall times are not compared** (other agents' load). Tables: `analysis/make_tables.sh` (jq + awk), figure `analysis/make_svg.sh`.

Columns (all multiply-adds): plain /tgt = `trace=0` per target; apply /tgt = replay work per target (all attempts); fallback /tgt = plain work after failed replays; trace /tgt = apply + fallback (learning excluded); L = learning cost (once); amortised = (L + trace total) / 100; n* = L / (plain - trace /tgt), the target count at which learning has paid back; fallbacks/replays at branch level (hits p/t = plain/trace arm); PR(cov) = per-relation cost on the harness's `coverage_exact` (per target / cov).

t	G	targets plain/trace	plain /tgt	apply /tgt	fallback /tgt	trace /tgt (no learn)	apply/plain	trace/plain	learn L	amortised /tgt	break-even n*	fallbacks/replays	hits p/t	verified p/t	cov	PR(cov) plain	PR(cov) trace amort.	learn runs/branches
6	0	100/100	5.55e+07	2.25e+07	0	2.25e+07	0.406	0.406	5.55e+07	2.31e+07	1.683	0/100 (0.0%)	0/0	0/0	0.00131	4.23e+10	1.76e+10	1/1
6	2	100/100	1.08e+07	4.7e+06	0	4.7e+06	0.434	0.434	1.08e+07	4.81e+06	1.766	0/400 (0.0%)	0/0	0/0	0.00131	8.27e+09	3.67e+09	4/4
6	4	100/100	7.1e+05	3.23e+05	0	3.23e+05	0.454	0.454	7.1e+05	3.3e+05	1.833	0/1600 (0.0%)	0/0	0/0	0.00131	5.42e+08	2.52e+08	16/16
7	0	100/100	7.46e+08	2.28e+08	7.46e+06	2.35e+08	0.305	0.315	7.46e+08	2.43e+08	1.461	1/100 (1.0%)	0/0	0/0	0.00905	8.23e+10	2.68e+10	1/1
7	2	100/100	9.03e+07	3.56e+07	0	3.56e+07	0.395	0.395	9.03e+07	3.65e+07	1.652	0/400 (0.0%)	0/0	0/0	0.00905	9.97e+09	4.04e+09	4/4
7	4	100/100	9.7e+06	4.13e+06	0	4.13e+06	0.426	0.426	9.7e+06	4.23e+06	1.742	0/1600 (0.0%)	0/0	0/0	0.00905	1.07e+09	4.67e+08	16/16
8	0	100/100	6.98e+09	2.04e+09	2.79e+08	2.32e+09	0.292	0.332	6.98e+09	2.39e+09	1.497	4/100 (4.0%)	4/4	4/4	0.035	1.99e+11	6.79e+10	1/1
8	2	100/100	6.8e+08	2.92e+08	8.76e+06	3.01e+08	0.429	0.442	6.96e+08	3.08e+08	1.833	5/391 (1.3%)	4/4	4/4	0.035	1.94e+10	8.76e+09	4/4
8	4	100/100	8.64e+07	3.81e+07	3.34e+05	3.85e+07	0.442	0.445	8.89e+07	3.94e+07	1.857	6/1554 (0.4%)	4/4	4/4	0.035	2.46e+09	1.12e+09	16/16



multiply-adds per target

`analysis/trace.svg`: multiply-adds per target, log scale, per (t, G): plain F4 (circle), trace arm apply + fallback (square), trace arm amortised over the cell's 100 targets with learning (triangle).

Compact view

t	G	plain /tgt	trace /tgt	trace / plain	n*	fallbacks / replays
6	0	5.55e7	2.25e7	0.41	1.68	0 / 100

t	G	plain /tgt	trace /tgt	trace / plain	n*	fallbacks / replays
6	2	1.08e7	4.70e6	0.43	1.77	0 / 400
6	4	7.10e5	3.23e5	0.45	1.83	0 / 1600
7	0	7.46e8	2.35e8	0.32	1.46	1 / 100
7	2	9.03e7	3.56e7	0.39	1.65	0 / 400
7	4	9.70e6	4.13e6	0.43	1.74	0 / 1600
8	0	6.98e9	2.32e9	0.33	1.50	4 / 100
8	2	6.80e8	3.01e8	0.44	1.83	5 / 391
8	4	8.64e7	3.85e7	0.45	1.86	6 / 1554

Learning cost L equals the plain per-target cost of the cell almost exactly (one plain run per branch system, the first try refuted in every case), so n* = L / (P - T) = 1 / (1 - trace/plain) is between 1.5 and 1.9 in all nine cells: the learning has paid back after two targets.

Predictions (frozen in PROTOCOL.md)

- **P1 (apply cost at G = 0 at most 0.25 x plain at t = 6, 7, 8): false.** Measured apply / plain at G = 0: 0.406 (t = 6), 0.305 (t = 7), 0.292 (t = 8). All three exceed 0.25. The replay still costs 29 % to 41 % of plain F4 at G = 0. Where the remaining work sits (initial echelon, the reducer block the kept rows reach, the unit-producing last steps) was not measured and is not claimed.
- **P2 (the ratio is larger at G = 4 than at G = 0): true at all three t.** apply / plain at G = 0 -> G = 4: 0.406 -> 0.454 (t = 6), 0.305 -> 0.426 (t = 7), 0.292 -> 0.442 (t = 8); G = 2 lies between at t = 7 (0.395) and t = 8 (0.429), and at t = 6 (0.434). The mechanism stated in the protocol (smaller branch systems leave less to drop) is not tested by this data; only the ordering is.
- **P3 (fallbacks / replays at most 10 % in every cell): true.** Largest is 4.0 % (t = 8, G = 0, 4 / 100). Fallbacks are the 4 consistent systems (the 4 hits of t = 8, `pkm_consistent_systems` = 4 in every t = 8 cell) plus degenerate specialisations of systems that plain F4 refutes: 1 at t = 7, G = 0 (0 hits in that cell; leads 242 vs 243 at step 17), 1 at t = 8, G = 2, 2 at t = 8, G = 4. At t = 6, no fallbacks. The fallback is therefore exercised on real data, and charged (it is the “fallback /tgt” column).
- **P4 (hits and verified hits equal between arms): true in all 9 pairs** (0 / 0 at t = 6 and 7, 4 / 4 at t = 8, verified equal to hits).
- **P5 (learning pays back within 5 targets where apply < plain): true.** Largest n* is 1.86 (t = 8, G = 4).

Per relation on `coverage_exact` (F4 multiply-adds per target / coverage)

Plain -> trace amortised over 100 targets (columns PR(cov) above): t = 6: 4.23e10 -> 1.76e10 (G = 0), 8.27e9 -> 3.67e9 (G = 2), 5.42e8 -> 2.52e8 (G = 4); t = 7: 8.23e10 -> 2.68e10, 9.97e9 -> 4.04e9, 1.07e9 -> 4.67e8; t = 8: 1.99e11 -> 6.79e10, 1.94e10 -> 8.76e9, 2.46e9 -> 1.12e9. The best cell of the grid is still isogeny t = 6, G = 4: 5.42e8 plain (lead 4’s best) -> 2.52e8 with the trace (2.15 x lower) in this unit. This is a measured reduction of F4 multiply-adds per relation on the same oracle, same targets, same verdicts; it is not a wall-time claim, and the unpriced native work (specialisation, row formation, grid reading) is not counted for either arm (AGENTS.md §5a would price it at 0 / 0.1 / 1 GAE in a cross-method comparison; none is made). With more targets the amortised cost tends to the trace column (trace/plain 0.32 to 0.45 here); with fewer than two it does not pay.

Failures, deviations, and what was not done

- **A bug in my first replay**, found by the self-check before any cell data: the replay rebuilt the set of lcm columns from the kept halves of critical pairs only. A column whose promoted row is a tower product then fell out of the set, was sent to the reducer search, and the matrix changed (every replay at G = 2 failed with “new leads differ”, 99 of 99; the self-replay failed 4 of 4). Fix: the replay keeps the original lcm columns. The test and all 18 cells use the fixed code; no cell data came from the buggy one.
- The self-check diagnostic and the failure-reason counters (`pkm_trace_failure_*`, `pkm_trace_mismatch_*`) were added after PROTOCOL.md was frozen; they change no cost and no verdict. The protocol text was not edited.
- Reducer pruning (`B'` only for reached reducers) is applied only in replays, as the protocol says. It is therefore part of what the “apply” column measures; a plain-F4 arm with the same pruning is not measured, so how much of the saving comes from dropping rows and how much from pruning is not separated.
- The learning `x_R` are drawn from a fixed stream, not from the targets; in all 9 cells the first draw per branch refuted (learn runs = branches). Sensitivity to the draw was not measured.
- The replay never certifies a Groebner basis, only a refutation. Targets whose system is consistent (hits) always go to plain F4, so the trace saves nothing on them and costs the failed replay (the “apply” share of the fallback rows): at t = 8, G = 0, the 4 hits cost an extra 4 failed replays in the apply column.
- Wall time was not measured as a claim: row formation, specialisation and the elimination of the replay run on a shared box. Not compared.
- 100 targets per cell, 0 to 4 hits per cell; the hit counts say nothing about yield beyond consistency with `coverage_exact`.
- Run locally (a development measurement inside the lead), not on EKS, as the task specified; no L2 or cross-method claim.